

December 6, 2021

Ms. Andrea Vasquez  
Delicato Vineyards  
12001 S Highway 99  
Manteca, CA 95336

**Re: Notice of Final Action - Title V Permit Renewal**  
**Facility Number: N-266**  
**Project Number: N-1201563**

Dear Ms. Vasquez:

The District has issued the Final Renewed Title V Permit for Delicato Vineyards (see enclosure). The preliminary decision for this project was made on October 18, 2021.

The public notice for issuance of the Final Title V Permit will be posted on the District's website ([www.valleyair.org](http://www.valleyair.org)).

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Brian Clements  
Director of Permit Services

Attachment

cc: Courtney Graham, CARB (w/enclosure) via email  
cc: Laura Yannayon, EPA (w/enclosure) via EPS

**Samir Sheikh**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: (661) 392-5500 FAX: (661) 392-5585

# Permit to Operate

**FACILITY:** N-266

**EXPIRATION DATE:** 10/31/2026

**LEGAL OWNER OR OPERATOR:** DELICATO VINEYARDS  
**MAILING ADDRESS:** 12001 S HIGHWAY 99  
MANTECA, CA 95336

**FACILITY LOCATION:** 12001 S HIGHWAY 99  
MANTECA, CA 95336

**FACILITY DESCRIPTION:** WINERY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

**Samir Sheikh**  
Executive Director / APCO

**Brian Clements**  
Director of Permit Services

# *San Joaquin Valley*

## *Air Pollution Control District*

**FACILITY:** N-266-0-2

**EXPIRATION DATE:** 10/31/2026

### **FACILITY-WIDE REQUIREMENTS**

---

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (8/18/11). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: DELICATO VINEYARDS  
Location: 12001 S HIGHWAY 99,MANTECA, CA 95336  
N-266-0-2 : Dec 6 2021 10:42AM -- NORMANR

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall: manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2 of District Rule 4601 (4/16/20), after the specified effective dates in Table 1 or Table 2 of District Rule 4601. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All architectural coating containers and containers of any VOC-containing materials subject to Rule 4601 (4/16/20) shall be closed when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601, sections 6.1 and 6.3 (4/16/20). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: San Joaquin County Rule 110, San Joaquin County Rule 202, and San Joaquin County Rule 401. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 2010, Sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin October 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. The winery operator shall achieve required annual emissions reductions (RAER) equal to at least 35% of the winery's baseline fermentation emissions (BFE) [District Rule 4694]
44. By December 1, 2006, and every three years thereafter, the winery operator subject to the requirements of Section 5.1 shall submit to the District a three-year compliance plan that demonstrates compliance with the applicable requirements of District Rule 4694 for each year of the applicable compliance period. The three-year compliance plan shall include all the information specified in sections 6.1.1 through 6.1.8 of the rule. [District Rule 4694, 6.1]
45. By July 1, 2007, and every three years thereafter, the winery operator shall submit to the District a three-year compliance plan verification that demonstrates that the three-year compliance plan elements are in effect. The compliance plan verification shall include all the information specified in sections 6.2.1 through 6.2.5 of District Rule 4694. [District Rule 4694, 6.2]
46. By March 1, 2008, and every year thereafter on or before March 1, the winery operator shall submit to the District an annual compliance plan demonstration that shows compliance with the applicable requirements of District Rule 4694. The compliance plan demonstration shall include all the information specified in sections 6.3.1 through 6.3.7 of the rule. All additional Required Annual Emissions Reductions (RAER) shall be obtained by April 1 of the year of the Annual Compliance Demonstration, per section 6.3.7.2 of the rule. [District Rule 4694, 6.3]
47. Operators using certified emission reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved three-year compliance plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
48. Payment of District Obtained Emissions Reductions (DOER) and administrative fees shall be made to the District no later than March 1, of the first year in the applicable compliance period. [District Rule 4694, 6.1.5.3.5]

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-1-7

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

GASOLINE DISPENSING OPERATION WITH ONE 4,000 GALLON (SPLIT 2,000 GALLON GASOLINE/2,000 GALLON DIESEL) CONVAULT ABOVEGROUND STORAGE TANK SERVED BY MORRISON BROTHERS PHASE I VAPOR RECOVERY SYSTEM (VR-402-B), STANDING LOSS CONTROL (VR-301-E), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-116F)

### **PERMIT UNIT REQUIREMENTS**

---

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
3. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
4. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
8. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
11. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
13. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
14. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
15. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



17. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
18. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
19. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
26. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
27. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-3-3

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

106 BHP DEUTZ MODEL NDC-BF4 M1013ES DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

## **PERMIT UNIT REQUIREMENTS**

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with a non-resettable hour meter with a minimum display capability of 9,999 hours, unless the District determines that a non-resettable hour meter with a different minimum display capability is appropriate in consideration of the historical use of the engine and the owner or operator's compliance history. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight shall be used. [District Rules 2201 and 4801, San Joaquin County Rule 407, and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. NOx emissions shall not exceed 5.9 g/hp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The PM10 emissions rate shall not exceed 0.1 g/hp-hr based on US EPA certification using ISO 8178 test procedure. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and to preserve or protect property, human life, or public health during a fire. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rules 2201, 4701, 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier in a manner consistent with good air pollution control practice for minimizing emissions. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee must maintain records of all required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions, including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
18. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
19. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-9-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

14,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 34 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-10-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

14,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 35 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-20-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 45 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-21-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 46 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-22-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 47 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-23-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,168 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 48 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-24-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,151 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-25-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-26-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,192 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-27-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,201 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-28-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,188 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-29-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,180 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-30-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-31-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 56 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-32-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 57 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-33-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,696 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 58 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-38-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

8,590 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 63 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-39-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

8,563 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 64 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-48-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-49-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,735 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-56-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,486 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-57-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-58-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-59-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,406 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-60-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-61-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-62-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-63-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,420 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-64-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,446 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 116 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-65-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 117 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-66-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,460 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 118 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-67-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 119 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-68-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 120 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-69-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-70-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-71-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-72-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-73-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,674 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-74-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,741 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-75-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-76-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,714 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-77-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-78-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-79-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 153 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-80-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 154 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-81-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 155 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-82-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 156 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-83-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,309 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 157 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-84-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 158 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-85-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,378 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 161 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-86-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,356 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 162 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-87-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 163 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-88-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 164 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-89-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 165 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-90-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 166 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-91-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 167 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-92-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,344 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 168 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-93-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,176 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 171 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-94-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,335 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 172 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-95-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 173 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-96-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 174 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-97-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 175 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-98-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 176 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-99-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,172 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 177 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-100-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 178 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-101-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

73,375 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 187 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-102-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

73,373 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 188 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-103-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

72,048 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 189 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-104-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

73,336 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 197 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-105-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

73,355 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 198 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-106-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

72,031 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 199 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-113-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,339 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-114-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,158 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-115-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,094 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 209 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-116-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 210 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-117-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-118-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-119-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,076 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 219 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-120-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,010 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 220 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-121-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,066 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-122-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,109 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-123-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,058 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-124-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,903 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-125-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,709 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-126-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,223 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-127-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,327 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-128-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,566 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-129-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,256 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-130-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,493 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-131-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,579 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-132-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,016 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-133-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,129 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-134-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-135-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,467 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-136-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,768 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-137-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-138-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,511 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-139-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,507 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-140-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-141-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-142-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,639 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-143-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,915 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 275 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-144-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,290 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 276 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-145-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 280 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-146-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

129,372 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 281 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-147-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,155 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 282 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-148-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 283 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-149-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,695 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 284 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-150-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,670 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 285 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-151-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

128,636 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 286 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-152-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,738 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 290 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-153-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

129,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 291 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-154-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

127,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 292 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-155-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 293 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-156-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 294 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-157-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 295 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-158-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 296 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-159-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

23,100 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 297 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-160-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,002 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-161-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

350,790 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-162-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,769 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-163-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-164-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,067 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-165-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,022 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-166-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,141 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-167-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,079 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 311 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-168-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,724 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 312 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-169-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,039 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 313 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-170-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

350,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-171-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,219 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-172-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,521 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 316 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-173-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,051 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 317 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-174-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

350,760 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-175-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

350,946 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-176-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,267 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-177-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-178-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-179-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,625 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-180-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,374 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-181-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,125 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 331 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-182-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,178 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 332 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-183-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

349,827 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 333 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-184-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,011 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 334 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-185-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

350,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 335 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-186-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,014 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 336 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-187-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,229 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 337 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-188-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,941 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 341 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-189-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,833 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 342 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-190-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,917 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 343 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-191-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,965 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 344 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-192-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,845 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 345 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-193-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 346 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-194-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

353,300 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 347 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-195-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-196-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,868 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-197-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,116 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-198-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-199-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,556 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-200-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,028 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-201-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,291 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-202-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

350,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-203-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,876 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-204-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,019 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-205-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,127 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-206-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-207-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-208-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,575 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-209-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,991 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-210-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,503 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-211-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

351,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-212-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

352,189 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-213-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

184,614 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-214-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

184,476 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-215-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

184,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-216-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

185,169 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-217-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

251,301 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-218-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

251,909 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-219-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

185,400 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-220-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

185,273 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-221-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

184,262 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-222-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

185,453 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-223-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

250,885 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-224-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

250,230 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-225-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

212,399 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-226-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

211,951 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-227-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

211,775 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-228-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

212,847 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-229-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

249,902 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-230-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

251,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-231-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

211,653 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-232-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

211,496 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-233-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

211,198 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 533 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-234-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

212,367 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 534 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-235-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

251,482 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-236-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

250,731 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-237-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

56,046 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-238-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-239-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

55,824 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-240-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

55,815 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-241-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

55,778 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-242-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

55,572 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-243-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

55,825 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-244-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

55,592 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-245-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-246-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,771 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-247-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,226 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-248-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,379 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 624 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-249-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,755 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-250-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,793 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-251-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,208 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-252-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,054 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-253-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,692 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-254-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,397 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-255-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-256-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,535 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-257-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-258-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-259-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,321 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-260-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,269 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 644 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-261-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 645 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-262-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 646 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-263-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,324 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 647 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-264-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,766 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 651 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-265-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 652 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-266-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,311 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 653 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-267-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 654 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-268-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,313 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 655 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-269-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,317 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 656 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-270-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,314 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 657 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-271-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 661 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-272-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 662 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-273-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 663 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-274-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,740 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 664 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-275-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 665 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-276-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,682 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 666 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-277-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,676 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 671 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-278-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 672 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-279-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,722 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 673 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-280-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,728 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 674 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-281-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,734 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 675 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-282-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,663 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 676 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-283-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 681 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-284-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,690 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 682 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-285-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,645 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 683 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-286-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,689 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 684 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-287-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,600 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 685 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-288-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,715 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 686 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-289-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 691 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-290-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,090 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 692 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-291-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,105 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 693 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-292-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,114 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 694 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-293-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,107 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 695 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-294-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,361 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-295-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,412 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-296-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,404 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-297-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-298-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,240 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-299-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,206 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-300-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,257 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-301-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,362 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-302-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,413 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-303-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,395 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-304-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,370 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-305-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

44,328 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-306-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,190 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-307-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-308-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 821 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-309-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,921 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 822 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-310-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,930 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 823 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-311-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,553 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 824 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-312-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 825 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-313-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,882 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 826 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-314-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,940 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 827 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-315-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,900 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 828 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-316-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,910 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 829 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-317-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,911 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 830 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-318-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,966 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 831 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-319-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,872 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 832 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-320-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,271 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 833 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-321-5

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,238 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 834 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE.

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine or distilled spirits storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine or distilled spirits stored in this tank shall not exceed 97 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine or distilled spirits storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine or distilled spirits storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine or distilled spirits storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine or distilled spirits storage operations may be determined using the total annual wine or distilled spirits throughput and a single storage emissions factor based on the average ethanol content of the annual wine or distilled spirits throughput; or using the throughputs for different batches of wine or distilled spirits and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-322-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 841 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-323-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 842 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-324-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,747 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 843 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-325-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 844 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-326-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

51,097 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 845 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-327-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

80,687 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 846 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-328-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,716 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 847 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-329-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,745 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 848 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-330-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,892 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 849 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-331-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 850 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-332-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,706 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 851 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-333-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,891 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 852 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-334-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,103 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 853 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-335-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,060 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 854 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-338-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1001 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-339-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,574 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1002 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-340-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,239 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1003 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-341-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,473 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1004 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-342-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,416 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1005 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-343-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,415 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1006 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-344-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1011 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-345-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,424 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1012 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-346-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,433 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1013 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-347-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1014 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-348-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,597 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1015 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-349-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,435 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1016 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-350-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1021 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-351-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1022 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-352-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1023 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-353-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1024 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-354-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1025 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-355-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,628 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1026 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-356-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1027 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-357-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1031 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-358-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1032 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-359-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1033 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-360-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1034 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-361-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1035 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-362-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1036 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-363-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1037 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-364-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1041 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-365-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1042 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-366-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1043 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-367-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1044 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-368-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,557 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1045 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-369-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1046 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-370-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1047 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-371-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,548 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1051 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-372-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1052 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-373-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,647 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1053 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-374-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1054 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-375-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,655 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1055 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-376-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,672 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1056 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-377-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,573 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1057 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-378-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,664 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1061 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-379-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,604 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1062 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-380-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,675 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1063 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-381-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,651 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1064 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-382-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1065 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-383-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1066 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-384-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1067 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-385-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,589 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1068 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-386-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,593 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1069 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-387-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,522 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1070 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-388-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1081 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-389-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1082 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-390-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,707 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1083 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-391-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1084 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-392-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1085 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-393-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,569 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1086 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-394-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,644 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1087 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-395-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,712 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1088 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-396-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,720 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1089 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-397-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,649 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1090 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-398-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1091 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-399-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1092 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-400-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1093 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-401-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,856 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1094 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-402-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1095 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-403-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,817 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1096 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-404-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,871 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1097 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-405-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,821 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1098 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-406-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,853 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1099 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-407-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1101 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-408-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1102 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-409-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1103 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-410-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1104 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-411-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1105 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-412-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1106 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-413-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1107 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-414-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,544 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1108 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-415-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1109 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-416-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1110 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-417-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1111 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-418-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1121 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-419-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1122 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-420-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1123 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-421-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1124 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-422-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1125 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-423-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1126 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-424-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1127 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-425-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1128 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-426-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1129 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-427-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1130 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-428-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1131 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-429-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1141 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-430-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1142 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-431-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1143 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-432-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1144 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-433-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1145 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-434-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1146 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-435-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1147 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-436-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,244 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1148 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-437-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1149 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-438-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1150 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-439-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1151 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-440-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

3,613 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1152 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-441-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1201 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-442-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,432 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1202 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-443-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,471 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1203 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-444-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,247 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1204 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-445-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

101,348 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1205 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-446-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

102,041 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1206 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-447-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

101,637 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1207 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-448-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

101,750 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1208 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-449-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,281 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1211 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-450-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,526 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1212 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-451-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,264 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1213 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-452-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

88,459 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1214 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-453-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

101,234 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1215 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-454-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

101,638 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1216 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-455-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

102,042 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1217 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-456-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

101,703 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1218 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-457-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,867 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1221 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-458-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,030 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1222 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-459-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,869 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1223 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-460-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,854 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1224 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-461-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1225 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-462-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,610 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1226 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-463-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,050 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1227 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-464-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,087 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1228 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-465-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,820 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1231 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-466-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,835 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1232 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-467-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,078 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1233 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-468-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,836 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1234 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-469-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,640 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1235 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-470-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

49,603 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1236 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-471-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,080 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1237 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-472-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,093 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1238 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-473-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1241 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-474-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,512 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1242 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-475-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,381 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1243 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-476-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,495 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1244 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-477-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1245 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-478-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,501 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1246 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-479-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,422 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1247 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-480-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1248 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-481-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,414 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1249 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-482-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1250 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-483-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,532 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1251 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-484-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,633 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1252 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-485-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,565 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1253 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-486-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,442 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1254 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-487-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1255 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-488-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1256 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-489-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,186 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1257 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-490-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,411 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1258 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-491-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,299 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1259 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-492-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,403 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1260 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-493-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1261 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-494-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1262 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-495-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1263 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-496-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1264 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-497-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1265 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-498-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,318 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1266 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-499-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1267 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-500-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,458 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1268 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-501-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1269 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-502-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,425 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1270 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-503-6

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

5.978 MMBTU/HR FULTON NATURAL GAS-FIRED BOILER WITH A FULTON MODEL 102347 LOW NOX BURNER

## **PERMIT UNIT REQUIREMENTS**

---

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-quality natural gas. [District Rules 2201, 4201, 4320, and 4801] Federally Enforceable Through Title V Permit
4. This boiler shall be equipped with an operational, non-resettable, totalizing fuel flow meter that records the quantity of fuel into this boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Heat input rate to this unit shall not exceed 125 MMBtu in any one day (equal to use of 125,000 scf/day of natural gas). [District Rule 2201] Federally Enforceable Through Title V Permit
6. NOx emissions shall not exceed 9 ppmvd @ 3% O<sub>2</sub> (0.011 lb/MMBtu) referenced as NO<sub>2</sub>. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. CO emissions shall not exceed 50 ppmvd @ 3% O<sub>2</sub> (0.037 lb/MMBtu). [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. SOx emissions shall not exceed 0.00285 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
9. PM<sub>10</sub> emissions shall not exceed 0.003 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC emissions shall not exceed 0.004 lb/MMBtu (referenced as methane). [District Rule 2201] Federally Enforceable Through Title V Permit
11. Source testing to measure NOx and CO emissions shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every thirty-six months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

15. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The higher heating value (HHV) of the fuel shall be certified by third-party fuel supplier or determined using ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels, or an alternative method approved by EPA and the District. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Fuel sulfur content shall be determined using EPA Method 11 or Method 15, as appropriate. [District Rule 4320] Federally Enforceable Through Title V Permit
20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. The results of each source test shall be submitted to the District within 60 days after completion of the source test. [District Rule 1081] Federally Enforceable Through Title V Permit
22. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
27. The permittee shall maintain daily records of the fuel combusted (scf/day) in this boiler. [District Rule 2201] Federally Enforceable Through Title V Permit
28. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. An Emission Control Plan and any Authority to Construct (ATC) application required for this unit for compliance with the applicable Tier 2 emission limits of District Rules 4306 and 4320 shall be submitted to the APCO pursuant to Section 6.4 of each rule. The owner or operator of this unit shall comply with all applicable deadlines in Section 7.0 of District Rules 4306 and 4320, including for submission of the Emission Control Plan and any required ATC application, and full compliance with District Rules 4306 and 4320. [District Rules 4306 and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-569-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1229 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-570-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1230 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-571-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1239 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-572-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,184 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1240 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-573-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1271 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-574-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1272 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-575-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1273 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-576-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1274 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-577-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-578-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-579-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-580-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-581-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-582-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-583-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-584-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-585-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-586-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-587-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-588-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-589-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-590-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-591-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-592-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-593-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-594-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-595-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-596-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-597-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1421 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-599-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1422 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-600-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1423 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-601-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1424 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-602-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1425 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-603-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1426 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-604-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1427 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-605-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1428 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-606-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1431 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-607-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1432 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-608-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1433 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-609-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1434 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-610-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1435 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-611-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1436 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-612-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1437 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-613-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

50,550 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1438 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-614-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1441 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-615-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1442 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-616-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1443 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-617-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1444 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-618-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1451 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-619-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1452 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-620-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1453 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-621-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1454 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-622-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1461 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-623-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1462 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-624-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1463 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-625-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1464 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-626-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1465 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-627-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1466 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-628-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1471 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-629-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1472 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-630-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1473 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-631-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1474 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-632-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1475 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-633-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,660 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1476 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-634-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 185 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-635-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 186 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-636-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 193 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-637-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 194 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-638-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 195 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-639-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

74,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 196 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-640-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

ORGANIC WASTE AND FEEDSTOCK MATERIAL RECEIVING, STORAGE, AND MIXING OPERATION.

### **PERMIT UNIT REQUIREMENTS**

---

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. The permittee is allowed to receive the following wastes for the composting operation: green waste, food waste, and construction wood waste. Green waste is defined as any organic waste material generated from gardening, agriculture, or landscaping activities including, but not limited to grass clippings, leave, tree and shrub trimmings, and plant remains. Food waste is defined as table scraps, vegetable and fruit peelings, meat, bones and fish, egg shells, solid dairy products, coffee grounds, bread and toast, paper waste including, but not limited to, napkins, towels, plates, coffee filters, and tea bags. Construction wood waste is defined as any untreated wood materials, including but not limited to, lumber, paper, and cardboard from construction. [District Rule 2010] Federally Enforceable Through Title V Permit
3. The permittee is prohibited to receive the following wastes for the composting operation: biosolids, animal manure, and poultry litter. Biosolids is defined as organic material resulting from the treatment os sewage sludge or wastewater. Animal manure is defines as non-human animal excretions and waste, including, but not limited to, dried solids and urine from cows, cattle, or swine. Poultry litter is defined as poultry excretions and waste, including, but not limited to, dried solids and urine from chickens, turkeys, geese, or ducks. [District Rule 2010] Federally Enforceable Through Title V Permit
4. The quantity of organic waste materials received at this facility shall not exceed 900 wet-tons in any single day and 82,000 wet tons in any one calendar year. For the purposes of this permit, organic waste material is considered to be green waste, food waste, and construction wood waste. [District Rules 2201 and 4566] Federally Enforceable Through Title V Permit
5. PM10 emissions from the receiving, handling, and mixing of the organic waste materials shall not exceed 0.00167 lb-PM10/wet-ton of material received and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC emissions from the storage and processing of the organic waste materials shall not exceed 10.63 lb-VOC/wet-ton of material stored and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
7. NH3 emissions from the storage and processing of the organic waste materials shall not exceed 3.18 lb-NH3/wet-ton of material stored and processed. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The operator shall perform one of the following to organic materials within 10 days of receipt at the facility to satisfy the stockpile requirements: (a). Remove the organic material from the facility; (b). Place the organic material in the active-phase composting windrow and start active phase composting; (c). Cover the organic material with a waterproof cover that have at least a six-foot overlap of adjacent sheets and be securely anchored. [District Rule 4566] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. A daily operations log shall be maintained and shall include the following: (a) The date, type, and weight (in wet tons) of each organic material received; (b). The date each stockpile was initially formed; (c). The date and action taken on each stockpile to satisfy the stockpile requirements; (d). Total quantity and type of each organic waste material stored for composting (in wet tons); (e). Total quantity and type of each organic waste material mixed for composting (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
10. A cumulative annual log shall be maintained and shall indicate the total quantity and type of each organic waste material received (in wet tons). The records shall be updated at least monthly. [District Rule 1070] Federally Enforceable Through Title V Permit
11. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 & 4566] Federally Enforceable Through Title V Permit
12. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-641-4

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

OPEN WINDROW ACTIVE AND CURING PHASE ORGANIC MATERIAL COMPOSTING OPERATION WITH AN INDEPENDENT WATERING SYSTEM SERVING THE ACTIVE-PHASE COMPOSTING WINDROW PILES.

### **PERMIT UNIT REQUIREMENTS**

---

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. PM10 emissions from the organic material composting operation shall not exceed 0.6 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation:  $PM10 \text{ Emissions (lb/day)} = 0.00066 \text{ lb-PM10/wet-ton} \times \text{Total daily quantity of material transferred from the feedstock piles to active-phase composting windrows (in wet-tons/day)}$ . [District Rule 2201] Federally Enforceable Through Title V Permit
3. VOC emissions from the organic material composting operation shall not exceed 360.2 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation:  $VOC \text{ Emissions (lb/day)} = 0.06966 \text{ lb-VOC/wet-ton} \times \text{Total daily quantity of active phase composting piles utilized onsite (in wet-tons/day)} + 0.0095 \text{ lb-VOC/wet-ton} \times \text{Total quantity of curing phase composting piles utilized onsite (in wet-tons/day)}$ . [District Rule 2201] Federally Enforceable Through Title V Permit
4. NH3 emissions from the organic material composting operation shall not exceed 86.0 pounds in any single day. Compliance with this condition shall be demonstrated using the following equation:  $NH3 \text{ Emissions (lb/day)} = 0.017 \text{ lb-NH3/wet-ton} \times \text{Total daily quantity of active phase composting piles utilized onsite (in wet-tons/day)} + 0.0019 \text{ lb-NH3/wet-ton} \times \text{Total daily quantity of curing phase composting piles utilized onsite (in wet-tons/day)}$ . [District Rule 2201] Federally Enforceable Through Title V Permit
5. The total quantity of organic materials composted shall not exceed 82,000 wet tons in any one calendar year. [District Rules 2201 & 4566] Federally Enforceable Through Title V Permit
6. The operator shall implement at least three turns of each organic material composting windrow during the active-phase of the composting process. [District Rule 4566]
7. The operator shall install, maintain, and utilize an independent watering system to apply water to the surface of each active-phase composting windrow prior to turning. The operator shall test each windrow within three hours before turning for adequate water by taking a sample of the organic material in the windrow and passing a "Ball Test". The "Ball Test" is performed by taking a sample of the compostable material from at least three inches below the surface, between the vertical midpoint and the peak of the windrow and forming the sample into a ball using hand pressure. There should be at least enough water in the material to form a ball when compressed by hand, but the ball may break when tapped. If the material cannot form a ball or crumbles during the ball test, then application of additional water to the windrow prior to turning is required until the material passes the ball test. If a rain event occurs prior to turning the windrow, application of additional water to the surface of the windrow will not be required if the material passes the ball test as previously described. [District Rule 4566] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. A daily operations log shall be maintained and shall include the following: (a). The date and time the organic material from the windrow was tested for adequate water content using the "Ball Test" and indicate if the material passed the ball test. If the windrow material did not pass the ball test indicate the corrective action taken; (b). The date and time each windrow was turned; (c). Total quantity of organic material transferred from the feedstock piles to the active-phase composting windrows (in wet tons); (d). Total quantity of active phase composting piles utilized onsite (in wet tons); (e). Total quantity of curing phase composting piles utilized onsite (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
9. A cumulative annual log shall be maintained and shall include the following: (a). Total quantity of active-phase composting piles utilized onsite (in wet tons); (b). Total quantity of curing phase composting piles utilized onsite (in wet tons). The records shall be updated at least monthly. [District Rule 1070] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070 & 4566] Federally Enforceable Through Title V Permit
11. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-642-3

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

FINISHED COMPOST LOADOUT OPERATION.

### **PERMIT UNIT REQUIREMENTS**

---

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. A daily log shall be maintained and shall indicate the number of vehicles used to load out finished compost and the total quantity of finished compost loaded out (in wet tons). [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
3. A cumulative annual log shall be maintained and shall indicate the total quantity of finished compost loaded out (in wet tons). The records shall be updated at least monthly. [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
4. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and San Joaquin County Rule 107] Federally Enforceable Through Title V Permit
5. This permit does not authorize the facility to operate without the required permits from other local, state, or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [District Rules 2070 and 2080] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-643-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B22 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-644-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B24 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-645-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B19 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-646-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B20 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-647-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B21 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-648-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B23 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-649-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B08 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-650-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B09 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-651-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B17 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-652-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

14,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B18 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-653-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B06 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-654-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B07 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-655-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B15 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-656-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

12,700 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B16 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-657-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B04 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-658-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B05 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-659-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B13 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-660-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

8,500 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B14 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-661-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B01 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-662-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B02 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-663-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B03 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-664-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B10 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-665-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B11 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-666-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

6,200 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK B12 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-667-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 352 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-668-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 353 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-669-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 354 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-670-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 355 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-671-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 356 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-672-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 362 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-673-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 363 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-674-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 364 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-675-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 365 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-676-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

200,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 366 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-678-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 712 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-679-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-680-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-681-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-682-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-683-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-684-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-685-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-686-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-687-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-688-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-689-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-690-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 725 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-691-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 726 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-692-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 727 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-693-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 728 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-694-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 729 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-695-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 730 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-696-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 731 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-697-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

70,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 733 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-698-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-699-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-700-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-701-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-702-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-703-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-704-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-705-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-706-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-707-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-708-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-709-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-710-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1537 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-711-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1538 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-712-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1539 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-713-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1540 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-714-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1547 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-715-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1548 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-716-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1549 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-717-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1550 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-718-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1557 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-719-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1558 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-720-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1559 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-721-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON, INSULATED, STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1560 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-722-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2501 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-723-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2502 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-724-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2503 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-725-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2504 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-726-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2511 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-727-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2512 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-728-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2513 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-729-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2514 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-730-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-731-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-732-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-733-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-734-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-735-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-736-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-737-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-738-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-739-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-740-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-741-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON, INSULATED, STAINLESS STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-742-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-743-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1506 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-744-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1515 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-745-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1516 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-746-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1525 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-747-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1526 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-748-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1536 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-749-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK  
1535 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-750-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 230  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-751-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 231  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-752-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 232  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-753-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 233  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-754-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 234  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-755-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 235  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-756-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 236  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-757-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 237  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-758-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 239  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-759-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 243  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-760-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2505 EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-761-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2506  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-762-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2515  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-763-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

25,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2516  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-764-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-765-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-766-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-767-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-768-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1333  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-769-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1334  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-770-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1335  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-771-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

13,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1336  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-772-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1312  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-773-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-774-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-775-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

7,000 GALLON STEEL ENCLOSED TOP, RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318  
EQUIPPED WITH PRESSURE/VACUUM RELIEF VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (4.0 lb-VOC/1,000 gallons) + (Total Annual White Wine Production - gallons) x (1.6 lb-VOC/1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-776-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1545) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-777-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #1546) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-778-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #242) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-779-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #238) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-780-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #240) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-781-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #241) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-782-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #244) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-783-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

60,000 GALLON (OR EQUIVALENT) WINE STORAGE TANK (TANK #245) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed ten times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from permit units N-266-776 through -783, calculated on a rolling 12-month total basis, shall not exceed 5,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
13. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-784-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,433 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1502) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-785-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,443 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1503) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-266-786-2

**EXPIRATION DATE:** 10/31/2020

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,888 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1504) WITH PRESSURE/VACUUM VALVE AND INSULATION

## PERMIT UNIT REQUIREMENTS

1. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
5. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
14. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-786-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,888 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1504) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
5. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
14. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
16. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-787-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,785 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1511) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley Air Pollution Control District*

**PERMIT UNIT:** N-266-788-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,308 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1512) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-789-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,435 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1513) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-790-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1514) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-791-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,537 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1521) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-792-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,932 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1522) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-793-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1523) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-794-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,986 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1524) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-795-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,365 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK #(1531) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-796-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,523 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1532) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-797-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,208 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1533) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-798-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,066 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1534) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-799-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,935 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1541) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-800-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,107 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1542) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-801-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,458 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1543) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-802-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,940 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1544) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-803-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,170 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1551) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-804-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (154,342 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1552) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-805-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

154,000 GALLON NOMINAL (153,842 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1553) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-806-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1161) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-807-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,315 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1162) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-808-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1163) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-809-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,705 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1164) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley Air Pollution Control District*

**PERMIT UNIT:** N-266-810-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,477 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1171) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-811-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,712 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1172) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-812-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,351 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1173) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-813-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,302 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1174) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-814-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,603 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1181) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-815-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,480 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1182) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-816-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,508 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1183) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley* *Air Pollution Control District*

**PERMIT UNIT:** N-266-817-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (102,777 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1184) WITH PRESSURE/VACUUM VALVE AND INSULATION

## **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-818-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,408 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1191) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-819-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,088 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1192) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-820-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (102,901 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1193) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-821-2

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

103,000 GALLON NOMINAL (103,826 GALLON GAUGE) STAINLESS STEEL WINE STORAGE TANK (#1194) WITH PRESSURE/VACUUM VALVE AND INSULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
7. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. Total annual VOC emissions from the tanks under permit units N-266-784 through N-266-821, calculated on a rolling 12-month total basis, shall not exceed 9,000 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility, calculated on a rolling 12-month total basis, shall not exceed 394,298 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation:  $EF = a * P^2 + b * P + c$ ; where EF is the VOC emission factor in pounds of VOC per 1,000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume % (when the ethanol content of wine is 24 volume %, P is equivalent to 0.24),  $a = -0.38194$ ,  $b = 0.97917$  and  $c = 0$ . [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of the 12-month rolling total storage emissions from the tanks under permit units N-266-784 through N-266-821, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. Records of the 12-month rolling total fermentation and total storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit
14. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
15. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-950-1

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

DIATOMACEOUS EARTH (DE) MATERIAL RECEIVING, STORAGE, AND TRANSFER OPERATION CONSISTING OF ONE 8,200 CUBIC FOOT STORAGE SILO SERVED BY FOUR DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTERS, AND THREE ENCLOSED HOPPERS EACH SERVED BY A DYNAMIC AIR MODEL MODU-KLEEN SERIES 343/200 BIN VENT FILTER

### **PERMIT UNIT REQUIREMENTS**

---

1. The bin vent filter shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The bin vent filter cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Emissions shall not exceed 0.00086 lb PM10 per ton of DE processed. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The maximum throughput for the receiving/pre-cleaning operation shall not exceed 50 tons of DE per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum throughput for the transfer to the hoppers shall not exceed 50 tons of DE per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
7. Records of all maintenance of the bin vent filters, including all change outs of filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily records of DE processed shall be maintained, retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-952-1

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

250 BHP (INTERMITTENT) JOHN DEERE MODEL 6068HFC48 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

### **PERMIT UNIT REQUIREMENTS**

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with a non-resettable hour meter with a minimum display capability of 9,999 hours, unless the District determines that a non-resettable hour meter with a different minimum display capability is appropriate in consideration of the historical use of the engine and the owner or operator's compliance history. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight shall be used. [District Rules 2201 and 4801, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. Emissions from this IC engine shall not exceed any of the following limits: 2.47 g-NOx/bhp-hr, 0.45 g-CO/bhp-hr, or 0.08 g-VOC/bhp-hr. [District Rule 2201, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed 0.07 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 2002 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 2201, 4102, 4701, and 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, emergency usage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
9. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4701, 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** N-266-953-1

**EXPIRATION DATE:** 10/31/2026

**EQUIPMENT DESCRIPTION:**

302 BHP (INTERMITTENT) DOOSAN MODEL D111L RICH-BURN NATURAL GAS-FIRED EMERGENCY STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR

### **PERMIT UNIT REQUIREMENTS**

---

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with an operational non-resettable elapsed time meter. [District Rule 4702 and 40 CFR 60.4237] Federally Enforceable Through Title V Permit
4. This IC engine shall be equipped with a three-way catalyst. [District Rule 2201 and 40 CFR 60.4243] Federally Enforceable Through Title V Permit
5. The air-to-fuel ratio controller must be maintained and operated appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times. [40 CFR 60.4243] Federally Enforceable Through Title V Permit
6. This IC engine shall be fired on Public Utility Commission (PUC) regulated natural gas only. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 0.022 g-NO<sub>x</sub>/bhp-hr, 0.063 g-PM<sub>10</sub>/bhp-hr, 0.216 g-CO/bhp-hr, or 0.254 g-VOC/bhp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60.4243] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, and 40 CFR 60.4243] Federally Enforceable Through Title V Permit
11. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
13. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, and 40 CFR 60.4245] Federally Enforceable Through Title V Permit
14. The operator shall maintain monthly records of the type of fuel used. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
15. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702, and 40 CFR 60.4245] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.