

May 2, 2022

Mr. Michael Donich  
The Wine Group Inc  
2916 S Reed Ave  
Sanger, CA 93657

**Re: Notice of Preliminary Decision – Title V Permit Renewal**  
**Facility Number: C-120**  
**Project Number: C-1203715**

Dear Mr. Donich:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for The Wine Group Inc at 2916 S Reed Ave, Sanger, California.

The notice of preliminary decision for this project has been posted on the District's website ([www.valleyair.org](http://www.valleyair.org)). After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Brian Clements  
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email  
cc: Gerardo Rios, EPA (w/enclosure) via EPS

**Samir Sheikh**  
Executive Director/Air Pollution Control Officer

---

**Northern Region**  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

**Central Region (Main Office)**  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

**Southern Region**  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: (861) 392-5500 FAX: (861) 392-5585

# San Joaquin Valley Air Pollution Control District

FACILITY: C-120-0-2

EXPIRATION DATE: 06/30/2021

## FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1]
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0]
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0]
4. {2288} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {2289} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. {2290} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
8. {2292} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {2293} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: THE WINE GROUP INC  
Location: 2916 S REED AVE, SANGER, CA 93657  
C-120-0-2 : May 10 2022 11:45AM -- BRARG

10. {2294} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {2295} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {2296} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {2297} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {2298} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {2299} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {2300} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {2301} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {2302} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {2303} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {2304} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {2305} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

22. {2306} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. No person shall manufacture, blend, repackage, supply, markets, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 2 of District Rule 4601 (4/16/20), and shall comply with Table 1 and Table 2 effective on and after 1/1/22 of District Rule 4601 (4/16/20) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (4/16/20) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (4/16/20). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {2310} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {2311} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {2312} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

35. {2319} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {2320} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {2321} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {2322} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {2324} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin July 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
44. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2018, and every three years thereafter on or before December 1. [District Rule 4694]
45. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2019, and every three years thereafter on or before July 1. [District Rule 4694]
46. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District every year, on or before March 1. [District Rule 4694]
47. Operators using Certified Emissions Reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-3-9

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION

## PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7.0 ppmv NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.008 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.0076 lb-PM<sub>10</sub>/MMBtu, 400 ppmv CO @ 3% O<sub>2</sub> or 0.296 lb-CO/MMBtu, or 0.004 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NO<sub>x</sub> and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
11. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 1081, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Stack gas velocities for source test purposes shall be determined using EPA Method 2. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Stack gas moisture content for source test purposes shall be determined using EPA Method 4. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Maximum annual heat input of the unit, calculated on a rolling 12 month basis, shall not exceed 140,910 MMBtu per year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall maintain records of the annual heat input per 12 month rolling period, calculated monthly. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-6-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-7-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-8-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,846 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 301

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-9-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

66,237 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 302

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-10-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,898 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 303

DRAFT

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-11-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,986 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 304

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-12-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,202 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 305

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-13-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,724 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 306

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-14-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,380 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 307

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-15-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,931 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 308

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-16-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

32,994 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 309

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-17-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,731 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 310

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-18-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,461 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 311

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-19-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,291 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 312

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-20-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

34,242 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 313

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-21-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,603 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 314

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-22-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,390 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 315

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-23-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,011 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 316

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-24-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,156 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 317

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-25-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,224 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 318

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-26-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,408 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 319

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-27-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

32,743 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 320

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-28-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

32,811 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 321

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-29-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,508 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 322

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-30-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 413

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-31-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,665 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 414

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-32-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,561 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION TANK 415

DRAFT

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-33-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,307 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 416

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-34-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,747 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 417

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-35-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 418

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-36-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,739 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 419

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-37-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,919 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 420

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-38-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,419 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 421

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-39-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,649 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 422

## **PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-40-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,824 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 423

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-41-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 424

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-42-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

42,008 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 425

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-43-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,612 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 426

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-44-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,550 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 427

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-45-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,608 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 428

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-46-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,713 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 429

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-47-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

42,020 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 430

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-48-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,650 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 431

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-49-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,885 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 432

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-50-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,541 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 433

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-51-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,258 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 434

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-52-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,598 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 435

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-53-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,847 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 436

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-54-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,763 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 437

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-55-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,911 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 438

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-56-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,671 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 439

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-57-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,647 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 440

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-58-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,716 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 441

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-59-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,835 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 442

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-60-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,737 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 443

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-61-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,882 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 444

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-62-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,489 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 445

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-63-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,383 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 446

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-64-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,832 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 447

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-65-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,728 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 448

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-66-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,736 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 449 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-67-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 450 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-68-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 451 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-69-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 452 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-70-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 453 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-71-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 454 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-72-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 455 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-73-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 462 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-74-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 463 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley Air Pollution Control District*

**PERMIT UNIT:** C-120-75-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 464 WITH PRESSURE/VACUUM VALVE

## **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-76-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 465 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-77-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 470 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-78-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 471 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-79-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 472 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-80-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 473 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-81-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 474 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-82-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 475 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-83-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 476 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-84-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 477 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-85-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 492 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-86-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 493 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-87-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 494 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-88-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 495 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-89-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 496 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-90-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 497 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-91-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 498 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-92-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,542 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 501

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-93-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,137 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 502

DRAFT

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-94-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,983 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 503

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-95-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

96,175 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 504

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-96-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,754 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 505

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-97-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,201 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 506

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-98-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,625 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 507

DRAFT

---

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-99-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,302 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 508

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-100-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,008 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 509

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-101-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

118,895 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 510

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-102-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,015 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 511

DRAFT

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-103-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

101,516 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 512

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-104-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,076 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 513

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-105-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

118,231 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 514

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-106-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,605 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 515

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-107-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

118,256 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 516

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-108-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,655 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 517

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-109-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,366 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 518

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-110-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

104,801 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 519

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-111-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

105,495 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 520

## **PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-112-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

103,715 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 521

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-113-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

105,085 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 522

DRAFT

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-114-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,097 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 523

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-115-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

81,242 GALLON NON-INSULATED STEEL WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-116-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

81,415 GALLON NON-INSULATED STEEL WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-117-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

81,377 GALLON NON-INSULATED STEEL WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-118-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,655 GALLON NON-INSULATED STEEL WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-119-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-120-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-121-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-122-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-123-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-124-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 533 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-125-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,922 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 534 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-126-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,874 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 535 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-127-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,898 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 536 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-128-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,366 GALLON NON-INSULATED STEEL WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-129-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,479 GALLON NON-INSULATED STEEL WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-130-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,545 GALLON NON-INSULATED STEEL WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-131-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,359 GALLON NON-INSULATED STEEL WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-132-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-133-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,417 GALLON NON-INSULATED STEEL WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-134-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,508 GALLON NON-INSULATED STEEL WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-135-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,626 GALLON NON-INSULATED STEEL WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-136-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,469 GALLON NON-INSULATED STEEL WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-137-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-138-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-139-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-140-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-141-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-142-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 615 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-143-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 616 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-144-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 617 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-145-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 618 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-146-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 619 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-147-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 620 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-148-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-149-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-150-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-151-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 625 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-152-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 626 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-153-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 627 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-154-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 628 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-155-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 630 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-156-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-157-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,629 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-158-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-159-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley Air Pollution Control District*

**PERMIT UNIT:** C-120-160-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 WITH PRESSURE/VACUUM VALVE

## **PERMIT UNIT REQUIREMENTS**

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-161-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-162-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-163-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-164-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 639 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-165-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 640 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-166-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-167-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-168-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-169-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 710 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-170-4

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** C-120-171-4

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

11. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-172-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

12,569 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 713 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-173-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-174-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-175-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-176-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-177-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-178-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-179-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-180-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-181-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-182-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-183-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**FACILITY:** C-120-0-1

**EXPIRATION DATE:** 06/30/2021

### **FACILITY-WIDE REQUIREMENTS**

---

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: THE WINE GROUP INC  
Location: 2916 S REED AVE, SANGER, CA 93657  
C-120-0-1 : May 10 2022 11:52AM -- BRARG

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (8/19/04) or Rule 8011 (8/19/04). [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On June 30, 2010, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin July 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
44. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2018, and every three years thereafter on or before December 1. [District Rule 4694]
45. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2019, and every three years thereafter on or before July 1. [District Rule 4694]
46. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District every year, on or before March 1. [District Rule 4694]
47. Operators using Certified Emissions Reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-3-8

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION

### **PERMIT UNIT REQUIREMENTS**

---

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7.0 ppmv NO<sub>x</sub> @ 3% O<sub>2</sub> or 0.008 lb-NO<sub>x</sub>/MMBtu, 0.00285 lb-SO<sub>x</sub>/MMBtu, 0.0076 lb-PM<sub>10</sub>/MMBtu, 400 ppmv CO @ 3% O<sub>2</sub> or 0.296 lb-CO/MMBtu, or 0.004 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NO<sub>x</sub> and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
11. NO<sub>x</sub> emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 1081, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Stack gas oxygen (O<sub>2</sub>) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. Stack gas velocities for source test purposes shall be determined using EPA Method 2. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Stack gas moisture content for source test purposes shall be determined using EPA Method 4. [District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NO<sub>x</sub>, CO, and O<sub>2</sub> at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. If either the NO<sub>x</sub> or CO concentrations corrected to 3% O<sub>2</sub>, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NO<sub>x</sub>, CO, and O<sub>2</sub> measurements, (2) the O<sub>2</sub> concentration in percent by volume and the measured NO<sub>x</sub> and CO concentrations corrected to 3% O<sub>2</sub>, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 2520, 9.3, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 2520, 9.4.2, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Maximum annual heat input of the unit, calculated on a rolling 12 month basis, shall not exceed 140,910 MMBtu per year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall maintain records of the annual heat input per 12 month rolling period, calculated monthly. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-6-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-7-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-8-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,846 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 301

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-9-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

66,237 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 302

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-10-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,898 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 303

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-11-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,986 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 304

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-12-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,202 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 305

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-13-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

67,724 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 306

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-14-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,380 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 307

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-15-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,931 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 308

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-16-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

32,994 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 309

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-17-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,731 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 310

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-18-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,461 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 311

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-19-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,291 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 312

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-20-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

34,242 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 313

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-21-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,603 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 314

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-22-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,390 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 315

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-23-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,011 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 316

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-24-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,156 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 317

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-25-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,224 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 318

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-26-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,408 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 319

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-27-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

32,743 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 320

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-28-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

32,811 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 321

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-29-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

33,508 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 322

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-30-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 413

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-31-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,665 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 414

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-32-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,561 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION TANK 415

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-33-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,307 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 416

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-34-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,747 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 417

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-35-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 418

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-36-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,739 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 419

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-37-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,919 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 420

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-38-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,419 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 421

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-39-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,649 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 422

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-40-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,824 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 423

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-41-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 424

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-42-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

42,008 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 425

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-43-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,612 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 426

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-44-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,550 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 427

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-45-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,608 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 428

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-46-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,713 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 429

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-47-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

42,020 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 430

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-48-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,650 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 431

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-49-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,885 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 432

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-50-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,541 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 433

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-51-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,258 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 434

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-52-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,598 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 435

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-53-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,847 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 436

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-54-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,763 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 437

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-55-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,911 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 438

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-56-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,671 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 439

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-57-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,647 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 440

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-58-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,716 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 441

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-59-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

41,835 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 442

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-60-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,737 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 443

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-61-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,882 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 444

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-62-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,489 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 445

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-63-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,383 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 446

**PERMIT UNIT REQUIREMENTS**

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-64-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,832 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 447

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-65-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

40,728 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 448

## PERMIT UNIT REQUIREMENTS

---

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-66-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,736 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 449 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-67-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 450 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-68-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 451 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-69-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 452 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-70-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 453 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-71-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 454 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-72-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 455 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-73-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 462 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-74-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 463 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-75-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 464 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-76-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

14,049 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 465 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-77-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 470 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-78-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 471 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-79-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 472 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-80-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 473 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-81-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 474 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-82-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 475 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-83-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 476 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-84-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 477 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-85-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 492 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-86-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 493 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-87-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 494 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-88-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 495 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-89-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 496 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-90-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 497 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-91-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 498 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-92-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,542 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 501

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-93-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,137 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 502

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-94-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,983 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 503

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-95-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

96,175 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 504

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-96-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,754 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 505

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-97-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,201 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 506

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-98-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

110,625 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 507

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-99-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

111,302 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 508

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-100-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,008 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 509

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-101-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

118,895 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 510

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-102-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,015 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 511

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-103-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

101,516 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 512

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-104-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,076 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 513

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-105-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

118,231 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 514

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-106-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

119,605 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 515

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-107-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

118,256 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 516

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-108-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,655 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 517

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-109-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,366 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 518

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-110-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

104,801 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 519

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-111-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

105,495 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 520

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-112-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

103,715 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 521

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-113-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

105,085 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 522

## PERMIT UNIT REQUIREMENTS

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-114-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,097 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 523

**PERMIT UNIT REQUIREMENTS**

---

1. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-115-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

81,242 GALLON NON-INSULATED STEEL WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-116-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

81,415 GALLON NON-INSULATED STEEL WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-117-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

81,377 GALLON NON-INSULATED STEEL WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-118-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

50,655 GALLON NON-INSULATED STEEL WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-119-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-120-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-121-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-122-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-123-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-124-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 533 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-125-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,922 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 534 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-126-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,874 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 535 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-127-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

5,898 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 536 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-128-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,366 GALLON NON-INSULATED STEEL WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-129-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,479 GALLON NON-INSULATED STEEL WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-130-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,545 GALLON NON-INSULATED STEEL WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-131-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,359 GALLON NON-INSULATED STEEL WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-132-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-133-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,417 GALLON NON-INSULATED STEEL WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-134-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,508 GALLON NON-INSULATED STEEL WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-135-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,626 GALLON NON-INSULATED STEEL WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-136-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,469 GALLON NON-INSULATED STEEL WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-137-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-138-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-139-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-140-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-141-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-142-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 615 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-143-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 616 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-144-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 617 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-145-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 618 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-146-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 619 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-147-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 620 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-148-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-149-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-150-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-151-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 625 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-152-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 626 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-153-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 627 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-154-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 628 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-155-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 630 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-156-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-157-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,629 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-158-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-159-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-160-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-161-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-162-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-163-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-164-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 639 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-165-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 640 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-166-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-167-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-168-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-169-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 710 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-170-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.



11. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-171-3

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage or distilled spirits storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The maximum distilled spirits storage throughput in this tank shall not exceed 75,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The combined maximum distilled spirits storage throughput for the tanks listed in permits C-120-170 and '171 shall not exceed 376,580 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The daily VOC emissions rate for distilled spirits storage shall not exceed 1.437 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The annual VOC emissions rate for distilled spirits storage shall not exceed 0.807 pounds per 1,000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, the volume percent ethanol in the batch, the volume of wine transferred, and the volume of distilled spirits transferred, shall be maintained. [District Rule 2201 and 4694] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-172-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

12,569 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 713 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-173-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-174-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-175-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-176-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.



*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-177-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-178-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-179-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-180-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley  
Air Pollution Control District*

**PERMIT UNIT:** C-120-181-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 WITH PRESSURE/VACUUM VALVE

**PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

*San Joaquin Valley*  
*Air Pollution Control District*

**PERMIT UNIT:** C-120-182-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 WITH PRESSURE/VACUUM VALVE

## PERMIT UNIT REQUIREMENTS

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# *San Joaquin Valley*

## *Air Pollution Control District*

**PERMIT UNIT:** C-120-183-2

**EXPIRATION DATE:** 06/30/2021

**EQUIPMENT DESCRIPTION:**

349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 WITH PRESSURE/VACUUM VALVE

### **PERMIT UNIT REQUIREMENTS**

---

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694, 6.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

**SAN JOAQUIN VALLEY  
AIR POLLUTION CONTROL DISTRICT**

**Proposed Title V Permit Renewal Evaluation  
The Wine Group Inc.  
C-120**

**TABLE OF CONTENTS**

---

I.	PROPOSAL.....	1
II.	FACILITY LOCATION .....	1
III.	EQUIPMENT LISTING .....	2
IV.	GENERAL PERMIT TEMPLATE USAGE .....	2
V.	SCOPE OF EPA AND PUBLIC REVIEW .....	2
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS .....	2
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE .....	5
VIII.	PERMIT REQUIREMENTS .....	7
X.	PERMIT SHIELD.....	15
XI.	CALIFORNIA ENVIRONMENTAL QUALITY ACT.....	16
XII.	PERMIT CONDITIONS .....	16
XIII.	ATTACHMENTS .....	16

- A. DRAFT RENEWED TITLE V OPERATING PERMIT
- B. PREVIOUS TITLE V OPERATING PERMIT
- C. DETAILED SUMMARY LIST OF FACILITY PERMITS
- D. DISTRICT RULE 4601 STRINGENCY ANALYSIS



# TITLE V PERMIT RENEWAL EVALUATION

## Winery

**Engineer:** Gurpreet Brar

**Date:** May 2, 2022

**Facility Number:** C-120  
**Facility Name:** The Wine Group Inc  
**Mailing Address:** 2916 S Reed Ave  
Sanger, CA 93657

**Contact Name:** Michael Donich  
**Title:** Executive Vice President Operations/Manager  
**Phone:** (559) 286-8367

**Responsible Official:** Michael Donich  
**Title:** Executive Vice President Operations/Manager

**Project # :** C-1203715  
**Deemed Complete:** September 23, 2020

---

### I. PROPOSAL

The Wine Group Inc was issued its initial Title V permit on June 30, 2010. The Title V permit was previously renewed in 2016. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

### II. FACILITY LOCATION

The facility is located at 2916 S Reed Ave in Sanger, California.

### **III. EQUIPMENT LISTING**

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

### **IV. GENERAL PERMIT TEMPLATE USAGE**

The applicant does not propose to use any model general permit templates.

### **V. SCOPE OF EPA AND PUBLIC REVIEW**

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

### **VI. FEDERALLY ENFORCEABLE REQUIREMENTS**

#### **A. Rules Updated or Evaluated**

- District Rule 2201, New and Modified Stationary Source Review Rule (amended April 21, 2011 – SIP version ⇒ amended August 15, 2019 – non-SIP version)
- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001– SIP version ⇒ amended August 15, 2019 – non-SIP version)
- District Rule 4306, Boilers, Steam Generators, and Process Heaters - Phase 3 (amended October 16, 2008 – SIP version ⇒ amended December 17, 2020 – non-SIP version)
- District Rule 4320, Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater Than 5.0 MMBtu/hr (amended October 16, 2008 – SIP version ⇒ last amended December 17, 2020 – non-SIP version)

- District Rule 4601, Architectural Coatings (amended December 17, 2009 – SIP version ⇒ amended April 16, 2020 – Non-SIP version)
- 40 CFR 63 Subpart JJJJJJ, National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boiler Area Sources (amended September 14, 2016)
- 40 CFR Part 64, Compliance Assurance Monitoring (CAM) (adopted October 22, 1997)
- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners (amended May 6, 2021)
- 40 CFR Part 82, Subpart F, Recycling and Emission Reduction (amended May 6, 2021)

#### **B. Rules Removed**

- Merced County Rule 109, Equipment Breakdown (SIP approved June 18, 1982)
- San Joaquin County Rule 110, Equipment Breakdown (SIP approved December 5, 1984)
- Fresno County Rule 110, Equipment Breakdown (SIP approved August 22, 1977 ⇒ District resolution to rescind from SIP February 17, 2022)
- Stanislaus County Rule 110, Equipment Breakdown (SIP approved June 1, 1983 ⇒ District resolution to rescind from SIP February 17, 2022)
- Kern County Rule 111, Equipment Breakdown (SIP approved October 24, 1980 ⇒ District resolution to rescind from SIP February 17, 2022)
- Kings County Rule 111, Equipment Breakdown (SIP approved, last amended June 18, 1982 ⇒ District resolution to rescind from SIP February 17, 2022)
- Tulare County Rule 111, Equipment Breakdown (SIP approved August 22, 1977 ⇒ District resolution to rescind from SIP February 17, 2022)
- Madera County Rule 113, Equipment Breakdown (SIP approved November 18, 1983 ⇒ District resolution to rescind from SIP February 17, 2022)

### **C. Rules Added**

There are no applicable rules that were added since the previous Title V was issued.

### **D. Rules Not Updated**

- District Rule 1070, Inspections (amended December 17, 1992)
- District Rule 1080, Stack Monitoring (amended December 17, 1992)
- District Rule 1081, Source Sampling (amended December 16, 1993)
- District Rule 2010, Permits Required (amended December 17, 1992)
- District Rule 2020, Exemptions (amended December 18, 2014)
- District Rule 2031, Transfer of Permits (amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080, Conditional Approval (amended December 17, 1992)
- District Rule 2410, Prevention of Significant Deterioration (adopted June 16, 2011)
- District Rule 4101, Visible Emissions (amended February 17, 2005)
- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)
- District Rule 4202, Particulate Matter - Emission Rate (amended December 17, 1992)
- District Rule 4301, Fuel Burning Equipment (amended December 17, 1992)
- District Rule 4304, Equipment Tuning Procedure for Boilers, Steam Generators and Process Heaters (adopted October 19, 1995)

- District Rule 4305, Boilers, Steam Generators, and Process Heaters - Phase 2 (amended August 21, 2003)
- District Rule 4351, Boilers, Steam Generators, and Process Heaters - Phase 1 (amended August 21, 2003)
- District Rule 4694, Wine Fermentation and Storage Tanks (adopted December 15, 2005)
- District Rule 4801, Sulfur Compounds (amended December 17, 1992)
- District Rule 8011, General Requirements (amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, and Extraction Activities (amended August 19, 2004)
- District Rule 8031, Bulk Materials (amended August 19, 2004)
- District Rule 8041, Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Open Area (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Areas (amended September 16, 2004)
- 40 CFR Part 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units (amended February 16, 2012)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos (amended July 20, 2004)

## **VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE**

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit."

For this facility, the following are not federally enforceable and will not be discussed in further detail:

**A. Rules Added**

None

**B. Rules Updated**

None

**C. Rules Not Updated**

- District Rule 1100, Equipment Breakdown (amended December 17, 1992)

The following condition is based on this rule and is therefore not federally enforceable through Title V:

Permit Unit	Permit Conditions
C-120-0-2	1 and 2

- District Rule 1160, Emission Statements (adopted November 18, 1992)

The following condition is based on this rule and is therefore not federally enforceable through Title V:

Permit Unit	Permit Condition
C-120-0-2	3

- District Rule 2040, Applications (amended December 17, 1992)

The following condition is based on this rule and is therefore not federally enforceable through Title V:

Permit Unit	Permit Condition
C-120-0-2	7

- District Rule 4102, Nuisance (amended December 17, 1992)

The following condition is based on this rule and is therefore not federally enforceable through Title V:

Permit Units	Permit Conditions
C-120-0-2	42

- District Rule 4694, Wine Fermentation and Storage Tanks (adopted December 15, 2005)

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any winery fermenting wine and/or storing wine in bulk containers.

The rule was adopted on December 15, 2005 and submitted to EPA for approval into the State Implementation Plan (SIP). On August 18, 2011, the District approved an amended SIP submittal which excludes the fermentation provisions of the rule while maintaining the storage provisions. Therefore, the fermentation provisions are not federally enforceable whereas all other provisions of this rule are federally enforceable.

The following conditions are based on this rule and are not Federally Enforceable through Title V:

Draft Permits	Permit Conditions
C-120-0-2	43 through 47
C-120-30-3 through -65-3	1
C-120-66-3 through -169-3, -172-3 through -183-3	5
C-120-170-4 through -171-4	10

## VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the last TV renewal in 2016.

**A. Fresno County Rule 110, Stanislaus County Rule 110, San Joaquin County Rule 110, Merced County Rule 109, Madera County Rule 113, Kern County Rule 111, Kings County Rule 111, and Tulare County Rule 111 - Equipment Breakdown**

In accordance with EPA's State Implementation Plan (SIP) Call, on February 17, 2022, the District rescinded Fresno County Rule 110, Kern County Rule 111, Kings County Rule 111, Madera County Rule 113, Stanislaus County Rule 110, and Tulare County Rule 111 from the San Joaquin Valley SIP.

Since the facility is not located within Merced or San Joaquin County, it is not subject to the requirements of San Joaquin County Rule 110 or Merced County Rule 109 and the reference to these rules will be removed from conditions #1 and 2 on draft facility-wide permit C-120-0-2. Therefore, proposed conditions #1 and 2 on draft facility-wide permit C-120-0-2 are no longer Federally Enforceable due to the removal of all county rules as shown below.

- {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; ~~County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)~~] Y
- {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; ~~County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)~~] Y

**B. District Rule 2201 - New and Modified Stationary Source Review Rule**

District Rule 2201 has been amended since this Title V permit was last renewed. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit. The updated requirements of this rule are therefore not applicable at this time.



**C. District Rule 2520 - Federally Mandated Operating Permits**

This rule has been amended since the issuance of the initial TV permit, but the last amended version of the rule is not SIP approved. Additionally, the amendments to this rule do not have any effect on current permit requirements. However, only greenhouse gas emissions will be addressed under Rule 2520 during this renewal.

Greenhouse Gas Discussion

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

**D. District Rule 4306 - Boilers, Steam Generators, and Process Heaters - Phase 3**

This rule limits NOx and CO emissions from boilers, steam generators and process heaters rated greater than 5 MMBtu/hr. The facility has one 40.26 MMBtu/hr natural gas-fired boiler (permit unit C-120-3) that is subject to the requirements of this rule.

The unit is in compliance with the current SIP version of the rule and will also comply with the emission limits of the last amended non-SIP approved version of the rule as summarized in the following table:

Table 1: Tier 1 NOx and CO Limits					
Category	Operated on Gaseous Fuel			Operated on Liquid Fuel	
	NOx Limit		CO Limit (ppmv)	NOx Limit	CO Limit (ppmv)
	Standard Option	Enhanced Option			
C. Oilfield Steam Generators	15 ppmv or 0.018 lb/MMBtu	No option	400	40 ppmv or 0.052 lb/MMBtu	400

Table 2: Tier 2 NOx and CO Limits				
Category	Operated on Gaseous Fuel		Operated on Liquid Fuel	
	NOx Limit	CO Limit (ppmv)	NOx Limit	CO Limit (ppmv)
C. Oilfield Steam Generators				
1. Units with a total rated heat input > 5.0 MMBtu/hr and ≤ 20.0 MMBtu/hr	9 ppmv or 0.011 lb/MMBtu	400	40 ppmv or 0.052 lb/MMBtu	400
2. Units with a total rated heat input > 20.0 MMBtu/hr and ≤ 75.0 MMBtu/hr	9 ppmv or 0.011 lb/MMBtu	400	40 ppmv or 0.052 lb/MMBtu	400
3. Units with a total rated heat input > 75.0 MMBtu/hr	7 ppmv or 0.0085 lb/MMBtu	400	40 ppmv or 0.052 lb/MMBtu	400
4. Units firing on less than 50%, by volume, PUC quality gas	15 ppmv or 0.018 lb/MMBtu	400	40 ppmv or 0.052 lb/MMBtu	400

Since the unit at this facility that is subject to this rule is currently in compliance with the current SIP version of the rule and recent non-SIP approved version of the rule, no further discussion of the requirements of this rule is necessary.

**E. District Rule 4320 - Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater Than 5.0 MMBtu/hr**

This rule limits NOx, CO, SO<sub>2</sub> and PM<sub>10</sub> emissions from boilers, steam generators and process heaters rated greater than 5 MMBtu/hr. The facility has one 40.26 MMBtu/hr natural gas-fired boiler (permit unit C-120-3) that is subject to the requirements of this rule.

The unit is in compliance with the current SIP approved version of the rule. However, the last amended version of the rule, which is not SIP approved, requires a lower NOx emission limit for this unit. The following table from the non-SIP version of the rule specifies the applicable NOx emission limits, Emission Control Plan, Authority to Construct, and compliance deadlines:

Table 2: Tier 2 NOx Emission Limits				
Category	NOx Limit	Emission Control Plan	Authority to Construct	Compliance Deadline
<b>C. Oilfield Steam Generators</b>				
1. Units with a total rated heat input > 5.0 MMBtu/hr and ≤ 20.0 MMBtu/hr	6 ppmv or 0.0073 lb/MMBtu	May 1, 2022	May 1, 2022	December 31, 2023
2. Units with a total rated heat input > 20.0 MMBtu/hr and ≤ 75.0 MMBtu/hr	5 ppmv or 0.0061 lb/MMBtu	May 1, 2022	May 1, 2022	December 31, 2023
3. Units with a total rated heat input > 75.0 MMBtu/hr	5 ppmv or 0.0061 lb/MMBtu	May 1, 2022	May 1, 2022	December 31, 2023
4. Units firing on less than 50%, by volume, PUC quality gas	5 ppmv or 0.0061 lb/MMBtu	May 1, 2022	May 1, 2022	December 31, 2023

Since the unit at this facility that is subject to this rule is currently in compliance with the current SIP version of the rule, and no compliance deadlines for the most recent non-SIP approved rule have passed, no further discussion of the requirements of this rule is necessary.

**F. District Rule 4601 - Architectural Coatings**

This rule limits the emissions of VOC's from architectural coatings. It requires limiting the application of any architectural coating to no more than what is listed in the Tables 1 and 2 of Section 5.0 of the amended rule. This rule specifies architectural coatings storage, cleanup, and labeling requirements.

The rule was amended in April 16, 2020 but had not been SIP approved. The stringency analysis in Attachment D shows that the amended rule is as stringent as the SIP approved version of the rule that was adopted in December 17, 2009.

The following changes were included in the latest rule amendment that resulted in revising current permit requirements:

- The tables outlining the VOC content of different specialty coatings and colorants have been largely replaced with the Table 1 and Table 2 in Section 5.0.

The updated conditions 23, 24 and 25 on the draft facility-wide permit C-120-0-2 will assure compliance with the requirements of this rule.

**G. 40 CFR 63 Subpart JJJJJJ - National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boiler Area Sources**

Section 63.1193 states that Subpart JJJJJJ is applicable to owners and operators of an industrial, commercial, or institutional boiler that is located at, or is part of, an area source of Hazardous Air Pollutant (HAP) emissions.

Section 63.11195(e) states that gas-fired boilers are not subject to the requirements of this Subpart. The natural gas-fired boiler at this facility under permit unit C-102-4 1 qualifies as a gas-fired boiler; therefore, it is not subject to the requirements of this subpart, and no further discussion is required.

**H. 40 CFR Part 64 - Compliance Assurance Monitoring (CAM)**

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

1. the unit must have an emission limit for the pollutant;
2. the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), SCR system, baghouses, and thermal/catalytic oxidizers; and
3. the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
VOC	20,000
NO <sub>x</sub>	20,000
CO	200,000
PM <sub>10</sub>	140,000
SO <sub>x</sub>	140,000

Each permit unit at this facility was evaluated for compliance with CAM requirements during the previous Title V action for this facility. The requirements of this subpart have not been amended since the previous Title V action; however, to ensure continued compliance with the requirements of this subpart, compliance with CAM will be demonstrated in this Title V renewal.

a. C-120-3-9: 40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION

- 1) This unit contains emission limits for NO<sub>x</sub>, SO<sub>x</sub>, PM<sub>10</sub>, CO and VOC.
- 2) This unit is served by a Flue Gas Recirculation (FGR) system to control NO<sub>x</sub> emissions. There are no add-on controls for SO<sub>x</sub>, PM<sub>10</sub>, VOC, or CO emissions. Therefore, this unit is not subject to CAM for SO<sub>x</sub>, PM<sub>10</sub>, VOC, or CO emissions
- 3) The FGR system will be assumed to have a 70% control efficiency.

**Pre-control Annual PE:**

$$\begin{aligned} PE &= EF \text{ (lb/MMBtu)} \times \text{Heat Input (MMBtu/hr)} \times 8,760 \text{ hr/year} \\ &= (0.008 \text{ lb-NO}_x\text{/MMBtu}) \times (140,910 \text{ MMBtu/year}) \\ &= \mathbf{1,127 \text{ lb-NO}_x\text{/year}} \end{aligned}$$

$$\begin{aligned} \text{Pre-control PE} &= PE \div (1 - CE) \\ &= (1,127 \text{ lb-NO}_x\text{/year}) \div (1 - 0.7) \\ &= \mathbf{3,758 \text{ lb-NO}_x\text{/year}} \end{aligned}$$

Since 3,758 lb-NO<sub>x</sub>/yr < 20,000 lb-NO<sub>x</sub>/yr (Major Source threshold for NO<sub>x</sub>), this unit is not subject to CAM for NO<sub>x</sub> emissions.

b. C-120-6-3 through -183-3 – Wine Fermentation and/or Storage Tanks

These wine fermentation and/or storage tanks are not equipped with add-on or external control equipment. Since these tank permits are not equipped with add-on control devices, they are not subject to the CAM requirements of 40 CFR Subpart 64.

**I. 40 CFR Part 82 Subpart B - Servicing of Motor Vehicle Air Conditioners**

Per §82.30(a) the purpose of 40 CFR Part 82 Subpart B is to implement section 609 of the Clean Air Act, as amended regarding the servicing of motor vehicle air conditioners (MVACs), and to implement section 608 of the Clean Air Act regarding certain servicing, maintenance, repair and disposal of air conditioners in MVACs and MVAC-like appliances (as that term is defined in 40 CFR 82.152).

Per §82.30(b) these regulations apply to any person performing service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner.

The amendments to this subpart did not have any effect on the current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this subpart:

Permit	Permit Condition
C-120-0-2	28

**J. 40 CFR Part 82 Subpart F - Recycling and Emissions Reductions**

Per §82.150(a) the purpose of 40 CFR Part 82 Subpart F is to reduce emissions of class I and class II refrigerants and their substitutes to the lowest achievable level by maximizing the recapture and recycling of such refrigerants during the service, maintenance, repair, and disposal of appliances and restricting the sale of refrigerants consisting in whole or in part of a class I and class II ODS in accordance with Title VI of the Clean Air Act.

Per §82.150(b) these regulations apply to any person servicing, maintaining, or repairing appliances. This subpart also applies to persons disposing of appliances, including small appliances and motor vehicle air conditioners. In addition, this subpart applies to refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

The amendments to this subpart did not have any effect on the current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this subpart:

Permit	Permit Condition
C-120-0-2	27

## X. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

### A. Requirements Addressed by Model General Permit Templates

The applicant does not propose to use any model general permit templates.

### B. Requirements not Addressed by Model General Permit Templates

The applicant does not propose to use any model general permit templates.

### C. Obsolete Permit Shields From Existing Permit Requirements

The facility had received permit shield from the county rules during the previous renewals by using model general permit template SJV-UM-0-3. However, the facility has not proposed to use any model general permit template in this renewal and there are few county rules have been removed from the San Joaquin Valley SIP recently and also the facility is not subject to rest of the county rules in the permit shield condition #39 as discussed in Section VII.A. Therefore, the permit shield from all the county rules will be removed from condition #39 on draft facility-wide permit C-120-0-2.

- {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), ~~Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings),~~ and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Y

## **XI. California Environmental Quality Act**

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

## **XII. PERMIT CONDITIONS**

See Attachment A - Draft Renewed Title V Operating Permit

## **XIII. ATTACHMENTS**

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Summary List of Facility Permits
- D. District Rule 4601 Stringency Analysis



---

# ATTACHMENT A

Draft Renewed Title V Operating Permit

---

---

# ATTACHMENT B

Previous Title V Operating Permit

---

---

# ATTACHMENT C

Detailed Summary List of Facility Permits

---

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

<b>THE WINE GROUP INC</b> <b>2916 S REED AVE</b> <b>SANGER, CA 93657</b>	FAC # STATUS: TELEPHONE:	<b>C 120</b> <b>A</b> <b>2095994111</b>	TYPE: TOXIC ID:	<b>TitleV</b> <b>51899</b>	EXPIRE ON: AREA: INSP. DATE:	<b>06/30/2021</b> <b>7 /</b> <b>06/22</b>
--	--------------------------------	---	--------------------	-------------------------------	------------------------------------	---

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-3-8	40.26 MMBtu/hr	3020-02 H	1	1,238.00	1,238.00	A	40.26 MMBTU/HR TRANE MURRAY NATURAL GAS-FIRED BOILER WITH A CLEAVER BROOKS PROFIRE MODEL NT420NGX-19 ULTRA LOW NOX BURNER AND FLUE GAS RECIRCULATION
C-120-6-2	13,632 gallons	3020-05 B	1	113.00	113.00	A	13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE
C-120-7-2	13,632 gallons	3020-05 B	1	113.00	113.00	A	13,632 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE
C-120-8-2	67,846 gallons	3020-05 D	1	223.00	223.00	A	67,846 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 301
C-120-9-2	66,237 gallons	3020-05 D	1	223.00	223.00	A	66,237 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 302
C-120-10-2	67,898 gallons	3020-05 D	1	223.00	223.00	A	67,898 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 303
C-120-11-2	67,986 gallons	3020-05 D	1	223.00	223.00	A	67,986 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 304
C-120-12-2	67,202 gallons	3020-05 D	1	223.00	223.00	A	67,202 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 305
C-120-13-2	67,724 gallons	3020-05 D	1	223.00	223.00	A	67,724 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 306
C-120-14-2	33,380 gallons	3020-05 C	1	165.00	165.00	A	33,380 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 307
C-120-15-2	33,931 gallons	3020-05 C	1	165.00	165.00	A	33,931 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 308
C-120-16-2	32,994 gallons	3020-05 C	1	165.00	165.00	A	32,994 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 309
C-120-17-2	33,731 gallons	3020-05 C	1	165.00	165.00	A	33,731 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 310
C-120-18-2	33,461 gallons	3020-05 C	1	165.00	165.00	A	33,461 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 311
C-120-19-2	33,291 gallons	3020-05 C	1	165.00	165.00	A	33,291 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 312
C-120-20-2	34,242 gallons	3020-05 C	1	165.00	165.00	A	34,242 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 313
C-120-21-2	33,603 gallons	3020-05 C	1	165.00	165.00	A	33,603 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 314
C-120-22-2	33,390 gallons	3020-05 C	1	165.00	165.00	A	33,390 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 315
C-120-23-2	33,011 gallons	3020-05 C	1	165.00	165.00	A	33,011 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 316
C-120-24-2	33,156 gallons	3020-05 C	1	165.00	165.00	A	33,156 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 317
C-120-25-2	33,224 gallons	3020-05 C	1	165.00	165.00	A	33,224 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 318
C-120-26-2	33,408 gallons	3020-05 C	1	165.00	165.00	A	33,408 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 319
C-120-27-2	32,743 gallons	3020-05 C	1	165.00	165.00	A	32,743 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 320
C-120-28-2	32,811 gallons	3020-05 C	1	165.00	165.00	A	32,811 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 321

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-29-2	33,508 gallons	3020-05 C	1	165.00	165.00	A	33,508 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 322
C-120-30-2	40,681 gallons	3020-05 C	1	165.00	165.00	A	40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 413
C-120-31-2	40,665 gallons	3020-05 C	1	165.00	165.00	A	40,665 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 414
C-120-32-2	40,561 gallons	3020-05 C	1	165.00	165.00	A	40,561 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION TANK 415
C-120-33-2	40,307 gallons	3020-05 C	1	165.00	165.00	A	40,307 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 416
C-120-34-2	40,747 gallons	3020-05 C	1	165.00	165.00	A	40,747 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 417
C-120-35-2	40,681 gallons	3020-05 C	1	165.00	165.00	A	40,681 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 418
C-120-36-2	41,739 gallons	3020-05 C	1	165.00	165.00	A	41,739 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 419
C-120-37-2	41,919 gallons	3020-05 C	1	165.00	165.00	A	41,919 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 420
C-120-38-2	41,419 gallons	3020-05 C	1	165.00	165.00	A	41,419 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 421
C-120-39-2	41,649 gallons	3020-05 C	1	165.00	165.00	A	41,649 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 422
C-120-40-2	41,824 gallons	3020-05 C	1	165.00	165.00	A	41,824 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 423
C-120-41-2	41,718 gallons	3020-05 C	1	165.00	165.00	A	41,718 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 424
C-120-42-2	42,008 gallons	3020-05 C	1	165.00	165.00	A	42,008 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 425
C-120-43-2	41,612 gallons	3020-05 C	1	165.00	165.00	A	41,612 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 426
C-120-44-2	41,550 gallons	3020-05 C	1	165.00	165.00	A	41,550 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 427
C-120-45-2	41,608 gallons	3020-05 C	1	165.00	165.00	A	41,608 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 428
C-120-46-2	41,718 gallons	3020-05 C	1	165.00	165.00	A	41,713 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 429
C-120-47-2	42,020 gallons	3020-05 C	1	165.00	165.00	A	42,020 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 430

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-48-2	41,650 gallons	3020-05 C	1	165.00	165.00	A	41,650 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 431
C-120-49-2	41,885 gallons	3020-05 C	1	165.00	165.00	A	41,885 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 432
C-120-50-2	41,541 gallons	3020-05 C	1	165.00	165.00	A	41,541 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 433
C-120-51-2	41,258 gallons	3020-05 C	1	165.00	165.00	A	41,258 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 434
C-120-52-2	41,598 gallons	3020-05 C	1	165.00	165.00	A	41,598 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 435
C-120-53-2	41,847 gallons	3020-05 C	1	165.00	165.00	A	41,847 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 436
C-120-54-2	41,736 gallons	3020-05 C	1	165.00	165.00	A	41,763 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 437
C-120-55-2	41,911 gallons	3020-05 C	1	165.00	165.00	A	41,911 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 438
C-120-56-2	41,671 gallons	3020-05 C	1	165.00	165.00	A	41,671 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 439
C-120-57-2	41,647 gallons	3020-05 C	1	165.00	165.00	A	41,647 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 440
C-120-58-2	41,716 gallons	3020-05 C	1	165.00	165.00	A	41,716 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 441
C-120-59-2	41,835 gallons	3020-05 C	1	165.00	165.00	A	41,835 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 442
C-120-60-2	40,736 gallons	3020-05 C	1	165.00	165.00	A	40,737 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 443
C-120-61-2	40,882 gallons	3020-05 C	1	165.00	165.00	A	40,882 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 444
C-120-62-2	40,489 gallons	3020-05 C	1	165.00	165.00	A	40,489 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 445
C-120-63-2	40,383 gallons	3020-05 C	1	165.00	165.00	A	40,383 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 446
C-120-64-2	40,832 gallons	3020-05 C	1	165.00	165.00	A	40,832 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 447
C-120-65-2	40,728 gallons	3020-05 C	1	165.00	165.00	A	40,728 GALLON CONCRETE ENCLOSED TOP RED WINE FERMENTATION AND WINE STORAGE TANK 448

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-66-2	10,736 gallons	3020-05 B	1	113.00	113.00	A	10,736 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 449 WITH PRESSURE/VACUUM VALVE
C-120-67-2	50,230 gallons	3020-05 D	1	223.00	223.00	A	50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 450 WITH PRESSURE/VACUUM VALVE
C-120-68-2	50,230 gallons	3020-05 D	1	223.00	223.00	A	50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 451 WITH PRESSURE/VACUUM VALVE
C-120-69-2	50,230 gallons	3020-05 D	1	223.00	223.00	A	50,230 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 452 WITH PRESSURE/VACUUM VALVE
C-120-70-2	51,745 gallons	3020-05 D	1	223.00	223.00	A	51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 453 WITH PRESSURE/VACUUM VALVE
C-120-71-2	51,745 gallons	3020-05 D	1	223.00	223.00	A	51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 454 WITH PRESSURE/VACUUM VALVE
C-120-72-2	51,745 gallons	3020-05 D	1	223.00	223.00	A	51,745 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 455 WITH PRESSURE/VACUUM VALVE
C-120-73-2	14,049 gallons	3020-05 B	1	113.00	113.00	A	14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 462 WITH PRESSURE/VACUUM VALVE
C-120-74-2	14,069 gallons	3020-05 B	1	113.00	113.00	A	14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 463 WITH PRESSURE/VACUUM VALVE
C-120-75-2	14,049 gallons	3020-05 B	1	113.00	113.00	A	14,049 GALLON NON-INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 464 WITH PRESSURE/VACUUM VALVE
C-120-76-2	14,049 gallons	3020-05 B	1	113.00	113.00	A	14,049 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 465 WITH PRESSURE/VACUUM VALVE
C-120-77-2	127,875 gallons	3020-05 E	1	296.00	296.00	A	127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 470 WITH PRESSURE/VACUUM VALVE
C-120-78-2	127,875 gallons	3020-05 E	1	296.00	296.00	A	127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 471 WITH PRESSURE/VACUUM VALVE
C-120-79-2	127,875 gallons	3020-05 E	1	296.00	296.00	A	127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 472 WITH PRESSURE/VACUUM VALVE

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-80-2	127,875 gallons	3020-05 E	1	296.00	296.00	A	127,875 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 473 WITH PRESSURE/VACUUM VALVE
C-120-81-2	28,087 gallons	3020-05 C	1	165.00	165.00	A	28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 474 WITH PRESSURE/VACUUM VALVE
C-120-82-2	28,087 gallons	3020-05 C	1	165.00	165.00	A	28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 475 WITH PRESSURE/VACUUM VALVE
C-120-83-2	28,087 gallons	3020-05 C	1	165.00	165.00	A	28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 476 WITH PRESSURE/VACUUM VALVE
C-120-84-2	28,087 gallons	3020-05 C	1	165.00	165.00	A	28,087 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 477 WITH PRESSURE/VACUUM VALVE
C-120-85-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 492 WITH PRESSURE/VACUUM VALVE
C-120-86-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 493 WITH PRESSURE/VACUUM VALVE
C-120-87-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON NON-INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 494 WITH PRESSURE/VACUUM VALVE
C-120-88-2	110,412 gallons	3020-05 E	1	296.00	296.00	A	110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 495 WITH PRESSURE/VACUUM VALVE
C-120-89-2	110,412 gallons	3020-05 E	1	296.00	296.00	A	110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 496 WITH PRESSURE/VACUUM VALVE
C-120-90-2	110,412 gallons	3020-05 E	1	296.00	296.00	A	110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 497 WITH PRESSURE/VACUUM VALVE
C-120-91-2	110,412 gallons	3020-05 E	1	296.00	296.00	A	110,412 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 498 WITH PRESSURE/VACUUM VALVE
C-120-92-2	111,543 gallons	3020-05 E	1	296.00	296.00	A	111,542 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 501
C-120-93-2	111,137 gallons	3020-05 E	1	296.00	296.00	A	111,137 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 502
C-120-94-2	110,983 gallons	3020-05 E	1	296.00	296.00	A	110,983 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 503
C-120-95-2	96,175 gallons	3020-05 D	1	223.00	223.00	A	96,175 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 504



**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-96-2	111,754 gallons	3020-05 E	1	296.00	296.00	A	111,754 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 505
C-120-97-2	110,201 gallons	3020-05 E	1	296.00	296.00	A	110,201 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 506
C-120-98-2	110,625 gallons	3020-05 E	1	296.00	296.00	A	110,625 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 507
C-120-99-2	111,302 gallons	3020-05 E	1	296.00	296.00	A	111,302 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 508
C-120-100-2	119,008 gallons	3020-05 E	1	296.00	296.00	A	119,008 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 509
C-120-101-2	118,895 gallons	3020-05 E	1	296.00	296.00	A	118,895 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 510
C-120-102-2	119,015 gallons	3020-05 E	1	296.00	296.00	A	119,015 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 511
C-120-103-2	101,516 gallons	3020-05 E	1	296.00	296.00	A	101,516 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 512
C-120-104-2	119,076 gallons	3020-05 E	1	296.00	296.00	A	119,076 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 513
C-120-105-2	118,231 gallons	3020-05 E	1	296.00	296.00	A	118,231 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 514
C-120-106-2	119,605 gallons	3020-05 E	1	296.00	296.00	A	119,605 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 515
C-120-107-2	118,256 gallons	3020-05 E	1	296.00	296.00	A	118,256 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 516
C-120-108-2	182,655 gallons	3020-05 E	1	296.00	296.00	A	182,655 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 517
C-120-109-2	182,366 gallons	3020-05 E	1	296.00	296.00	A	182,366 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 518
C-120-110-2	104,801 gallons	3020-05 E	1	296.00	296.00	A	104,801 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 519
C-120-111-2	105,495 gallons	3020-05 E	1	296.00	296.00	A	105,495 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 520
C-120-112-2	103,715 gallons	3020-05 E	1	296.00	296.00	A	103,715 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 521
C-120-113-2	105,085 gallons	3020-05 E	1	296.00	296.00	A	105,085 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 522

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-114-2	106,097 gallons	3020-05 E	1	296.00	296.00	A	106,097 GALLON CONCRETE ENCLOSED TOP WINE STORAGE TANK 523
C-120-115-2	81,242 gallons	3020-05 D	1	223.00	223.00	A	81,242 GALLON NON-INSULATED STEEL WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE
C-120-116-2	81,415 gallons	3020-05 D	1	223.00	223.00	A	81,415 GALLON NON-INSULATED STEEL WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE
C-120-117-2	81,377 gallons	3020-05 D	1	223.00	223.00	A	81,377 GALLON NON-INSULATED STEEL WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE
C-120-118-2	50,655 gallons	3020-05 D	1	223.00	223.00	A	50,655 GALLON NON-INSULATED STEEL WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE
C-120-119-2	5,438 gallons	3020-05 B	1	113.00	113.00	A	5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE
C-120-120-2	5,438 gallons	3020-05 B	1	113.00	113.00	A	5,438 GALLON NON-INSULATED STAINLESS STEEL WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE
C-120-121-2	37,658 gallons	3020-05 C	1	165.00	165.00	A	37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE
C-120-122-2	37,658 gallons	3020-05 C	1	165.00	165.00	A	37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE
C-120-123-2	37,658 gallons	3020-05 C	1	165.00	165.00	A	37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE
C-120-124-2	37,658 gallons	3020-05 C	1	165.00	165.00	A	37,658 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 533 WITH PRESSURE/VACUUM VALVE
C-120-125-2	5,922 gallons	3020-05 B	1	113.00	113.00	A	5,922 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 534 WITH PRESSURE/VACUUM VALVE
C-120-126-2	5,874 gallons	3020-05 B	1	113.00	113.00	A	5,874 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 535 WITH PRESSURE/VACUUM VALVE
C-120-127-2	5,898 gallons	3020-05 B	1	113.00	113.00	A	5,898 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK 536 WITH PRESSURE/VACUUM VALVE
C-120-128-2	93,366 gallons	3020-05 D	1	223.00	223.00	A	93,366 GALLON NON-INSULATED STEEL WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE
C-120-129-2	93,479 gallons	3020-05 D	1	223.00	223.00	A	93,479 GALLON NON-INSULATED STEEL WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE
C-120-130-2	93,545 gallons	3020-05 D	1	223.00	223.00	A	93,545 GALLON NON-INSULATED STEEL WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE
C-120-131-2	93,359 gallons	3020-05 D	1	223.00	223.00	A	93,359 GALLON NON-INSULATED STEEL WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-132-2	93,583 gallons	3020-05 D	1	223.00	223.00	A	93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE
C-120-133-2	93,417 gallons	3020-05 D	1	223.00	223.00	A	93,417 GALLON NON-INSULATED STEEL WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE
C-120-134-2	93,508 gallons	3020-05 D	1	223.00	223.00	A	93,508 GALLON NON-INSULATED STEEL WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE
C-120-135-2	93,626 gallons	3020-05 D	1	223.00	223.00	A	93,626 GALLON NON-INSULATED STEEL WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE
C-120-136-2	93,469 gallons	3020-05 D	1	223.00	223.00	A	93,469 GALLON NON-INSULATED STEEL WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE
C-120-137-2	93,583 gallons	3020-05 D	1	223.00	223.00	A	93,583 GALLON NON-INSULATED STEEL WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE
C-120-138-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 WITH PRESSURE/VACUUM VALVE
C-120-139-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON INSULATED STEEL WHITE WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 WITH PRESSURE/VACUUM VALVE
C-120-140-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 WITH PRESSURE/VACUUM VALVE
C-120-141-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 614 WITH PRESSURE/VACUUM VALVE
C-120-142-2	182,785 gallons	3020-05 E	1	296.00	296.00	A	182,785 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 615 WITH PRESSURE/VACUUM VALVE
C-120-143-2	307,391 gallons	3020-05 E	1	296.00	296.00	A	307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 616 WITH PRESSURE/VACUUM VALVE
C-120-144-2	307,391 gallons	3020-05 E	1	296.00	296.00	A	307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 617 WITH PRESSURE/VACUUM VALVE
C-120-145-2	307,391 gallons	3020-05 E	1	296.00	296.00	A	307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 618 WITH PRESSURE/VACUUM VALVE
C-120-146-2	307,391 gallons	3020-05 E	1	296.00	296.00	A	307,391 GALLON INSULATED STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 619 WITH PRESSURE/VACUUM VALVE
C-120-147-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 620 WITH PRESSURE/VACUUM VALVE
C-120-148-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 621 WITH PRESSURE/VACUUM VALVE

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-149-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 622 WITH PRESSURE/VACUUM VALVE
C-120-150-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 623 WITH PRESSURE/VACUUM VALVE
C-120-151-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 625 WITH PRESSURE/VACUUM VALVE
C-120-152-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 626 WITH PRESSURE/VACUUM VALVE
C-120-153-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 627 WITH PRESSURE/VACUUM VALVE
C-120-154-2	106,062 gallons	3020-05 E	1	296.00	296.00	A	106,062 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 628 WITH PRESSURE/VACUUM VALVE
C-120-155-2	260,529 gallons	3020-05 E	1	296.00	296.00	A	260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 630 WITH PRESSURE/VACUUM VALVE
C-120-156-2	260,529 gallons	3020-05 E	1	296.00	296.00	A	260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 WITH PRESSURE/VACUUM VALVE
C-120-157-2	260,629 gallons	3020-05 E	1	296.00	296.00	A	260,629 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 WITH PRESSURE/VACUUM VALVE
C-120-158-2	260,529 gallons	3020-05 E	1	296.00	296.00	A	260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 WITH PRESSURE/VACUUM VALVE
C-120-159-2	260,529 gallons	3020-05 E	1	296.00	296.00	A	260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 WITH PRESSURE/VACUUM VALVE
C-120-160-2	260,529 gallons	3020-05 E	1	296.00	296.00	A	260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 WITH PRESSURE/VACUUM VALVE
C-120-161-2	260,529 gallons	3020-05 E	1	296.00	296.00	A	260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 WITH PRESSURE/VACUUM VALVE
C-120-162-2	260,529 gallons	3020-05 E	1	296.00	296.00	A	260,529 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 WITH PRESSURE/VACUUM VALVE

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-163-2	258,548 gallons	3020-05 E	1	296.00	296.00	A	258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 WITH PRESSURE/VACUUM VALVE
C-120-164-2	258,548 gallons	3020-05 E	1	296.00	296.00	A	258,548 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 639 WITH PRESSURE/VACUUM VALVE
C-120-165-2	349,273 gallons	3020-05 E	1	296.00	296.00	A	349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 640 WITH PRESSURE/VACUUM VALVE
C-120-166-2	349,273 gallons	3020-05 E	1	296.00	296.00	A	349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 WITH PRESSURE/VACUUM VALVE
C-120-167-2	349,273 gallons	3020-05 E	1	296.00	296.00	A	349,273 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 WITH PRESSURE/VACUUM VALVE
C-120-168-2	349,457 gallons	3020-05 E	1	296.00	296.00	A	349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 WITH PRESSURE/VACUUM VALVE
C-120-169-2	22,612 gallons	3020-05 C	1	165.00	165.00	A	22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 710 WITH PRESSURE/VACUUM VALVE
C-120-170-3	22,612 gallons	3020-05 C	1	165.00	165.00	A	22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE
C-120-171-3	10,620 gallons	3020-05 B	1	113.00	113.00	A	10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE AND DISTILLED SPIRITS STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE
C-120-172-2	12,569 gallons	3020-05 B	1	113.00	113.00	A	12,569 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 713 WITH PRESSURE/VACUUM VALVE
C-120-173-2	22,612 gallons	3020-05 C	1	165.00	165.00	A	22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 WITH PRESSURE/VACUUM VALVE
C-120-174-2	22,612 gallons	3020-05 C	1	165.00	165.00	A	22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 WITH PRESSURE/VACUUM VALVE
C-120-175-2	10,620 gallons	3020-05 B	1	113.00	113.00	A	10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 WITH PRESSURE/VACUUM VALVE
C-120-176-2	10,620 gallons	3020-05 B	1	113.00	113.00	A	10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 WITH PRESSURE/VACUUM VALVE

**Detailed Facility Report**  
For Facility=120 and excluding Deleted Permits  
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-120-177-2	22,612 gallons	3020-05 C	1	165.00	165.00	A	22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 WITH PRESSURE/VACUUM VALVE
C-120-178-2	22,612 gallons	3020-05 C	1	165.00	165.00	A	22,612 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 WITH PRESSURE/VACUUM VALVE
C-120-179-2	10,620 gallons	3020-05 B	1	113.00	113.00	A	10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 WITH PRESSURE/VACUUM VALVE
C-120-180-2	10,620 gallons	3020-05 B	1	113.00	113.00	A	10,620 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 WITH PRESSURE/VACUUM VALVE
C-120-181-2	349,457 gallons	3020-05 E	1	296.00	296.00	A	349,457 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 WITH PRESSURE/VACUUM VALVE
C-120-182-2	349,090 gallons	3020-05 E	1	296.00	296.00	A	349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 723 WITH PRESSURE/VACUUM VALVE
C-120-183-2	349,090 gallons	3020-05 E	1	296.00	296.00	A	349,090 GALLON INSULATED STAINLESS STEEL WHITE WINE FERMENTATION AND WINE STORAGE TANK 724 WITH PRESSURE/VACUUM VALVE

Number of Facilities Reported: 1

---

# ATTACHMENT D

District Rule 4601 Stringency Analysis

---

**Stringency Comparison of District Rule 4601 Non-SIP Version (4/16/20) to Current SIP Version (12/17/09)**

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
<p><b>2.0 Applicability</b></p>	<p>This rule is applicable to any person who supplies, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating for use within the District.</p>	<p>This rule is applicable to any person who supplies, markets, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating for use within the District.</p>	<p><b>The only change is to include applicability of this rule to the person marketing the coatings, therefore, non-SIP version of rule is more stringent than SIP version.</b></p>
<p><b>4.0 Exemptions</b></p>	<p>4.1 The provisions of this rule shall not apply to:</p> <p>4.1.1 Any architectural coating that is supplied, sold, offered for sale, or manufactured for use outside of the District or for shipment to other manufacturers for reformulation or repackaging.</p> <p>4.1.2 Any aerosol coating product.</p> <p>4.2 With the exception of Section 6.2, the provisions of this rule shall not apply to any architectural coating that is sold in a container with a volume of one liter (1.057 quarts) or less.</p>	<p>4.1 The provisions of this rule shall not apply to:</p> <p>4.1.1 Any architectural coating that is supplied, sold, offered for sale, or manufactured for use outside of the District or for shipment to other manufacturers for reformulation or repackaging.</p> <p>4.1.2 Any aerosol coating product.</p> <p>4.2 With the exception of Section 6.2 and Section 4.3, the provisions of this rule shall not apply to any architectural coating that is sold in a container with a volume of one liter (1.057 quarts) or less, provided the following requirements are met:</p> <p>4.2.1 The coating container is not bundled together with other containers of the same specific coating category (listed in Table 1) to be sold as a unit that exceeds one liter (1.057 quart), excluding containers packed together for shipping to a retail outlet, and</p> <p>4.2.2 The label or any other product literature does not suggest combining multiple containers of the same specific category (listed in Table 1) so that the combination exceeds one liter (1.057 quart).</p> <p>4.3 On and after sixty days following the effective date of EPA final rulemaking that the conditions described in Clean Air Act Sections 172(c)(9) and 182(c)(9) have occurred in the San Joaquin Valley regarding the 2008 8-hour Ozone National Ambient Air Quality Standard, the categories of coatings listed below shall no longer be exempt from the provisions of Table 1 of this rule when sold in containers having capacities of one liter (1.057 quarts) or less:</p> <p>4.3.1 Bituminous Roof Coatings;</p>	<p><b>The exemptions for colorant and for architectural coatings sold in a container with a volume of one liter (1.057 quarts) or less have been added to the rule in order to make the amended rule consistent with the exemptions presented in 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</b></p>



Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
		<p>4.3.2 Flat Coatings that are sold in containers having capacities greater than eight fluid ounces;</p> <p>4.3.3 Magnesite Cement Coatings;</p> <p>4.3.4 Multi-Color Coatings;</p> <p>4.3.5 Nonflat Coatings that are sold in containers having capacities greater than eight fluid ounces;</p> <p>4.3.6 Pre-Treatment Wash Primers;</p> <p>4.3.7 Reactive Penetrating Sealers;</p> <p>4.3.8 Shellacs (Clear and Opaque);</p> <p>4.3.9 Stone Consolidants;</p> <p>4.3.10 Swimming Pool Coatings;</p> <p>4.3.11 Tub and Tile Refinishing Coatings;</p> <p>4.3.12 Wood Coatings, including Lacquers, Varnishes, and Sanding Sealers; and</p> <p>4.3.13 Wood Preservatives.</p> <p>4.4 Colorant added at the factory or at the worksite is not subject to the VOC limits in Table 2. In addition, containers of colorant sold at the point of sale for use in the field or on a job site are also not subject to the VOC limit in Table 2.</p>	
<p><b>5.0 Requirements</b></p>	<p>5.1 VOC Content Limits: Except as provided in Sections 5.2 and 5.3, no person shall: manufacture, blend, or repackage for use within the District; or supply, sell, or offer for sale within the District; or solicit for application or apply within the District any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards 1 or the Table of Standards 2, after the specified effective date in the Table of Standards 1 or the Table of Standards 2. Limits are expressed as VOC Regulatory, thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.</p> <p>5.2 Most Restrictive VOC Limit: If a coating meets the definition in Section 3.0 for one or more specialty coating categories listed in the Table of Standards 1 or the Table of Standards 2, then that coating is not required to meet the VOC limits for Flat, Nonflat, or Nonflat – High Gloss coatings, but is required to meet the VOC limit for the applicable specialty coating listed in the Table of Standards 1 or the Table of Standards 2.</p> <p>5.2.1 Effective until December 31, 2010, with the exception of the specialty coating categories specified in Section 5.2.3.1 through 5.2.3.15, if a coating is recommended for use in more than one of the specialty coating categories listed in the Table</p>	<p>5.1 VOC Content Limits: Except as provided in Sections 5.2 and 5.3, no person shall: manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2, after the specified effective date in Table 1 or Table 2. Limits are expressed as VOC Regulatory, thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.</p> <p>5.2 Most Restrictive VOC Limit: If a coating meets the definition in Section 3.0 for one or more specialty coating categories listed in Table 1 or, then that coating is not required to meet the VOC limits for Flat or Nonflat coatings, but is required to meet the VOC limit for the applicable specialty coating listed in Table 1 or . With the exception of the specialty coating categories specified in Sections 5.2.1 through 5.2.12, if a coating is recommended for use in more than one of the specialty coating categories listed in Table 1, then the most restrictive (or lowest) VOC content limit shall apply. This requirement applies to: usage recommendations that appear anywhere on the coating</p>	<p><b>The Table of Standards 1 and the Table of Standard 2 have been replaced with more stringent Table 1 with VOC content limit for coatings and Table 2 with VOC content limit for colorants with more stringent VOC limits as shown in the tables at the end of this document. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</b></p> <p><b>The VOC limit of the non-SIP version is at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</b></p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>of Standards 1, the most restrictive (or lowest) VOC content limit shall apply.</p> <p>5.2.2 Effective on and after January 1, 2011, with the exception of the specialty coating categories specified in Sections 5.2.3.2, 5.2.3.3, 5.2.3.5 through 5.2.3.9, and 5.2.3.14 through 5.2.3.18, if a coating is recommended for use in more than one of the specialty coating categories listed in the Table of Standards 2, the most restrictive (or lowest) VOC content limit shall apply.</p> <p>5.2.3 This requirement applies to: usage recommendations that appear anywhere on the coating container, anywhere on any label or sticker affixed to the container, or in any sales, advertising, or technical literature supplied by a manufacturer or anyone acting on their behalf.</p> <p>5.2.3.1 Lacquer coatings (including lacquer sanding sealers)</p> <p>5.2.3.2 Metallic pigmented coatings</p> <p>5.2.3.3 Shellacs</p> <p>5.2.3.4 Fire-retardant coatings</p> <p>5.2.3.5 Pretreatment wash primers</p> <p>5.2.3.6 Industrial maintenance coatings</p> <p>5.2.3.7 Low-solids coatings</p> <p>5.2.3.8 Wood preservatives</p> <p>5.2.3.9 High temperature coatings</p> <p>5.2.3.10 Temperature-indicator safety coatings</p> <p>5.2.3.11 Antenna coatings</p> <p>5.2.3.12 Antifouling coatings</p> <p>5.2.3.13 Flow coatings</p> <p>5.2.3.14 Bituminous roof primers</p> <p>5.2.3.15 Specialty primers, sealers and undercoaters</p> <p>5.2.3.16 Aluminum roof coatings</p> <p>5.2.3.17 Zinc-rich primers</p> <p>5.2.3.18 Wood Coatings</p>	<p>container, anywhere on any label or sticker affixed to the container, or in any sales, advertising, or technical literature supplied by a manufacturer or anyone acting on their behalf.</p> <p>5.2.1 Metallic pigmented coatings;</p> <p>5.2.2 Shellacs;</p> <p>5.2.3 Pretreatment wash primers;</p> <p>5.2.4 Industrial maintenance coatings;</p> <p>5.2.5 Low-solids coatings;</p> <p>5.2.6 Wood preservatives;</p> <p>5.2.7 High temperature coatings;</p> <p>5.2.8 Bituminous roof primers;</p> <p>5.2.9 Specialty primers, sealers and undercoaters;</p> <p>5.2.10 Aluminum roof coatings;</p> <p>5.2.11 Zinc-rich primers; and</p> <p>5.2.12 Wood Coatings.</p>	
	<p>5.3 Sell-Through of Coatings: A coating manufactured prior to the effective date specified for that coating in the Table of Standards 1 or the Table of Standards 2, and that complied with the standards in effect at the time the coating was manufactured, may be sold, supplied, or offered for sale for up to three years after the specified effective date. In addition, a coating manufactured before the effective date specified for that coating in the Table of Standards 1 or the Table of Standards 2 may be applied at any time, both before and after the specified effective date, so long as the coating complied with the standards in effect at the time the coating was manufactured. This Section 5.3 does not apply to any</p>	<p>5.3 Sell-Through of Coatings: 5.3.1 A coating manufactured prior to January 1, 2022, may be sold, supplied, or offered for sale for up to three years after January 1, 2022. In addition, a coating manufactured before January 1, 2022 may be applied at any time, both before and after January 1, 2022, so long as the coating complied with the standards in effect at the time the coating was manufactured. This subsection 5.3.1 does not apply to any coating that does not display the date or date-code required by subsection 6.1.1. 5.3.2 A colorant manufactured prior to January 1, 2022, may be sold, supplied, or offered for sale for up to three years after January 1, 2022. In addition, a</p>	<p><b>The VOC limit of the non-SIP version is at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</b></p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	coating that does not display the date or date-code required by Section 6.1.1.	colorant manufactured before January 1, 2022 may be applied at any time, both before and after January 1, 2022, so long as the colorant complied with the standards in effect at the time the colorant was manufactured. This subsection 5.3.2 does not apply to any colorant that does not display the date or date-code required by subsection 6.1.1.	
	5.4 Painting Practices: All architectural coating containers used to apply the contents therein to a surface directly from the container by pouring, siphoning, brushing, rolling, padding, ragging or other means, shall be closed when not in use. These architectural coating containers include, but are not limited to, drums, buckets, cans, pails, trays or other application containers. Containers of any VOC-containing materials used for thinning and cleanup shall also be closed when not in use.	5.4 Painting Practices: All architectural coating containers used to apply the contents therein to a surface directly from the container by pouring, siphoning, brushing, rolling, padding, ragging or other means, shall be closed when not in use. These architectural coating containers include, but are not limited to, drums, buckets, cans, pails, trays or other application containers. Containers of any VOC-containing materials used for thinning and cleanup shall also be closed when not in use.	<b>No change in the requirements, therefore, non-SIP version of rule is as stringent as SIP version.</b>
	5.5 Thinning: No person who applies or solicits the application of any architectural coating shall apply a coating that is thinned to exceed the applicable VOC limit specified in the Table of Standards 1 or the Table of Standards 2.	5.5 Thinning: No person who applies or solicits the application of any architectural coating shall apply a coating that is thinned to exceed the applicable VOC limit specified in the Table of Standards 1 or the Table of Standards 2.	<b>No change in the requirements, therefore, non-SIP version of rule is as stringent as SIP version.</b>
	5.6 Rust Preventative Coatings: Effective through December 31, 2010, no person shall apply or solicit the application of any rust preventative coating for industrial use, unless such a rust preventative coating complies with the industrial maintenance coating VOC limit specified in the Table of Standards 1.		<b>The VOC limit of the SIP version is no longer applicable at this time and has been removed.</b>
	5.7 Coatings Not Listed in the Table of Standards 1 or the Table of Standards 2: For any coating that does not meet any of the definitions for the specialty coatings categories listed in the Table of Standards 1 or the Table of Standards 2, the VOC content limit shall be determined by classifying the coating as a Flat, Nonflat, or Nonflat – High Gloss coating, based on its gloss, and the corresponding Flat, Nonflat, or Nonflat – High Gloss VOC limit in the Table of Standards 1 or the Table of Standards 2 shall apply.	5.6 Coatings Not Listed in Table 1: For any coating that does not meet any of the definitions for the specialty coatings categories listed in Table 1, the VOC content limit shall be determined by classifying the coating as Flat or Nonflat, based on its gloss, and the corresponding Flat or Nonflat VOC limit in Table 1 shall apply.	<b>The VOC limit of the non-SIP version is at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</b>
		5.7 Colorants: No person within the District shall, at the point of sale of any architectural coating subject to subsection 5.1, add to such coating any colorant that contains VOCs in excess of the corresponding applicable VOC limit specified in Table 2. The point of sale includes retail outlets that add colorant to a coating container to obtain a specific color.	<b>The VOC limit for colorants in non-SIP version more stringent than the SIP version of the rule.</b>
	5.8 Prior to January 1, 2011, any coating that		<b>The VOC limit of the SIP</b>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	meets a definition in Section 3.0 for a coating category listed in the Table of Standards 2 and complies with the applicable VOC limit in the Table of Standards 2 and with Sections 5.2 and 6.1 (including those provision of Section 6.1 otherwise effective on January 1, 2011) shall be considered in compliance with this rule.		version is no longer applicable at this time and has been removed.
	Table of Standards 1 (Effective on and after 1/1/11)	Table 1 VOC Content Limits for Coatings (Effective on and after 1/1/22) (See end of the document for Table Comparison)	<b>The requirements of Table of Standard 1 are more stringent than the Table 1 in the SIP rule. Therefore, non-SIP version of rule is as stringent as SIP version.</b>
	Table of Standards 2 (Effective on and after 1/1/11)	Table 2 VOC Content Limits for Colorants (Effective on and after 1/1/22) (See end of the document for Table Comparison)	<b>VOC content limits for colorants were added under the amended rule. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</b>
<b>6.0 Administrative Requirements</b>	<p>6.1 Labeling Requirements: Each manufacturer of any architectural coating subject to this rule shall display the information listed in Sections 6.1.1 through 6.1.14 on the coating container (or label) in which the coating is sold or distributed.</p> <p>6.1.1 Date Code: The date the coating was manufactured, or a date code representing the date, shall be indicated on the label, lid or bottom of the container. If the manufacturer uses a date code for any coating, the manufacturer shall file an explanation of each code with the Executive Officer of the ARB.</p> <p>6.1.2 Thinning Recommendations: A statement of the manufacturer's recommendation regarding thinning of the coating shall be indicated on the label or lid of the container. This requirement does not apply to the thinning of architectural coatings with water. If thinning of the coating prior to use is not necessary, the recommendation must specify that the coating is to be applied without thinning.</p> <p>6.1.3 VOC Content: Each container of any coating subject to this rule shall display one of the following values, in grams of VOC per liter of coating:</p> <p>6.1.3.1 Maximum VOC Content, as determined from all potential product formulations; or</p> <p>6.1.3.2 VOC Content, as determined</p>	<p>6.1 Labeling Requirements: Each manufacturer of any architectural coating subject to this rule shall display the information listed in Sections 6.1.1 through 6.1.12 on the coating container (or label) in which the coating is sold or distributed.</p> <p>6.1.1 Date Code: The date the coating was manufactured, or a date code representing the date, shall be indicated on the label, lid or bottom of the container. If the manufacturer uses a date code for any coating, the manufacturer shall file an explanation of each code with the Executive Officer of the ARB.</p> <p>6.1.2 Thinning Recommendations: A statement of the manufacturer's recommendation regarding thinning of the coating shall be indicated on the label or lid of the container. This requirement does not apply to the thinning of architectural coatings with water. If thinning of the coating prior to use is not necessary, the recommendation must specify that the coating is to be applied without thinning.</p> <p>6.1.3 VOC Content: Each container of any coating subject to this rule shall display one of the following values, in grams of VOC per liter of coating:</p> <p>6.1.3.1 Maximum VOC Content, as determined from all potential product formulations; or</p>	<b>The non-SIP approved rule contain sections listed in the SIP rule plus additional requirements not found in the SIP version for colorants. Therefore, non-SIP version of rule is as stringent as SIP version.</b>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>from actual formulation data; or</p> <p>6.1.3.3 VOC Content, as determined using the test methods in Section 6.3.2.</p> <p>If the manufacturer does not recommend thinning, the container must display the VOC Content, as supplied. If the manufacturer recommends thinning, the container must display the VOC Content, including the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multicomponent product, the container must display the VOC content as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOCs during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.1.4 Faux Finishing Coatings: Effective January 1, 2011, the labels of all clear topcoat Faux Finishing coatings shall prominently display the statement "This product can only be sold or used as part of a Faux Finishing coating system".</p> <p>6.1.5 Industrial Maintenance Coatings: Each manufacturer of any industrial maintenance coating subject to this rule shall display on the label or lid of the container in which the coating is sold or distributed one or more of the following descriptions listed in Section 6.1.5.1 through 6.1.5.3.</p> <p>6.1.5.1 "For industrial use only"</p> <p>6.1.5.2 "For professional use only"</p> <p>6.1.5.3 "Not for residential use" or "Not intended for residential use"</p> <p>6.1.6 Clear Brushing Lacquers: The labels of all clear brushing lacquers shall prominently display the statements "For brush application only," and "This product must not be thinned or sprayed." (Category deleted effective January 1, 2011.)</p> <p>6.1.7 Rust Preventative Coatings: The labels of all rust preventative coatings shall prominently display the statement "For Metal Substrates Only".</p> <p>6.1.8 Specialty Primers, Sealers and Undercoaters: Effective until December 31, 2010, the labels of all specialty primers, sealers and undercoaters shall prominently display one or more of the descriptions listed in Section 6.1.8.1 through 6.1.8.5. Effective on and after January 1, 2011, the labels of all specialty primers, sealers, and undercoaters shall prominently display one or more of the descriptions listed in</p>	<p>6.1.3.2 VOC Content, as determined from actual formulation data; or</p> <p>6.1.3.3 VOC Content, as determined using the test methods in Section 6.3.2.</p> <p>If the manufacturer does not recommend thinning, the container must display the VOC Content, as supplied. If the manufacturer recommends thinning, the container must display the VOC Content, including the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multicomponent product, the container must display the VOC content as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOCs during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.1.4 Faux Finishing Coatings: The labels of all clear topcoat Faux Finishing coatings shall prominently display the statement "This product can only be sold or used as part of a Faux Finishing coating system".</p> <p>6.1.5 Industrial Maintenance Coatings: Each manufacturer of any industrial maintenance coating subject to this rule shall display on the label or lid of the container in which the coating is sold or distributed one or more of the following descriptions listed in Section 6.1.5.1 through 6.1.5.3.</p> <p>6.1.5.1 "For industrial use only"</p> <p>6.1.5.2 "For professional use only"</p> <p>6.1.6 Rust Preventative Coatings: The labels of all rust preventative coatings shall prominently display the statement "For Metal Substrates Only".</p> <p>6.1.7 Specialty Primers, Sealers and Undercoaters: The labels of all specialty primers, sealers, and undercoaters shall prominently display the statement "Specialty Primer, Sealer, Undercoater"</p> <p>6.1.8 Reactive Penetrating Sealers: The labels of all Reactive Penetrating Sealers shall prominently display the statement "Reactive Penetrating Sealer."</p> <p>6.1.9 Stone Consolidants: The labels of all Stone Consolidants shall prominently display the statement "Stone Consolidant - For Professional Use Only."</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>Sections 6.1.8.1 through 6.1.8.3. On and after January 1, 2011, Sections 6.1.8.4 and 6.1.8.5 will be no longer effective.</p> <p>6.1.8.1 For fire-damaged substrates.</p> <p>6.1.8.2 For smoke-damaged substrates.</p> <p>6.1.8.3 For water-damaged substrates.</p> <p>6.1.8.4 For excessively chalky substrates.</p> <p>6.1.8.5 For blocking stains.</p> <p>6.1.9 Quick Dry Enamels: The labels of all quick dry enamels shall prominently display the words "Quick Dry" and the dry hard time. (Category deleted effective January 1, 2011.)</p> <p>6.1.10 Reactive Penetrating Sealers: Effective January 1, 2011, the labels of all Reactive Penetrating Sealers shall prominently display the statement "Reactive Penetrating Sealer."</p> <p>6.1.11 Stone Consolidants: Effective January 1, 2011, the labels of all Stone Consolidants shall prominently display the statement "Stone Consolidant - For Professional Use Only."</p> <p>6.1.12 Nonflat– High Gloss Coatings: The labels of all Nonflat – high gloss coatings shall prominently display the words "High Gloss."</p> <p>6.1.13 Wood Coatings: Effective January 1, 2011, the labels of all Wood Coatings shall prominently display the statement "For Wood Substrates Only."</p> <p>6.1.14 Zinc Rich Primers: Effective January 1, 2011, the labels of all Zinc Rich Primers shall prominently display one or more of the following descriptions listed in Section 6.1.14.1 through 6.1.14.3.</p> <p>6.1.14.1 "For industrial use only"</p> <p>6.1.14.2 "For professional use only"</p> <p>6.1.14.3 "Not for residential use" or "Not intended for residential use"</p>	<p>6.1.10 Wood Coatings: The labels of all Wood Coatings shall prominently display the statement "For Wood Substrates Only."</p> <p>6.1.11 Zinc Rich Primers: The labels of all Zinc Rich Primers shall prominently display the statement "For professional use only."</p> <p>6.1.12 Colorants: Effective January 1, 2022, each manufacturer of any colorant subject to this rule shall display the information listed in subsections 6.1.12.1 and 6.1.12.2 on the container (or label) in which the colorant is sold or distributed.</p> <p>6.1.12.1 Date Code: The date the colorant was manufactured, or a date code representing the date, shall be indicated on the label, lid, or bottom of the container. If the manufacturer uses a date code for any colorant, the manufacturer shall file an explanation of each code with the APCO.</p> <p>6.1.12.2 VOC Content: Each container of any colorant subject to this rule shall display one of the following values in grams of VOC per liter of colorant.</p> <p>6.1.12.2.1 Maximum VOC Content as determined from all potential product formulations; or</p> <p>6.1.12.2.2 VOC Content as determined from actual formulation data; or</p> <p>6.1.12.2.3 VOC Content as determined using the test methods in subsection 6.3.2.</p> <p>If the colorant contains silanes, siloxanes, or other ingredients that generate ethanol or other VOCs during the curing process, the VOC content must include the VOCs emitted during curing. VOC Content shall be determined as defined in subsections 3.72, 3.73, and 3.74.</p>	
	<p>6.2 Reporting Requirements</p> <p>The reporting requirements specified in Sections 6.2.1 through 6.2.6 shall apply until December 31, 2010.</p> <p>6.2.1 Clear Brushing Lacquers: Each manufacturer of clear brushing lacquers shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall specify the number of gallons of clear brushing lacquers sold in the State during the preceding calendar year, and shall describe the</p>	<p>6.2 Reporting Requirements</p> <p>6.2.1 Sales Data: All sales data listed in Sections 6.2.1.1 to 6.2.1.14 shall be maintained on-site by the responsible official for a minimum of three years. A responsible official from each manufacturer shall upon request of the Executive Officer of CARB, or his or her delegate, provide data concerning the distribution and sales of architectural coatings. Sales data submitted by the responsible official to the Executive Officer of the ARB may be claimed as confidential, and such information shall be handled in</p>	<p><b>All the reporting requirements were removed except the sales data requirements presented in 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings in order to make the amended rule consistent with SCM. Therefore, non-SIP version of rule is as stringent as SIP version.</b></p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>method used by the manufacturer to calculate State sales.</p> <p>6.2.2 Rust Preventative Coatings: Each manufacturer of rust preventative coatings shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall specify the number of gallons of rust preventative coatings sold in the State during the preceding calendar year, and shall describe the method used by the manufacturer to calculate State sales.</p> <p>6.2.3 Specialty Primers, Sealers and Undercoaters: Each manufacturer of specialty primers, sealers and undercoaters shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall specify the number of gallons of specialty primers, sealers and undercoaters sold in the State during the preceding calendar year, and shall describe the method used by the manufacturer to calculate State sales.</p> <p>6.2.4 Toxic Exempt Compounds: For each architectural coating that contains perchloroethylene or methylene chloride, the manufacturer shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB the following information for products sold in the State during the preceding year:</p> <p>6.2.4.1 the product brand name and a copy of the product label with legible usage instructions;</p> <p>6.2.4.2 the product category listed in the Table of Standards 1 or the Table of Standards 2 to which the coating belongs;</p> <p>6.2.4.3 the total sales in California during the calendar year to the nearest gallon;</p> <p>6.2.4.4 the volume percent, to the nearest 0.10 percent, of perchloroethylene and methylene chloride in the coating.</p> <p>6.2.5 Recycled Coatings: Manufacturers of recycled coatings must submit a letter to the Executive Officer of the ARB certifying their status as a Recycled Paint Manufacturer. The manufacturer shall, on or before April 1 of each calendar year beginning with the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall include, for all recycled coatings, the total number of gallons</p>	<p>accordance with the procedures specified in Title 17, California Code of Regulations Sections 91000-91022. The responsible official shall within 180 days provide information, including, but not limited to the data listed in Sections 6.2.1.1 through 6.2.1.14:</p> <p>6.2.1.1 The name and mailing address of the manufacturer;</p> <p>6.2.1.2 The name, address and telephone number of a contact person;</p> <p>6.2.1.3 The name of the coating product as it appears on the label and the applicable coating category;</p> <p>6.2.1.4 Whether the product is marketed for interior or exterior use or both;</p> <p>6.2.1.5 The number of gallons sold in California in containers greater than one liter (1.057 quart) and equal to or less than one liter (1.057 quart);</p> <p>6.2.1.6 The VOC Actual content and VOC Regulatory content in grams per liter. If thinning is recommended, list the VOC Actual content and VOC Regulatory content after maximum recommended thinning. If containers less than one liter have a different VOC content than containers greater than one liter, list separately. If the coating is a multi-component product, provide the VOC content as mixed or catalyzed;</p> <p>6.2.1.7 The names and CAS numbers of the VOC constituents in the product;</p> <p>6.2.1.8 The names and CAS numbers of any compounds in the product specifically exempted from the VOC definition;</p> <p>6.2.1.9 Whether the product is marketed as solvent-borne, waterborne, or 100% solids;</p> <p>6.2.1.10 Description of resin or binder in the product;</p> <p>6.2.1.11 Whether the coating is a single-component or multi-component product;</p> <p>6.2.1.12 The density of the product in pounds per gallon;</p> <p>6.2.1.13 The percent by weight of: solids, all volatile materials, water, and any compounds in the product specifically exempted from the VOC</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>distributed in the State during the preceding year, and shall describe the method used by the manufacturer to calculate State distribution.</p> <p>6.2.6 Bituminous Coatings: Each manufacturer of bituminous roof coatings or bituminous roof primers shall, on or before April 1 of each calendar year beginning with the year 2004, submit an annual report to the Executive Officer of ARB. The report shall specify the number of gallons of bituminous roof coatings or bituminous roof primers sold in the State during the preceding calendar year, and shall describe the method used by the manufacturer to calculate state sales.</p> <p>6.2.7 Effective on and after January 1, 2011, Sales Data: All sales data listed in Sections 6.2.7.1 to 6.2.7.14 shall be maintained on-site by the responsible official for a minimum of three years. A responsible official from each manufacturer shall upon request of the Executive Officer of the ARB, or his or her delegate, provide data concerning the distribution and sales of architectural coatings. Sales data submitted by the responsible official to the Executive Officer of the ARB may be claimed as confidential, and such information shall be handled in accordance with the procedures specified in Title 17, California Code of Regulations Sections 91000-91022. The responsible official shall within 180 days provide information, including, but not limited to the data listed in Sections 6.2.7.1 through 6.2.7.14:</p> <p>6.2.7.1 the name and mailing address of the manufacturer;</p> <p>6.2.7.2 the name, address and telephone number of a contact person;</p> <p>6.2.7.3 the name of the coating product as it appears on the label and the applicable coating category;</p> <p>6.2.7.4 whether the product is marketed for interior or exterior use or both;</p> <p>6.2.7.5 the number of gallons sold in California in containers greater than one liter (1.057 quart) and equal to or less than one liter (1.057 quart);</p> <p>6.2.7.6 the VOC Actual content and VOC Regulatory content in grams per liter. If thinning is recommended, list the VOC Actual content and VOC Regulatory content after maximum recommended</p>	<p>definition; and</p> <p>6.2.1.14 The percent by volume of solids, water, and any compounds in the product specifically exempted from the VOC definition.</p>	



Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>thinning. If containers less than one liter have a different VOC content than containers greater than one liter, list separately. If the coating is a multi-component product, provide the VOC content as mixed or catalyzed;</p> <p>6.2.7.7 the names and CAS numbers of the VOC constituents in the product;</p> <p>6.2.7.8 the names and CAS numbers of any compounds in the product specifically exempted from the VOC definition;</p> <p>6.2.7.9 whether the product is marketed as solvent-borne, waterborne, or 100% solids;</p> <p>6.2.7.10 description of resin or binder in the product;</p> <p>6.2.7.11 whether the coating is a single-component or multi-component product;</p> <p>6.2.7.12 the density of the product in pounds per gallon;</p> <p>6.2.7.13 the percent by weight of: solids, all volatile materials, water, and any compounds in the product specifically exempted from the VOC definition; and</p> <p>6.2.7.14 the percent by volume of: solids, water, and any compounds in the product specifically exempted from the VOC definition.</p>		
	<p>6.3 Test Methods</p> <p>The test methods listed below shall be used to demonstrate compliance with this rule. Alternate equivalent test methods may be used provided the test methods have been approved by the APCO and EPA.</p> <p>6.3.1 Calculation of VOC Content: For the purpose of determining compliance with the VOC content limits in the Table of Standards 1 or the Table of Standards 2, the VOC content of a coating shall be determined as defined in Section 3.77, 3.78, or 3.79 as appropriate. The VOC content of a tint base shall be determined without colorant that is added after the tint base is manufactured. If the manufacturer does not recommend thinning, the VOC Content must be calculated for the product as supplied. If the manufacturer recommends thinning, the VOC Content must be calculated including</p>	<p>6.3 Test Methods</p> <p>The test methods listed below shall be used to demonstrate compliance with this rule. Alternate equivalent test methods may be used provided the test methods have been approved by the APCO and EPA.</p> <p>6.3.1 Calculation of VOC Content: For the purpose of determining compliance with the VOC content limits in Table 1 or the 2, the VOC content of a coating shall be determined as defined in Section 3.71, 3.72, or 3.73 as appropriate. The VOC content of a tint base shall be determined without colorant that is added after the tint base is manufactured. If the manufacturer does not recommend thinning, the VOC Content must be calculated for the product as supplied. If the manufacturer recommends thinning, the VOC Content must be calculated including</p>	<p><b>Numerous definitions were added, deleted or modified in order to make the amended rule consistent with definitions and rule requirements presented in 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</b></p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multi-component product, the VOC content must be calculated as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOC during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.3.2 VOC Content of Coatings: To determine the physical properties of a coating in order to perform the calculations in Section 3.77 and 3.79, the reference method for VOC content is EPA Method 24, except as provided in Sections 6.3.3 and 6.3.16. An alternative method to determine the VOC content of coatings is SCAQMD Method 304-91 (Revised February 1996). The exempt compounds content shall be determined by SCAQMD Method 303-91 (Revised 1993), BAAQMD Method 43 (Revised 1996), or BAAQMD Method 41 (Revised 1995), as applicable. To determine the VOC content of a coating, the manufacturer may use EPA Method 24, or an alternative method as provided in Section 6.3.3, formulation data, or any other reasonable means for predicting that the coating has been formulated as intended (e.g., quality assurance checks, recordkeeping). However, if there are any inconsistencies between the results of EPA Method 24 test and any other means for determining VOC content, the EPA Method 24 test results will govern, except when an alternative method is approved as specified in Section 6.3.3. The District Air Pollution Control Officer (APCO) may require the manufacturer to conduct an EPA Method 24 analysis.</p> <p>6.3.3 Alternative Test Methods: Other test methods demonstrated to provide results that are acceptable for purposes of determining compliance with Section 6.3.2 1, after review and approved in writing by the staffs of the District, ARB and EPA, may also be used.</p> <p>6.3.4 Methacrylate Traffic Marking Coatings: Analysis of methacrylate multicomponent coatings used as traffic marking coatings shall be conducted according to a modification of EPA Method 24 (40 CFR 59, subpart D, Appendix A). This method has not been approved for methacrylate multicomponent coatings used for other purposes than as traffic marking coatings or for other classes of</p>	<p>the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multi-component product, the VOC content must be calculated as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOC during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.3.2 VOC Content of Coatings: To VOC Content of Coatings or Colorants: To determine the physical properties of a coating or colorant in order to perform the calculations in Section 3.71 and 3.73, the reference method for VOC content is EPA Method 24, except as provided in Sections 6.3.3 and 6.3.15. An alternative method to determine the VOC content of coatings or colorants is SCAQMD Method 304-91 (Revised February 1996). The exempt compounds content shall be determined by SCAQMD Method 303-91 (Revised 1996), BAAQMD Method 43 (Revised 2005), or BAAQMD Method 41 (Revised 2005), as applicable. To determine the VOC content of a coating or colorant, the manufacturer may use EPA Method 24, or an alternative method as provided in Section 6.3.4, formulation data, or any other reasonable means for predicting that the coating or colorant has been formulated as intended (e.g., quality assurance checks, recordkeeping). However, if there are any inconsistencies between the results of EPA Method 24 test and any other means for determining VOC content, the EPA Method 24 test results will govern, except when an alternative method is approved as specified in Section 6.3.4. The District Air Pollution Control Officer (APCO) may require the manufacturer to conduct an EPA Method 24 analysis.</p> <p>6.3.3 To determine the VOC content of a coating or colorant with a VOC content of 150 g/l or less, the manufacturer may use SCAQMD Method 313, incorporated by reference in subsection 6.3.34, ASTM D6886-18, incorporated by reference in subsection 6.3.35, or any other reasonable means for predicting that the coating or colorant has been formulated as intended (e.g., quality assurance checks, record keeping).</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>multicomponent coatings.</p> <p>6.3.5 Flame Spread Index: The flame spread index of a fire-retardant coating shall be determined by ASTM E84-07, "Standard Test Method for Surface Burning Characteristics of Building Materials" (see Section 3.0, Fire-Retardant Coating).</p> <p>6.3.6 Fire Resistance Rating: The fire resistance rating of a fire-resistive coating shall be determined by ASTM E119-07, "Standard Test Methods for Fire Tests of Building Construction Materials" (see Section 3.0, Fire-Resistive Coating).</p> <p>6.3.7 Gloss Determination: The gloss of a coating shall be determined by ASTM D523-89 (1999), "Standard Test Method for Specular Gloss" (see Section 3.0, Flat Coating, Nonflat Coating, Nonflat-High Gloss Coating and Quick-Dry Enamel).</p> <p>6.3.8 Metal Content of Coatings: The metallic content of a coating shall be determined by SCAQMD Method 318-95, Determination of Weight Percent Elemental Metal in Coatings by X-Ray Diffraction, <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Metallic Pigmented Coating, Aluminum Roof Coating and Faux Finish).</p> <p>6.3.9 Acid Content of Coatings: The acid content of a coating shall be determined by ASTM D1613-06, "Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer and related products" (see Section 3.0, Pre-Treatment Wash Primer).</p> <p>6.3.10 Drying Times: The set-to-touch, dry-hard, dry-to-touch and dry-to-recoat times of a coating shall be determined by ASTM D1640-95, "Standard Test Methods for Drying, Curing, or Film Formation of Organic Coatings at Room Temperature" (see Section 3.0, Quick-Dry Enamel and Quick-Dry Primer, Sealer and Undercoater) The tack-free time of a quick-dry enamel coating shall be determined by the Mechanical Test Method of ASTM D1640-95. (Category deleted effective January 1, 2011.)</p> <p>6.3.11 Surface Chalkiness: The chalkiness of a surface shall be determined using ASTM D4214-98, "Standard Test Methods for Evaluating the Degree of Chalking of Exterior Paint Films"(see Section 3, Specialty Primer, Sealer and Undercoater). (Category deleted effective January 1, 2011.)</p> <p>6.3.12 Exempt Compounds—Siloxanes:</p>	<p>6.3.4 Alternative Test Methods: Other test methods demonstrated to provide results that are acceptable for purposes of determining compliance with Section 6.3.2 4, after review and approved in writing by the staffs of the District, ARB and EPA, may also be used.</p> <p>6.3.5 Methacrylate Traffic Marking Coatings: Analysis of methacrylate multicomponent coatings used as traffic marking coatings shall be conducted according to a modification of EPA Method 24 (40 CFR 59, subpart D, Appendix A). This method has not been approved for methacrylate multicomponent coatings used for other purposes than as traffic marking coatings or for other classes of multicomponent coatings.</p> <p>6.3.6 Flame Spread Index: The flame spread index of a fire-retardant coating shall be determined by ASTM E84-18B, "Standard Test Method for Surface Burning Characteristics of Building Materials" (see Section 3.0, Fire-Retardant Coating).</p> <p>6.3.7 Fire Resistance Rating: The fire resistance rating of a fire-resistive coating shall be determined by ASTM E119-18ce1, "Standard Test Methods for Fire Tests of Building Construction Materials" (see Section 3.0, Fire-Resistive Coating).</p> <p>6.3.8 Gloss Determination: The gloss of a coating shall be determined by ASTM D523-14 (2018), "Standard Test Method for Specular Gloss" (see Section 3.0, Flat Coating and Nonflat Coating).</p> <p>6.3.9 Metal Content of Coatings: The metallic content of a coating shall be determined by SCAQMD Method 318-95, Determination of Weight Percent Elemental Metal in Coatings by X-Ray Diffraction, <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Metallic Pigmented Coating, Aluminum Roof Coating and Faux Finish).</p> <p>6.3.10 Acid Content of Coatings: The acid content of a coating shall be determined by ASTM D1613-17, "Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer and related products" (see Section 3.0, Pre-Treatment Wash Primer).</p> <p>6.3.11 Exempt Compounds—Siloxanes: Exempt compounds that are cyclic,</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>Exempt compounds that are cyclic, branched, or linear completely methylated siloxanes, shall be analyzed as exempt compounds for compliance with Section 6 by BAAQMD Method 43, "Determination of Volatile Methylsiloxanes in Solvent-Based Coatings, Inks, and Related Materials," <i>BAAQMD Manual of Procedures</i>, Volume III, adopted 11/6/96 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.13 Exempt Compounds—Parachlorobenzotrifluoride (PCBTF): The exempt compound parachlorobenzotrifluoride, shall be analyzed as an exempt compound for compliance with Section 6 by BAAQMD Method 41, "Determination of Volatile Organic Compounds in Solvent Based Coatings and Related Materials Containing Parachlorobenzotrifluoride," <i>BAAQMD Manual of Procedures</i>, Volume III, adopted 12/20/95 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.14 Exempt Compounds: The content of compounds under U.S. EPA Method 24 shall be analyzed by SCAQMD Method 303-91 (Revised 1993), "Determination of Exempt Compounds," <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.15 VOC Content of Coatings: The VOC content of a coating shall be determined by EPA Method 24 as it exists in appendix A of 40 <i>Code of Federal Regulations</i> (CFR) part 60, "Determination of Volatile Matter Content, Water Content, Density, Volume Solids and Weight Solids of Surface Coatings" (see Section 6.3.2).</p> <p>6.3.16 <i>Alternative VOC Content of Coatings: The VOC content of coatings may be analyzed either by U.S. EPA Method 24 or SCAQMD Method 304-91 (Revised 1996), "Determination of Volatile Organic Compounds (VOC) in Various Materials," SCAQMD Laboratory Methods of Analysis for Enforcement Samples.</i></p> <p>6.3.17 Methacrylate Traffic Marking Coatings: The VOC content of methacrylate multicomponent coatings used as traffic marking coatings shall be analyzed by the procedures in 40 CFR part 59, subpart D, appendix A, "Determination of Volatile Matter Content of Methacrylate Multicomponent Coatings Used as Traffic Marking Coatings" (September</p>	<p>branched, or linear completely methylated siloxanes, shall be analyzed as exempt compounds for compliance with Section 6 by BAAQMD Method 43, "Determination of Volatile Methylsiloxanes in Solvent-Based Coatings, Inks, and Related Materials," <i>BAAQMD Manual of Procedures</i>, Volume III, revised 2006 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.12 Exempt Compounds—Parachlorobenzotrifluoride (PCBTF): The exempt compound parachlorobenzotrifluoride, shall be analyzed as an exempt compound for compliance with Section 6 by BAAQMD Method 41, "Determination of Volatile Organic Compounds in Solvent Based Coatings and Related Materials Containing Parachlorobenzotrifluoride," <i>BAAQMD Manual of Procedures</i>, Volume III, revised 2006 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.13 Exempt Compounds: The content of compounds exempted under U.S. EPA Method 24 shall be analyzed by SCAQMD Method 303-91 (Revised 1996), "Determination of Exempt Compounds," <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.14 VOC Content of Coatings: The VOC content of a coating shall be determined by EPA Method 24 as it exists in appendix A of 40 <i>Code of Federal Regulations</i> (CFR) part 60, "Determination of Volatile Matter Content, Water Content, Density, Volume Solids and Weight Solids of Surface Coatings" (see Section 6.3.2).</p> <p>6.3.15 Alternative VOC Content of Coatings: The VOC content of coatings may be analyzed either by U.S. EPA Method 24 or SCAQMD Method 304-91 (Revised 1996), "Determination of Volatile Organic Compounds (VOC) in Various Materials," <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i>.</p> <p>6.3.16 Methacrylate Traffic Marking Coatings: The VOC content of methacrylate multicomponent coatings used as traffic marking coatings shall be analyzed by the procedures in 40 CFR part 59,</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>11, 1998).</p> <p>6.3.18 Hydrostatic Pressure for Basement Specialty Coatings: The hydrostatic pressure resistance for basement specialty coatings shall be analyzed using ASTM D7088-04, "Standard Practice for Resistance to Hydrostatic Pressure for Coatings Used in Below Grade Applications Applied to Masonry".</p> <p>6.3.19 Tub and Tile Refinish Coating Adhesion: The adhesion of tub and tile coating shall be determined by ASTM D4585-99, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D3359-02, "Standard Test Methods for Measuring Adhesion by Tape Test".</p> <p>6.3.20 Tub and Tile Refinish Coating Hardness: The hardness of tub and tile refinish coating shall be determined by ASTM D3363-05, "Standard Test Method for Film Hardness by Pencil Test".</p> <p>6.3.21 Tub and Tile Refinish Coating Abrasion Resistance: Abrasion resistance of tub and tile refinish coating shall be analyzed by ASTM D4060-07, "Standard Test Methods for Abrasion Resistance of Organic Coatings by the Taber Abraser".</p> <p>6.3.22 Tub and Tile Refinish Coating Water Resistance: Water resistance of tub and tile refinish coatings shall be determined by ASTM D4585-99, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D714-02e1, "Standard Test Method for Evaluating Degree of Blistering of Paints".</p> <p>6.3.23 Waterproofing Membrane: Waterproofing membrane shall be tested by ASTM C836-06, "Standard Specification for High Solids Content, Cold Liquid-Applied Elastomeric Waterproofing Membrane for Use with Separate Wearing Course".</p> <p>6.3.24 Mold and Mildew Growth for Basement Specialty Coatings: Mold and mildew growth resistance for basement specialty coatings shall be determined by ASTM D3273-00, "Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings in an Environmental Chamber" and ASTM D3274-95, "Standard Test Method for Evaluating Degree of Surface Disfigurement of Paint Films by Microbial (Fungal or Algal) Growth or Soil and Dirt Accumulation".</p> <p>6.3.25 Reactive Penetrating Sealer Water</p>	<p>subpart D, appendix A, "Determination of Volatile Matter Content of Methacrylate Multicomponent Coatings Used as Traffic Marking Coatings" (September 11, 1998).</p> <p>6.3.17 Hydrostatic Pressure for Basement Specialty Coatings: The hydrostatic pressure resistance for basement specialty coatings shall be analyzed using ASTM D7088-17, "Standard Practice for Resistance to Hydrostatic Pressure for Coatings Used in Below Grade Applications Applied to Masonry".</p> <p>6.3.18 Tub and Tile Refinish Coating Adhesion: The adhesion of tub and tile coating shall be determined by ASTM D4585/4585M-18, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D3359-17, "Standard Test Methods for Measuring Adhesion by Tape Test".</p> <p>6.3.19 Tub and Tile Refinish Coating Hardness: The hardness of tub and tile refinish coating shall be determined by ASTM D3363-05 (2011)e2, "Standard Test Method for Film Hardness by Pencil Test".</p> <p>6.3.20 Tub and Tile Refinish Coating Abrasion Resistance: Abrasion resistance of tub and tile refinish coating shall be analyzed by ASTM D4060-14, "Standard Test Methods for Abrasion Resistance of Organic Coatings by the Taber Abraser".</p> <p>6.3.21 Tub and Tile Refinish Coating Water Resistance: Water resistance of tub and tile refinish coatings shall be determined by ASTM D4585/4585M-18, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D714-02 (2017), "Standard Test Method for Evaluating Degree of Blistering of Paints".</p> <p>6.3.22 Waterproofing Membrane: Waterproofing membrane shall be ASTM C836/836M-18, "Standard Specification for High Solids Content, Cold Liquid-Applied Elastomeric Waterproofing Membrane for Use with Separate Wearing Course".</p> <p>6.3.23 Mold and Mildew Growth for Basement Specialty Coatings: Mold and mildew growth resistance for basement specialty coatings shall be determined by ASTM D3273-16, "Standard Test Method for Resistance to Growth of Mold on the</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>Repellency: Reactive penetrating sealer water repellency shall be analyzed by ASTM C67-07, "Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile"; or ASTM C97-02, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C140-06, "Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units".</p> <p>6.3.26 Reactive Penetrating Sealer Water Vapor Transmission: Reactive penetrating sealer water vapor transmission shall be analyzed ASTM E96/E96M-05, "Standard Test Method for Water Vapor Transmission of Materials".</p> <p>6.3.27 Reactive Penetrating Sealer - Chloride Screening Applications: Reactive penetrating sealers shall be analyzed by National Cooperative Highway Research Report 244 (1981), "Concrete Sealers for the Protection of Bridge Structures".</p> <p>6.3.28 Stone Consolidants: Stone consolidants shall be tested using ASTM E2167-01, "Standard Guide for Selection and Use of Stone Consolidants".</p>	<p>Surface of Interior Coatings in an Environmental Chamber" and ASTM D3274-09 (2017), "Standard Test Method for Evaluating Degree of Surface Disfigurement of Paint Films by Fungal or Algal Growth or Soil and Dirt Accumulation". 6.3.25 Reactive Penetrating Sealer Water Repellency: Reactive penetrating sealer water repellency shall be analyzed by ASTM C67-07, "Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile"; or ASTM C97-02, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C140-06, "Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units".</p> <p>6.3.24 Reactive Penetrating Sealer Water Repellency: Reactive penetrating sealer water repellency shall be analyzed by ASTM C67/C67M-18, "Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile"; or ASTM C97/97M-18, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C140-140M-18a, "Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units"</p> <p>6.3.25 Reactive Penetrating Sealer Water Vapor Transmission: Reactive penetrating sealer water vapor transmission shall be analyzed ASTM E96/E96M-16, "Standard Test Method for Water Vapor Transmission of Materials" or ASTM D6490-99 (2014), "Standard Test Method for Water Vapor Transmission of Nonfilm Forming Treatments Used on Cementitious Panels".</p> <p>6.3.26 Reactive Penetrating Sealer - Chloride Screening Applications: Reactive penetrating sealers shall be analyzed by National Cooperative Highway Research Report 244 (1981), "Concrete Sealers for the Protection of Bridge Structures".</p> <p>6.3.27 Stone Consolidants: Stone consolidants shall be tested using ASTM E2167-01 (2008), "Standard Guide for Selection and Use of Stone Consolidants".</p> <p>6.3.28 Building Envelope Coating Air Permeance of Building Materials: ASTM E2178-13, "Standard Test Method for Air Permeance of Building Materials".</p> <p>6.3.29 Building Envelope Coating Water</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
		<p>Penetration Testing: ASTM E331-00 (2016), "Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference".</p> <p>6.3.30 Building Envelope Coating Water Vapor Transmission: ASTM E96/96M-16, "Standard Test Methods for Water Vapor Transmission of Materials".</p> <p>6.3.31 Tile and Stone Sealers Absorption: ASTM C373-18, "Standard Test Methods for Determination of Water Absorption and Associated Properties by Vacuum Method for Pressed Ceramic Tile and Glass Tiles and Boil Method for Extruded Ceramic Tiles and Non-tile Fired Ceramic Whiteware Products"; or ASTM C97/97M-18, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C642-13, "Standard Test Method for Density, Absorption, and Voids in Hardened Concrete".</p> <p>6.3.32 Tile and Stone Sealers – Static Coefficient of Friction: ANSI A137.1 (2012), "American National Standard of Specifications for Ceramic Tile".</p> <p>6.3.33 Tile and Stone Sealers Water Vapor Transmissions: ASTM E96/96M-16, "Standard Test Methods for Water Vapor Transmission of Materials".</p> <p>6.3.34 VOC Content of Coatings: South Coast AQMD Method 313, "Determination of Volatile Organic Compounds (VOC) by Gas Chromatography/Mass Spectrometry/Flame Ionization Detection (GS/MS/FID)".</p> <p>6.3.35 VOC Content of Coatings: ASTM D6886-18, "Standard Test Method for Determination of the Weight Percent Individual Volatile Organic Compounds in Waterborne Air-Dry Coatings by Gas Chromatography".</p>	
<b>7.0 Compliance Schedule</b>	Persons subject to this rule shall be in compliance with this rule by the dates specified within the rule.	Persons subject to this rule shall be in compliance with this rule by the dates specified within the rule.	<b>No change in the requirements, therefore, non-SIP version of rule is as stringent as SIP version.</b>

Here is the link to 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings:

[https://ww2.arb.ca.gov/sites/default/files/2020-07/2020SCM\\_final.pdf](https://ww2.arb.ca.gov/sites/default/files/2020-07/2020SCM_final.pdf)

District Rule 4601 was amended (4/16/20). As analyzed, each amended section of the non-SIP version of the rule is at least as stringent as, or more stringent than the corresponding section of the SIP version of the rule. Therefore, it is concluded that overall the non-SIP version of the rule is more stringent than the SIP version of the rule.

<b>Table 1 VOC Content Limits for Coatings</b>		
<b>COATING CATEGORY</b>	<b>Current Rule 4601 VOC Limit (g/l) Effective on and after 1/1/2012</b>	<b>Amended Rule 4601 VOC Limit (g/l) Effective on and after 1/1/2022</b>
<b>Flat Coatings</b>	50	50
<b>Nonflat Coatings</b>	100	50
<b>Specialty Coatings -</b>		
Aluminum Roof Coatings	400	100
Basement Specialty Coatings	400	400
Bituminous Roof Coatings	50	50
Bituminous Roof Primers	350	350
Bond Breakers	350	350
Building Envelope Coatings	-	50
Concrete Curing Compounds	350	350
Concrete/Masonry Sealers	100	100
Driveway Sealers	50	50
Dry Fog Coatings	150	50
Faux Finishing Coatings	350	350
Fire Resistive Coatings	350	150
Floor Coatings	100	50
Form-Release Compounds	250	100
Graphic Arts Coatings (Sign Paints)	500	500
High Temperature Coatings	420	420
Industrial Maintenance Coatings	250	250
Low Solids Coatings <sup>12</sup>	120 <sup>1</sup>	120 <sup>1</sup>
Magnesite Cement Coatings	450	450
Mastic Texture Coatings	100	100
Metallic Pigmented Coatings	500	500
Multi-Color Coatings	250	250
Pre-Treatment Wash Primers	420	420
Primers, Sealers, and Undercoaters	100	100
Reactive Penetrating Sealers	350	350
Recycled Coatings	250	250
Roof Coatings	50	50
Rust Preventative Coatings	250	250
Shellacs:		
Clear	730	730
Opaque	550	550
Specialty Primers, Sealers, and Undercoaters	100	100
Stains	250	100
Interior Stains	250	
Stone Consolidants	450	450
Swimming Pool Coatings	340	340



Tile and Stone Sealers	100	
Traffic Marking Coatings	100	100
Tub and Tile Refinish Coatings	420	420
Waterproofing Membranes	250	100
Wood Coatings	275	275
Wood Preservatives	350	350
Zinc-Rich Primers	340	340

**Table 2 VOC Content Limits for Colorants**

<b>Colorants Added To</b>	<b>VOC Limit (g/l) Effective on and after 1/1/2022</b>
Architectural Coatings, excluding Industrial Maintenance Coatings	50
Solvent Based Industrial Maintenance Coatings	600
Waterborne Industrial Maintenance Coatings	50
Wood Coatings	600