

August 30, 2022

Mr. Scott Manley
SFPP, L.P.
1001 Louisiana St, Ste 1000, 8th Floor
Houston, TX 77002

Re: Notice of Final Action - Title V Permit Renewal
Facility Number: C-1077
Project Number: C-1203989


Dear Mr. Manley:

The District has issued the Final Renewed Title V Permit for SFPP, L.P. (see enclosure). The preliminary decision for this project was made on June 15, 2022 for CARB and June 23, 2022 for EPA. A summary of the comments and the District's response to each comment is included as an attachment to the engineering evaluation.

The public notice for issuance of the Final Title V Permit will be posted on the District's website (www.valleyair.org).

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Brian Clements
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email
cc: Gerardo Rios, EPA (w/enclosure) via EPS

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

**SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT**

**Final Title V Permit Renewal Evaluation
SFPP, L.P.
C-1077**

TABLE OF CONTENTS

I.	PROPOSAL	2
II.	FACILITY LOCATION	2
III.	EQUIPMENT LISTING	3
IV.	GENERAL PERMIT TEMPLATE USAGE	3
V.	SCOPE OF EPA AND PUBLIC REVIEW	3
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS	3
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE	6
VIII.	PERMIT REQUIREMENTS	8
IX.	PERMIT SHIELD	19
X.	CALIFORNIA ENVIRONMENTAL QUALITY ACT	20
XI.	PERMIT CONDITIONS	20
	ATTACHMENTS	20
A.	RENEWED TITLE V OPERATING PERMIT	
B.	PREVIOUS TITLE V OPERATING PERMIT	
C.	DETAILED SUMMARY LIST OF FACILITY PERMITS	
D.	DISTRICT RULE 4601 STRINGENCY ANALYSIS	
E.	PUBLIC COMMENTS AND DISTRICT RESPONSES	

TITLE V PERMIT RENEWAL EVALUATION
Petroleum Transportation

Engineer: Jesse A. Garcia
Date: June 14, 2022

Facility Number: C-1077
Facility Name: SFPP, L.P.
Mailing Address: 1001 Louisiana St, Ste 1000
Houston, TX 77002

Contact Name: Ling Li
Work Phone: (713) 420-6076
Cellphone: (281) 382-5924

Responsible Official: Robyn Lopez
Title: Area Manager

Project # : C-1203989
Deemed Complete: January 22, 2021

I. PROPOSAL

SFPP, L.P. was issued their last Title V permit after it was renewed on May 25, 2016. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the renewed Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

SFPP, L.P. is located at 4149 S Maple Ave in Fresno, California.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment A.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit Templates:

The applicant does not propose to use any model general permit templates.

V. SCOPE OF EPA AND PUBLIC REVIEW

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated

- District Rule 2201, New and Modified Stationary Source Review Rule (amended August 15, 2019)
- District Rule 2520, Federally Mandated Operating Permits (amended August 15, 2019)
- District Rule 4601, Architectural Coatings (amended April 16, 2020)
- District Rule 4702, Internal Combustion Engines (amended August 19, 2021)
- 40 CFR Part 60, Subpart Kb, Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984 (amended January 19, 2021)
- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners (amended March 24, 2021)
- 40 CFR Part 82, Subpart F, Recycling and Emission Reduction (amended December 1, 2016)

B. Rules Removed

- Merced County Rule 109, Equipment Breakdown (SIP approved June 18, 1982)
- San Joaquin County Rule 110, Equipment Breakdown (SIP approved December 5, 1984)
- Fresno County Rule 110, Equipment Breakdown (SIP approved 8/22/1977 ⇒ District resolution to rescind from SIP 2/17/2022)
- Kern County Rule 111, Equipment Breakdown (SIP approved 10/24/1980 ⇒ District resolution to rescind from SIP 2/17/2022)
- Kings County Rule 111, Equipment Breakdown (SIP approved, last amended 6/18/1982 ⇒ District resolution to rescind from SIP 2/17/2022)
- Madera County Rule 113, Equipment Breakdown (SIP approved 11/18/1983 ⇒ District resolution to rescind from SIP 2/17/2022)
- Stanislaus County Rule 110, Equipment Breakdown (SIP approved 6/1/1983 ⇒ District resolution to rescind from SIP 2/17/2022)
- Tulare County Rule 111, Equipment Breakdown (SIP approved 8/22/1977 ⇒ District resolution to rescind from SIP 2/17/2022)

C. Rules Added or Evaluated

- District Rule 4311, Flares (amended December 17, 2020)
- 40 CFR Part 63, Subpart BBBBBB, Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities (Amended January 24, 2011)
- 40 CFR Part 64, Compliance Assurance Monitoring (CAM) (amended October 10, 1997)

D. Rules Not Updated

- District Rule 1070, Inspections (amended December 17, 1992)
- District Rule 1081, Source Sampling (amended December 16, 1993)
- District Rule 1100, Equipment Breakdown (amended December 17, 1992)

- District Rule 2010, Permits Required (amended December 17, 1992)
- District Rule 2020, Exemptions (amended December 18, 2014)
- District Rule 2031, Transfer of Permits (amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080, Conditional Approval (amended December 17, 1992)
- District Rule 2410, Prevention of Significant Deterioration (adopted June 16, 2011 and effective November 26, 2012)
- District Rule 4101, Visible Emissions (amended February 17, 2005)
- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)
- District Rule 4202, Particulate Matter - Emission Rate (amended December 17, 1992)
- District Rule 4623, Storage of Organic Liquids (amended May 19, 2005)
- District Rule 4624, Organic Liquid Loading (amended December 20, 2007)
- District Rule 4701, Internal Combustion Engines — Phase I (amended August 21, 2003)
- District Rule 8011, General Requirements (amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, Extraction and Other Earthmoving Activities (amended August 19, 2004)
- District Rule 8031, Bulk Materials (amended August 19, 2004)
- District Rule 8041, Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Open Areas (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)

- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas (amended August 19, 2004)
- 40 CFR Part 60, Subpart K, Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978 (amended October 17, 2000)
- 40 CFR Part 60, Subpart Ka, Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1987 (amended December 14, 2000)
- 40 CFR Part 60, Subpart XX, Standards of Performance for Bulk Gasoline Terminals (Amended December 19, 2003)
- 40 CFR Part 63, Subpart ZZZZ, National Emissions Standards of Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (amended February 27, 2014)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos (amended July 20, 2004)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Added/Updated

None

B. Rules Not Updated

- District Rule 1100, Equipment Breakdown (Amended December 17, 1992)

The following conditions are based on this rule and is therefore not federally enforceable through Title V:

Permits	Conditions
C-1077-0-5	1 and 2

- District Rule 1160, Emission Statements (Adopted November 18, 1992)

The following condition is based on this rule and is therefore not federally enforceable through Title V:

Permits	Conditions
C-1077-0-5	3

- District Rule 2040, Applications (Amended December 17, 1992)

The following condition is based on this rule and is therefore not federally enforceable through Title V:

Permits	Conditions
C-1077-0-5	7

- District Rule 4102, Nuisance (Amended December 17, 1992)

The following conditions are based on this rule and is therefore not federally enforceable through Title V:

Permits	Conditions
C-1077-0-5	42
C-1077-1-6, -2-6	19

Title 13 California Code of Regulations (CCR), Section 2423 – Exhaust Emission Standards and Test Procedures, Off-Road Compression-Ignition Engines and Equipment (Required by Title 17 CCR, Section 93115 for Emergency Diesel IC Engines)

The Air Toxic Control Measure (ATCM) is a rule under the California Code of Regulations (CCR) which is the official compilation and publication of the regulations adopted, amended or repealed by state agencies. The purpose of this rule is to reduce diesel particulate matter (PM) and criteria pollutant emissions from stationary diesel-fueled compression ignition engines.

a) C-1077-1-6 and -2-6: DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIREWATER PUMP

The existing permit conditions demonstrating compliance with the requirements of these rules are summarized in the table below:

Permits	Conditions
C-1077-1-6 and -2-6	7, 8, 9, 10, 12, 17

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit or most recent renewal of the Title V permit.

A. Fresno County Rule 110, Kern County Rule 111, Kings County Rule 111, Madera County Rule 113, Stanislaus County Rule 110, and Tulare County Rule 111 – Equipment Breakdown

In accordance with EPA’s State Implementation Plan (SIP) Call, on February 17, 2022, the District rescinded Fresno County Rule 110, Kern County Rule 111, Kings County Rule 111, Madera County Rule 113, Stanislaus County Rule 110, and Tulare County Rule 111 from the San Joaquin Valley SIP.

Since the facility is not located within Merced or San Joaquin County, it is not subject to the requirements of San Joaquin County Rule 110 or Merced County Rule 109 and the reference to these rules will be removed from conditions #1 and 2 on draft facility-wide permit C-3839-0. Therefore, proposed conditions #1 and 2 on draft facility-wide permit C-3839-0 are no longer Federally Enforceable due to the removal of all county rules as shown below.

- {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; ~~County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Y~~

- {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; ~~County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)~~] ✕

B. District Rule 2201 - New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this Title V permit was last renewed. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit. The updated requirements of this rule are therefore not applicable at this time.

C. District Rule 2520 - Federally Mandated Operating Permits

This rule has been amended since this TV permit was last renewed, but the last amended version of the rule is not SIP approved. Additionally, the amendments to this rule do not have any effect on current permit requirements. However, only greenhouse gas emissions will be addressed under Rule 2520 during this renewal.

Greenhouse Gas Discussion

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

D. District Rule 4311, Flares (Amended December 17, 2020)

This rule limits VOC, NOx, and CO emissions from flares.

The rule was amended on December 17, 2020. The amended rule changed the definition of a “flare” to remove the exclusion that “flares” are not equipped with devices for fuel-air mix control or for temperature control. Therefore, due to this change, the vapor burner combustor listed under C-1077-3 is now subject to the requirements of this rule.

The requirements of this rule become effective on December 31, 2023. The facility is required to submit an Authority to Construct permit to comply with the future requirement by July 1, 2022.

E. District Rule 4601 – Architectural Coatings

This rule limits the emissions of VOCs from architectural coatings. It requires limiting the application of any architectural coating to no more than what is listed in the Tables 1 and 2 of Section 5.0 of the amended rule. This rule specifies architectural coatings storage, cleanup, and labeling requirements.

The rule was amended in April 16, 2020 but had not been SIP approved. The stringency analysis in Attachment D shows that the amended rule is as stringent as the SIP approved version of the rule that was adopted in December 17, 2009.

The following changes were included in the latest rule amendment that resulted in revising current permit requirements:

- The tables outlining the VOC content of different specialty coatings and colorants have been largely replaced with the Table 1 and Table 2 in Section 5.0.

The updated conditions 23, 24 and 25 on draft facility-wide permit C-1077-0 will assure compliance with the requirements of this rule.

F. District Rule 4702 – Internal Combustion Engines

The purpose of this rule is to limit the emissions of nitrogen oxides (NO_x), carbon monoxide (CO), volatile organic compounds (VOC), particulate matter (PM), and sulfur oxides (SO_x) from internal combustion engines. This rule applies to any internal combustion engine rated at 25 brake horsepower or greater. The permit units C-1077-1 and -2 are in compliance with the current SIP approved version of the rule. However, the last amended version of the rule, which is not SIP approved, requires lowering NO_x and VOC emissions for spark-ignited IC engines, clarifying definitions, and updating test methods. Also the Particulate Matter Emission Control Requirements were added to the rule as Section 5.8, and as such, the purpose of the rule was amended to encompass the new requirements.

The engines listed under permits C-1077-1 and -2 are compression-ignited emergency standby engines equipped with a nonresettable elapsed time meter. Therefore, the amended sections of this rule are not applicable to these engines. Because the amendments to District Rule 4702 do not affect

the requirements for any permit unit at this site and no additional conditions are required, the changes will not be addressed any further in this evaluation.

- G. 40 CFR Part 60, Subpart K – Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced after June 11, 1973, and Prior to May 19, 1978**
- H. 40 CFR Part 60, Subpart Ka – Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced after May 18, 1978, and Prior to July 23, 1984**
- I. 40 CFR Part 60, Subpart Kb – Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction or Modification Commenced after July 23, 1984**

The current Title V permit for each of the organic liquid storage tanks contain the 40 CFR 60, Subpart K, Ka, and Kb requirements for external floating roof storage tanks or are exempt as they were constructed prior to June 11, 1973 and were never reconstructed or modified.

Subpart K and Subpart Ka have not been updated since the last Title V renewal action, so there are no changes to the existing permit conditions for permit units C-1077-6-, -8, -9, -10, -11, -12, -14, -15, -16, and -17. However, Subpart Kb was recently updated by the EPA to allow owners or operators of storage vessels subject to Subpart Kb, and equipped with either an external floating roof or an internal floating roof, the choice to elect to comply with the requirements specified in NESHAP Subpart WW as an alternative standard, in lieu of the requirements specified in NSPS Subpart Kb. SFPP, L.P. has applied, under project C-1220221, to modify their permits electing to comply with the alternative requirements in NESHAP Subpart WW. Therefore, the changes to Subpart Kb does not affect the existing Title V permits as the requirements of NESHAP Subpart WW will be incorporated in to the Title V permit through Authority to Construct permits and Title V Minor Modifications or Administrative Amendments.

The existing permit conditions demonstrating compliance with the requirements of these rules are summarized in the table below:

Permits	Conditions
C-1077-6-7, -8-6, -9-7, -10-6, -11-8, -12-6, -14-7, -15-6, -16-6, -17-7	42 and 43
C-1077-22-7	9
C-1077-23-8	11

J. 40 CFR Part 63, Subpart BBBBBB – National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities

§63.11080 The purpose of this subpart

§63.11080 states that this subpart established national emission limitations and management practices for Hazardous Air Pollutants (HAP) emitted from area source (not a major HAP source) gasoline distribution bulk terminals, bulk plants, and pipeline facilities. This subpart also established requirements to demonstrate compliance with the emission limitations and management practices.

§63.11081 Applicability of this subpart

§63.11081(a) states that the affected source to which this subpart applies is each area source bulk gasoline terminal, pipeline breakout station, pipeline pumping station, and bulk gasoline plant.

§63.11100 defines that a bulk gasoline terminal means any gasoline storage and distribution facility that receives gasoline by pipeline, ship or barge, or cargo tank and has a gasoline throughput of 20,000 gallons per day or greater.

The facility has a daily throughput greater than 20,000 gallons per day. Therefore, the requirements of this subpart apply to this facility.

§63.11082 Affected source covered by this subpart

§63.11082(a) states the emission sources to which this subpart applies are gasoline storage tanks, gasoline loading racks, vapor collection-equipped gasoline cargo tanks, and equipment components in vapor or liquid gasoline service that meet the criteria specified in Table 1 through 3 to this subpart.

This facility has the emissions units listed above, and therefore are required to comply with the applicable requirements of this subpart.

§63.11083 Compliance Date of this subpart

§63.11083(b) states an existing affected source must comply with the standards in this subpart no later than January 10, 2011. The compliance date has passed and continuous compliance with the requirements of this section is expected.

§63.11087 Gasoline Storage Tanks Requirements

§63.11087(a) requires each gasoline storage tank to meet the emissions limit and management practices in Table 1 to this subpart.

The capacity of each of the organic liquid (including gasoline) storage tanks listed under the following permits is greater than 75 m³ (equivalent 19,813 gallons): C-1077-4, -5, -6, -7, -8, -9, -10, -11, -12, -13, -14, -15-, 16, -17, -18, -19, -20, -21, -22. Therefore, these storage tanks must meet the requirements listed under §63.11100, Table 1, item 2, as follows:

- a. reduce emissions of total organic HAP or TOC by 95% (by weight) with a closed vent system and control device; or
- b. equip each internal floating roof gasoline tank according to the requirements in 40 CFR Part 60 Subpart Kb, specifically, §60.112b(a)(1) except for the secondary seal requirement under §60.112b(a)(1)(ii)(B) and the requirements in §60.112b(a)(1)(iv) through (ix); and
- c. equip each external roof gasoline storage tank according to the requirements in §60.112b(a)(2), except that the requirements of §60.112b(a)(2)(ii) shall only be required if such storage tank does not currently meet the requirements of §60.112b(a)(2)(i); or
- d. equip and operate each internal and external floating roof gasoline storage tank according to the applicable requirements in §63.1063(a)(1) and (b), and equip each external floating roof gasoline storage tank according to the requirements of §63.1063(a)(2) if such storage tank does not currently meet the requirements of §63.1063(a)(1).

§63.11087(c) requires the owner or operator to perform testing and monitoring specified in §63.11092(e).

§63.11092(e) requires the owner or operator to perform inspections of internal floating roof gasoline storage tank per §60.113b(a).

§63.11087(d) requires the owner or operator to submit the applicable notifications as required under §63.11093.

§63.11093(a) requires the owner or operator to submit an Initial Notification as specified in §63.9(b). If the facility is in compliance with the requirements of this subpart at the time the Initial Notification is due, the Notification of Compliance Status required under paragraph (b) of this section may be submitted in lieu of the Initial Notification.

§63.11093(b) requires the owner or operator of an affected source under this subpart must submit a Notification of Compliance Status as specified in §63.9(b). The Notification of Compliance Status must specify which of the compliance options included in Table 1 of this subpart is used to comply with this subpart.

§63.11087(e) requires the owner or operator to keep records and submit reports as specified in §63.11094 and §63.11095.

§63.11094 and §63.11095 require to keep records and submit reports per §60.115b(a).

§63.11088 Gasoline Loading Rack Requirements

§63.11088(a) requires each loading rack to meet the emissions limit and management practices in Table 2 to this subpart.

The bulk gasoline terminal loading racks listed under permit C-1077-26, -27, -28, -29, -38, -42, and -51 are subject to this section.

§63.11089 Equipment Leak Inspections Requirements

§63.11089(a) requires the owner or operator to perform a monthly leak inspection of all equipment in gasoline service. For this inspection, detection methods incorporating sight, sound, and smell are acceptable.

§63.11089(b) requires that a log book must be used and must be signed by the owner or operator at the completion of each inspection. A section of the log book must contain a list, summary description, or diagram(s) showing the location of all equipment in gasoline service at the facility.

§63.11089(c) requires that each detection of a liquid or vapor leak must be recorded in the log book. When a leak is detected, an initial attempt at repair must be made as soon as practicable, but no later than 5 calendar days after the leak is detected. Repair or replacement of leaking equipment must be

completed within 15 days after detection of the leak, except as provided in §63.11089(d).

§63.11089(d) states that delay of repair of leaking equipment will be allowed if the repair is not feasible within 15 days. The owner or operator must submit a semiannual report that includes the reason(s) why the repair was not feasible and the date each repair was completed.

§63.11089(e) requires the owner or operator to comply with the requirements of this subpart by the applicable dates specified in §63.11083. §63.11089(f) requires the owner or operator must submit the applicable notifications as required under §63.11093.

As discussed in §63.11083(c), the facility is currently complying with the requirements of these sections.

§63.11089(g) requires the owner or operator to keep records and submit reports as specified in §63.11094 and §63.11095.

§63.11092 Testing and Monitoring Requirements

§63.11092(a)(1) requires the owner or operator to conduct a performance test on the vapor processing and collection system according to either paragraph (a)(1)(i) or paragraph (a)(1)(ii) of this section.

§63.11092(e)(1) requires the owner or operator operates gasoline storage tanks to perform inspections according to the requirement of §60.113b(a).

§63.11094(a) requires that all records be kept for at least five years. Therefore, the following condition will be included on the permit to ensure continuous compliance:

§63.11094(b) lists recordkeeping requirements for vapor tightness of trucks.

§63.11094(d) requires owners or operators that are subject to leak provisions, to keep a record describing the types, identification numbers, and locations of all equipment in gasoline service.

§63.11094(e) requires the owner or operator to keep records of equipment leak inspections.

§63.11095 Reporting Requirements

§63.11095(a)(1) requires the owner or operator to submit a semi-annual compliance report that includes information specified in §60.115(b)(a) for internal floating roof storage tank.

§63.11095(a)(2) requires the owner or operator to report each loading of a gasoline cargo tank for which vapor tightness document had not been previously obtained by the facility.

§63.11095(a)(3) requires the owner or operator to report the number of equipment leaks not repaired within 15 days after detection. However, District Rule 4624 requires leaks to be repaired with 72 hours.

§63.11095(a)(4) states the storage vessels complying with §63.11087(b) after January 10, 2011, the storage vessel's Notification of Compliance Status information can be included in the next semi-annual compliance report in lieu of filing a separate Notification of Compliance Status report under §63.11093.

§63.11095(b) requires the owner or operator of an affected source subject to the control requirements of this subpart to submit an excess emissions report to the Administrator at the time the semi-annual compliance report is submitted.

§63.11095(d) requires the owner or operator of an affected source under this subpart to submit a semi-annual report including the number, duration, and a brief description of each type of malfunction which occurred during the reporting period and which caused or may have caused any applicable emission limitation to be exceeded. The report must also include a description of actions taken by an owner or operator during a malfunction of an affected source to minimize emissions in accordance with §63.11085(a), including actions taken to correct a malfunction.

Compliance with the requirements of this rule is expected.

The permit conditions demonstrating compliance with the requirements of these rules are summarized in the table below:

Permits	Conditions
C-1077-4-5, -19-7	30
C-1077-5-11, -22-7	35
C-1077-6-7, -8-6, -9-7, -10-6, -11-8, -12-6, -14-7, -15-6, -16-6, -17-7	48

C-1077-7-7	32
C-1077-13-12	25
C-1077-18-8	33
C-1077-20-6, -21-6	38
C-1077-23-8	37
C-1077-24-7	8
C-1077-50-4	40
C-1077-53-2	11

K. 40 CFR Part 64 – Compliance Assurance Monitoring

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
NO _x	20,000
SO _x	140,000
PM ₁₀	140,000
CO	200,000
VOC	20,000

- a) C-1077-1, -2, -4 through -23, -43 -49, -50, -52, -53

These units have no add-on controls; therefore, they are not subject to CAM.

- b) C-1077-24

This unit has no emission limits listed on the permit; therefore, it is not subject to CAM.

- c) C-1077-3, -26, -27, -28, -29, -38, -42, -51,

These units have an emissions limit, are served by an add-on control for VOC emissions, and have a pre-control potential to emit greater than the

major source threshold for VOC emissions. Therefore, CAM is applicable to these units.

Since all these units are served by a shared vapor burner combustion system listed under permit C-1077-3 as the control device, permit conditions to require monitoring to assure compliance for all these units will be listed under permit C-1077-3. As previously approved, a continuous temperature recorder is required to ensure a minimum temperature of 900 degrees F in the vapor combustion system listed under permit C-1077-3.

The existing permit conditions demonstrating compliance with the requirements of this Subpart are summarized in the following table:

Permits	Conditions
C-1077-3-17	4, 5, 19, 20, 21

L. 40 CFR Part 82, Subpart B – Servicing of Motor Vehicle Air Conditioners

Per §82.30(a) the purpose of 40 CFR Part 82 Subpart B is to implement section 609 of the Clean Air Act, as amended regarding the servicing of motor vehicle air conditioners (MVACs), and to implement section 608 of the Clean Air Act regarding certain servicing, maintenance, repair and disposal of air conditioners in MVACs and MVAC-like appliances (as that term is defined in 40 CFR 82.152).

Per §82.30(b) these regulations apply to any person performing service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner.

The amendments to this subpart did not have any effect on the current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this subpart:

Permits	Conditions
C-1077-0-5	28

M. 40 CFR Part 82, Subpart F – Recycling and Emissions Reductions

Per §82.150(a) the purpose of 40 CFR Part 82 Subpart F is to reduce emissions of class I and class II refrigerants and their substitutes to the

lowest achievable level by maximizing the recapture and recycling of such refrigerants during the service, maintenance, repair, and disposal of appliances and restricting the sale of refrigerants consisting in whole or in part of a class I and class II ODS in accordance with Title VI of the Clean Air Act.

Per §82.150(b) these regulations apply to any person servicing, maintaining, or repairing appliances. This subpart also applies to persons disposing of appliances, including small appliances and motor vehicle air conditioners. In addition, this subpart applies to refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

The amendments to this subpart did not have any effect on the current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this subpart:

Permits	Conditions
C-1077-0-5	27

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

The applicant does not propose to use any model general permit templates.

B. Requirements not Addressed by Model General Permit Templates

The applicant is not requesting any permit shields.

C. Obsolete Permit Shields From Existing Permit Requirements

There are few county rules have been removed from the San Joaquin Valley SIP as discussed in Section VII.A and also the facility is not subject to the other county rules; therefore, the permit shield for all county rules will be removed from condition 39 on draft facility-wide permit C-1077-0.

39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), ~~Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings),~~ and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Y

X. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XI. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit.

ATTACHMENTS

- A. Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Summary List of Facility Permits
- D. District Rule 4601 Stringency Analysis
- E. Public Comments and District Responses

ATTACHMENT A

Renewed Title V Operating Permit

Permit to Operate

FACILITY: C-1077

EXPIRATION DATE: 05/31/2027

LEGAL OWNER OR OPERATOR:

SFPP, L.P.

MAILING ADDRESS:

SFPP, LP

1001 LOUISIANA STREET, STE 1000, 8TH FLOOR
HOUSTON, TX 77002

FACILITY LOCATION:

4149 S MAPLE AVE
FRESNO, CA 93725

FACILITY DESCRIPTION:

PETROLEUM TRANSPORTATION

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Samir Sheikh
Executive Director / APCO

Brian Clements
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: C-1077-0-5

EXPIRATION DATE: 05/31/2027

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1]
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0]
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0]
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-0-5 : Aug 30 2022 9:02AM -- GARCIAJ

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, or repackage for use within the District; or supply, sell, market, or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2, after the specified effective date in Table 1 or Table 2 of District Rule 4601 (4/16/20). [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to District Rule 4601 shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the applicable administrative requirements specified Section 6.0 of District Rule 4601. [District Rule 4601, 6.0] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of each year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. When applicable to 40 CFR Part 68, a subject facility shall submit to the proper authority a Risk Management Plan. [40 CFR 68] Federally Enforceable Through Title V Permit
44. The facility wide hazardous air pollutants (HAPs) emissions shall not exceed 16.7 tons/year and any individual HAP emissions shall not exceed 10 tons/year. The facility shall keep records demonstrating compliance with these limits. [District Rule 1160] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-1-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

460 BHP CATERPILLAR MODEL #3406B TIER 0 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all time other than startup in tables 1a, 2a, 2c, and 2d to 40. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. The engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 6.2.1 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, 3.15, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115]
10. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rules 2201 and 4702, 4.2.1, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. Engine shall be equipped with turbocharger and aftercooler. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Permit holder shall notify the District within ten days in event engine is used during an emergency. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Engine ignition timing shall be inspected, adjusted and certified, initially and, at a minimum, once every 3 years. Inspections, adjustments, and certifications shall be performed by a qualified mechanic according to the manufacturer's procedures. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of operation shall be maintained and made available for District inspection upon request, and shall include: days and hours of operation, fuel consumed, dates of maintenance, and ignition timing noted. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.1 and 17 CCR 93115] Federally Enforceable Through Title V Permit
18. Daily emissions from the engine shall not exceed 1.7 lbs/day of PM10, 3.8 lbs/day of SOx, 173.0 lbs/day of NOx, 3.0 lbs/day of VOC and 15.0 lbs/day of CO emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
19. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
20. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702, 5.6] Federally Enforceable Through Title V Permit
21. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702, 3.15] Federally Enforceable Through Title V Permit
22. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702,3.15] Federally Enforceable Through Title V Permit
23. The permittee shall maintain monthly records that include any information necessary to demonstrate compliance with 40 CFR 63, ZZZZ. [District Rule 1070 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-2-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

460 BHP CATERPILLAR MODEL #3406B TIER 0 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all time other than startup in tables 1a, 2a, 2c, and 2d to 40. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. The engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 6.2.1 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, 3.15, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115]
10. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District NSR Rule, Rule 4702, 4.2.1, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. Engine shall be equipped with turbocharger and aftercooler. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Permit holder shall notify the District within ten days in event engine is used during an emergency. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Engine ignition timing shall be inspected, adjusted and certified, initially and, at a minimum, once every 3 years. Inspections, adjustments, and certifications shall be performed by a qualified mechanic according to the manufacturer's procedures. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Records of operation shall be maintained and made available for District inspection upon request, and shall include: days and hours of operation, fuel consumed, dates of maintenance, and ignition timing noted. [District Rule 2201] Federally Enforceable Through Title V Permit
17. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.1 and 17 CCR 93115] Federally Enforceable Through Title V Permit
18. Daily emissions from the engine shall not exceed 1.7 lbs/day of PM10, 3.8 lbs/day of SOx, 173.0 lbs/day of NOx, 3.0 lbs/day of VOC and 15.0 lbs/day of CO emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
19. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102] Federally Enforceable Through Title V Permit
20. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702, 5.6] Federally Enforceable Through Title V Permit
21. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702,3.15] Federally Enforceable Through Title V Permit
22. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702, 3.15] Federally Enforceable Through Title V Permit
23. The permittee shall maintain monthly records that include any information necessary to demonstrate compliance with 40 CFR 63, ZZZZ. [District Rule 1070 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-3-18

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

78.0 MMBTU/HR JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM AS THE CONTROL DEVICE OF THE BULK LOADING OPERATION WITH A VARIABLE FREQUENCY DRIVE FOR AIR INTAKE FAN MOTOR AND FLAME ARRESTORS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Auxiliary fuel supplied to John Zink ZTOF burner/thermal oxidizer shall be monitored daily to determine the amount of fuel consumed. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The John Zink ZTOF burner operating temperature shall be monitored by a continuously recording temperature device. Upon the detection of a vapor combustion temperature below 900 degrees F, the permittee shall investigate the cause of the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [District Rule 2201, 40 CFR part 64] Federally Enforceable Through Title V Permit
5. All vapors from the loading racks shall be incinerated in the vapor combustion system at a minimum temperature of 900 degrees F (averaged over each burn period) and retention time of at least 0.5 seconds when running at by-pass mode or direct mode. [District Rules 2201 and 4624 and 40 CFR part 64] Federally Enforceable Through Title V Permit
6. VOC emissions from loading racks #1, #2, #3, #4, #5, #6, and #8 served by the John Zink ZTOF combustion system shall not exceed 0.02 pound VOC per 1,000 gallons of organic liquid with greatest vapor pressure loaded. [District Rule 4624] Federally Enforceable Through Title V Permit
7. Daily emission limits from the John Zink ZTOF combustion system shall not exceed any of the following limits: 105.0 pounds VOC per day, 97.0 pounds NOx per day, 264.0 pounds CO per day, 30.7 pounds SOx per day, or 6.0 pounds PM10 per day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records of monthly LPG consumption and the daily and annual amount of gasoline loaded from the loading racks shall be maintained, retained on the premises and made available for District inspection upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
9. Source testing to demonstrate compliance with permit conditions and all rules and regulations shall be conducted annually. [District Rules 1081, 2201, and 4624] Federally Enforceable Through Title V Permit
10. Source testing shall be conducted using the methods and procedures approved by the District. A pretest plan outlining the test methods and procedures shall be submitted for the District's approval no later than 15 days prior to each test. [District Rule 1081] Federally Enforceable Through Title V Permit
11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Sampling facilities for source testing shall be provided in accordance with the provisions of District Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit
13. The operator of the facility shall comply with the provisions of District Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
14. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per 12-month period. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624 and Fresno County Rule 412] Federally Enforceable Through Title V Permit
16. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503 "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 432, or ARB Method 2-4. [District Rule 4624 and Fresno County Rule 412] Federally Enforceable Through Title V Permit
17. Loading and vapor collection and control equipment shall be maintained and operated such that there are no leaks or excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at a distance of one centimeter from the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624 and Fresno County Rule 412] Federally Enforceable Through Title V Permit
18. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624 and Fresno County Rule 412. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
19. Devices used to monitor the John Zink ZTOF burner operating temperature shall be maintained in accordance with the manufacturer's specifications. [40 CFR part 64] Federally Enforceable Through Title V Permit
20. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR 64.7. [40 CFR part 64] Federally Enforceable Through Title V Permit
21. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR part 64] Federally Enforceable Through Title V Permit
22. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-5-11

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

762,500 GALLON ABOVEGROUND MULTI-PRODUCT (GASOLINE & ETHANOL) ORGANIC LIQUID STORAGE TANK FR-2 EQUIPPED WITH DOMED EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP AND ETHANOL TRUCK UNLOADING STATION WITH TWO FOUR-INCH FLEXIBLE UNLOADING HOSES

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The only organic liquids approved for storage in the external floating roof tank shall be gasoline and ethanol. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The true vapor pressure (TVP) of liquids stored in the external floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
4. The total annual organic liquid throughput for Tank FR-2 shall not exceed 6,626,575 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Daily VOC emissions shall not exceed 5.4 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.4.2 and District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the District in writing at least five calendar days prior to performing the work. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. The tank pressure-vacuum (PV) relief valve shall be set to within 10% of the maximum allowable working pressure of the tank. The PV relief valve shall be permanently labeled with the operating pressure settings. The PV relief valve shall be properly installed and maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
9. Gaps between the tank shell and the primary seal shall not exceed one and one-half (1-1/2) inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than one-half (1/2) inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. The cumulative length of all primary seal gaps greater than one-eighth (1/8) inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No continuous gap greater than one-eighth (1/8) inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. No gap between the tank shell and the secondary seal shall exceed one-half (1/2) inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The cumulative length of all gaps between the tank shell and the secondary seal, greater than one-eighth (1/8) inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
15. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
16. The maximum gap between the shoe and the tank shell shall be no greater than double the gap allowed by the seal gap criteria for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
17. There shall be no tears, holes or openings in the secondary seal or in the primary seal envelope surrounding the annular vapor space enclosed by the roof edge, stored liquid surface, shoe, and seal fabric. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
18. The secondary seal shall allow easy insertion of probes of up to one and one-half (1-1/2) inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
19. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
20. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak free, except when the device or appurtenance is in use for sampling or gauging. [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit
27. The well shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

28. The well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well provided the gap does not exceed one-eighth (1/8) inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed one-eighth (1/8) inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
30. The permittee of external floating roof tanks shall make the primary seal envelope available for unobstructed inspection by the District on an annual basis at locations selected along its circumference at random by the District. In the case of riveted tanks with toroid-type seals, a minimum of eight (8) locations shall be made available; in all other cases, a minimum of four (4) locations shall be made available. If the District suspects a violation may exist, the District may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
31. The permittee shall inspect all floating tanks at least once every 12 months to determine compliance with the requirements of Rule 4623. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the District as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
32. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time a tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
33. The permittee shall submit the reports of the floating roof tank inspections to the District within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the District, but the inspection report shall be kept on-site and made available upon request by the District. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
34. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, and type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. The permittee shall keep the records at the facility (on-site) for a period of five years. The records shall be made available to the APCO upon request. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
35. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-6-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

370,400 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-3, EXTERNAL FLOATING ROOF WITH A RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-3 shall not exceed 3,219,300 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 10.3 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended May 19, 2005) A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-7-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

1,260,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-4, INTERNAL FLOATING ROOF EQUIPPED WITH A LIQUID MOUNTED METALLIC SHOE PRIMARY SEAL AND A RIM-MOUNTED SECONDARY SEAL MADE OF STEEL COMPRESSION PLATES AND A RUBBER WIPER BLADE TIP WITH A RECIRCULATION SYSTEM AND ELECTRIC HEATER FOR MAINTAINING TANK TEMPERATURE

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. The electronic heater shall not operate unless the storage tank is in biodiesel blendstock service. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, District Rule 4623] Federally Enforceable Through Title V Permit
4. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
8. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
9. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623] Federally Enforceable Through Title V Permit
13. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
14. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
15. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
16. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak free, except when the device or appurtenance is in use for sampling or gauging. [District Rule 4623] Federally Enforceable Through Title V Permit
17. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
24. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

25. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
26. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623] Federally Enforceable Through Title V Permit
27. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5/19/05). [District Rule 4623] Federally Enforceable Through Title V Permit
28. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
29. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
30. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
31. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
32. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-8-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

1,736,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-5, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-5 shall not exceed 15,088,735 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 15 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-9-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

923,000 GALLON ABOVEGROUND GASOLINE TANK (FR-6) WITH AN EXTERNAL FLOATING ROOF AND A MATRIX SERVICE RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-6 shall not exceed 8,023,430 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 12.6 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-10-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

519,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-7, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-7 shall not exceed 4,512,130 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 11 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBBBB. [40 CFR 60 Subpart BBBBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-11-8

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

370,000 GALLON ABOVEGROUND GASOLINE, DIESEL, JET FUEL, TRANSMIX, AND ETHANOL STORAGE TANK FR-8, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-8 shall not exceed 3,218,570 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 10.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-12-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

925,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-9, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-9 shall not exceed 8,038,030 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 12.6 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBBBB. [40 CFR 60 Subpart BBBBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-13-12

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

634,000 GALLON ABOVEGROUND MULTI-PRODUCT (GASOLINE, DIESEL, JET FUEL, & ETHANOL) ORGANIC LIQUID STORAGE TANK FR-10 EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The only organic liquids approved for storage in the internal floating roof tank shall be gasoline, diesel, jet fuel, and ethanol. [District Rule 2201] Federally Enforceable Through Title V Permit
3. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
4. Tank gauging and sampling devices shall be leak free (as defined in District Rule 4623, 3.17 (amended 5/19/2005)). [District Rule 4623, 5.5.2.1] Federally Enforceable Through Title V Permit
5. Records of monthly organic liquid throughput shall be maintained and shall be made available for District inspection upon request. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
6. The total annual organic liquid throughput for Tank FR-10 shall not exceed 4,737,700 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily VOC emissions shall not exceed 5.42 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The permittee shall comply with recordkeeping requirements in section 6.3 of District Rule 4623 (Amended 5/19/2005) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
9. Vapor pressure of stored liquids shall be determined as described in section 6.2 of District Rule 4623 (Amended 5/19/2005). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
10. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
11. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
12. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
15. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
16. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
17. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.4.1] Federally Enforceable Through Title V Permit
18. Primary seal envelope surrounding the annular vapor space enclosed by the roof edge, stored liquid surface, shoe and seal fabric shall have no openings, holes or tears. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
19. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
20. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
21. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
22. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
23. Each roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. [District Rule 4623, 5.1.6] Federally Enforceable Through Title V Permit
24. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak free, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-14-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

1,145,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-11, EXTERNAL FLOATING ROOF WITH AN HMT SCISSOR SHOE PRIMARY SEAL, AND AN HMT RIM-MOUNTED SECONDARY SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-11 shall not exceed 3,218,570 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 10.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-15-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

761,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-12, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-12 shall not exceed 6,622,560 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 12 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-16-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

1,343,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-13, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-13 shall not exceed 11,699,415 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 14 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-17-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

1,145,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-14, EXTERNAL FLOATING ROOF WITH A RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-14 shall not exceed 9,953,185 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 13.3 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
48. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBBBB. [40 CFR 60 Subpart BBBBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-18-8

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

1,470,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-16, INTERNAL FLOATING ROOF EQUIPPED WITH PDM'S DELTA PRIMARY SEAL AND WIPER TYPE SECONDARY SEAL

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520] Federally Enforceable Through Title V Permit
3. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. The total annual gasoline throughput for Tank FR-16 shall not exceed 17,520,000 barrels. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Daily VOC emissions shall not exceed 16.6 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
9. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
10. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623] Federally Enforceable Through Title V Permit
14. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
15. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
16. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
17. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak-free, except when the device or appurtenance is in use. [District Rule 4623] Federally Enforceable Through Title V Permit
18. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
25. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
27. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5/19/05). [District Rule 4623] Federally Enforceable Through Title V Permit
29. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
30. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
31. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
33. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-19-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

1,512,000 GALLON ABOVEGROUND CONE ROOF GASOLINE STORAGE TANK FR-17, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED MECHANICAL SHOE TYPE PRIMARY SEAL AND A RIM-MOUNTED STEEL COMPRESSION PLATE SECONDARY SEAL

PERMIT UNIT REQUIREMENTS

1. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
2. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
3. Gasoline throughput shall not exceed 36,000 barrels per day based on a monthly average. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
5. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
6. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
8. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
10. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
11. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.4.1] Federally Enforceable Through Title V Permit
12. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
14. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
15. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
16. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
17. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
18. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1] Federally Enforceable Through Title V Permit
19. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1] Federally Enforceable Through Title V Permit
20. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3] Federally Enforceable Through Title V Permit
21. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4] Federally Enforceable Through Title V Permit
22. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6] Federally Enforceable Through Title V Permit
24. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1] Federally Enforceable Through Title V Permit
25. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
27. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
28. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
29. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
30. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-20-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

210,000-GALLON ABOVEGROUND CONE ROOF STORAGE TANK FR-18, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS

PERMIT UNIT REQUIREMENTS

1. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3, District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
3. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3, CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
4. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
5. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
6. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
8. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
9. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.4.1] Federally Enforceable Through Title V Permit
10. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
12. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
13. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
14. All openings in the roof used for sampling and gauging, except pressure-vacuum comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
15. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
16. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
17. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
18. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3, 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
19. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4, 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
20. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5, 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
21. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6, 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
22. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
25. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5-19-05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
26. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
27. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
28. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
29. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
30. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
31. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
32. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
33. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
34. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
35. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
37. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
38. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBBBB. [40 CFR 60 Subpart BBBBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-21-6

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

2,100,000 GALLON ABOVEGROUND CONE ROOF STORAGE TANK FR-19, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS

PERMIT UNIT REQUIREMENTS

1. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3, District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
3. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3, CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
4. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
5. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
6. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
8. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
9. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.4.1] Federally Enforceable Through Title V Permit
10. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
12. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
13. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
14. All openings in the roof used for sampling and gauging, except pressure-vacuum comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
15. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
16. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
17. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
18. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3, 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
19. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4, 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
20. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5, 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
21. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6, 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
22. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
25. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5-19-05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
26. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
27. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
28. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
29. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
30. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
31. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
32. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
33. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
34. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
35. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
37. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
38. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBBBB. [40 CFR 60 Subpart BBBBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-22-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

3,360,000 GALLON ABOVEGROUND CONE ROOF GASOLINE STORAGE TANK FR-20, INTERNAL FLOATING ROOF EQUIPPED WITH AN HMT MINI-SHOE SEAL AND AN HMT VAPORFLEX SECONDARY SEAL

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the external floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
3. Maintain tank-to-seal gaps according to the criteria in section 5.3.2 of District Rule 4623 (amended 5-19-05). [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
4. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
5. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
6. The total annual gasoline throughput for Tank FR-20 shall not exceed 29,200,000 barrels per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily VOC emissions shall not exceed 13.8 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The permittee shall comply with all other applicable provisions of Rule 4623 (amended 5-19-05). [District Rule 4623] Federally Enforceable Through Title V Permit
9. The permittee shall comply with all applicable provisions of 40 CFR 60 Subpart Kb. [40 CFR 60 Subpart Kb] Federally Enforceable Through Title V Permit
10. The permittee shall comply with recordkeeping requirements in section 6.3 of District Rule 4623 (amended 5-19-05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. [District Rule 4623, 5.3.1.3 and 40 CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
12. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [District Rule 4623, 5.5.2.1.5 and 40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
13. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
14. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.2, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
15. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3 and 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
16. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4 and 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
17. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening. [District Rule 4623, 5.5.2.1.5 and 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
18. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. [District Rule 4623, 5.5.2.1.6 and 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
19. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
20. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
21. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. For this vessel which is equipped with a double seal system, inspections may be carried out as specified above, or using the following procedure every 5 years: Visually inspect the internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes and sleeve seals each time the vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other opening in the seal or the seal fabric, or the secondary seal has holes, tears, or other opening in the seal or seal fabric, or the gaskets no longer close off the liquid surfaces, or the slotted membrane has more than 10 percent open area, the operator shall make necessary repairs prior to filling the vessel. [40 CFR 60.113b(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
24. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5-19-05). [District Rule 4623, 6.2 and 40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
25. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
26. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
27. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available for District staff upon request. [District Rule 2520, 9.3 and District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
28. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
29. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
30. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
31. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [District Rule 4623, 6.3.5 and 40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
32. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [District Rule 4623, 6.1.2 and 40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

33. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
34. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
35. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit
36. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-23-8

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

2,520,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-21, INTERNAL FLOATING ROOF EQUIPPED WITH URETHANE FABRIC "RESILIENT TOROIDAL SEAL" WITH WOVEN NYLON INSERT, AND "FOAM LOGS" INSERTED BETWEEN TANK SHELL AND PAN RIM

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. No gap between the tank shell and the primary seal shall exceed one-half (1/2) inch. The cumulative length of all primary seal gaps greater than one-eighth (1/8) inch shall not exceed five (5) percent of the tank circumference. No continuous gap greater than one-eighth (1/8) inch shall exceed ten (10) percent of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
4. No gap between the tank shell and the secondary seal shall exceed one-half (1/2) inch. The cumulative length of all gaps between the tank shell and the secondary seal, greater than one-eighth (1/8) inch shall not exceed five (5) percent of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
5. No gap between the tank shell and the secondary seal shall exceed one-half (1/2) inch. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The secondary seal shall extend from the roof of the tank to the shell and not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The secondary seal shall allow easy insertion of probes up to one-half (1/2) in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
8. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak-free, except when the device or appurtenance is in use. [District Rule 4623] Federally Enforceable Through Title V Permit
9. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The permittee shall comply with all other applicable provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The permittee shall comply with all applicable provisions of 40 CFR 60 Subpart Kb. [40 CFR 60 Subpart Kb] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The permittee shall comply with recordkeeping requirements in section 6.3 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. [District Rule 4623 and 40 CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
14. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [District Rule 4623 and 40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
15. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623 and 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
16. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623 and 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
17. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623 and 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
18. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623 and 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
19. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening. [District Rule 4623 and 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
20. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. [District Rule 4623 and 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
21. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
22. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623 and 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. For this vessel which is equipped with a double seal system, inspections may be carried out as specified above, or using the following procedure every 5 years: Visually inspect the internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes and sleeve seals each time the vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other opening in the seal or the seal fabric, or the secondary seal has holes, tears, or other opening in the seal or seal fabric, or the gaskets no longer close off the liquid surfaces, or the slotted membrane has more than 10 percent open area, the operator shall make necessary repairs prior to filling the vessel. [40 CFR 60.113b(a)(3) and (4)] Federally Enforceable Through Title V Permit
25. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623 and 40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
27. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
29. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
30. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
31. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
32. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
33. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
34. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

35. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
36. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
37. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-24-7

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

375,000 GALLON VAPOR HOLDER TANK EQUIPPED WITH A BLADDER SYSTEM TO CONTROL HYDROCARBON EMISSIONS VENTING TO THE VAPOR BURNER LISTED UNDER PERMIT C-1077-3

PERMIT UNIT REQUIREMENTS

1. The air pollution control measure "bladder system" shall be maintained as per manufacturer's specifications submitted to the District. [District Rule 2201] Federally Enforceable Through Title V Permit
2. There shall be no uncontrolled vapor venting from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The vapor transfer lines to the vapor recovery unit shall be maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All processor and transfer equipment, including vapor transfer lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspections shall be conducted using sight, sound and smell, and instrument methods to detect leaks every month to maintain compliance with the leak-free condition. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
6. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
7. Any vapor control device, other than a flare, shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
8. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-26-12

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

LOADING RACK #1 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day or 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-27-12

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

LOADING RACK #2 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day or 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-28-12

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

LOADING RACK #3 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day or 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-29-12

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

LOADING RACK #4 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day or 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-38-12

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

LOADING RACK #6 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day or 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-42-8

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

LOADING RACK #5 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO JOHN ZINK VAPOR BURNER

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day or 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-49-9

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

TWO-LANE DENATURED ETHANOL TRUCK UNLOADING STATION EACH LANE WITH TWO FLEXIBLE UNLOADING HOSES, TWO PUMPS, PRODUCT ACCUMULATOR, AIR ELIMINATOR, METER AND SUPPORT EQUIPMENT, AND ORGANIC VAPORS RETURNED TO DELIVERY TRUCKS

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Vapor return hose(s) shall connect displaced vapors to the delivery truck whenever tank truck, trailer, or car is unloading organic liquid. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
4. All delivery trucks must be equipped with vapor collection equipment capable of undergoing a pressure change of no more than 1 inch of water within 5 minutes after it is pressured to 18 inches of water. This must be demonstrated annually for each truck using the procedures specified in EPA Method 27 of 40 CFR 60, Appendix A or CARB Test Methods CP-204, TP-204.1, TP204-2, and TP-204.3. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The vapor collection and control system shall operate such that the pressure in the delivery tank being unloaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
6. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624] Federally Enforceable Through Title V Permit
7. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv as methane above a background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624] Federally Enforceable Through Title V Permit
8. The operator shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624] Federally Enforceable Through Title V Permit
9. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-49-9 : Aug 30 2022 9:02AM -- GARCIAJ

10. An operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and the operator shall contact the APCO in writing within 14 days. [District Rule 4624] Federally Enforceable Through Title V Permit
11. Fugitive component VOC emissions from the denatured ethanol unloading system shall not exceed 1.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-3, Marketing Terminal Average Emission Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The maximum throughput of denatured ethanol unloaded shall not exceed 427,350 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The maximum volume of liquid spilled during disconnect shall not exceed 10 milliliters. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Daily records of amount of denatured ethanol unloaded at the denatured ethanol unloading system shall be maintained. [District Rules 1070, 2201, 4624] Federally Enforceable Through Title V Permit
17. Permittee shall maintain the following records for each truck: 1) the annual vapor collection equipment test result, 2) date the test was performed, and 3) truck identification. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 72 hours after detection. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
19. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-50-4

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

80,000 BARREL INTERNAL FLOATING ROOF GASOLINE, DIESEL, JET FUEL, AND TRANSMIX STORAGE TANK (FR-26)

PERMIT UNIT REQUIREMENTS

1. Emissions from this tank shall not exceed 23.4 lbs VOC per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Daily throughput of this tank shall not exceed 80,000 barrels per day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3, District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
4. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
5. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3, CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
6. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
8. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
10. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
11. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-50-4 : Aug 30 2022 9:02AM -- GARCIAJ

12. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
13. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
14. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
15. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
16. All openings in the roof used for sampling and gauging, except pressure-vacuum comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
17. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
18. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
19. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
20. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3, 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
21. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4, 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
22. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5, 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6, 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
24. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

25. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit
26. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
27. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5-19-05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
29. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
30. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
31. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
32. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
33. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
34. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
35. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
36. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit
38. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
39. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
40. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-51-5

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

TWO LANE FUEL LOADING RACK #8 FOR PETROLEUM DISTILLATES AND GASOLINE WITH EIGHT LOADING STATIONS PER LANE CONTROLLED BY THE VAPOR COMBUSTION SYSTEM LISTED UNDER PERMIT C-1077-3, AND PERMIT EXEMPT DIESEL DYE INJECTION AND FUEL ADDITIVE INJECTION

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day or 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-52-2

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

OFF-SPECIFICATION PRODUCT TRUCK UNLOADING STATION WITH ONE UNLOADING CONNECTION GRAVITY DRAINED TO ONE PUMP SLEEVE, ONE PUMP, AIR ELIMINATOR, METER AND SUPPORT EQUIPMENT, AND VAPOR RETURN SYSTEM (VAPOR VENTED BACK TO TANKER TRUCK)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Vapor return hose(s) shall connect displaced vapors to the delivery truck whenever tank truck, trailer, or car is unloading organic liquid. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
4. All delivery trucks must be equipped with vapor collection equipment capable of undergoing a pressure change of no more than 1 inch of water within 5 minutes after it is pressured to 18 inches of water. This must be demonstrated annually for each truck using the procedures specified in EPA Method 27 of 40 CFR 60, Appendix A or CARB Test Methods CP-204, TP-204.1, TP204-2, and TP-204.3. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The vapor collection and control system shall operate such that the pressure in the delivery tank being unloaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
6. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624] Federally Enforceable Through Title V Permit
7. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv as methane above a background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624] Federally Enforceable Through Title V Permit
8. The operator shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
9. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-52-2: Aug 30 2022 9:02AM -- GARCIAJ

10. An operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and the operator shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
11. Unloading VOC emissions from the unloading system shall not exceed 0.093 lb-VOC/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Unloading VOC emissions from the unloading system shall not exceed 0.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The maximum number of unloading events shall not exceed either of the following limits: 45 events/day or 16,400 events/year. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Fugitive component VOC emissions from the unloading system shall not exceed 0.06 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The maximum volume of liquid spillage/leaks from each hose disconnect shall not exceed 10 milliliters. [District Rule 2201] Federally Enforceable Through Title V Permit
16. VOC emissions from truck unloading connections shall not exceed 0.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-3, Marketing Terminal Average Emission Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
18. The maximum throughput of off-specification product unloaded shall not exceed any of the following: 75,600 gallons per day or 27,552,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Daily records of amount of off-specification product unloaded and number of trucks unloaded at the unloading system shall be maintained. [District Rules 1070, 2201, 4624] Federally Enforceable Through Title V Permit
21. Permittee shall maintain the following records for each truck: 1) the annual vapor collection equipment test result, 2) date the test was performed, and 3) truck identification. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 72 hours after detection. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
23. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-53-2

EXPIRATION DATE: 05/31/2027

EQUIPMENT DESCRIPTION:

500 GALLON FUEL ADDITIVE STORAGE TANK WITH PV VALVE LINKED BY PIPE TO LOADING RACK LISTED IN PERMIT C-1077-51

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.4 psia under all storage conditions. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Daily throughput of this tank shall not exceed 500 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Annual throughput of this tank shall not exceed 6,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. VOC emission rate from the tank shall not exceed 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain daily records of organic liquid throughput and shall keep accurate records of each organic liquid stored in the tank, including its storage temperature and TVP. [District Rule 1070] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
11. The permittee shall comply with all applicable provisions of 40 CFR 63 Subpart BBBB. [40 CFR 60 Subpart BBBB] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT B

Previous Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: C-1077-0-4

EXPIRATION DATE: 05/31/2021

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-0-4 : Jun 14 2022 11:35AM -- GARCIAJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-1-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

460 HP MODEL #3406B DIESEL-FIRED EMERGENCY IC ENGINE POWERING ONE FIRE PROTECTION PUMP

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all time other than startup in tables 1a, 2a, 2c, and 2d to 40. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. The engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 6.2.1 and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, 3.15, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-1-5 : Jun 14 2022 11:36AM -- GARCIAJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-2-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

460 HP MODEL #3406B DIESEL-FIRED EMERGENCY IC ENGINE POWERING ONE FIRE PROTECTION PUMP

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all time other than startup in tables 1a, 2a, 2c, and 2d to 40. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. The engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 6.2.1 and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, 3.15, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-3-17

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

78.0 MMBTU/HR JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM AS THE CONTROL DEVICE OF THE BULK LOADING OPERATION WITH A VARIABLE FREQUENCY DRIVE FOR AIR INTAKE FAN MOTOR AND FLAME ARRESTORS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Auxiliary fuel supplied to John Zink ZTOF burner/thermal oxidizer shall be monitored daily to determine the amount of fuel consumed. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The John Zink ZTOF burner operating temperature shall be monitored by a continuously recording temperature device. Upon the detection of a vapor combustion temperature below 900 degrees F, the permittee shall investigate the cause of the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [District Rule 2201, 40 CFR part 64] Federally Enforceable Through Title V Permit
5. All vapors from the loading racks shall be incinerated in the vapor combustion system at a minimum temperature of 900 degrees F (averaged over each burn period) and retention time of at least 0.5 seconds when running at by-pass mode or direct mode. [District Rules 2201 and 4624 and 40 CFR part 64] Federally Enforceable Through Title V Permit
6. VOC emissions from loading racks #1, #2, #3, #4, #5, #6, and #8 served by the John Zink ZTOF combustion system shall not exceed 0.02 pound VOC per 1,000 gallons of organic liquid with greatest vapor pressure loaded. [District Rule 4624] Federally Enforceable Through Title V Permit
7. Daily emission limits from the John Zink ZTOF combustion system shall not exceed any of the following limits: 105.0 pounds VOC per day, 97.0 pounds NOx per day, 264.0 pounds CO per day, 30.7 pounds SOx per day, or 6.0 pounds PM10 per day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records of monthly LPG consumption and the daily and annual amount of gasoline loaded from the loading racks shall be maintained, retained on the premises and made available for District inspection upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
9. Source testing to demonstrate compliance with permit conditions and all rules and regulations shall be conducted annually. [District Rules 1081, 2201, and 4624] Federally Enforceable Through Title V Permit
10. Source testing shall be conducted using the methods and procedures approved by the District. A pretest plan outlining the test methods and procedures shall be submitted for the District's approval no later than 15 days prior to each test. [District Rule 1081] Federally Enforceable Through Title V Permit
11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-3-17: Jun 14 2022 11:36AM -- GARCIAJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-4-4

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

63,000 GALLON ABOVEGROUND FIXED ROOF STORAGE TANK, FR-1, WITH CONAKO VACONODECK INTERNAL FLOATING PAN.

PERMIT UNIT REQUIREMENTS

1. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.4.2, District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
3. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
4. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
5. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
6. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
7. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
8. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
10. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-5-10

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

762,500 GALLON ABOVEGROUND MULTI-PRODUCT (GASOLINE & ETHANOL) ORGANIC LIQUID STORAGE TANK FR-2 EQUIPPED WITH DOMED EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP AND ETHANOL TRUCK UNLOADING STATION WITH TWO FOUR-INCH FLEXIBLE UNLOADING HOSES

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The only organic liquids approved for storage in the external floating roof tank shall be gasoline and ethanol. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The true vapor pressure (TVP) of liquids stored in the external floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
4. The total annual organic liquid throughput for Tank FR-2 shall not exceed 6,626,575 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Daily VOC emissions shall not exceed 5.4 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.4.2 and District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the District in writing at least five calendar days prior to performing the work. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. The tank pressure-vacuum (PV) relief valve shall be set to within 10% of the maximum allowable working pressure of the tank. The PV relief valve shall be permanently labeled with the operating pressure settings. The PV relief valve shall be properly installed and maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
9. Gaps between the tank shell and the primary seal shall not exceed one and one-half (1-1/2) inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than one-half (1/2) inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. The cumulative length of all primary seal gaps greater than one-eighth (1/8) inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-6-6

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

370,400 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-3, EXTERNAL FLOATING ROOF WITH A RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-3 shall not exceed 3,219,300 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 10.3 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-7-6

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

1,260,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-4, INTERNAL FLOATING ROOF EQUIPPED WITH A LIQUID MOUNTED METALLIC SHOE PRIMARY SEAL AND A RIM-MOUNTED SECONDARY SEAL MADE OF STEEL COMPRESSION PLATES AND A RUBBER WIPER BLADE TIP WITH A RECIRCULATION SYSTEM AND ELECTRIC HEATER FOR MAINTAINING TANK TEMPERATURE

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. The electronic heater shall not operate unless the storage tank is in biodiesel blendstock service. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, District Rule 4623] Federally Enforceable Through Title V Permit
4. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
5. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
8. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
9. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-8-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

1,736,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-5, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-5 shall not exceed 15,088,735 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 15 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-9-6

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

923,000 GALLON ABOVEGROUND GASOLINE TANK (FR-6) WITH AN EXTERNAL FLOATING ROOF AND A MATRIX SERVICE RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-6 shall not exceed 8,023,430 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 12.6 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-10-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

519,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-7, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-7 shall not exceed 4,512,130 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 11 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-10-5: Jun 14 2022 11:36AM -- GARCIAJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-11-7

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

370,000 GALLON ABOVEGROUND GASOLINE, DIESEL, JET FUEL, TRANSMIX, AND ETHANOL STORAGE TANK FR-8, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-8 shall not exceed 3,218,570 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 10.2 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-12-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

925,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-9, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-9 shall not exceed 8,038,030 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 12.6 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-13-11

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

634,000 GALLON ABOVEGROUND MULTI-PRODUCT (GASOLINE, DIESEL, JET FUEL, & ETHANOL) ORGANIC LIQUID STORAGE TANK FR-10 EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The only organic liquids approved for storage in the internal floating roof tank shall be gasoline, diesel, jet fuel, and ethanol. [District NSR Rule] Federally Enforceable Through Title V Permit
3. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
4. Tank gauging and sampling devices shall be leak free (as defined in District Rule 4623, 3.17 (amended 5/19/2005)). [District Rule 4623, 5.5.2.1] Federally Enforceable Through Title V Permit
5. Records of monthly organic liquid throughput shall be maintained and shall be made available for District inspection upon request. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
6. The total annual organic liquid throughput for Tank FR-10 shall not exceed 4,737,700 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Daily VOC emissions shall not exceed 5.42 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The permittee shall comply with recordkeeping requirements in section 6.3 of District Rule 4623 (Amended 5/19/2005) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
9. Vapor pressure of stored liquids shall be determined as described in section 6.2 of District Rule 4623 (Amended 5/19/2005). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
10. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
11. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
12. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-14-6

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

1,145,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-11, EXTERNAL FLOATING ROOF WITH AN HMT SCISSOR SHOE PRIMARY SEAL, AND AN HMT RIM-MOUNTED SECONDARY SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-11 shall not exceed 3,218,570 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 10.2 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-15-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

761,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-12, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-12 shall not exceed 6,622,560 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 12 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-16-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

1,343,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-13, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-13 shall not exceed 11,699,415 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 14 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-17-6

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

1,145,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-14, EXTERNAL FLOATING ROOF WITH A RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The total annual gasoline throughput for Tank FR-14 shall not exceed 9,953,185 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Daily VOC emissions shall not exceed 13.3 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
5. True vapor pressure of the organic liquid stored shall be less than 11 psia. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a floating roof consisting of a pan type that was installed before December 20, 2001, pontoon-type or double-deck-type cover which rests upon the surface of the liquid being stored and is equipped with a closure device between the tank shell and roof edge consisting of a primary and a secondary seal. [District Rule 4623, 5.3.1] Federally Enforceable Through Title V Permit
7. The external floating roof shall float on the surface of the stored liquid at all times (i.e., off the roof leg supports) except during the initial fill until the roof is lifted off the leg supports and when the tank is completely emptied and subsequently refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on its legs, the permittee shall notify the APCO in writing at least five calendar days prior to performing the work. The tank must be in compliance with this rule before it may land on its legs. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
8. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
10. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
11. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-18-7

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

1,470,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-16, INTERNAL FLOATING ROOF EQUIPPED WITH PDM'S DELTA PRIMARY SEAL AND WIPER TYPE SECONDARY SEAL

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520] Federally Enforceable Through Title V Permit
3. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
4. The total annual gasoline throughput for Tank FR-16 shall not exceed 17,520,000 barrels. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Daily VOC emissions shall not exceed 16.6 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623] Federally Enforceable Through Title V Permit
8. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
9. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
10. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-19-6

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

1,512,000 GALLON ABOVEGROUND CONE ROOF GASOLINE STORAGE TANK FR-17, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED MECHANICAL SHOE TYPE PRIMARY SEAL AND A RIM-MOUNTED STEEL COMPRESSION PLATE SECONDARY SEAL

PERMIT UNIT REQUIREMENTS

1. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
2. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
3. Gasoline throughput shall not exceed 36,000 barrels per day based on a monthly average. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3] Federally Enforceable Through Title V Permit
5. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
6. The cumulative length of all gaps between the tank shell and the primary seal greater than 1/2 inch shall not exceed 10% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. The cumulative length of all primary seal gaps greater than 1/8 inch shall not exceed 30% of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
8. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
10. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
11. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
12. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-20-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

210,000-GALLON ABOVEGROUND CONE ROOF STORAGE TANK FR-18, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS.

PERMIT UNIT REQUIREMENTS

1. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3, District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
3. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3, CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
4. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
5. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
6. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
8. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
9. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
10. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-21-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

2,100,000 GALLON ABOVEGROUND CONE ROOF STORAGE TANK FR-19, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS.

PERMIT UNIT REQUIREMENTS

1. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3, District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
3. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3, CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
4. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
5. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
6. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
8. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
9. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
10. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-22-6

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

3,360,000 GALLON ABOVEGROUND CONE ROOF GASOLINE STORAGE TANK FR-20, INTERNAL FLOATING ROOF EQUIPPED WITH AN HMT MINI-SHOE SEAL AND AN HMT VAPORFLEX SECONDARY SEAL.

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the external floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
3. Maintain tank-to-seal gaps according to the criteria in section 5.3.2 of District Rule 4623 (amended 5-19-05). [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
4. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
5. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
6. The total annual gasoline throughput for Tank FR-20 shall not exceed 29,200,000 barrels per year. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Daily VOC emissions shall not exceed 13.8 pounds per day. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The permittee shall comply with all other applicable provisions of Rule 4623 (amended 5-19-05). [District Rule 4623] Federally Enforceable Through Title V Permit
9. The permittee shall comply with all applicable provisions of 40 CFR 60 Subpart Kb. [40 CFR 60 Subpart Kb] Federally Enforceable Through Title V Permit
10. The permittee shall comply with recordkeeping requirements in section 6.3 of District Rule 4623 (amended 5-19-05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-23-7

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

2,520,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-21, INTERNAL FLOATING ROOF EQUIPPED WITH URETHANE FABRIC "RESILIENT TOROIDAL SEAL" WITH WOVEN NYLON INSERT, AND "FOAM LOGS" INSERTED BETWEEN TANK SHELL AND PAN RIM

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. No gap between the tank shell and the primary seal shall exceed one-half (1/2) inch. The cumulative length of all primary seal gaps greater than one-eighth (1/8) inch shall not exceed five (5) percent of the tank circumference. No continuous gap greater than one-eighth (1/8) inch shall exceed ten (10) percent of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
4. No gap between the tank shell and the secondary seal shall exceed one-half (1/2) inch. The cumulative length of all gaps between the tank shell and the secondary seal, greater than one-eighth (1/8) inch shall not exceed five (5) percent of the tank circumference. [District Rule 4623] Federally Enforceable Through Title V Permit
5. No gap between the tank shell and the secondary seal shall exceed one-half (1/2) inch. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The secondary seal shall extend from the roof of the tank to the shell and not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
7. The secondary seal shall allow easy insertion of probes up to one-half (1/2) in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
8. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak-free, except when the device or appurtenance is in use. [District Rule 4623] Federally Enforceable Through Title V Permit
9. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
10. The permittee shall comply with all other applicable provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The permittee shall comply with all applicable provisions of 40 CFR 60 Subpart Kb. [40 CFR 60 Subpart Kb] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-24-5

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

375,000 GALLON VAPOR HOLDER TANK EQUIPPED WITH A BLADDER SYSTEM TO CONTROL HYDROCARBON EMISSIONS VENTING TO THE VAPOR BURNER LISTED UNDER PERMIT C-1077-3

PERMIT UNIT REQUIREMENTS

1. The air pollution control measure "bladder system" shall be maintained as per manufacturer's specifications submitted to the District. [District Rule 2201] Federally Enforceable Through Title V Permit
2. There shall be no uncontrolled vapor venting from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The vapor transfer lines to the vapor recovery unit shall be maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All processor and transfer equipment, including vapor transfer lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Inspections shall be conducted using sight, sound and smell, and instrument methods to detect leaks every month to maintain compliance with the leak-free condition. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
6. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 2520, 9.3] Federally Enforceable Through Title V Permit
7. Any vapor control device, other than a flare, shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-26-11

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

LOADING RACK #1 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-27-11

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

LOADING RACK #2 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-28-11

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

LOADING RACK #3 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-29-11

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

LOADING RACK #4 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-38-11

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

LOADING RACK #6 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-42-7

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

LOADING RACK #5 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO JOHN ZINK VAPOR BURNER

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-43-8

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

TWO 500 GALLON FUEL ADDITIVE STORAGE CONTAINERS, LINKED BY PIPE TO LOADING ARM, FOR STORAGE OF FUEL ADDITIVE

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. These tanks shall only store fuel additive having a vapor pressure (TVP) of less than 1.5 psia under actual storage conditions. [District Rule 2520, Section 9.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-49-8

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

TWO-LANE DENATURED ETHANOL TRUCK UNLOADING STATION EACH LANE WITH TWO FLEXIBLE UNLOADING HOSES, TWO PUMPS, PRODUCT ACCUMULATOR, AIR ELIMINATOR, METER AND SUPPORT EQUIPMENT, AND ORGANIC VAPORS RETURNED TO DELIVERY TRUCKS

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Vapor return hose(s) shall connect displaced vapors to the delivery truck whenever tank truck, trailer, or car is unloading organic liquid. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
4. All delivery trucks must be equipped with vapor collection equipment capable of undergoing a pressure change of no more than 1 inch of water within 5 minutes after it is pressured to 18 inches of water. This must be demonstrated annually for each truck using the procedures specified in EPA Method 27 of 40 CFR 60, Appendix A or CARB Test Methods CP-204, TP-204.1, TP204-2, and TP-204.3. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The vapor collection and control system shall operate such that the pressure in the delivery tank being unloaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
6. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624] Federally Enforceable Through Title V Permit
7. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv as methane above a background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624] Federally Enforceable Through Title V Permit
8. The operator shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624] Federally Enforceable Through Title V Permit
9. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-50-3

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

80,000 BARREL INTERNAL FLOATING ROOF GASOLINE, DIESEL, JET FUEL, AND TRANSMIX STORAGE TANK (FR-26)

PERMIT UNIT REQUIREMENTS

1. Emissions from this tank shall not exceed 23.4 lbs VOC per day. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Daily throughput of this tank shall not exceed 80,000 barrels per day. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall inspect all seals of the floating roof or floating cover at least once a year and shall maintain the seals and vapor control features of the tank in accordance with the manufacturer's recommendations. [District Rule 2520, 9.3, District Rule 4623, 6.1] Federally Enforceable Through Title V Permit
4. The true vapor pressure (TVP) of liquids stored in the internal floating roof tank shall be less than 11 psia under storage conditions. [District Rule 4623, 5.1.1] Federally Enforceable Through Title V Permit
5. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. Whenever the permittee intends to land the roof on it's legs, the permittee shall notify the APCO in writing at least five days prior to performing the work. [District Rule 4623, 5.3.1.3, CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
6. Gaps between the tank shell and the primary seal shall not exceed 1 1/2 inches. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
7. The cumulative length of all gaps, between the tank shell and the primary seal: 1) Greater than one-half (1/2) inch shall not exceed 10 percent of the circumference of the tank; and 2) Greater than one-eighth (1/8) inch shall not exceed 30 percent of the circumference of the tank. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
8. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
9. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
10. Cumulative length of all gaps between the tank shell and secondary seal greater than one-eighth (1/8) inch shall not exceed 5 percent of the tank circumference for all seal types. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
11. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-50-3: Jun 14 2022 11:38AM -- GARCIAJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-51-4

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

TWO LANE FUEL LOADING RACK #8 FOR PETROLEUM DISTILLATES AND GASOLINE WITH EIGHT LOADING STATIONS PER LANE CONTROLLED BY THE VAPOR COMBUSTION SYSTEM LISTED UNDER PERMIT C-1077-3, AND PERMIT EXEMPT DIESEL DYE INJECTION AND FUEL ADDITIVE INJECTION

PERMIT UNIT REQUIREMENTS

1. Petroleum distillates includes the following products: diesel, biodiesel blends, and B100 biodiesel blendstock. [District Rule 2080] Federally Enforceable Through Title V Permit
2. Vapor collection and control system shall operate such that the pressure in the delivery tank being loaded does not exceed 18 inches water column pressure and 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
3. Construction, reconstruction (as defined in 40 CFR 60.15), or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
4. During the loading of petroleum products, the operator shall perform and record the results of monthly leak inspections of the loading and vapor collection equipment at each loading arm. Leak inspections shall be conducted using sight, sound, smell and instrument methods to detect leaks. Instrument detection shall be conducted using EPA Method 21 and shall be measured at the surface of the component interface of the potential source. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520 and 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
5. Corrective steps shall be taken at any time the operator observes excess drainage at disconnect. In addition, the operator shall perform and record the results of monthly drainage inspections at disconnect for each loading arm. If no excess drainage conditions are found during five consecutive monthly inspections, the drainage inspection frequency may be changed from monthly to quarterly. However, if one or more excess drainage condition is found during a quarterly inspection, the inspection frequency shall return to monthly. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Drainage inspections shall be completed before 10:00 AM the day of inspection. Compliance shall be demonstrated by collecting all drainage at disconnect in a spouted container. The drainage shall be transferred to a graduated cylinder and the volume determined within one (1) minute of collection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. The permittee shall maintain an inspection log containing at least the following: A) date and time of leak and drainage inspections, B) type of component leaking, C) leak determination method, D) findings, E) date and time of leak repair, and emission level of recheck after leak is repaired, F) method used to minimize the leak to lowest possible level within 72 hours after detection, and G) inspector name and signature. [District Rules 2520 and 4624 and 40 CFR 60.505(c)] Federally Enforceable Through Title V Permit
8. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-52-1

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

OFF-SPECIFICATION PRODUCT TRUCK UNLOADING STATION WITH ONE UNLOADING CONNECTION GRAVITY DRAINED TO ONE PUMP SLEEVE, ONE PUMP, AIR ELIMINATOR, METER AND SUPPORT EQUIPMENT, AND VAPOR RETURN SYSTEM (VAPOR VENTED BACK TO TANKER TRUCK)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Vapor return hose(s) shall connect displaced vapors to the delivery truck whenever tank truck, trailer, or car is unloading organic liquid. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
5. All delivery trucks must be equipped with vapor collection equipment capable of undergoing a pressure change of no more than 1 inch of water within 5 minutes after it is pressured to 18 inches of water. This must be demonstrated annually for each truck using the procedures specified in EPA Method 27 of 40 CFR 60, Appendix A or CARB Test Methods CP-204, TP-204.1, TP204-2, and TP-204.3. [District NSR Rule] Federally Enforceable Through Title V Permit
6. The vapor collection and control system shall operate such that the pressure in the delivery tank being unloaded does not exceed 18 inches water column pressure and six (6) inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit
7. The transfer rack and vapor collection equipment shall be designed, installed, maintained and operated such that there are no leaks and no excess organic liquid drainage at disconnections. [District Rule 4624] Federally Enforceable Through Title V Permit
8. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of VOC greater than 1,000 ppmv as methane above a background when measured using a portable hydrocarbon detection instrument in accordance with EPA Method 21. [District Rule 4624] Federally Enforceable Through Title V Permit
9. The operator shall inspect the vapor collection system, the vapor disposal system, and each transfer rack handling organic liquids for leaks during transfer at least once every calendar quarter using the EPA Method 21. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
10. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SFPP, L.P.

Location: 4149 S MAPLE AVE, FRESNO, CA 93725

C-1077-52-1: Jun 14 2022 11:38AM -- GARCIAJ

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-1077-53-1

EXPIRATION DATE: 05/31/2021

EQUIPMENT DESCRIPTION:

500 GALLON FUEL ADDITIVE STORAGE TANK WITH PV VALVE LINKED BY PIPE TO LOADING RACK LISTED IN PERMIT C-1077-51

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.4 psia under all storage conditions. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 2201] Federally Enforceable Through Title V Permit
6. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Daily throughput of this tank shall not exceed 500 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Annual throughput of this tank shall not exceed 6,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. VOC emission rate from the tank shall not exceed 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Permittee shall maintain daily records of organic liquid throughput and shall keep accurate records of each organic liquid stored in the tank, including its storage temperature and TVP. [District Rule 1070] Federally Enforceable Through Title V Permit
11. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

11. An operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and the operator shall contact the APCO in writing within 14 days. [District Rule 4624, 5.9] Federally Enforceable Through Title V Permit
12. Unloading VOC emissions from the unloading system shall not exceed 0.093 lb-VOC/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Unloading VOC emissions from the unloading system shall not exceed 0.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The maximum number of unloading events shall not exceed either of the following limits: 45 events/day or 16,400 events/year. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Fugitive component VOC emissions from the unloading system shall not exceed 0.06 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The maximum volume of liquid spillage/leaks from each hose disconnect shall not exceed 10 milliliters. [District Rule 2201] Federally Enforceable Through Title V Permit
17. VOC emissions from truck unloading connections shall not exceed 0.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-3, Marketing Terminal Average Emission Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
19. The maximum throughput of off-specification product unloaded shall not exceed any of the following: 75,600 gallons per day or 27,552,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Daily records of amount of off-specification product unloaded and number of trucks unloaded at the unloading system shall be maintained. [District Rules 1070, 2201, 4624] Federally Enforceable Through Title V Permit
22. Permittee shall maintain the following records for each truck: 1) the annual vapor collection equipment test result, 2) date the test was performed, and 3) truck identification. [District NSR Rule] Federally Enforceable Through Title V Permit
23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 72 hours after detection. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
24. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Detailed Facility Report
For Facility=1077 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

SFPP, L.P. 4149 S MAPLE AVE FRESNO, CA 93725	FAC #	C 1077	TYPE:	TitleV	EXPIRE ON:	05/31/2021
	STATUS:	A	TOXIC ID:	40210	AREA:	2 /
	TELEPHONE:	7145604400			INSP. DATE:	05/22

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-1077-1-5	460 hp IC Engine	3020-10 D	1	577.00	577.00	A	460 HP MODEL #3406B DIESEL-FIRED EMERGENCY IC ENGINE POWERING ONE FIRE PROTECTION PUMP
C-1077-2-5	460 hp IC Engine	3020-10 D	1	577.00	577.00	A	460 HP MODEL #3406B DIESEL-FIRED EMERGENCY IC ENGINE POWERING ONE FIRE PROTECTION PUMP
C-1077-3-17	78 MMBtu/hr	3020-02 H	1	1,238.00	1,238.00	A	78.0 MMBTU/HR JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM AS THE CONTROL DEVICE OF THE BULK LOADING OPERATION WITH A VARIABLE FREQUENCY DRIVE FOR AIR INTAKE FAN MOTOR AND FLAME ARRESTORS
C-1077-4-4	63.0 KGAL TANK FR-1	3020-05 D	1	223.00	223.00	A	63,000 GALLON ABOVEGROUND FIXED ROOF STORAGE TANK, FR-1, WITH CONAKO VACONODECK INTERNAL FLOATING PAN.
C-1077-5-10	762,000 GALLONS	3020-05 F	1	362.00	362.00	A	762,500 GALLON ABOVEGROUND MULTI-PRODUCT (GASOLINE & ETHANOL) ORGANIC LIQUID STORAGE TANK FR-2 EQUIPPED WITH DOMED EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP AND ETHANOL TRUCK UNLOADING STATION WITH TWO FOUR-INCH FLEXIBLE UNLOADING HOSES
C-1077-6-6	370.4 KGAL TANK FR-3	3020-05 E	1	296.00	296.00	A	370,400 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-3, EXTERNAL FLOATING ROOF WITH A RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-7-6	1,260.0 KGAL TANK FR-4	3020-05 G	1	461.00	461.00	A	1,260,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-4, INTERNAL FLOATING ROOF EQUIPPED WITH A LIQUID MOUNTED METALLIC SHOE PRIMARY SEAL AND A RIM-MOUNTED SECONDARY SEAL MADE OF STEEL COMPRESSION PLATES AND A RUBBER WIPER BLADE TIP WITH A RECIRCULATION SYSTEM AND ELECTRIC HEATER FOR MAINTAINING TANK TEMPERATURE
C-1077-8-5	1,736.0 KGAL TANK FR-5	3020-05 G	1	461.00	461.00	A	1,736,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-5, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-9-6	923.0 KGAL TANK FR-6	3020-05 G	1	461.00	461.00	A	923,000 GALLON ABOVEGROUND GASOLINE TANK (FR-6) WITH AN EXTERNAL FLOATING ROOF AND A MATRIX SERVICE RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-10-5	519.0 KGAL TANK FR-7	3020-05 F	1	362.00	362.00	A	519,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-7, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-11-7	370.0 KGAL TANK FR-8	3020-05 E	1	296.00	296.00	A	370,000 GALLON ABOVEGROUND GASOLINE, DIESEL, JET FUEL, TRANSMIX, AND ETHANOL STORAGE TANK FR-8, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP

Detailed Facility Report
For Facility=1077 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-1077-12-5	925.0 KGAL TANK FR-9	3020-05 G	1	461.00	461.00	A	925,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-9, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-13-11	634,000 gallon tank	3020-05 F	1	362.00	362.00	A	634,000 GALLON ABOVEGROUND MULTI-PRODUCT (GASOLINE, DIESEL, JET FUEL, & ETHANOL) ORGANIC LIQUID STORAGE TANK FR-10 EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS
C-1077-14-6	1,145.0 KGAL TANK FR-11	3020-05 G	1	461.00	461.00	A	1,145,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-11, EXTERNAL FLOATING ROOF WITH AN HMT SCISSOR SHOE PRIMARY SEAL, AND AN HMT RIM-MOUNTED SECONDARY SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-15-5	761.0 KGAL TANK FR-12	3020-05 F	1	362.00	362.00	A	761,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-12, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-16-5	1,343.0 KGAL TANK FR-13	3020-05 G	1	461.00	461.00	A	1,343,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-13, EXTERNAL FLOATING ROOF WITH AN HMT, INC. RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-17-6	1,145.0 KGAL TANK FR-14	3020-05 G	1	461.00	461.00	A	1,145,000 GALLON ABOVEGROUND GASOLINE STORAGE TANK FR-14, EXTERNAL FLOATING ROOF WITH A RIM-MOUNTED SEAL MADE OF STEEL COMPRESSION PLATES AND RUBBER WIPER TIP.
C-1077-18-7	1,470,000 gallon Tank #FR-16	3020-05 G	1	461.00	461.00	A	1,470,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-16, INTERNAL FLOATING ROOF EQUIPPED WITH PDM'S DELTA PRIMARY SEAL AND WIPER TYPE SECONDARY SEAL
C-1077-19-6	1,512,000 gallon tank	3020-05 G	1	461.00	461.00	A	1,512,000 GALLON ABOVEGROUND CONE ROOF GASOLINE STORAGE TANK FR-17, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED MECHANICAL SHOE TYPE PRIMARY SEAL AND A RIM-MOUNTED STEEL COMPRESSION PLATE SECONDARY SEAL
C-1077-20-5	210.0 KGAL TANK FR-18	3020-05 E	1	296.00	296.00	A	210,000-GALLON ABOVEGROUND CONE ROOF STORAGE TANK FR-18, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS.
C-1077-21-5	2,100.0 KGAL TANK FR-19	3020-05 G	1	461.00	461.00	A	2,100,000 GALLON ABOVEGROUND CONE ROOF STORAGE TANK FR-19, INTERNAL FLOATING ROOF EQUIPPED WITH APPROVED PRIMARY AND SECONDARY SEALS.
C-1077-22-6	3,360.0 KGAL TANK FR-20	3020-05 G	1	461.00	461.00	A	3,360,000 GALLON ABOVEGROUND CONE ROOF GASOLINE STORAGE TANK FR-20, INTERNAL FLOATING ROOF EQUIPPED WITH AN HMT MINI-SHOE SEAL AND AN HMT VAPORFLEX SECONDARY SEAL.
C-1077-23-7	2,520,000 gallon Tank #FR-21	3020-05 G	1	461.00	461.00	A	2,520,000 GALLON ABOVEGROUND CONE ROOF PETROLEUM DISTILLATES AND GASOLINE STORAGE TANK FR-21, INTERNAL FLOATING ROOF EQUIPPED WITH URETHANE FABRIC "RESILIENT TOROIDAL SEAL" WITH WOVEN NYLON INSERT, AND "FOAM LOGS" INSERTED BETWEEN TANK SHELL AND PAN RIM

Detailed Facility Report
For Facility=1077 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-1077-24-5	375.0 KGAL VAPOR HOLDER TANK	3020-05 E	1	296.00	296.00	A	375,000 GALLON VAPOR HOLDER TANK EQUIPPED WITH A BLADDER SYSTEM TO CONTROL HYDROCARBON EMISSIONS VENTING TO THE VAPOR BURNER LISTED UNDER PERMIT C-1077-3
C-1077-26-11	135 electrical HP	3020-01 D	1	379.00	379.00	A	LOADING RACK #1 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3
C-1077-27-11	130 electrical HP	3020-01 D	1	379.00	379.00	A	LOADING RACK #2 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3
C-1077-28-11	115 electrical HP	3020-01 D	1	379.00	379.00	A	LOADING RACK #3 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3
C-1077-29-11	215 electrical HP	3020-01 E	1	495.00	495.00	A	LOADING RACK #4 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3
C-1077-38-11	115 electrical HP	3020-01 D	1	379.00	379.00	A	LOADING RACK #6 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO ONE JOHN ZINK ZTOF VAPOR BURNER COMBUSTION SYSTEM LISTED UNDER C-1077-3
C-1077-42-7	80 electrical HP	3020-01 C	1	239.00	239.00	A	LOADING RACK #5 FOR PETROLEUM DISTILLATES AND GASOLINE, WITH ORGANIC VAPORS EXHAUSTED TO JOHN ZINK VAPOR BURNER
C-1077-43-8	1,000 gallons	3020-05 A	1	91.00	91.00	A	TWO 500 GALLON FUEL ADDITIVE STORAGE CONTAINERS, LINKED BY PIPE TO LOADING ARM, FOR STORAGE OF FUEL ADDITIVE
C-1077-49-8	50 hp	3020-01 C	1	239.00	239.00	A	TWO-LANE DENATURED ETHANOL TRUCK UNLOADING STATION EACH LANE WITH TWO FLEXIBLE UNLOADING HOSES, TWO PUMPS, PRODUCT ACCUMULATOR, AIR ELIMINATOR, METER AND SUPPORT EQUIPMENT, AND ORGANIC VAPORS RETURNED TO DELIVERY TRUCKS
C-1077-50-3	3,360,000 gallons	3020-05 G	1	461.00	461.00	A	80,000 BARREL INTERNAL FLOATING ROOF GASOLINE, DIESEL, JET FUEL, AND TRANSMIX STORAGE TANK (FR-26)
C-1077-51-4	199 electrical HP	3020-01 D	1	379.00	379.00	A	TWO LANE FUEL LOADING RACK #8 FOR PETROLEUM DISTILLATES AND GASOLINE WITH EIGHT LOADING STATIONS PER LANE CONTROLLED BY THE VAPOR COMBUSTION SYSTEM LISTED UNDER PERMIT C-1077-3, AND PERMIT EXEMPT DIESEL DYE INJECTION AND FUEL ADDITIVE INJECTION
C-1077-52-1	5 Electric HP	3020-01 A	1	107.00	107.00	A	OFF-SPECIFICATION PRODUCT TRUCK UNLOADING STATION WITH ONE UNLOADING CONNECTION GRAVITY DRAINED TO ONE PUMP SLEEVE, ONE PUMP, AIR ELIMINATOR, METER AND SUPPORT EQUIPMENT, AND VAPOR RETURN SYSTEM (VAPOR VENTED BACK TO TANKER TRUCK)
C-1077-53-1	500 gallons	3020-05 A	1	91.00	91.00	A	500 GALLON FUEL ADDITIVE STORAGE TANK WITH PV VALVE LINKED BY PIPE TO LOADING RACK LISTED IN PERMIT C-1077-51

Number of Facilities Reported: 1

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

37. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit
38. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
39. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

25. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit
26. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
27. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5-19-05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
28. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
29. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
30. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
31. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
32. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
33. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
34. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
35. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
36. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
13. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
14. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
15. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
16. All openings in the roof used for sampling and gauging, except pressure-vacuum comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
17. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
18. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
19. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
20. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3, 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
21. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4, 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
22. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5, 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6, 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
24. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. An operator may apply for a written approval from the APCO to change the inspection frequency from quarterly to annually provided no leaks were found during five consecutive quarterly inspections. Upon identification of any leak during an annual inspection, the inspection frequency shall revert back to quarterly, and the operator shall contact the APCO in writing within 14 days. [District Rule 4624] Federally Enforceable Through Title V Permit
11. Fugitive component VOC emissions from the denatured ethanol unloading system shall not exceed 1.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Permittee shall maintain accurate component count for tank according to EPA's "Protocol for Equipment Leak Emission Estimate," Table 2-3, Marketing Terminal Average Emission Factors. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The maximum throughput of denatured ethanol unloaded shall not exceed 427,350 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The maximum volume of liquid spilled during disconnect shall not exceed 10 milliliters. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Daily records of amount of denatured ethanol unloaded at the denatured ethanol unloading system shall be maintained. [District Rules 1070, 2201, 4624] Federally Enforceable Through Title V Permit
17. Permittee shall maintain the following records for each truck: 1) the annual vapor collection equipment test result, 2) date the test was performed, and 3) truck identification. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 72 hours after detection. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
19. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

9. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503. "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 422, or ARB Method 2-4. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The loading rack's vapor collection and control system (VCCS) shall be tested annually to demonstrate the pressure in the delivery tanks being loaded complies with the requirements specified in this permit. Compliance shall be determined by calibrating and installing a liquid manometer, magnehelic device, or other instrument demonstrated to be equivalent, capable of measuring up to 500 mm water gauge pressure with a precision of 2.5 mm water gauge, on the terminal's VCCS at a pressure tap as close as possible to the connection with the product tank truck. The highest instantaneous pressure measurement as well as all pressure measurements at 5 minute intervals during delivery vessel loading must be recorded. Every loading position must be tested at least once during the annual performance test. [District Rule 2520 and 40 CFR 60.503(d)] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained and operated such that there are no leaks or and no excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface of the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624] Federally Enforceable Through Title V Permit
12. The product and vapor lines shall be connected and disconnected in a manner such that liquid and vapor emissions will be minimized. [District Rule 4624] Federally Enforceable Through Title V Permit
13. All liquid transfer lines, piping, and associated fittings shall be maintained in a leak tight condition. [District Rule 4624] Federally Enforceable Through Title V Permit
14. Processor and support equipment, including vapor return lines and connections, must be maintained in proper operating condition at all times. Permittee shall comply with all maintenance instructions associated with vapor control equipment. [District Rule 4624] Federally Enforceable Through Title V Permit
15. The vapor control system shall be maintained in proper operating condition at all times. [District Rule 4624] Federally Enforceable Through Title V Permit
16. All leaking components shall be repaired or replaced within 72 hours of discovery. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624 and 40 CFR 60.502(j)] Federally Enforceable Through Title V Permit
17. The loading rack shall be equipped with bottom loading and a vapor collection and control system such that TOC emissions do not exceed 0.02 pounds per 1000 gallons or organic liquid with greatest vapor pressure loaded. [District Rule 4624 and 40 CFR 60.502(b)] Federally Enforceable Through Title V Permit
18. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Records of daily and annual gasoline throughput shall be maintained, retained on the premises, and made available to District staff upon request. [District Rules 2201 and 4624] Federally Enforceable Through Title V Permit
20. All records shall be retained for a period of at least 5 years and shall be made available for APCO, ARB, or EPA inspection upon request. [District Rules 1070 and 4624] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624, Fresno County Rule 412 and 40 CFR 60 Subpart XX. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

35. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
36. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

24. For this vessel which is equipped with a double seal system, inspections may be carried out as specified above, or using the following procedure every 5 years: Visually inspect the internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes and sleeve seals each time the vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other opening in the seal or the seal fabric, or the secondary seal has holes, tears, or other opening in the seal or seal fabric, or the gaskets no longer close off the liquid surfaces, or the slotted membrane has more than 10 percent open area, the operator shall make necessary repairs prior to filling the vessel. [40 CFR 60.113b(a)(3) and (4)] Federally Enforceable Through Title V Permit
25. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623] Federally Enforceable Through Title V Permit
26. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623 and 40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
27. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
29. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
30. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
31. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
32. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
33. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
34. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The permittee shall comply with recordkeeping requirements in section 6.3 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. [District Rule 4623 and 40 CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
14. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [District Rule 4623 and 40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
15. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623 and 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
16. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623 and 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
17. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623 and 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
18. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623 and 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
19. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening. [District Rule 4623 and 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
20. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. [District Rule 4623 and 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
21. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
22. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623 and 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

33. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
34. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
35. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

22. For this vessel which is equipped with a double seal system, inspections may be carried out as specified above, or using the following procedure every 5 years: Visually inspect the internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes and sleeve seals each time the vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other opening in the seal or the seal fabric, or the secondary seal has holes, tears, or other opening in the seal or seal fabric, or the gaskets no longer close off the liquid surfaces, or the slotted membrane has more than 10 percent open area, the operator shall make necessary repairs prior to filling the vessel. [40 CFR 60.113b(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
24. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5-19-05). [District Rule 4623, 6.2 and 40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit
25. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
26. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
27. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available for District staff upon request. [District Rule 2520, 9.3 and District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
28. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
29. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
30. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
31. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [District Rule 4623, 6.3.5 and 40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
32. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [District Rule 4623, 6.1.2 and 40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal roof shall be floating on the liquid surface except during initial fill and when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible. [District Rule 4623, 5.3.1.3 and 40 CFR 60.112b(a)(1)(i)] Federally Enforceable Through Title V Permit
12. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [District Rule 4623, 5.5.2.1.5 and 40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
13. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
14. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.2, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
15. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3 and 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
16. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4 and 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
17. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening. [District Rule 4623, 5.5.2.1.5 and 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
18. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. [District Rule 4623, 5.5.2.1.6 and 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
19. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
20. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
21. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
37. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
25. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5-19-05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
26. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
27. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
28. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
29. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
30. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
31. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
32. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
33. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
34. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
35. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
12. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
13. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
14. All openings in the roof used for sampling and gauging, except pressure-vacuum comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
15. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
16. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
17. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
18. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3, 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
19. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4, 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
20. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5, 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
21. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6, 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
22. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. Available data on the storage temperature may be used to determine the maximum true vapor pressure. For vessels operated above or below ambient temperatures, the maximum true vapor pressure may be calculated using the highest expected calendar month average of the storage temperature. For vessels operated at ambient temperature, the maximum true vapor pressure may be calculated using maximum local monthly ambient temperatures as reported by the National Weather Service. [40 CFR 60.116b(e)(1)] Federally Enforceable Through Title V Permit
37. For crude oil or refined petroleum products the vapor pressure may be obtained by either: a) available data on the Reid vapor pressure and maximum expected storage temperature from nomographs contained in API Bulletin 2517, b) obtained from standard reference texts, c) determined by ASTM Method D2879-83, or c) measured or calculated by an appropriate method approved by the APCO. [40 CFR 60.116b(e)(2) and (3)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
25. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5-19-05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
26. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
27. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
28. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
29. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
30. The internal floating roof tank shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: a) a foam or liquid-filled seal mounted in contact with the liquid, b) two seals mounted one above the other so that each forms a continuous closure c) a mechanical shoe seal. [40 CFR 60.112b(a)(1)(ii)] Federally Enforceable Through Title V Permit
31. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover. [40 CFR 60.112b(a)(1)(ix)] Federally Enforceable Through Title V Permit
32. The operator shall visually inspect the internal floating roof, the primary seal and the secondary seal prior to filling the storage vessel. If holes, tears, or other openings are found, they shall be repaired prior to filling. [40 CFR 60.113b(a)(1)] Federally Enforceable Through Title V Permit
33. Operator shall notify the APCO in writing 30 days prior to the filling or refilling of the vessel. If the inspection is not planned and the operator could not have known about the inspection 30 days in advance of refilling the tank, the operator shall make notification 7 days prior to refilling the tank. [40 CFR 60.113b(a)(5)] Federally Enforceable Through Title V Permit
34. Records of each inspection shall be maintained. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment. If any defects are detected during an inspection, operator shall provide the APCO with a report within 30 days of the inspection. The report shall identify the storage vessel, the nature of the defects, and the date the vessel was emptied or the nature of and date the repair was made. [40 CFR 60.115b(a)(2), (3) and (4)] Federally Enforceable Through Title V Permit
35. The operator shall keep readily available accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. The operator shall also keep a record of the liquid stored, the period of storage, and the maximum true vapor pressure of the liquid during the respective storage period. [40 CFR 60.116b(b) and (c)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
12. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
13. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
14. All openings in the roof used for sampling and gauging, except pressure-vacuum comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
15. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
16. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iii)] Federally Enforceable Through Title V Permit
17. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1, 40 CFR 60.112b(a)(1)(iv)] Federally Enforceable Through Title V Permit
18. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3, 40 CFR 60.112b(a)(1)(v)] Federally Enforceable Through Title V Permit
19. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4, 40 CFR 60.112b(a)(1)(vi)] Federally Enforceable Through Title V Permit
20. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5, 40 CFR 60.112b(a)(1)(vii)] Federally Enforceable Through Title V Permit
21. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6, 40 CFR 60.112b(a)(1)(viii)] Federally Enforceable Through Title V Permit
22. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1, 40 CFR 60.113b(b)(a)(3) and (4)] Federally Enforceable Through Title V Permit
23. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
27. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
28. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
29. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

13. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
14. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
15. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
16. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
17. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
18. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1] Federally Enforceable Through Title V Permit
19. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1] Federally Enforceable Through Title V Permit
20. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3] Federally Enforceable Through Title V Permit
21. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4] Federally Enforceable Through Title V Permit
22. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6] Federally Enforceable Through Title V Permit
24. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1] Federally Enforceable Through Title V Permit
25. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
27. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623] Federally Enforceable Through Title V Permit
28. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5/19/05). [District Rule 4623] Federally Enforceable Through Title V Permit
29. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all necessary information to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
30. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
31. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 18 inches above the stored liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
13. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623] Federally Enforceable Through Title V Permit
14. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
15. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
16. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
17. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak-free, except when the device or appurtenance is in use. [District Rule 4623] Federally Enforceable Through Title V Permit
18. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
25. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. No continuous gap in the primary seal greater than 1/8 inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
15. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
16. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
17. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
18. Primary seal envelope surrounding the annular vapor space enclosed by the roof edge, stored liquid surface, shoe and seal fabric shall have no openings, holes or tears. [District Rule 4623, 5.1.3] Federally Enforceable Through Title V Permit
19. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
20. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
21. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
22. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
23. Each roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. [District Rule 4623, 5.1.6] Federally Enforceable Through Title V Permit
24. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak free, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and Reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623, 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended December 20, 2001). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623. 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

25. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of vapors. Any defects found are violations of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
26. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623] Federally Enforceable Through Title V Permit
27. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (revised 5/19/05). [District Rule 4623] Federally Enforceable Through Title V Permit
28. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623] Federally Enforceable Through Title V Permit
29. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623] Federally Enforceable Through Title V Permit
30. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
31. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623] Federally Enforceable Through Title V Permit
13. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
14. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
15. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623] Federally Enforceable Through Title V Permit
16. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak free, except when the device or appurtenance is in use for sampling or gauging. [District Rule 4623] Federally Enforceable Through Title V Permit
17. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
18. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623] Federally Enforceable Through Title V Permit
19. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting. [District Rule 4623] Federally Enforceable Through Title V Permit
22. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
23. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623] Federally Enforceable Through Title V Permit
24. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Maximum true vapor pressure may be determined from nomographs contained in API Bulletin 2517, by using the typical Reid vapor pressure and the maximum expected storage temperature of the stored product, unless the APCO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s). Operator shall maintain a record of the petroleum liquid stored and the maximum true vapor pressure of that liquid during the period of storage. [40 CFR 60.113(a) and (b)] Federally Enforceable Through Title V Permit
38. Operator shall determine the true vapor pressure of each type of crude oil with a Reid vapor pressure less than 2.0 psia or whose physical properties preclude determination by the recommended method from available data and record if the true vapor pressure is greater than 1.0 psia. [40 CFR 60.113(c)] Federally Enforceable Through Title V Permit
39. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
40. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
41. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
42. Compliance with permit conditions in the Title V permit shall be deemed compliance with 40 CFR 60 Subpart K and District Rule 4623 (Amended May 19, 2005) A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
43. This unit commenced construction, modification, or reconstruction prior to May 19, 1978. Therefore, the requirements of 40 CFR 60 Subpart Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
44. Records of monthly gasoline throughput and annual throughput based on a rolling 12-month basis shall be maintained and shall be made available upon District request. [District Rule 2520, 9.3 and District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
45. The permittee shall comply with recordkeeping requirements in section 6.3.1 of District Rule 4623 (amended 5/19/05) including recording type of liquid stored, storage temperature, and reid vapor pressure. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
46. Vapor pressure of stored liquids shall be determined as described in section 6.4 of District Rule 4623 (amended 5/19/05). [District Rule 4623. 6.2] Federally Enforceable Through Title V Permit
47. Daily emissions will be determined based on using monthly throughput data and number of days per month. [District Rule 2520, 9.4] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All wells and similar fixed projections through the floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.3.1] Federally Enforceable Through Title V Permit
28. The solid guidepole well shall be equipped with a pole wiper and a gasketed cover, seal or lid which shall be in a closed position at all times (i.e., no visible gap) except when the well is in use. [District Rule 4623, 5.5.2.3.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the solid guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/2 inch. [District Rule 4623, 5.5.2.3.3] Federally Enforceable Through Title V Permit
30. The slotted guidepole well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well, and provided the gap shall not exceed 1/8 inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
31. The gap between the pole wiper and the slotted guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed 1/8 inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
32. The permittee shall make the primary seal envelope available for unobstructed inspection by the APCO on an annual basis at locations selected along its circumference at random by the APCO. In the case of riveted tanks with toroid-type seals, a minimum of eight locations shall be made available; in all other cases, a minimum of four locations shall be made available. If the APCO suspects a violation may exist the APCO may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
33. The permittee shall inspect this floating roof tank at least once every 12 months to determine compliance with the requirements of this rule. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the APCO as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
34. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time this tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
35. The permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of this rule, including the following: 1) Date of inspection and names and titles of company personnel doing the inspection. 2) Tank identification number and Permit to Operate number. 3) Measurements of the gaps between the tank shell and primary and secondary seals. 4) Gas-tight status of the tank and floating roof deck fittings. Records of the gas-tight status shall include the vapor concentration values measured in parts per million by volume (ppmv). 5) Data, supported by calculations, demonstrating compliance with the requirements specified in Sections 5.3, 5.5.2.3.3, 5.5.2.4.2, and 5.5.2.4.3 of Rule 4623. 6) Any corrective actions or repairs performed on the tank in order to comply with rule 4623 and the date(s) such actions were taken. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
36. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No gap between the tank shell and the secondary seal shall exceed 1/2 inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
13. The cumulative length of all gaps between the tank shell and the secondary seal, greater than 1/8 inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
15. The geometry of the metallic-shoe type seal shall be such that the maximum gap between the shoe and the tank shell shall be no greater than 3 inches for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
16. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
17. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
18. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
19. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be gas tight, except when the device or appurtenance is in use [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
20. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv, as methane, above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11 and 6.4.8] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3, 5.5.2.1.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

28. The well on the external floating roof shall be equipped with the following: a sliding cover, a well gasket, a pole sleeve, a pole wiper, and an internal float and float wiper designed to minimize the gap between the float and the well provided the gap does not exceed one-eighth (1/8) inch; or shall be equipped with a well gasket, a zero gap pole wiper seal and a pole sleeve that projects below the liquid surface. [District Rule 4623, 5.5.2.4.2] Federally Enforceable Through Title V Permit
29. The gap between the pole wiper and the guidepole shall be added to the gaps measured to determine compliance with the secondary seal requirement, and in no case shall exceed one-eighth (1/8) inch. [District Rule 4623, 5.5.2.4.3] Federally Enforceable Through Title V Permit
30. The permittee of external floating roof tanks shall make the primary seal envelope available for unobstructed inspection by the District on an annual basis at locations selected along its circumference at random by the District. In the case of riveted tanks with toroid-type seals, a minimum of eight (8) locations shall be made available; in all other cases, a minimum of four (4) locations shall be made available. If the District suspects a violation may exist, the District may require such further unobstructed inspection of the primary seal as may be necessary to determine the seal condition for its entire circumference. [District Rule 4623, 6.1.1] Federally Enforceable Through Title V Permit
31. The permittee shall inspect all floating tanks at least once every 12 months to determine compliance with the requirements of Rule 4623. The actual gap measurements of the floating roof primary and secondary seals shall be recorded. The inspection results shall be submitted to the District as specified in Section 6.3.5. [District Rule 4623, 6.1.3.1] Federally Enforceable Through Title V Permit
32. The permittee shall inspect the primary and secondary seals for compliance with the requirements of Rule 4623 every time a tank is emptied or degassed. Actual gap measurements shall be performed when the liquid level is static but not more than 24 hours after the tank roof is re-floated. [District Rule 4623, 6.1.3.2] Federally Enforceable Through Title V Permit
33. The permittee shall submit the reports of the floating roof tank inspections to the District within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the District, but the inspection report shall be kept on-site and made available upon request by the District. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
34. Permittee shall maintain the records of the external floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the True Vapor pressure (TVP), API gravity, and type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. The permittee shall keep the records at the facility (on-site) for a period of five years. The records shall be made available to the APCO upon request. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

12. No continuous gap greater than one-eighth (1/8) inch wide shall exceed 10% of the tank circumference. [District Rule 4623, 5.3.2.1.1] Federally Enforceable Through Title V Permit
13. No gap between the tank shell and the secondary seal shall exceed one-half (1/2) inch. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
14. The cumulative length of all gaps between the tank shell and the secondary seal, greater than one-eighth (1/8) inch shall not exceed 5% of the tank circumference. [District Rule 4623, 5.3.2.1.2] Federally Enforceable Through Title V Permit
15. The metallic shoe-type seal shall be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface. [District Rule 4623, 5.3.2.1.3] Federally Enforceable Through Title V Permit
16. The maximum gap between the shoe and the tank shell shall be no greater than double the gap allowed by the seal gap criteria for a length of at least 18 inches in the vertical plane above the liquid. [District Rule 4623, 5.3.2.1.4] Federally Enforceable Through Title V Permit
17. There shall be no tears, holes or openings in the secondary seal or in the primary seal envelope surrounding the annular vapor space enclosed by the roof edge, stored liquid surface, shoe, and seal fabric. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
18. The secondary seal shall allow easy insertion of probes of up to one and one-half (1-1/2) inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
19. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
20. All openings in the roof used for sampling and gauging, except pressure-vacuum valves comply with section 5.2, shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak free, except when the device or appurtenance is in use for sampling or gauging. [District Rule 4623, 5.5.1] Federally Enforceable Through Title V Permit
21. Except for automatic bleeder vents, rim vents, and pressure relief vents, each opening in a non-contact external floating roof shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.2.1] Federally Enforceable Through Title V Permit
22. Except for automatic bleeder vents and rim vents, roof drains, and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid that shall be maintained in a closed position at all times (i.e., no visible gap) except when in actual use. [District Rule 4623, 5.5.2.2.2] Federally Enforceable Through Title V Permit
23. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.2.3] Federally Enforceable Through Title V Permit
24. Rim vents shall be equipped with a gasket and shall be set to open when the roof is being floated off the roof leg supports or at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.2.4] Federally Enforceable Through Title V Permit
25. Each emergency roof drain shall be provided with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening. The fabric cover must be impermeable if the liquid is drained into the contents of the tanks. [District Rule 4623, 5.5.2.2.5] Federally Enforceable Through Title V Permit
26. External floating roof legs shall be equipped with vapor socks or vapor barriers in order to maintain a leak free condition so as to prevent VOC emissions from escaping through the roof leg opening. [District Rule 4623, 5.5.2.2.6] Federally Enforceable Through Title V Permit
27. The well shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. The permittee shall visually inspect, through the manholes, roof hatches, or other openings on the fixed roof, the internal floating roof and its appurtenant parts, fittings, etc., and the primary seal and/or secondary seal at least once every 12 months after the tank is initially filled with an organic liquid. There should be no visible organic liquid on the roof, tank walls, or anywhere. Other than the gap criteria specified by this rule, no holes, tears, or other openings are allowed that would permit the escape of hydrocarbon vapors. Any defects found are violations of this rule. [District Rule 4623, 6.1.4.2] Federally Enforceable Through Title V Permit
24. The permittee shall conduct actual gap measurements of the primary seal and/or secondary seal at least once every 60 months. [District Rule 4623, 6.1.4.3] Federally Enforceable Through Title V Permit
25. Vapor pressure of stored liquids shall be determined as described in section 6.4.3 of District Rule 4623 (revised 5/19/05). [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit
26. Permittee shall submit the reports of the floating roof tank inspections to the APCO within five calendar days after the completion of the inspection only for those tanks that failed to meet the applicable requirements of Rule 4623, Sections 5.2 through 5.5. The inspection report for tanks that have been determined to be in compliance with the requirements of Sections 5.2 through 5.5 need not be submitted to the APCO, but the inspection report shall be kept on-site and made available upon request by the APCO. The inspection report shall contain all information necessary to demonstrate compliance with the provisions of Rule 4623. [District Rule 4623, 6.3.5] Federally Enforceable Through Title V Permit
27. Permittee shall maintain the records of the internal floating roof landing activities that are performed pursuant to Rule 4623, Sections 5.3.1.3 and 5.4.3. The records shall include information on the true vapor pressure (TVP), API gravity, storage temperature, type of organic liquid stored in the tank, the purpose of landing the roof on its legs, the date of roof landing, duration the roof was on its legs, the level or height at which the tank roof was set to land on its legs, and the lowest liquid level in the tank. [District Rule 4623, 6.3.1] Federally Enforceable Through Title V Permit
28. Records of monthly organic liquid throughput shall be maintained on the premises and shall be made available for District inspection upon request. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit
29. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623, 6.3.7] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

11. There shall be no holes, tears, or openings in the secondary seal or in the primary seal envelope that surrounds the annular vapor space enclosed by the roof edge, seal fabric, and secondary seal. [District Rule 4623, 5.3.2.1.5] Federally Enforceable Through Title V Permit
12. The secondary seal shall allow easy insertion of probes of up to 1 1/2 inches in width in order to measure gaps in the primary seal. [District Rule 4623, 5.3.2.1.6] Federally Enforceable Through Title V Permit
13. The secondary seal shall extend from the roof to the tank shell and shall not be attached to the primary seal. [District Rule 4623, 5.3.2.1.7] Federally Enforceable Through Title V Permit
14. All openings in the roof used for sampling and gauging, except pressure-vacuum valves which shall be set to within 10% of the maximum allowable working pressure of the roof, shall provide a projection below the liquid surface to prevent belching of liquid and to prevent entrained or formed organic vapor from escaping from the liquid contents of the tank and shall be equipped with a cover, seal or lid that shall be in a closed position at all times, with no visible gaps and be leak-free, except when the device or appurtenance is in use. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
15. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11] Federally Enforceable Through Title V Permit
16. Each opening in a non-contact internal floating roof, except for automatic bleeder vents (vacuum breaker vents) and rim space vents, shall provide a projection below the liquid surface. [District Rule 4623, 5.5.2.1.1] Federally Enforceable Through Title V Permit
17. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, combination manway/vacuum breakers, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use. [District Rule 4623, 5.5.2.1.1] Federally Enforceable Through Title V Permit
18. Automatic bleeder vents shall be equipped with a gasket and shall be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports. [District Rule 4623, 5.5.2.1.3] Federally Enforceable Through Title V Permit
19. Rim vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or set to open at the manufacturer's recommended setting. [District Rule 4623, 5.5.2.1.4] Federally Enforceable Through Title V Permit
20. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The well shall have a slit fabric cover that covers at least 90% of the opening. The fabric cover must be impermeable. [District Rule 4623, 5.5.2.1.5] Federally Enforceable Through Title V Permit
21. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover. The fabric sleeve must be impermeable. [District Rule 4623, 5.5.2.1.6] Federally Enforceable Through Title V Permit
22. The permittee shall visually inspect the internal floating roof, and its appurtenant parts, fittings, etc. and measure the gaps of the primary seal and/or secondary seal prior to filling the tank for newly constructed, repair, or rebuilt internal floating roof tanks. If holes, tears, or openings in the primary seal, the secondary seal, the seal fabric or defects in the internal floating roof or its appurtenant parts, components, fittings, etc., are found, they shall be repaired prior to filling the tank. [District Rule 4623, 6.1.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Sampling facilities for source testing shall be provided in accordance with the provisions of District Rule 1081 (Source Sampling). [District Rule 1081] Federally Enforceable Through Title V Permit
13. The operator of the facility shall comply with the provisions of District Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
14. The facility maximum gasoline throughput shall not exceed either of the following limits: 5.25 million gallons per day and 1,916,250,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Analysis of halogenated exempt compounds shall be by ARB Method 432. [District Rule 4624 and Fresno County Rule 412] Federally Enforceable Through Title V Permit
16. VOC emissions from the vapor collection and control system shall be determined annually using 40 CFR 60.503 "Test Methods and Procedures" and EPA Reference Methods 2A, 2B, 25A and 25B and ARB Method 432, or ARB Method 2-4. [District Rule 4624 and Fresno County Rule 412] Federally Enforceable Through Title V Permit
17. Loading and vapor collection and control equipment shall be maintained and operated such that there are no leaks or excess organic liquid drainage at disconnections. A leak shall be defined as the dripping of organic compounds at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at a distance of one centimeter from the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 mls per average of 3 consecutive disconnects. [District Rule 4624 and Fresno County Rule 412] Federally Enforceable Through Title V Permit
18. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4624 and Fresno County Rule 412. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
19. Devices used to monitor the John Zink ZTOF burner operating temperature shall be maintained in accordance with the manufacturer's specifications. [40 CFR part 64] Federally Enforceable Through Title V Permit
20. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR 64.7. [40 CFR part 64] Federally Enforceable Through Title V Permit
21. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR part 64] Federally Enforceable Through Title V Permit
22. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
13. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District NSR Rule, Rule 4702, 4.2.1, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. Engine shall be equipped with turbocharger and aftercooler. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Permit holder shall notify the District within ten days in event engine is used during an emergency. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Engine ignition timing shall be inspected, adjusted and certified, initially and, at a minimum, once every 3 years. Inspections, adjustments, and certifications shall be performed by a qualified mechanic according to the manufacturer's procedures. [District NSR Rule] Federally Enforceable Through Title V Permit
17. Records of operation shall be maintained and made available for District inspection upon request, and shall include: days and hours of operation, fuel consumed, dates of maintenance, and ignition timing noted. [District NSR Rule] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.1 and 17 CCR 93115]
19. Daily emissions from the engine shall not exceed 1.7 lbs/day of PM10, 3.8 lbs/day of SOx, 173.0 lbs/day of NOx, 3.0 lbs/day of VOC and 15.0 lbs/day of CO emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
20. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102] Federally Enforceable Through Title V Permit
21. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102] Federally Enforceable Through Title V Permit
22. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702,5.6] Federally Enforceable Through Title V Permit
23. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702,3.15] Federally Enforceable Through Title V Permit
24. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702,3.15] Federally Enforceable Through Title V Permit
25. The permittee shall maintain monthly records that include any information necessary to demonstrate compliance with 40 CFR 63, ZZZZ. [District Rule 1070 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
13. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District NSR Rule, Rule 4702, 4.2.1, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. Engine shall be equipped with turbocharger and aftercooler. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Permit holder shall notify the District within ten days in event engine is used during an emergency. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Engine ignition timing shall be inspected, adjusted and certified, initially and, at a minimum, once every 3 years. Inspections, adjustments, and certifications shall be performed by a qualified mechanic according to the manufacturer's procedures. [District NSR Rule] Federally Enforceable Through Title V Permit
17. Records of operation shall be maintained and made available for District inspection upon request, and shall include: days and hours of operation, fuel consumed, dates of maintenance, and ignition timing noted. [District NSR Rule] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 6.2.1 and 17 CCR 93115]
19. Daily emissions from the engine shall not exceed 1.7 lbs/day of PM10, 3.8 lbs/day of SOx, 173.0 lbs/day of NOx, 3.0 lbs/day of VOC and 15.0 lbs/day of CO emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
20. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
21. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
22. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702,5.6] Federally Enforceable Through Title V Permit
23. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702,3.15] Federally Enforceable Through Title V Permit
24. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702,3.15] Federally Enforceable Through Title V Permit
25. The permittee shall maintain monthly records that include any information necessary to demonstrate compliance with 40 CFR 63, ZZZZ. [District Rule 1070 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of each year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. When applicable to 40 CFR Part 68, a subject facility shall submit to the proper authority a Risk Management Plan. [40 CFR 68] Federally Enforceable Through Title V Permit
44. The facility wide hazardous air pollutants (HAPs) emissions shall not exceed 16.7 tons/year and any individual HAP emissions shall not exceed 10 tons/year. The facility shall keep records demonstrating compliance with these limits. [District Rule 1160] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT C

Detailed Summary List of Facility Permits

ATTACHMENT D

District Rule 4601 Stringency Analysis

Stringency Comparison of District Rule 4601 Non-SIP Version (4/16/20) to Current SIP Version (12/17/09)

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
<p>2.0 Applicability</p>	<p>This rule is applicable to any person who supplies, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating for use within the District.</p>	<p>This rule is applicable to any person who supplies, markets, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating for use within the District.</p>	<p>The only change is to include applicability of this rule to the person marketing the coatings, therefore, non-SIP version of rule is more stringent than SIP version.</p>
<p>4.0 Exemptions</p>	<p>4.1 The provisions of this rule shall not apply to:</p> <p>4.1.1 Any architectural coating that is supplied, sold, offered for sale, or manufactured for use outside of the District or for shipment to other manufacturers for reformulation or repackaging.</p> <p>4.1.2 Any aerosol coating product.</p> <p>4.2 With the exception of Section 6.2, the provisions of this rule shall not apply to any architectural coating that is sold in a container with a volume of one liter (1.057 quarts) or less.</p>	<p>4.1 The provisions of this rule shall not apply to:</p> <p>4.1.1 Any architectural coating that is supplied, sold, offered for sale, or manufactured for use outside of the District or for shipment to other manufacturers for reformulation or repackaging.</p> <p>4.1.2 Any aerosol coating product.</p> <p>4.2 With the exception of Section 6.2 and Section 4.3, the provisions of this rule shall not apply to any architectural coating that is sold in a container with a volume of one liter (1.057 quarts) or less, provided the following requirements are met:</p> <p>4.2.1 The coating container is not bundled together with other containers of the same specific coating category (listed in Table 1) to be sold as a unit that exceeds one liter (1.057 quart), excluding containers packed together for shipping to a retail outlet, and</p> <p>4.2.2 The label or any other product literature does not suggest combining multiple containers of the same specific category (listed in Table 1) so that the combination exceeds one liter (1.057 quart).</p> <p>4.3 On and after sixty days following the effective date of EPA final rulemaking that the conditions described in Clean Air Act Sections 172(c)(9) and 182(c)(9) have occurred in the San Joaquin Valley regarding the 2008 8-hour Ozone National Ambient Air Quality Standard, the categories of coatings listed below shall no longer be exempt from the provisions of Table 1 of this rule when sold in containers having capacities of one liter (1.057 quarts) or less:</p> <p>4.3.1 Bituminous Roof Coatings;</p>	<p>The exemptions for colorant and for architectural coatings sold in a container with a volume of one liter (1.057 quarts) or less have been added to the rule in order to make the amended rule consistent with the exemptions presented in 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
		<p>4.3.2 Flat Coatings that are sold in containers having capacities greater than eight fluid ounces;</p> <p>4.3.3 Magnesite Cement Coatings;</p> <p>4.3.4 Multi-Color Coatings;</p> <p>4.3.5 Nonflat Coatings that are sold in containers having capacities greater than eight fluid ounces;</p> <p>4.3.6 Pre-Treatment Wash Primers;</p> <p>4.3.7 Reactive Penetrating Sealers;</p> <p>4.3.8 Shellacs (Clear and Opaque);</p> <p>4.3.9 Stone Consolidants;</p> <p>4.3.10 Swimming Pool Coatings;</p> <p>4.3.11 Tub and Tile Refinishing Coatings;</p> <p>4.3.12 Wood Coatings, including Lacquers, Varnishes, and Sanding Sealers; and</p> <p>4.3.13 Wood Preservatives.</p> <p>4.4 Colorant added at the factory or at the worksite is not subject to the VOC limits in Table 2. In addition, containers of colorant sold at the point of sale for use in the field or on a job site are also not subject to the VOC limit in Table 2.</p>	
<p>5.0 Requirements</p>	<p>5.1 VOC Content Limits: Except as provided in Sections 5.2 and 5.3, no person shall: manufacture, blend, or repackage for use within the District; or supply, sell, or offer for sale within the District; or solicit for application or apply within the District any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards 1 or the Table of Standards 2, after the specified effective date in the Table of Standards 1 or the Table of Standards 2. Limits are expressed as VOC Regulatory, thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.</p> <p>5.2 Most Restrictive VOC Limit: If a coating meets the definition in Section 3.0 for one or more specialty coating categories listed in the Table of Standards 1 or the Table of Standards 2, then that coating is not required to meet the VOC limits for Flat, Nonflat, or Nonflat – High Gloss coatings, but is required to meet the VOC limit for the applicable specialty coating listed in the Table of Standards 1 or the Table of Standards 2.</p> <p>5.2.1 Effective until December 31, 2010, with the exception of the specialty coating categories specified in Section 5.2.3.1 through 5.2.3.15, if a coating is recommended for use in more than one of the specialty coating categories listed in the Table</p>	<p>5.1 VOC Content Limits: Except as provided in Sections 5.2 and 5.3, no person shall: manufacture, blend, or repackage for use within the District; or supply, sell, market or offer for sale within the District; or solicit for application or apply within the District any architectural coating or colorant with a VOC content in excess of the corresponding limit specified in Table 1 or Table 2, after the specified effective date in Table 1 or Table 2. Limits are expressed as VOC Regulatory, thinned to the manufacturer's maximum thinning recommendation, excluding any colorant added to tint bases.</p> <p>5.2 Most Restrictive VOC Limit: If a coating meets the definition in Section 3.0 for one or more specialty coating categories listed in Table 1 or, then that coating is not required to meet the VOC limits for Flat or Nonflat coatings, but is required to meet the VOC limit for the applicable specialty coating listed in Table 1 or . With the exception of the specialty coating categories specified in Sections 5.2.1 through 5.2.12, if a coating is recommended for use in more than one of the specialty coating categories listed in Table 1, then the most restrictive (or lowest) VOC content limit shall apply. This requirement applies to: usage recommendations that appear anywhere on the coating</p>	<p>The Table of Standards 1 and the Table of Standard 2 have been replaced with more stringent Table 1 with VOC content limit for coatings and Table 2 with VOC content limit for colorants with more stringent VOC limits as shown in the tables at the end of this document. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</p> <p>The VOC limit of the non-SIP version is at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>of Standards 1, the most restrictive (or lowest) VOC content limit shall apply.</p> <p>5.2.2 Effective on and after January 1, 2011, with the exception of the specialty coating categories specified in Sections 5.2.3.2, 5.2.3.3, 5.2.3.5 through 5.2.3.9, and 5.2.3.14 through 5.2.3.18, if a coating is recommended for use in more than one of the specialty coating categories listed in the Table of Standards 2, the most restrictive (or lowest) VOC content limit shall apply.</p> <p>5.2.3 This requirement applies to: usage recommendations that appear anywhere on the coating container, anywhere on any label or sticker affixed to the container, or in any sales, advertising, or technical literature supplied by a manufacturer or anyone acting on their behalf.</p> <p>5.2.3.1 Lacquer coatings (including lacquer sanding sealers)</p> <p>5.2.3.2 Metallic pigmented coatings</p> <p>5.2.3.3 Shellacs</p> <p>5.2.3.4 Fire-retardant coatings</p> <p>5.2.3.5 Pretreatment wash primers</p> <p>5.2.3.6 Industrial maintenance coatings</p> <p>5.2.3.7 Low-solids coatings</p> <p>5.2.3.8 Wood preservatives</p> <p>5.2.3.9 High temperature coatings</p> <p>5.2.3.10 Temperature-indicator safety coatings</p> <p>5.2.3.11 Antenna coatings</p> <p>5.2.3.12 Antifouling coatings</p> <p>5.2.3.13 Flow coatings</p> <p>5.2.3.14 Bituminous roof primers</p> <p>5.2.3.15 Specialty primers, sealers and undercoaters</p> <p>5.2.3.16 Aluminum roof coatings</p> <p>5.2.3.17 Zinc-rich primers</p> <p>5.2.3.18 Wood Coatings</p>	<p>container, anywhere on any label or sticker affixed to the container, or in any sales, advertising, or technical literature supplied by a manufacturer or anyone acting on their behalf.</p> <p>5.2.1 Metallic pigmented coatings;</p> <p>5.2.2 Shellacs;</p> <p>5.2.3 Pretreatment wash primers;</p> <p>5.2.4 Industrial maintenance coatings;</p> <p>5.2.5 Low-solids coatings;</p> <p>5.2.6 Wood preservatives;</p> <p>5.2.7 High temperature coatings;</p> <p>5.2.8 Bituminous roof primers;</p> <p>5.2.9 Specialty primers, sealers and undercoaters;</p> <p>5.2.10 Aluminum roof coatings;</p> <p>5.2.11 Zinc-rich primers; and</p> <p>5.2.12 Wood Coatings.</p>	
	<p>5.3 Sell-Through of Coatings: A coating manufactured prior to the effective date specified for that coating in the Table of Standards 1 or the Table of Standards 2, and that complied with the standards in effect at the time the coating was manufactured, may be sold, supplied, or offered for sale for up to three years after the specified effective date. In addition, a coating manufactured before the effective date specified for that coating in the Table of Standards 1 or the Table of Standards 2 may be applied at any time, both before and after the specified effective date, so long as the coating complied with the standards in effect at the time the coating was manufactured. This Section 5.3 does not apply to any</p>	<p>5.3 Sell-Through of Coatings: 5.3.1 A coating manufactured prior to January 1, 2022, may be sold, supplied, or offered for sale for up to three years after January 1, 2022. In addition, a coating manufactured before January 1, 2022 may be applied at any time, both before and after January 1, 2022, so long as the coating complied with the standards in effect at the time the coating was manufactured. This subsection 5.3.1 does not apply to any coating that does not display the date or date-code required by subsection 6.1.1. 5.3.2 A colorant manufactured prior to January 1, 2022, may be sold, supplied, or offered for sale for up to three years after January 1, 2022. In addition, a</p>	<p>The VOC limit of the non-SIP version is at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	coating that does not display the date or date-code required by Section 6.1.1.	colorant manufactured before January 1, 2022 may be applied at any time, both before and after January 1, 2022, so long as the colorant complied with the standards in effect at the time the colorant was manufactured. This subsection 5.3.2 does not apply to any colorant that does not display the date or date-code required by subsection 6.1.1.	
	5.4 Painting Practices: All architectural coating containers used to apply the contents therein to a surface directly from the container by pouring, siphoning, brushing, rolling, padding, ragging or other means, shall be closed when not in use. These architectural coating containers include, but are not limited to, drums, buckets, cans, pails, trays or other application containers. Containers of any VOC-containing materials used for thinning and cleanup shall also be closed when not in use.	5.4 Painting Practices: All architectural coating containers used to apply the contents therein to a surface directly from the container by pouring, siphoning, brushing, rolling, padding, ragging or other means, shall be closed when not in use. These architectural coating containers include, but are not limited to, drums, buckets, cans, pails, trays or other application containers. Containers of any VOC-containing materials used for thinning and cleanup shall also be closed when not in use.	No change in the requirements, therefore, non-SIP version of rule is as stringent as SIP version.
	5.5 Thinning: No person who applies or solicits the application of any architectural coating shall apply a coating that is thinned to exceed the applicable VOC limit specified in the Table of Standards 1 or the Table of Standards 2.	5.5 Thinning: No person who applies or solicits the application of any architectural coating shall apply a coating that is thinned to exceed the applicable VOC limit specified in the Table of Standards 1 or the Table of Standards 2.	No change in the requirements, therefore, non-SIP version of rule is as stringent as SIP version.
	5.6 Rust Preventative Coatings: Effective through December 31, 2010, no person shall apply or solicit the application of any rust preventative coating for industrial use, unless such a rust preventative coating complies with the industrial maintenance coating VOC limit specified in the Table of Standards 1.		The VOC limit of the SIP version is no longer applicable at this time and has been removed.
	5.7 Coatings Not Listed in the Table of Standards 1 or the Table of Standards 2: For any coating that does not meet any of the definitions for the specialty coatings categories listed in the Table of Standards 1 or the Table of Standards 2, the VOC content limit shall be determined by classifying the coating as a Flat, Nonflat, or Nonflat – High Gloss coating, based on its gloss, and the corresponding Flat, Nonflat, or Nonflat – High Gloss VOC limit in the Table of Standards 1 or the Table of Standards 2 shall apply.	5.6 Coatings Not Listed in Table 1: For any coating that does not meet any of the definitions for the specialty coatings categories listed in Table 1, the VOC content limit shall be determined by classifying the coating as Flat or Nonflat, based on its gloss, and the corresponding Flat or Nonflat VOC limit in Table 1 shall apply.	The VOC limit of the non-SIP version is at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.
		5.7 Colorants: No person within the District shall, at the point of sale of any architectural coating subject to subsection 5.1, add to such coating any colorant that contains VOCs in excess of the corresponding applicable VOC limit specified in Table 2. The point of sale includes retail outlets that add colorant to a coating container to obtain a specific color.	The VOC limit for colorants in non-SIP version more stringent than the SIP version of the rule.
	5.8 Prior to January 1, 2011, any coating that		The VOC limit of the SIP

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	meets a definition in Section 3.0 for a coating category listed in the Table of Standards 2 and complies with the applicable VOC limit in the Table of Standards 2 and with Sections 5.2 and 6.1 (including those provision of Section 6.1 otherwise effective on January 1, 2011) shall be considered in compliance with this rule.		version is no longer applicable at this time and has been removed.
	Table of Standards 1 (Effective on and after 1/1/11)	Table 1 VOC Content Limits for Coatings (Effective on and after 1/1/22) (See end of the document for Table Comparison)	The requirements of Table of Standard 1 are more stringent than the Table 1 in the SIP rule. Therefore, non-SIP version of rule is as stringent as SIP version.
	Table of Standards 2 (Effective on and after 1/1/11)	Table 2 VOC Content Limits for Colorants (Effective on and after 1/1/22) (See end of the document for Table Comparison)	VOC content limits for colorants were added under the amended rule. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.
6.0 Administrative Requirements	<p>6.1 Labeling Requirements: Each manufacturer of any architectural coating subject to this rule shall display the information listed in Sections 6.1.1 through 6.1.14 on the coating container (or label) in which the coating is sold or distributed.</p> <p>6.1.1 Date Code: The date the coating was manufactured, or a date code representing the date, shall be indicated on the label, lid or bottom of the container. If the manufacturer uses a date code for any coating, the manufacturer shall file an explanation of each code with the Executive Officer of the ARB.</p> <p>6.1.2 Thinning Recommendations: A statement of the manufacturer's recommendation regarding thinning of the coating shall be indicated on the label or lid of the container. This requirement does not apply to the thinning of architectural coatings with water. If thinning of the coating prior to use is not necessary, the recommendation must specify that the coating is to be applied without thinning.</p> <p>6.1.3 VOC Content: Each container of any coating subject to this rule shall display one of the following values, in grams of VOC per liter of coating:</p> <p>6.1.3.1 Maximum VOC Content, as determined from all potential product formulations; or</p> <p>6.1.3.2 VOC Content, as determined</p>	<p>6.1 Labeling Requirements: Each manufacturer of any architectural coating subject to this rule shall display the information listed in Sections 6.1.1 through 6.1.12 on the coating container (or label) in which the coating is sold or distributed.</p> <p>6.1.1 Date Code: The date the coating was manufactured, or a date code representing the date, shall be indicated on the label, lid or bottom of the container. If the manufacturer uses a date code for any coating, the manufacturer shall file an explanation of each code with the Executive Officer of the ARB.</p> <p>6.1.2 Thinning Recommendations: A statement of the manufacturer's recommendation regarding thinning of the coating shall be indicated on the label or lid of the container. This requirement does not apply to the thinning of architectural coatings with water. If thinning of the coating prior to use is not necessary, the recommendation must specify that the coating is to be applied without thinning.</p> <p>6.1.3 VOC Content: Each container of any coating subject to this rule shall display one of the following values, in grams of VOC per liter of coating:</p> <p>6.1.3.1 Maximum VOC Content, as determined from all potential product formulations; or</p>	The non-SIP approved rule contain sections listed in the SIP rule plus additional requirements not found in the SIP version for colorants. Therefore, non-SIP version of rule is as stringent as SIP version.

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>from actual formulation data; or</p> <p>6.1.3.3 VOC Content, as determined using the test methods in Section 6.3.2.</p> <p>If the manufacturer does not recommend thinning, the container must display the VOC Content, as supplied. If the manufacturer recommends thinning, the container must display the VOC Content, including the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multicomponent product, the container must display the VOC content as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOCs during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.1.4 Faux Finishing Coatings: Effective January 1, 2011, the labels of all clear topcoat Faux Finishing coatings shall prominently display the statement "This product can only be sold or used as part of a Faux Finishing coating system".</p> <p>6.1.5 Industrial Maintenance Coatings: Each manufacturer of any industrial maintenance coating subject to this rule shall display on the label or lid of the container in which the coating is sold or distributed one or more of the following descriptions listed in Section 6.1.5.1 through 6.1.5.3.</p> <p>6.1.5.1 "For industrial use only"</p> <p>6.1.5.2 "For professional use only"</p> <p>6.1.5.3 "Not for residential use" or "Not intended for residential use"</p> <p>6.1.6 Clear Brushing Lacquers: The labels of all clear brushing lacquers shall prominently display the statements "For brush application only," and "This product must not be thinned or sprayed." (Category deleted effective January 1, 2011.)</p> <p>6.1.7 Rust Preventative Coatings: The labels of all rust preventative coatings shall prominently display the statement "For Metal Substrates Only".</p> <p>6.1.8 Specialty Primers, Sealers and Undercoaters: Effective until December 31, 2010, the labels of all specialty primers, sealers and undercoaters shall prominently display one or more of the descriptions listed in Section 6.1.8.1 through 6.1.8.5. Effective on and after January 1, 2011, the labels of all specialty primers, sealers, and undercoaters shall prominently display one or more of the descriptions listed in</p>	<p>6.1.3.2 VOC Content, as determined from actual formulation data; or</p> <p>6.1.3.3 VOC Content, as determined using the test methods in Section 6.3.2.</p> <p>If the manufacturer does not recommend thinning, the container must display the VOC Content, as supplied. If the manufacturer recommends thinning, the container must display the VOC Content, including the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multicomponent product, the container must display the VOC content as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOCs during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.1.4 Faux Finishing Coatings: The labels of all clear topcoat Faux Finishing coatings shall prominently display the statement "This product can only be sold or used as part of a Faux Finishing coating system".</p> <p>6.1.5 Industrial Maintenance Coatings: Each manufacturer of any industrial maintenance coating subject to this rule shall display on the label or lid of the container in which the coating is sold or distributed one or more of the following descriptions listed in Section 6.1.5.1 through 6.1.5.3.</p> <p>6.1.5.1 "For industrial use only"</p> <p>6.1.5.2 "For professional use only"</p> <p>6.1.6 Rust Preventative Coatings: The labels of all rust preventative coatings shall prominently display the statement "For Metal Substrates Only".</p> <p>6.1.7 Specialty Primers, Sealers and Undercoaters: The labels of all specialty primers, sealers, and undercoaters shall prominently display the statement "Specialty Primer, Sealer, Undercoater"</p> <p>6.1.8 Reactive Penetrating Sealers: The labels of all Reactive Penetrating Sealers shall prominently display the statement "Reactive Penetrating Sealer."</p> <p>6.1.9 Stone Consolidants: The labels of all Stone Consolidants shall prominently display the statement "Stone Consolidant - For Professional Use Only."</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>Sections 6.1.8.1 through 6.1.8.3. On and after January 1, 2011, Sections 6.1.8.4 and 6.1.8.5 will be no longer effective.</p> <p>6.1.8.1 For fire-damaged substrates.</p> <p>6.1.8.2 For smoke-damaged substrates.</p> <p>6.1.8.3 For water-damaged substrates.</p> <p>6.1.8.4 For excessively chalky substrates.</p> <p>6.1.8.5 For blocking stains.</p> <p>6.1.9 Quick Dry Enamels: The labels of all quick dry enamels shall prominently display the words "Quick Dry" and the dry hard time. (Category deleted effective January 1, 2011.)</p> <p>6.1.10 Reactive Penetrating Sealers: Effective January 1, 2011, the labels of all Reactive Penetrating Sealers shall prominently display the statement "Reactive Penetrating Sealer."</p> <p>6.1.11 Stone Consolidants: Effective January 1, 2011, the labels of all Stone Consolidants shall prominently display the statement "Stone Consolidant - For Professional Use Only."</p> <p>6.1.12 Nonflat– High Gloss Coatings: The labels of all Nonflat – high gloss coatings shall prominently display the words "High Gloss."</p> <p>6.1.13 Wood Coatings: Effective January 1, 2011, the labels of all Wood Coatings shall prominently display the statement "For Wood Substrates Only."</p> <p>6.1.14 Zinc Rich Primers: Effective January 1, 2011, the labels of all Zinc Rich Primers shall prominently display one or more of the following descriptions listed in Section 6.1.14.1 through 6.1.14.3.</p> <p>6.1.14.1 "For industrial use only"</p> <p>6.1.14.2 "For professional use only"</p> <p>6.1.14.3 "Not for residential use" or "Not intended for residential use"</p>	<p>6.1.10 Wood Coatings: The labels of all Wood Coatings shall prominently display the statement "For Wood Substrates Only."</p> <p>6.1.11 Zinc Rich Primers: The labels of all Zinc Rich Primers shall prominently display the statement "For professional use only."</p> <p>6.1.12 Colorants: Effective January 1, 2022, each manufacturer of any colorant subject to this rule shall display the information listed in subsections 6.1.12.1 and 6.1.12.2 on the container (or label) in which the colorant is sold or distributed.</p> <p>6.1.12.1 Date Code: The date the colorant was manufactured, or a date code representing the date, shall be indicated on the label, lid, or bottom of the container. If the manufacturer uses a date code for any colorant, the manufacturer shall file an explanation of each code with the APCO.</p> <p>6.1.12.2 VOC Content: Each container of any colorant subject to this rule shall display one of the following values in grams of VOC per liter of colorant.</p> <p>6.1.12.2.1 Maximum VOC Content as determined from all potential product formulations; or</p> <p>6.1.12.2.2 VOC Content as determined from actual formulation data; or</p> <p>6.1.12.2.3 VOC Content as determined using the test methods in subsection 6.3.2.</p> <p>If the colorant contains silanes, siloxanes, or other ingredients that generate ethanol or other VOCs during the curing process, the VOC content must include the VOCs emitted during curing. VOC Content shall be determined as defined in subsections 3.72, 3.73, and 3.74.</p>	
	<p>6.2 Reporting Requirements</p> <p>The reporting requirements specified in Sections 6.2.1 through 6.2.6 shall apply until December 31, 2010.</p> <p>6.2.1 Clear Brushing Lacquers: Each manufacturer of clear brushing lacquers shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall specify the number of gallons of clear brushing lacquers sold in the State during the preceding calendar year, and shall describe the</p>	<p>6.2 Reporting Requirements</p> <p>6.2.1 Sales Data: All sales data listed in Sections 6.2.1.1 to 6.2.1.14 shall be maintained on-site by the responsible official for a minimum of three years. A responsible official from each manufacturer shall upon request of the Executive Officer of CARB, or his or her delegate, provide data concerning the distribution and sales of architectural coatings. Sales data submitted by the responsible official to the Executive Officer of the ARB may be claimed as confidential, and such information shall be handled in</p>	<p>All the reporting requirements were removed except the sales data requirements presented in 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings in order to make the amended rule consistent with SCM. Therefore, non-SIP version of rule is as stringent as SIP version.</p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>method used by the manufacturer to calculate State sales.</p> <p>6.2.2 Rust Preventative Coatings: Each manufacturer of rust preventative coatings shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall specify the number of gallons of rust preventative coatings sold in the State during the preceding calendar year, and shall describe the method used by the manufacturer to calculate State sales.</p> <p>6.2.3 Specialty Primers, Sealers and Undercoaters: Each manufacturer of specialty primers, sealers and undercoaters shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall specify the number of gallons of specialty primers, sealers and undercoaters sold in the State during the preceding calendar year, and shall describe the method used by the manufacturer to calculate State sales.</p> <p>6.2.4 Toxic Exempt Compounds: For each architectural coating that contains perchloroethylene or methylene chloride, the manufacturer shall, on or before April 1 of each calendar year beginning in the year 2004, submit an annual report to the Executive Officer of the ARB the following information for products sold in the State during the preceding year:</p> <p>6.2.4.1 the product brand name and a copy of the product label with legible usage instructions;</p> <p>6.2.4.2 the product category listed in the Table of Standards 1 or the Table of Standards 2 to which the coating belongs;</p> <p>6.2.4.3 the total sales in California during the calendar year to the nearest gallon;</p> <p>6.2.4.4 the volume percent, to the nearest 0.10 percent, of perchloroethylene and methylene chloride in the coating.</p> <p>6.2.5 Recycled Coatings: Manufacturers of recycled coatings must submit a letter to the Executive Officer of the ARB certifying their status as a Recycled Paint Manufacturer. The manufacturer shall, on or before April 1 of each calendar year beginning with the year 2004, submit an annual report to the Executive Officer of the ARB. The report shall include, for all recycled coatings, the total number of gallons</p>	<p>accordance with the procedures specified in Title 17, California Code of Regulations Sections 91000-91022. The responsible official shall within 180 days provide information, including, but not limited to the data listed in Sections 6.2.1.1 through 6.2.1.14:</p> <p>6.2.1.1 The name and mailing address of the manufacturer;</p> <p>6.2.1.2 The name, address and telephone number of a contact person;</p> <p>6.2.1.3 The name of the coating product as it appears on the label and the applicable coating category;</p> <p>6.2.1.4 Whether the product is marketed for interior or exterior use or both;</p> <p>6.2.1.5 The number of gallons sold in California in containers greater than one liter (1.057 quart) and equal to or less than one liter (1.057 quart);</p> <p>6.2.1.6 The VOC Actual content and VOC Regulatory content in grams per liter. If thinning is recommended, list the VOC Actual content and VOC Regulatory content after maximum recommended thinning. If containers less than one liter have a different VOC content than containers greater than one liter, list separately. If the coating is a multi-component product, provide the VOC content as mixed or catalyzed;</p> <p>6.2.1.7 The names and CAS numbers of the VOC constituents in the product;</p> <p>6.2.1.8 The names and CAS numbers of any compounds in the product specifically exempted from the VOC definition;</p> <p>6.2.1.9 Whether the product is marketed as solvent-borne, waterborne, or 100% solids;</p> <p>6.2.1.10 Description of resin or binder in the product;</p> <p>6.2.1.11 Whether the coating is a single-component or multi-component product;</p> <p>6.2.1.12 The density of the product in pounds per gallon;</p> <p>6.2.1.13 The percent by weight of: solids, all volatile materials, water, and any compounds in the product specifically exempted from the VOC</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>distributed in the State during the preceding year, and shall describe the method used by the manufacturer to calculate State distribution.</p> <p>6.2.6 Bituminous Coatings: Each manufacturer of bituminous roof coatings or bituminous roof primers shall, on or before April 1 of each calendar year beginning with the year 2004, submit an annual report to the Executive Officer of ARB. The report shall specify the number of gallons of bituminous roof coatings or bituminous roof primers sold in the State during the preceding calendar year, and shall describe the method used by the manufacturer to calculate state sales.</p> <p>6.2.7 Effective on and after January 1, 2011, Sales Data: All sales data listed in Sections 6.2.7.1 to 6.2.7.14 shall be maintained on-site by the responsible official for a minimum of three years. A responsible official from each manufacturer shall upon request of the Executive Officer of the ARB, or his or her delegate, provide data concerning the distribution and sales of architectural coatings. Sales data submitted by the responsible official to the Executive Officer of the ARB may be claimed as confidential, and such information shall be handled in accordance with the procedures specified in Title 17, California Code of Regulations Sections 91000-91022. The responsible official shall within 180 days provide information, including, but not limited to the data listed in Sections 6.2.7.1 through 6.2.7.14:</p> <p>6.2.7.1 the name and mailing address of the manufacturer;</p> <p>6.2.7.2 the name, address and telephone number of a contact person;</p> <p>6.2.7.3 the name of the coating product as it appears on the label and the applicable coating category;</p> <p>6.2.7.4 whether the product is marketed for interior or exterior use or both;</p> <p>6.2.7.5 the number of gallons sold in California in containers greater than one liter (1.057 quart) and equal to or less than one liter (1.057 quart);</p> <p>6.2.7.6 the VOC Actual content and VOC Regulatory content in grams per liter. If thinning is recommended, list the VOC Actual content and VOC Regulatory content after maximum recommended</p>	<p>definition; and</p> <p>6.2.1.14 The percent by volume of solids, water, and any compounds in the product specifically exempted from the VOC definition.</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>thinning. If containers less than one liter have a different VOC content than containers greater than one liter, list separately. If the coating is a multi-component product, provide the VOC content as mixed or catalyzed;</p> <p>6.2.7.7 the names and CAS numbers of the VOC constituents in the product;</p> <p>6.2.7.8 the names and CAS numbers of any compounds in the product specifically exempted from the VOC definition;</p> <p>6.2.7.9 whether the product is marketed as solvent-borne, waterborne, or 100% solids;</p> <p>6.2.7.10 description of resin or binder in the product;</p> <p>6.2.7.11 whether the coating is a single-component or multi-component product;</p> <p>6.2.7.12 the density of the product in pounds per gallon;</p> <p>6.2.7.13 the percent by weight of: solids, all volatile materials, water, and any compounds in the product specifically exempted from the VOC definition; and</p> <p>6.2.7.14 the percent by volume of: solids, water, and any compounds in the product specifically exempted from the VOC definition.</p>		
	<p>6.3 Test Methods</p> <p>The test methods listed below shall be used to demonstrate compliance with this rule. Alternate equivalent test methods may be used provided the test methods have been approved by the APCO and EPA.</p> <p>6.3.1 Calculation of VOC Content: For the purpose of determining compliance with the VOC content limits in the Table of Standards 1 or the Table of Standards 2, the VOC content of a coating shall be determined as defined in Section 3.77, 3.78, or 3.79 as appropriate. The VOC content of a tint base shall be determined without colorant that is added after the tint base is manufactured. If the manufacturer does not recommend thinning, the VOC Content must be calculated for the product as supplied. If the manufacturer recommends thinning, the VOC Content must be calculated including</p>	<p>6.3 Test Methods</p> <p>The test methods listed below shall be used to demonstrate compliance with this rule. Alternate equivalent test methods may be used provided the test methods have been approved by the APCO and EPA.</p> <p>6.3.1 Calculation of VOC Content: For the purpose of determining compliance with the VOC content limits in Table 1 or the 2, the VOC content of a coating shall be determined as defined in Section 3.71, 3.72, or 3.73 as appropriate. The VOC content of a tint base shall be determined without colorant that is added after the tint base is manufactured. If the manufacturer does not recommend thinning, the VOC Content must be calculated for the product as supplied. If the manufacturer recommends thinning, the VOC Content must be calculated including</p>	<p>Numerous definitions were added, deleted or modified in order to make the amended rule consistent with definitions and rule requirements presented in 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</p>

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multi-component product, the VOC content must be calculated as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOC during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.3.2 VOC Content of Coatings: To determine the physical properties of a coating in order to perform the calculations in Section 3.77 and 3.79, the reference method for VOC content is EPA Method 24, except as provided in Sections 6.3.3 and 6.3.16. An alternative method to determine the VOC content of coatings is SCAQMD Method 304-91 (Revised February 1996). The exempt compounds content shall be determined by SCAQMD Method 303-91 (Revised 1993), BAAQMD Method 43 (Revised 1996), or BAAQMD Method 41 (Revised 1995), as applicable. To determine the VOC content of a coating, the manufacturer may use EPA Method 24, or an alternative method as provided in Section 6.3.3, formulation data, or any other reasonable means for predicting that the coating has been formulated as intended (e.g., quality assurance checks, recordkeeping). However, if there are any inconsistencies between the results of EPA Method 24 test and any other means for determining VOC content, the EPA Method 24 test results will govern, except when an alternative method is approved as specified in Section 6.3.3. The District Air Pollution Control Officer (APCO) may require the manufacturer to conduct an EPA Method 24 analysis.</p> <p>6.3.3 Alternative Test Methods: Other test methods demonstrated to provide results that are acceptable for purposes of determining compliance with Section 6.3.2 1, after review and approved in writing by the staffs of the District, ARB and EPA, may also be used.</p> <p>6.3.4 Methacrylate Traffic Marking Coatings: Analysis of methacrylate multicomponent coatings used as traffic marking coatings shall be conducted according to a modification of EPA Method 24 (40 CFR 59, subpart D, Appendix A). This method has not been approved for methacrylate multicomponent coatings used for other purposes than as traffic marking coatings or for other classes of</p>	<p>the maximum amount of thinning solvent recommended by the manufacturer. If the coating is a multi-component product, the VOC content must be calculated as mixed or catalyzed. If the coating contains silanes, siloxanes, or other ingredients that generate ethanol or other VOC during the curing process, the VOC content must include the VOCs emitted during curing.</p> <p>6.3.2 VOC Content of Coatings: To VOC Content of Coatings or Colorants: To determine the physical properties of a coating or colorant in order to perform the calculations in Section 3.71 and 3.73, the reference method for VOC content is EPA Method 24, except as provided in Sections 6.3.3 and 6.3.15. An alternative method to determine the VOC content of coatings or colorants is SCAQMD Method 304-91 (Revised February 1996). The exempt compounds content shall be determined by SCAQMD Method 303-91 (Revised 1996), BAAQMD Method 43 (Revised 2005), or BAAQMD Method 41 (Revised 2005), as applicable. To determine the VOC content of a coating or colorant, the manufacturer may use EPA Method 24, or an alternative method as provided in Section 6.3.4, formulation data, or any other reasonable means for predicting that the coating or colorant has been formulated as intended (e.g., quality assurance checks, recordkeeping). However, if there are any inconsistencies between the results of EPA Method 24 test and any other means for determining VOC content, the EPA Method 24 test results will govern, except when an alternative method is approved as specified in Section 6.3.4. The District Air Pollution Control Officer (APCO) may require the manufacturer to conduct an EPA Method 24 analysis.</p> <p>6.3.3 To determine the VOC content of a coating or colorant with a VOC content of 150 g/l or less, the manufacturer may use SCAQMD Method 313, incorporated by reference in subsection 6.3.34, ASTM D6886-18, incorporated by reference in subsection 6.3.35, or any other reasonable means for predicting that the coating or colorant has been formulated as intended (e.g., quality assurance checks, record keeping).</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>multicomponent coatings.</p> <p>6.3.5 Flame Spread Index: The flame spread index of a fire-retardant coating shall be determined by ASTM E84-07, "Standard Test Method for Surface Burning Characteristics of Building Materials" (see Section 3.0, Fire-Retardant Coating).</p> <p>6.3.6 Fire Resistance Rating: The fire resistance rating of a fire-resistive coating shall be determined by ASTM E119-07, "Standard Test Methods for Fire Tests of Building Construction Materials" (see Section 3.0, Fire-Resistive Coating).</p> <p>6.3.7 Gloss Determination: The gloss of a coating shall be determined by ASTM D523-89 (1999), "Standard Test Method for Specular Gloss" (see Section 3.0, Flat Coating, Nonflat Coating, Nonflat-High Gloss Coating and Quick-Dry Enamel).</p> <p>6.3.8 Metal Content of Coatings: The metallic content of a coating shall be determined by SCAQMD Method 318-95, Determination of Weight Percent Elemental Metal in Coatings by X-Ray Diffraction, <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Metallic Pigmented Coating, Aluminum Roof Coating and Faux Finish).</p> <p>6.3.9 Acid Content of Coatings: The acid content of a coating shall be determined by ASTM D1613-06, "Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer and related products" (see Section 3.0, Pre-Treatment Wash Primer).</p> <p>6.3.10 Drying Times: The set-to-touch, dry-hard, dry-to-touch and dry-to-recoat times of a coating shall be determined by ASTM D1640-95, "Standard Test Methods for Drying, Curing, or Film Formation of Organic Coatings at Room Temperature" (see Section 3.0, Quick-Dry Enamel and Quick-Dry Primer, Sealer and Undercoater) The tack-free time of a quick-dry enamel coating shall be determined by the Mechanical Test Method of ASTM D1640-95. (Category deleted effective January 1, 2011.)</p> <p>6.3.11 Surface Chalkiness: The chalkiness of a surface shall be determined using ASTM D4214-98, "Standard Test Methods for Evaluating the Degree of Chalking of Exterior Paint Films"(see Section 3, Specialty Primer, Sealer and Undercoater). (Category deleted effective January 1, 2011.)</p> <p>6.3.12 Exempt Compounds—Siloxanes:</p>	<p>6.3.4 Alternative Test Methods: Other test methods demonstrated to provide results that are acceptable for purposes of determining compliance with Section 6.3.2 4, after review and approved in writing by the staffs of the District, ARB and EPA, may also be used.</p> <p>6.3.5 Methacrylate Traffic Marking Coatings: Analysis of methacrylate multicomponent coatings used as traffic marking coatings shall be conducted according to a modification of EPA Method 24 (40 CFR 59, subpart D, Appendix A). This method has not been approved for methacrylate multicomponent coatings used for other purposes than as traffic marking coatings or for other classes of multicomponent coatings.</p> <p>6.3.6 Flame Spread Index: The flame spread index of a fire-retardant coating shall be determined by ASTM E84-18B, "Standard Test Method for Surface Burning Characteristics of Building Materials" (see Section 3.0, Fire-Retardant Coating).</p> <p>6.3.7 Fire Resistance Rating: The fire resistance rating of a fire-resistive coating shall be determined by ASTM E119-18ce1, "Standard Test Methods for Fire Tests of Building Construction Materials" (see Section 3.0, Fire-Resistive Coating).</p> <p>6.3.8 Gloss Determination: The gloss of a coating shall be determined by ASTM D523-14 (2018), "Standard Test Method for Specular Gloss" (see Section 3.0, Flat Coating and Nonflat Coating).</p> <p>6.3.9 Metal Content of Coatings: The metallic content of a coating shall be determined by SCAQMD Method 318-95, Determination of Weight Percent Elemental Metal in Coatings by X-Ray Diffraction, <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Metallic Pigmented Coating, Aluminum Roof Coating and Faux Finish).</p> <p>6.3.10 Acid Content of Coatings: The acid content of a coating shall be determined by ASTM D1613-17, "Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer and related products" (see Section 3.0, Pre-Treatment Wash Primer).</p> <p>6.3.11 Exempt Compounds—Siloxanes: Exempt compounds that are cyclic,</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>Exempt compounds that are cyclic, branched, or linear completely methylated siloxanes, shall be analyzed as exempt compounds for compliance with Section 6 by BAAQMD Method 43, "Determination of Volatile Methylsiloxanes in Solvent-Based Coatings, Inks, and Related Materials," <i>BAAQMD Manual of Procedures</i>, Volume III, adopted 11/6/96 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.13 Exempt Compounds—Parachlorobenzotrifluoride (PCBTF): The exempt compound parachlorobenzotrifluoride, shall be analyzed as an exempt compound for compliance with Section 6 by BAAQMD Method 41, "Determination of Volatile Organic Compounds in Solvent Based Coatings and Related Materials Containing Parachlorobenzotrifluoride," <i>BAAQMD Manual of Procedures</i>, Volume III, adopted 12/20/95 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.14 Exempt Compounds: The content of compounds under U.S. EPA Method 24 shall be analyzed by SCAQMD Method 303-91 (Revised 1993), "Determination of Exempt Compounds," <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.15 VOC Content of Coatings: The VOC content of a coating shall be determined by EPA Method 24 as it exists in appendix A of 40 <i>Code of Federal Regulations</i> (CFR) part 60, "Determination of Volatile Matter Content, Water Content, Density, Volume Solids and Weight Solids of Surface Coatings" (see Section 6.3.2).</p> <p>6.3.16 <i>Alternative VOC Content of Coatings: The VOC content of coatings may be analyzed either by U.S. EPA Method 24 or SCAQMD Method 304-91 (Revised 1996), "Determination of Volatile Organic Compounds (VOC) in Various Materials," SCAQMD Laboratory Methods of Analysis for Enforcement Samples.</i></p> <p>6.3.17 Methacrylate Traffic Marking Coatings: The VOC content of methacrylate multicomponent coatings used as traffic marking coatings shall be analyzed by the procedures in 40 CFR part 59, subpart D, appendix A, "Determination of Volatile Matter Content of Methacrylate Multicomponent Coatings Used as Traffic Marking Coatings" (September</p>	<p>branched, or linear completely methylated siloxanes, shall be analyzed as exempt compounds for compliance with Section 6 by BAAQMD Method 43, "Determination of Volatile Methylsiloxanes in Solvent-Based Coatings, Inks, and Related Materials," <i>BAAQMD Manual of Procedures</i>, Volume III, revised 2006 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.12 Exempt Compounds—Parachlorobenzotrifluoride (PCBTF): The exempt compound parachlorobenzotrifluoride, shall be analyzed as an exempt compound for compliance with Section 6 by BAAQMD Method 41, "Determination of Volatile Organic Compounds in Solvent Based Coatings and Related Materials Containing Parachlorobenzotrifluoride," <i>BAAQMD Manual of Procedures</i>, Volume III, revised 2006 (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.13 Exempt Compounds: The content of compounds exempted under U.S. EPA Method 24 shall be analyzed by SCAQMD Method 303-91 (Revised 1996), "Determination of Exempt Compounds," <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i> (see Section 3.0, Volatile Organic Compound, and Section 6.3.2).</p> <p>6.3.14 VOC Content of Coatings: The VOC content of a coating shall be determined by EPA Method 24 as it exists in appendix A of 40 <i>Code of Federal Regulations</i> (CFR) part 60, "Determination of Volatile Matter Content, Water Content, Density, Volume Solids and Weight Solids of Surface Coatings" (see Section 6.3.2).</p> <p>6.3.15 Alternative VOC Content of Coatings: The VOC content of coatings may be analyzed either by U.S. EPA Method 24 or SCAQMD Method 304-91 (Revised 1996), "Determination of Volatile Organic Compounds (VOC) in Various Materials," <i>SCAQMD Laboratory Methods of Analysis for Enforcement Samples</i>.</p> <p>6.3.16 Methacrylate Traffic Marking Coatings: The VOC content of methacrylate multicomponent coatings used as traffic marking coatings shall be analyzed by the procedures in 40 CFR part 59,</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>11, 1998).</p> <p>6.3.18 Hydrostatic Pressure for Basement Specialty Coatings: The hydrostatic pressure resistance for basement specialty coatings shall be analyzed using ASTM D7088-04, "Standard Practice for Resistance to Hydrostatic Pressure for Coatings Used in Below Grade Applications Applied to Masonry".</p> <p>6.3.19 Tub and Tile Refinish Coating Adhesion: The adhesion of tub and tile coating shall be determined by ASTM D4585-99, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D3359-02, "Standard Test Methods for Measuring Adhesion by Tape Test".</p> <p>6.3.20 Tub and Tile Refinish Coating Hardness: The hardness of tub and tile refinish coating shall be determined by ASTM D3363-05, "Standard Test Method for Film Hardness by Pencil Test".</p> <p>6.3.21 Tub and Tile Refinish Coating Abrasion Resistance: Abrasion resistance of tub and tile refinish coating shall be analyzed by ASTM D4060-07, "Standard Test Methods for Abrasion Resistance of Organic Coatings by the Taber Abraser".</p> <p>6.3.22 Tub and Tile Refinish Coating Water Resistance: Water resistance of tub and tile refinish coatings shall be determined by ASTM D4585-99, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D714-02e1, "Standard Test Method for Evaluating Degree of Blistering of Paints".</p> <p>6.3.23 Waterproofing Membrane: Waterproofing membrane shall be tested by ASTM C836-06, "Standard Specification for High Solids Content, Cold Liquid-Applied Elastomeric Waterproofing Membrane for Use with Separate Wearing Course".</p> <p>6.3.24 Mold and Mildew Growth for Basement Specialty Coatings: Mold and mildew growth resistance for basement specialty coatings shall be determined by ASTM D3273-00, "Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings in an Environmental Chamber" and ASTM D3274-95, "Standard Test Method for Evaluating Degree of Surface Disfigurement of Paint Films by Microbial (Fungal or Algal) Growth or Soil and Dirt Accumulation".</p> <p>6.3.25 Reactive Penetrating Sealer Water</p>	<p>subpart D, appendix A, "Determination of Volatile Matter Content of Methacrylate Multicomponent Coatings Used as Traffic Marking Coatings" (September 11, 1998).</p> <p>6.3.17 Hydrostatic Pressure for Basement Specialty Coatings: The hydrostatic pressure resistance for basement specialty coatings shall be analyzed using ASTM D7088-17, "Standard Practice for Resistance to Hydrostatic Pressure for Coatings Used in Below Grade Applications Applied to Masonry".</p> <p>6.3.18 Tub and Tile Refinish Coating Adhesion: The adhesion of tub and tile coating shall be determined by ASTM D4585/4585M-18, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D3359-17, "Standard Test Methods for Measuring Adhesion by Tape Test".</p> <p>6.3.19 Tub and Tile Refinish Coating Hardness: The hardness of tub and tile refinish coating shall be determined by ASTM D3363-05 (2011)e2, "Standard Test Method for Film Hardness by Pencil Test".</p> <p>6.3.20 Tub and Tile Refinish Coating Abrasion Resistance: Abrasion resistance of tub and tile refinish coating shall be analyzed by ASTM D4060-14, "Standard Test Methods for Abrasion Resistance of Organic Coatings by the Taber Abraser".</p> <p>6.3.21 Tub and Tile Refinish Coating Water Resistance: Water resistance of tub and tile refinish coatings shall be determined by ASTM D4585/4585M-18, "Standard Practice for Testing Water Resistance of Coatings Using Controlled Condensation" and ASTM D714-02 (2017), "Standard Test Method for Evaluating Degree of Blistering of Paints".</p> <p>6.3.22 Waterproofing Membrane: Waterproofing membrane shall be ASTM C836/836M-18, "Standard Specification for High Solids Content, Cold Liquid-Applied Elastomeric Waterproofing Membrane for Use with Separate Wearing Course".</p> <p>6.3.23 Mold and Mildew Growth for Basement Specialty Coatings: Mold and mildew growth resistance for basement specialty coatings shall be determined by ASTM D3273-16, "Standard Test Method for Resistance to Growth of Mold on the</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
	<p>Repellency: Reactive penetrating sealer water repellency shall be analyzed by ASTM C67-07, "Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile"; or ASTM C97-02, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C140-06, "Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units".</p> <p>6.3.26 Reactive Penetrating Sealer Water Vapor Transmission: Reactive penetrating sealer water vapor transmission shall be analyzed ASTM E96/E96M-05, "Standard Test Method for Water Vapor Transmission of Materials".</p> <p>6.3.27 Reactive Penetrating Sealer - Chloride Screening Applications: Reactive penetrating sealers shall be analyzed by National Cooperative Highway Research Report 244 (1981), "Concrete Sealers for the Protection of Bridge Structures".</p> <p>6.3.28 Stone Consolidants: Stone consolidants shall be tested using ASTM E2167-01, "Standard Guide for Selection and Use of Stone Consolidants".</p>	<p>Surface of Interior Coatings in an Environmental Chamber" and ASTM D3274-09 (2017), "Standard Test Method for Evaluating Degree of Surface Disfigurement of Paint Films by Fungal or Algal Growth or Soil and Dirt Accumulation". 6.3.25 Reactive Penetrating Sealer Water Repellency: Reactive penetrating sealer water repellency shall be analyzed by ASTM C67-07, "Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile"; or ASTM C97-02, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C140-06, "Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units".</p> <p>6.3.24 Reactive Penetrating Sealer Water Repellency: Reactive penetrating sealer water repellency shall be analyzed by ASTM C67/C67M-18, "Standard Test Methods for Sampling and Testing Brick and Structural Clay Tile"; or ASTM C97/97M-18, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C140-140M-18a, "Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units"</p> <p>6.3.25 Reactive Penetrating Sealer Water Vapor Transmission: Reactive penetrating sealer water vapor transmission shall be analyzed ASTM E96/E96M-16, "Standard Test Method for Water Vapor Transmission of Materials" or ASTM D6490-99 (2014), "Standard Test Method for Water Vapor Transmission of Nonfilm Forming Treatments Used on Cementitious Panels".</p> <p>6.3.26 Reactive Penetrating Sealer - Chloride Screening Applications: Reactive penetrating sealers shall be analyzed by National Cooperative Highway Research Report 244 (1981), "Concrete Sealers for the Protection of Bridge Structures".</p> <p>6.3.27 Stone Consolidants: Stone consolidants shall be tested using ASTM E2167-01 (2008), "Standard Guide for Selection and Use of Stone Consolidants".</p> <p>6.3.28 Building Envelope Coating Air Permeance of Building Materials: ASTM E2178-13, "Standard Test Method for Air Permeance of Building Materials".</p> <p>6.3.29 Building Envelope Coating Water</p>	

Requirement Category	SIP Version of Rule 4601 (12/17/09)	Non-SIP Version of Rule 4601 (4/16/20)	Conclusion
		<p>Penetration Testing: ASTM E331-00 (2016), "Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference".</p> <p>6.3.30 Building Envelope Coating Water Vapor Transmission: ASTM E96/96M-16, "Standard Test Methods for Water Vapor Transmission of Materials".</p> <p>6.3.31 Tile and Stone Sealers Absorption: ASTM C373-18, "Standard Test Methods for Determination of Water Absorption and Associated Properties by Vacuum Method for Pressed Ceramic Tile and Glass Tiles and Boil Method for Extruded Ceramic Tiles and Non-tile Fired Ceramic Whiteware Products"; or ASTM C97/97M-18, "Standard Test Methods for Absorption and Bulk Specific Gravity of Dimension Stone"; or ASTM C642-13, "Standard Test Method for Density, Absorption, and Voids in Hardened Concrete".</p> <p>6.3.32 Tile and Stone Sealers – Static Coefficient of Friction: ANSI A137.1 (2012), "American National Standard of Specifications for Ceramic Tile".</p> <p>6.3.33 Tile and Stone Sealers Water Vapor Transmissions: ASTM E96/96M-16, "Standard Test Methods for Water Vapor Transmission of Materials".</p> <p>6.3.34 VOC Content of Coatings: South Coast AQMD Method 313, "Determination of Volatile Organic Compounds (VOC) by Gas Chromatography/Mass Spectrometry/Flame Ionization Detection (GS/MS/FID)".</p> <p>6.3.35 VOC Content of Coatings: ASTM D6886-18, "Standard Test Method for Determination of the Weight Percent Individual Volatile Organic Compounds in Waterborne Air-Dry Coatings by Gas Chromatography".</p>	
7.0 Compliance Schedule	Persons subject to this rule shall be in compliance with this rule by the dates specified within the rule.	Persons subject to this rule shall be in compliance with this rule by the dates specified within the rule.	No change in the requirements, therefore, non-SIP version of rule is as stringent as SIP version.

Here is the link to 2020 California Air Resources Board (ARB) Suggested Control Measures (SCM) for Architectural Coatings:
https://ww2.arb.ca.gov/sites/default/files/2020-07/2020SCM_final.pdf

District Rule 4601 was amended (4/16/20). As analyzed, each amended section of the non-SIP version of the rule is at least as stringent as, or more stringent than the corresponding section of the SIP version of the rule. Therefore, it is concluded that overall the non-SIP version of the rule is more stringent than the SIP version of the rule.

Table 1 VOC Content Limits for Coatings		
COATING CATEGORY	Current Rule 4601 VOC Limit (g/l) Effective on and after 1/1/2012	Amended Rule 4601 VOC Limit (g/l) Effective on and after 1/1/2022
Flat Coatings	50	50
Nonflat Coatings	100	50
Specialty Coatings -		
Aluminum Roof Coatings	400	100
Basement Specialty Coatings	400	400
Bituminous Roof Coatings	50	50
Bituminous Roof Primers	350	350
Bond Breakers	350	350
Building Envelope Coatings	-	50
Concrete Curing Compounds	350	350
Concrete/Masonry Sealers	100	100
Driveway Sealers	50	50
Dry Fog Coatings	150	50
Faux Finishing Coatings	350	350
Fire Resistive Coatings	350	150
Floor Coatings	100	50
Form-Release Compounds	250	100
Graphic Arts Coatings (Sign Paints)	500	500
High Temperature Coatings	420	420
Industrial Maintenance Coatings	250	250
Low Solids Coatings ¹²	1201	120 1
Magnesite Cement Coatings	450	450
Mastic Texture Coatings	100	100
Metallic Pigmented Coatings	500	500
Multi-Color Coatings	250	250
Pre-Treatment Wash Primers	420	420
Primers, Sealers, and Undercoaters	100	100
Reactive Penetrating Sealers	350	350
Recycled Coatings	250	250
Roof Coatings	50	50
Rust Preventative Coatings	250	250
Shellacs:		
Clear	730	730
Opaque	550	550
Specialty Primers, Sealers, and Undercoaters	100	100
Stains	250	100
Interior Stains	250	

Stone Consolidants	450	450
Swimming Pool Coatings	340	340
Tile and Stone Sealers	100	
Traffic Marking Coatings	100	100
Tub and Tile Refinish Coatings	420	420
Waterproofing Membranes	250	100
Wood Coatings	275	275
Wood Preservatives	350	350
Zinc-Rich Primers	340	340

Table 2 VOC Content Limits for Colorants

Colorants Added To	VOC Limit (g/l) Effective on and after 1/1/2022
Architectural Coatings, excluding Industrial Maintenance Coatings	50
Solvent Based Industrial Maintenance Coatings	600
Waterborne Industrial Maintenance Coatings	50
Wood Coatings	600

ATTACHMENT E

Public Comments and District Responses

Public Comments / District Responses

Public comments regarding the preliminary decision SFPP, L.P.'s Title V permit renewal are provided below followed by the District's responses.

SFPP, L.P. Comment #1:

An application has been submitted to incorporate NESHAP Subpart WW for the internal floating roof tanks. Is it possible to incorporate the WW alternative compliance requirements in the renewed Title V permit?

District Response to SFPP, L.P. Comment #1:

The District has received your Authority to Construct application to incorporate the NESHAP requirements of Subpart WW and has begun processing the request under Project C-1220221. In order to streamline the Title V renewal and not duplicate any work already performed under project C-1220221, the Title V renewal project will not be modified to include the requirements of Subpart WW. The requirements of Subpart WW can be incorporated in to the Title V permit through a Title V Minor Modification. Additionally, the discussion of 40 CFR 60 Subpart within this evaluation

SFPP, L.P. Comment #2:

Rule 4623 citations (Sections 5.3.1.3 and 5.3.2) for internal floating roof tanks included on the permit are for external floating roof tanks.

District Response to SFPP, L.P. Comment #2:

Section 5.3.1.3 of Rule 4623 specifies the landing requirement for floating roofs that is under the section entitled "Specifications for External Floating Roof Tanks", but is also applicable to internal floating roof tanks as required under Section 5.4.3. Therefore, the references to Section 5.3.1.3 will remain on the permits for the floating roof tanks.

Section 5.3.2 of Rule 4623 specifies the criteria for seal designs for floating roofs, also under the section entitled "Specifications for External Floating Roof Tanks". The provisions of Section 5.3.2 are required of internal floating roof tanks as specified in Section 5.4.1 with the exception of complying with the requirements specified in Section 5.3.2.1.3. Section 5.3.2.1.3 requires the seals to be installed so that one end of the shoe extends into the stored liquid and the other end extends a minimum vertical distance of 24 inches above the stored liquid surface; however, Section 5.4.1 only requires a minimum vertical distance of 18 inches above the surface of the liquid surface. Therefore, the following conditions on the draft permits were updated with changes reflected on the final permits:

Permits	Conditions	Notes
C-1077-4-5	9	Rule 4623 Section reference was updated from 5.3.2.1.3 to 5.4.1.
C-1077-20-6	9	
C-1077-21-6	9	
C-1077-50-4	11	
C-1077-13-12	17	The minimum vertical distance was corrected from 24 inches to 18 inches and the Rule 4623 Section reference was updated from 5.3.2.1.3 to 5.4.1
C-1077-19-7	11	