

March 13, 2023

Ms. Melinda Palmer
Kern Oil & Refining Co.
7724 E Panama Ln
Bakersfield, CA 93307

Re: Final - Authorities to Construct / Certificates of Conformity (Significant Mod)
Facility Number: S-37
Project Number: S-1220184

Dear Ms. Palmer:

The Air Pollution Control Officer has issued Authorities to Construct (ATCs) S-37-8-37 and S-37-175-0 with Certificates of Conformity to Kern Oil & Refining Co. for the replacement of a 3,600 bbl organic liquid storage tank (S-37-42-4) with a new 5,000 bbl organic liquid storage tank (S-37-175-0) connected to the vapor recovery system associated with permit unit S-37-8-37, at 7724 E Panama Ln in Bakersfield, CA. Enclosed are the ATCs and a copy of the notice of final action that has been posted on the District's website (www.valleyair.org).

Notice of the District's preliminary decision to issue the ATCs was posted on January 20, 2023. The District's analysis of the proposal was also sent to CARB and US EPA Region IX on January 20, 2023. No comments were received following the District's preliminary decision on this project.

Also enclosed is an invoice for the engineering evaluation fees pursuant to District Rule 3010. Please remit the amount owed, along with a copy of the attached invoice, within 60 days.

Prior to operating with the modifications authorized by the ATCs, you must submit an application to modify the Title V permit as an administrative amendment in accordance with District Rule 2520, Section 11.5. Application forms are found on the District's website at www.valleyair.org/permits/TVforms.

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

Ms. Melinda Palmer
Page 2

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Brian Clements
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email
cc: Gerardo Rios, EPA (w/enclosure) via EPS
cc: Gabe Castro, Kern Energy, via email

Facility # S-37
KERN OIL & REFINING CO.
7724 E PANAMA LN
BAKERSFIELD, CA 93307-9210

AUTHORITY TO CONSTRUCT (ATC)

QUICK START GUIDE

1. **Pay Invoice:** Please pay enclosed invoice before due date.
2. **Fully Understand ATC:** Make sure you understand ALL conditions in the ATC prior to construction, modification and/or operation.
3. **Follow ATC:** You must construct, modify and/or operate your equipment as specified on the ATC. Any unspecified changes may require a new ATC.
4. **Notify District:** You must notify the District's Compliance Department, at the telephone numbers below, upon start-up and/or operation under the ATC. Please record the date construction or modification commenced and the date the equipment began operation under the ATC. A startup inspection may be required prior to receiving your Permit to Operate.
5. **Source Test:** Schedule and perform any required source testing. See http://www.valleyair.org/busind/comply/source_testing.htm for source testing resources.
6. **Maintain Records:** Maintain all records required by ATC. Records are reviewed during every inspection (or upon request) and must be retained for at least 5 years. Sample record keeping forms can be found at http://www.valleyair.org/busind/comply/compliance_forms.htm.

By operating in compliance, you are doing your part to improve air quality for all Valley residents.

**For assistance, please contact District Compliance staff at
any of the telephone numbers listed below.**

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

AUTHORITY TO CONSTRUCT

PERMIT NO: S-37-8-37

ISSUANCE DATE: 03/13/2023

LEGAL OWNER OR OPERATOR: KERN OIL & REFINING CO.
MAILING ADDRESS: 7724 E PANAMA LN
BAKERSFIELD, CA 93307-9210

LOCATION: PANAMA LN & WEEDPATCH HWY
BAKERSFIELD, CA 93307-9210

SECTION: 25 **TOWNSHIP:** 30S **RANGE:** 28E

EQUIPMENT DESCRIPTION:

MODIFICATION OF ORGANIC LIQUID LOADING AREAS AND REFINERY VAPOR RECOVERY SYSTEM SERVING TANK S-37-150, AND '-171 THRU '-173 AND INCLUDING COMPRESSOR(S), LOADING RACKS (RACKS A, F, K, L, N) WITH 10 PRODUCT LINES AND 9 VAPOR RETURN LINES: CONNECT VAPOR CONTROL SYSTEM TO S-37-175

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Authority to Construct (ATC) S-37-8-36 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Transfer Racks N and F may be used for loading and unloading. Transfer Racks A, K, and L shall be used only for loading. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO



Brian Clements, Director of Permit Services

S-37-8-37 : Mar 13 2023 10:45AM -- LEEG : Joint Inspection NOT Required

5. All liquids and gases from the transfer operation shall be routed to one of the following systems: a vapor collection and control system; a fixed roof container that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); a floating roof container that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); or a pressure vessel equipped with an APCO-approved vapor recovery system that meets the control requirements specified in Rule 4623 (Storage of Organic Liquids); or a closed VOC emission control system. [District Rules 4623 and 4624] Federally Enforceable Through Title V Permit
6. A floating roof container that meets the applicable control requirements of Section 5.0 of Rule 4623 (Storage of Organic Liquids) shall be considered not leaking when receiving unloaded liquids for compliance with Rule 4624. [District Rule 4624] Federally Enforceable Through Title V Permit
7. For the transfer of gasoline only, transfer to any stationary storage container with 250 gallon capacity or more, that is not subject to Rule 4623, shall not be allowed unless the container is equipped with a permanent submerged fill pipe and an ARB certified Phase I vapor recovery system, which is maintained and operated according to the manufacturer's specifications, or a vapor recovery system with 95% control approved by the District. [District Rule 4621] Federally Enforceable Through Title V Permit
8. All delivery tanks which previously contained organic liquids, including gasoline, with a TVP 1.5 psia or greater at the storage container's maximum organic liquid storage temperature shall be filled only at Class 1 or Class 2 loading facilities that meet the vapor collection and control requirements of District Rule 4624 or listed herein. [District Rule 4624] Federally Enforceable Through Title V Permit
9. Construction, reconstruction (as defined in District Rule 4001) or expansion of any top loading facility shall not be allowed. [District Rule 4624] Federally Enforceable Through Title V Permit
10. The organic liquid and gasoline loading operation shall be equipped with bottom loading equipment with a vapor collection and control system meeting the requirements listed in this permit. [District Rules 4621 and 4624] Federally Enforceable Through Title V Permit
11. Transfer rack and vapor collection and control equipment shall be designed, installed, maintained in accordance with the manufacturers specifications, and operated such that there are no leaks or excess organic liquid drainage at disconnections as defined herein. [District Rules 4621 and 4624] Federally Enforceable Through Title V Permit
12. During unloading of gasoline, a leak shall be defined as the dripping of VOC-containing liquid at a rate of more than three drops per minute or a reading greater than 100 percent of the Lower Explosive Limit (21,000 ppmv as propane) in accordance with EPA Method 21. [District Rule 4621] Federally Enforceable Through Title V Permit
13. For components used in the gasoline loading operation, a leak shall be defined as the dripping of VOC-containing liquid at a rate of more than three drops per minute or the detection of organic compounds, in excess of 10,000 ppm as methane measured at the surface of the component interface from the potential source in accordance with EPA Method 21. Excess liquid drainage shall be defined as exceeding 10 milliliters per average of 3 consecutive disconnects. [District Rules 4621 and 4624] Federally Enforceable Through Title V Permit
14. For delivery vessels and components used in the organic liquid transfer operation, a leak shall be defined as the detection of organic compounds, in excess of 1,000 ppm as methane measured at the surface of the component interface from the potential source in accordance with EPA Method 21. [District Rule 4624] Federally Enforceable Through Title V Permit
15. Equipment under vapor control shall not vent to atmosphere. [District Rules 4621 and 4624.] Federally Enforceable Through Title V Permit
16. The vapor collection and control system shall operate such that VOC emissions do not exceed 0.08 lb/1000 gallons of organic liquid loaded; maintains at least 95% capture and control efficiency of VOC and which operates so the delivery tank does not exceed 18 inches water column pressure nor 6 inches water column vacuum. [District Rule 4624] Federally Enforceable Through Title V Permit

17. No gasoline delivery vessel shall be used or operated unless it is leak-free. No gasoline delivery vessel shall be operated or loaded unless valid State of California decals are displayed on the cargo tank, attesting to the vapor integrity of the tank as verified by annual performance of CARB required Certification and Test Procedures for Vapor Recovery Systems for Cargo Tanks (Executive Order G-70-10-A) or EPA Method 27 for testing delivery vessels owned or operated by this facility. [District Rule 4621, Health & Safety Code, section 41962, and CCR, Title 17 section 94004] Federally Enforceable Through Title V Permit
18. Measurements of leak concentrations for organic liquid delivery vessels, including gasoline, shall be conducted according to the ARB Test Procedure for Determination of Leaks, TP-204.3, or EPA Method 21. [District Rules 4621 and 4624] Federally Enforceable Through Title V Permit
19. VOC emission rate from diesel loading rack shall not exceed any of the following: Fugitive emissions: 0.12 lb/hr and vapor recovery system: 0.09 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
20. VOC emission rate from fugitive components associated with the refinery vapor control system shall not exceed 6.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
21. During loading of a delivery vessel, the truck-mounted vapor return line shall be connected to the vapor recovery system listed on this permit. [District Rules 2201 and 4621] Federally Enforceable Through Title V Permit
22. A delivery vessel loading gasoline shall discontinue if its pressure relief valve opens. Corrective action shall be taken should this condition occur. [District Rules 2520 and 4621] Federally Enforceable Through Title V Permit
23. Switch loading shall not be conducted unless such transfer is made using an ARB certified vapor recovery system. [District Rules 2201 and 4621] Federally Enforceable Through Title V Permit
24. Operators shall conduct all performance tests required by the facility installation and operations manual as per the frequency outlined therein or as designated by the APCO. [District Rules 4621 and 4624] Federally Enforceable Through Title V Permit
25. The operator shall perform and record the results of monthly leak and drainage inspections of the loading and vapor collection equipment at each loading arm. During the loading of gasoline or organic liquids, leak detection shall be conducted using EPA Method 21 measuring at the surface of the component interface from the potential source. When not in current operation, excess drainage inspections shall be conducted before 10:00 am at the disconnect of each loading arm by collecting all drainage at disconnect in a container and determining the volume within one (1) minute of collection [District Rules 2520, 40 CFR 60.502(j) and 4624] Federally Enforceable Through Title V Permit
26. The leak detection instrument shall be calibrated each day of its use, prior to use, by the procedures specified in Method 21 using the following calibration gases: A) Zero air (less than 10 ppm of hydrocarbon in air); and B) Mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane. [District Rules 2520, 9.3.2 and 4624] Federally Enforceable Through Title V Permit
27. Corrective steps shall be taken at any time the operator observes a leak or excess drainage at disconnect. All equipment found leaking shall be repaired or replaced within 72 hours. If the leaking component cannot be repaired or replaced within 72 hours, the component shall be taken out of service until such time the component is repaired or replaced. The repaired or replacement equipment shall be reinspected the first time the equipment is in operation after the repair or replacement. [District Rule 4624] Federally Enforceable Through Title V Permit
28. All inspections shall be documented within the inspection log. Inspection records shall include, at a minimum, 1) date of inspection, 2) location and description of any missing, loose, leaking, or damaged equipment and any malfunction requiring repair, 3) corrective steps taken to repair or replace the equipment, 4) test method and results for leak and drainage inspections, 5) location and description of any of equipment which shall be inspected upon commencing operation after repair or replacement and 6) inspector name and signature. [District Rules 4621 and 4624] Federally Enforceable Through Title V Permit
29. Records of daily throughput of each loading rack shall be maintained and made available to the APCO, ARB, or EPA during normal business hours. [District Rules 2201, 4621, and 4624] Federally Enforceable Through Title V Permit

30. Permit holder shall maintain accurate component count and resultant emissions according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-3a (Feb 1999), CAPCOA-Revised 1995 EPA Correlation Equations and Factors for Refineries and Marketing Terminals. Components shall be screened and leak rate shall be measured at least once each quarter. If compliance with the daily emission limit is shown during each of five (5) consecutive quarterly inspections, the inspection frequency may be changed from quarterly to annual. If any annual inspection shows non-compliance with the daily emission limit, then quarterly inspections shall be resumed. [District Rule 2201] Federally Enforceable Through Title V Permit
31. This unit is subject to Rule 4455 Leak Detection and Repair Conditions on the facility wide permit S-37-0. [District Rule 4455] Federally Enforceable Through Title V Permit

AUTHORITY TO CONSTRUCT

PERMIT NO: S-37-175-0

ISSUANCE DATE: 03/13/2023

LEGAL OWNER OR OPERATOR: KERN OIL & REFINING CO.
MAILING ADDRESS: 7724 E PANAMA LN
BAKERSFIELD, CA 93307-9210

LOCATION: PANAMA LN & WEEDPATCH HWY
BAKERSFIELD, CA 93307-9210

EQUIPMENT DESCRIPTION:
5,000 BBL ORGANIC LIQUID STORAGE TANK (#5013) SERVED BY SHARED VAPOR RECOVERY SYSTEM LISTED ON PERMIT S-37-8

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Permit to Operate S-37-42-4 shall be cancelled prior to or concurrent with the implementation of this Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 164 lb, 2nd quarter - 164 lb, 3rd quarter - 164 lb, and fourth quarter - 165 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 8/15/19) for the ERC specified below. [District Rule 2201] Federally Enforceable Through Title V Permit
5. ERC Certificate Number C-1523-1 (or certificate split from this certificates) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Samir Sheikh, Executive Director / APCO


Brian Clements, Director of Permit Services

S-37-175-0 : Mar 13 2023 10:46AM - LEEG : Joint Inspection NOT Required

6. As part of its notification required by 40 CFR 60.7(a)(1) or 60.7(a)(2), the operator shall submit to the APCO for approval an operating plan as described in 40 CFR 60.113b(c) and shall operate the closed vent system and monitor the parameters of the system in accordance with the approved operating plan. The operator shall keep a record of the measured values of the parameters monitored in accordance with the approved operating plan. The operating plan shall be retained for the life of the control equipment. [40 CFR 60.113b(c), 60.115b(c)] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Vapors shall be discharged to permit S-37-8 and controlled with an efficiency of at least 95% by weight as determined by EPA Test Method 21. [District Rules 2201 and 4623 and 40 CFR 60.112b(a)(3)(ii)] Federally Enforceable Through Title V Permit
8. The closed vent system shall operate with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background and visual inspections, as determined in 40 CFR 60.485(b). Emissions from the closed vent system in excess of this limit shall be considered a leak. [40 CFR 60.112b(a)(3)(i)] Federally Enforceable Through Title V Permit
9. All piping, valves, and fittings shall be constructed and maintained in a leak free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
10. Storage tank shall be fully enclosed and shall be maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. A leak free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
12. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. VOC fugitive emissions from the components in gas service within five (5) feet of this tank shall not exceed 1.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623] Federally Enforceable Through Title V Permit
15. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
17. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit

18. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
19. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit
20. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
23. Permit holder shall maintain accurate component counts for components on this tank and on piping from this tank to the vapor control system listed on S-37-8 and resultant emissions according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-3a (Feb 1999), Correlation Equations Method. [District Rule 2201] Federally Enforceable Through Title V Permit
24. Operator shall maintain records to demonstrate compliance with fugitive VOC emissions limit of this permit annually. Compliance shall be demonstrated by calculation, using the correlation equations, zero default and 10,000 ppmv pegged factors set forth in the CAPCOA California implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-3a, February 1999, and the average emission concentrations of total organic compounds measured for each component during all inspections conducted during the prior 365 day period. [District Rule 2201] Federally Enforceable Through Title V Permit
25. All records required by this permit shall be retained for a minimum period of 5 years and shall be made available to the APCO, ARB and US EPA upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit