San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

OCT 26 2011

Peggy Shue
Aera Energy LLC
PO Box 11164
Bakersfield, CA 93389

Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # S-1135
Project # 1064857

Dear Mr. Shue:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Aera Energy LLC for its heavy oil production stationary source in the western Kern County fields, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

David Warner
Director of Permit Services

Attachments
C: Richard Edgehill, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

OCT 26 2011

Gerardo C. Rios, Chief
Permits Office (AIR-3)
U.S. EPA - Region IX
75 Hawthorne St.
San Francisco, CA 94105

Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # S-1135
Project # 1064857

Dear Mr. Rios:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Aera Energy LLC for its heavy oil production stationary source in the western Kern County fields, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 45-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

David Warner
Director of Permit Services

Attachments
C: Richard Edgehill, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

OCT 26 2011

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # S-1135
Project # 1064857

Dear Mr. Tollstrup:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Aera Energy LLC for its heavy oil production stationary source in the western Kern County fields, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

David Warner
Director of Permit Services

Attachments
C: Richard Edgehill, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Bakersfield Californian

NOTICE OF PRELIMINARY DECISION

FOR THE PROPOSED RENEWAL OF

THE FEDERALLY MANDATED OPERATING PERMIT

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District solicits public comment on the proposed renewal of the Federally Mandated Operating Permit to Aera Energy LLC for its heavy oil production stationary source in the western Kern County fields, California.

The District's analysis of the legal and factual basis for this proposed action, project #1064857, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. There are no emission changes associated with this proposed action. This will be the public's only opportunity to comment on the specific conditions of the proposed renewal of the Federally Mandated Operating permit. If requested by the public, the District will hold a public hearing regarding issuance of this renewed permit. For additional information, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500. Written comments on the proposed renewed permit must be submitted within 30 days of the publication date of this notice to DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 34946 FLYOVER COURT, BAKERSFIELD, CALIFORNIA 93308.

TITLE V PERMIT RENEWAL EVALUATION
Heavy Crude Oil Production

Engineer: Richard Edgehill
Date: October 17, 2011

Facility Number: S-1135
Facility Name: Aera Energy LLC
Mailing Address: P.O. Box 11164
Bakersfield CA 93389

Reviewed by AP SUPR AQE

OCT 20 2011

Contact Name: Peggy Shue
Phone: (661) 665-5689

Responsible Official: W.J. Dittman
Title: Vice President

Project # : S-1064857
Deemed Complete: December 27, 2006

I. PROPOSAL

Aera Energy LLC (Aera) was issued a Title V permit on August 31, 2002. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

Aera Energy LLC is located at Heavy Oil Western Production Stationary Source in Kern County.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as **Attachment C**.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant has requested to utilize template # SJV-UM-0-3, Facility Wide Umbrella. Based on the information submitted in the Template Qualification Form, the applicant qualifies for the use of this template. Applicant has requested that Condition 23 be revised to provide for the exemptions allowed in Sections 4.1 and 4.2 of the rule. Therefore Condition 23 was revised by including the following underlined words:

23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating <u>not exempt as allowed by Sections 4.1 and 4.2 of Rule 4601</u> with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Y

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Renewed Operating Permit may be based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are not subject to further EPA and public review.

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated (since August 31, 2002)

- District Rule 2020, <u>Exemptions</u>, (amended August 18, 2011)
- District Rule 2201, <u>New and Modified Stationary Source Review Rule</u> (amended April 21, 2011)
- District Rule 4101, <u>Visible Emissions</u> (amended February 17, 2005)
- District Rule 4305, <u>Boilers, Steam Generators, and Process Heaters–Phase 2</u> (Amended August 21, 2003)

- District Rule 4306, Boilers, Steam Generators and Process Heaters – Phase 3, (amended October 16, 2008)
- District Rule 4311, Flares, (amended June 18, 2009)
- District Rule 4401 Steam Enhanced Crude Oil Production Wells (Amended June 16, 2011)
- District Rule 4601, Architectural Coatings, (amended December 17, 2009)
- District Rule 4623, Storage of Organic Liquids (amended May 19, 2005)
- District Rule 4701, Internal Combustion Engines – Phase I (August 21, 2003)
- District Rule 4702, Internal Combustion Engines – Phase 2 (August 18, 2011)
- 40 CFR 63, Subpart HH, National Emission Standards for Hazardous Air Pollutants from Oil and Natural Gas Production Facilities
- 40 CFR Part 64, Compliance Assurance Monitoring (CAM)
- Kern County Rule 407, Sulfur Compounds
- Kern County Rule 424, Sulfur Compounds from Oil Field Steam Generators
- District Rule 8011, General Requirements (amended August 19, 2004)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities (amended August 19, 2004)
- District Rule 8031, Bulk Materials (amended August 19, 2004)
- District Rule 8041, Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Open Areas (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas (amended September 16, 2004)

- 40 CFR Part 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units (amended January 28, 2009)
- 40 CFR 60, Subpart KKKK—Standards of Performance for Stationary Combustion Turbines
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos (amended September 18, 2003)
- 40 CFR Part 82, Subpart B, Stratospheric Ozone (amended November 9, 2007)
- 40 CFR Part 82, Subpart F, Stratospheric Ozone (amended June 8, 2008)

B. Rules Adopted (since August 31, 2002)

- District Rule 4307, Boilers, Steam Generators, and Process Heaters– 2.0 MMBtu/hr to 5.0 MMBtu/hr (adopted December 15, 2005)
- District Rule 4308, Boilers, Steam Generators, and Process Heaters– 0.075 MMBtu/hr to 2.0 MMBtu/hr (adopted October 20, 2005)
- District Rule 4320, Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr (adopted October 16, 2008)

C. Rules Not Updated (since August 31, 2002)

- District Rule 2010, Permits Required (amended December 17, 1992)
- District Rule 2031, Transfer of Permits (amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080, Conditional Approval (amended December 17, 1992)
- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001)
- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)

- District Rule 4202, Particulate Matter–Emission Rate (amended December 17, 1992)

- District Rule 4402, Crude Oil Production Sumps (amended December 17, 1992)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit."

For this facility, the following are not federally enforceable and will not be discussed in further detail:

District Rule 4102, Nuisance

Condition 41 of permit unit S-1135-0-3 is based on District Rule 4102 and will therefore not be discussed any further.

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit.

A. District Rule 2020 - Exemptions

District Rule 2020 lists equipment, which are specifically exempt from obtaining permits, and specifies recordkeeping requirements to verify such exemptions. The rule was amended in August 18, 2011. The amendments to this rule do not have any affect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201–New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this facility's initial Title V permit was issued. This Title V permit renewal does not constitute a modification per section 3.25, defined as an action including at least one of the following items:

1) Any change in hours of operation, production rate, or method of operation of an existing emissions unit, which would necessitate a change in permit conditions.

2) Any structural change or addition to an existing emissions unit which would necessitate a change in permit conditions. Routine replacement shall not be considered to be a structural change.
3) An increase in emissions from an emissions unit caused by a modification of the Stationary Source when the emissions unit is not subject to a daily emissions limitation.
4) Addition of any new emissions unit which is subject to District permitting requirements.
5) A change in a permit term or condition proposed by an applicant to obtain an exemption from an applicable requirement to which the source would otherwise be subject.

Therefore, the updated requirements of this rule are not applicable at this time.

C. District Rule 2520 – Federally Mandated Operating Permits

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

D. District Rule 4101 - Visible Emissions

District Rule 4101 prohibits the discharge of any air contaminant for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker in shade as that designated as No. 1 on the Ringelmann Chart; or is of such opacity as to obscure an observer's view to a degree equal to or greater than the smoke described in Section 5.1 of Rule 4101. The rule was amended in February 17, 2005.

a. <u>S-1135-0-3 – Facility-Wide Requirements</u>

- Condition 22 on the proposed permit assures compliance with the requirements of this rule.

E. District Rule 4305, Boilers, Steam Generators, and Process Heaters – Phase 2

The facility includes units subject to Rule 4305, Boilers, Steam Generators and Process Heaters – Phase 2. However the units are also subject to District Rule 4306. Since emissions limits of Rule 4306 and all other requirements are equivalent or more stringent than District Rule 4305 requirements, compliance with District Rule 4306 requirements will satisfy

requirements of District Rule 4305. Additionally, permit conditions referencing Rule 4305 also reference Rule 4306.

F. District Rule 4306 – Boilers, Steam Generators, and Process Heaters – Phase 3

This rule applies to any boiler, steam generator or process heater, with a rated heat input greater than 5 million Btu per hour that is fired with gaseous and/or liquid fuels.

Section 5.1 requires that NO_X and CO emissions shall not exceed the limits specified in Table 1. For oil field steam generators (Table 1 Category C), NO_X and CO emissions shall not exceed 15 ppmv and 400 ppmv, respectively. Units emissions, limited to an annual heat input of 9 billion Btu/year to 30 billion Btu/year (Table 1, Category H), shall not exceed 30 ppmv NO_X per year and 400 ppmv CO per year.

Section 5.3 states that emission limits shall not apply during start-up or shutdown provided an operator complies with the requirements that the duration of each start-up or each shutdown shall not exceed two hours, the emission control system shall be in operation and emissions shall be minimized insofar as technologically feasible during start-up or shutdown, and an operator may submit an application for a permit condition to allow more than two hours for each start-up or each shutdown provided the operator meets all of the conditions specified in Sections 5.3.3.1 through 5.3.3.3.

Section 5.4 requires that operators of any unit subject to the applicable emission limits of the rule shall install and maintain an operational APCO approved Continuous Emissions Monitoring System (CEMS) for NO_X, CO, and oxygen, or implement an APCO-approved Alternate Monitoring System. The operator of any Category H units shall install and maintain an operational non-resettable, totalizing mass or volumetric flow meter in each fuel line to each unit.

Section 6.1 requires that records required by Sections 6.1.1 through 6.1.4 shall be maintained for five calendar years and shall be made available to the APCO upon request.

Section 6.2 identifies the applicable test methods.

Section 6.3 requires that units subject to the requirements in Sections 5.1 or 5.2.3 shall be source tested to determine compliance with the applicable emission limits at least once every 12 months.

G. District Rule 4307 – BOILERS, STEAM GENERATORS, AND PROCESS HEATERS - 2.0 MMBTU/HR TO 5.0 MMBTU/HR

This rule limits the NO_x and CO emissions from boiler, steam generator, or process heater with a total heat input of 2.0 MMBtu/hr ≤ 5.0 MMBtu/hr.

Section 5.0 Emissions Limits
The heater treaters are in compliance with the Section 5.0 emissions limits requirements of the rule.

Section 5.3 Particulate Matter Control Requirements
These requirements are not applicable until 2015

Section 5.5 Monitoring Provisions – Monthly Monitoring
Section 6.0 Administrative Requirements – Startup/Shutdown

The units are in compliance with the monitoring (tuning) and startup and shutdown provisions.

Permit	Equipment	Rule 4307 Conditions
S-1135-3	8.4 MMBTU/HR (DERATED TO 5 MMBTU/HR) NATURAL GAS FIRED HEATER TREATER #1 WITH A MAXON MODEL M-PAKT BURNER WITH VARIABLE FREQUENCY DRIVE (VFD) BLOWER, SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE	20-27
S-1135-29	NATURAL GAS-FIRED HEATER TREATER (#2) WITH A 4.2 MMBTU/HR MAXON MODEL M-PAKT BURNER SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE	16, 20, 22-28, 30, 31

H. District Rule 4320, Advanced Emission Reduction Options for Boilers, Steam Generators, and Process Heaters Greater than 5.0 MMBtu/hr

Outstanding ATC for unit S-1131-12-36 for Rule 4320 compliance will not be implemented prior to permit renewal. Other units comply with Section 5.1.2 of the rule which authorizes payment of fees or are dormant emissions units.

Permit	Equipment	Rule 4305/4306 Conditions	Rule 4320 Compliance Status
S-1135-5	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #41 DIS #11867-75 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR (BUENA FE LEASE)	14,15,17,18,19-25, 27,28, 31-33	Fees SOx 0.001 lb/MMBtu
S-1135-6	62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #43 WITH A COEN QLN-ULN LOW NOX BURNER AND FLUE GAS RECIRCULATION (KENDON LEASE)	14,15,17,19-26, 28-30	Fees
S-1135-8	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS FIRED NATIONAL STEAM GENERATOR #17, DIS# 9236-68, WITH NORTH AMERICAN BURNER (MAXWELL LEASE)	3-5, 10, 16-23	Dormant with Fee condition
S-1135-9	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #18, DIS# 9237-68 (MAXWELL LEASE)	3-5, 10, 11, 17-24	Dormant with Fee condition
S-1135-10	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #19, DIS# 9238 68 (MAXWELL LEASE)	3-5, 10, 16-23	Dormant with Fee condition
S-1135-12	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #45 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR AND OPTIONAL SO2 SCRUBBER (KENDON LEASE)	18-20, 22-28,30,31,33-35	ATC S-1135-12-36 lower NOx limit to 5 ppmv @ 3% O2 for Rule 4320 PTO Fees
S-1135-13	62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #44 WITH COEN QLN-ULN 3.2 BURNER (WILBERT LEASE)	1-4, 10, 23, 24, 27-36, 38-40	Fees
S-1135-24	DORMANT 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #25, DIS# 26916 66, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND SO2 SCRUBBER (KENDON LEASE)	1,2, 8, 10, 19, 22-31, 33, 35, 36	Dormant No Fee Condition

S-1135-26	62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #32, DIS# 12051 71, WITH A COEN ULN 3.2 LOW-NOX BURNER AND OPTIONAL SO2 SCRUBBER - METSON LEASE	10-12,17, 19,20 , 22-27	10-12,17, 20, 22-27
S-1135-27	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #27, DIS# 12069-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)	2-4. 12, 21), 24-34, 36-37	Dormant Fees
S-1135-28	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #26, DIS# 12071-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)	2-4, 10, 12, 21, 24-34, 36, 37	Dormant Fees
S-1135-30	DORMANT 30 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #MO-2, DIS# 19961-68, WITH NORTH AMERICAN 5131-FACR BURNER - MOCAL LEASE	2, 3, 8, 14-18, 20-22	Dormant No Fees
S-1135-115	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #1 (NEELY LEASE)	10,15-21, 29	Fees
S-1135-119	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #5 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)	8, 12-18, 27	Dormant Conditions no Fee
S-1135-122	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #6 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)	12-18, 26	Dormant Conditions no Fee
S-1135-123	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #7 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)	12-18, 26	Dormant Conditions no Fee
S-1135-266	62.5 MMBTU/HR STRUTHERS STEAM GENERATOR, WITH A COEN QLN-ULN BURNER, O2 CONTROLLER, AND FLUE GAS RECIRCULATION (METSON 48)	16, 18-26, 28-31	Fees
S-1135-267	62.5 MMBTU/HR STRUTHERS GAS-FIRED STEAM GENERATOR (#49) WITH A COEN MODEL QLN-ULN BURNER WITH FLUE GAS RECIRCULATION (FGR) (KENDON LEASE)	16, 18-26, 28-30	Fees

S-1135-299	62.5 MMBTU/HR GAS-/LPG-FIRED STEAM GENERATOR #50 WITH A COEN MODEL QLN-ULN LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM AND AN OXYGEN CONTROLLER (KENDON LEASE)	14, 16-25, 27, 28	Fees
S-1135-302	62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR (#5) WITH A COEN MODEL QLN-ULN ULTRA LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) (BUENA FE LEASE)	16-24, 26-28	Fees
S-1135-305	62.5 MMBTU/HR NAT GAS-FIRED STEAM GENERATOR # 52, WITH A COEN QLN-ULN LOW NOX BURNER, WITH FLUE GAS RECIRCULATION, (PRU LEASE)	6, 14, 16-26, 28	Fees

I. District Rule 4623 - Storage of Organic Liquids

This rule limits volatile organic compound (VOC) emissions from the storage of organic liquids. It applies to any tank with a capacity of 1,100 gallons or greater in which any organic liquid is placed, held, or stored. The rule was amended in May 19, 2005.

Section 5.1 requires that no organic liquid shall be placed, held, or stored in any tank unless the tank is equipped with a VOC control system identified in Table 1. Tank permits with a TVP limit of 0.5 psia or less are not subject to the leak free and vapor control requirements of the rule. TVP testing and recordkeeping is not required for tanks under vapor control (but may be included on the permit for enforcement of the NSR TVP limit).

Tanks, and unfired heater treaters served by Vapor Control (S-1135-70, '-71, '-72, '-149, '-150, '-151, '-152, '-156,5, 173, '-174, '-175, '-178, '-270, '-281, '-284, '-285, '-'-286, '-287, '-301, '-322, '-323, '-325, '-326, '-327, '-328, '-329, '-330, '-331, '-332, '-333, '-334, '-335, '-336, '-337

The following permit requirements ensure compliance with this rule:

Permit	Equipment	Rule 4623 Conditions
S-1135-70	43,470 GALLON FIXED ROOF REJECT TANK T-110, WITH SHARED VAPOR RECOVERY SYSTEM - METSON LEASE TANK BATTERY	8-18
S-1135-71	84,000 GALLON FIXED ROOF LACT TANK T-100 WITH VAPOR RECOVERY (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY	5-15

S-1135-72	210,000 GALLON FIXED ROOF STANDBY TANK T-120, WITH VAPOR RECOVERY SYSTEM (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY	6-9, 11-16
S-1135-149	126,000 GALLON CRUDE OIL LACT TANK ID# AG-01, WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-150, '151, '152, '155, '270, '301 AND '323 (ANDERSON/GOODWIN LEASE)	5, 6, 14-18
S-1135-150	126,000 GALLON CRUDE OIL LACT TANK ID# AG-02, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)	9, 10, 12-16
S-1135-151	210,000 GALLON REJECT TANK ID# AG-03, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)	10, 12-16
S-1135-152	210,000 GALLON REJECT TANK ID# AG-04, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)	10, 12,-16
S-1131-155	281,400 GALLON (6,700 BBL) FIXED ROOF WASH TANK ID# AG-07, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)	9, 10, 12-16
S-1131-173	1,600 BBL (67,200 GALLON) FIXED ROOF LACT TANK ID# WS-01, HANDLING MAXWELL LEASE PRODUCTION, AND VESSELS V-101, V-102, V-103, AND V-104; WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-174, -175, -178, -325, AND -337 (W&S LEASE) DISCHARGING TO TEOR WVVCS S-1135-125	
S-1131-174	2,000 BBL (84,000 GALLON) FIXED ROOF LACT TANK ID# WS-02, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)	6 (vapor pressure 0.45 psia)
S-1135-175	1,600 BBL (67,200 GALLON) FIXED ROOF WASH TANK ID# WS-03, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)	6 (vapor pressure 0.45 psia)

S-1135-178	3,000 BBL (126,000 GALLON) FIXED ROOF SUMP PROCESS TANK ID# WS-06, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)	5 (vapor pressure 0.45 psia)
S-1135-270	210,000 GALLON FIXED ROOF OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)	4, 8, 10 (vapor pressure 0.45 psia), 11-14, (tvp testing)
S-1135-281	3,000 BBL FIXED ROOF SUMP REPLACEMENT TANK WITH VAPOR CONTROL SYSTEM SHARED WITH S-1135-284, -285, -286, -287, -328, '-329, '-330, '-331, '-332, '-333, '-334, '-335, AND '-336	11, 13 (vapor pressure 0.45 psia),14-19 (tvp testing)
S-1135-284	126,000 GALLON FIXED ROOF RUN TANK #5, WITH VAPOR CONTROL SYSTEM LISTED ON S-1135-281	7 (vapor pressure 0.45 psia), 8-13 (tvp testing)
S-1135-285	126,000 GALLON FIXED ROOF LACT TANK #6 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281	7 (vapor pressure 0.45 psia), 8-13 (tvp testing)
S-1135-286	126,000 GALLON FIXED ROOF LACT TANK #7 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281	7 (vapor pressure 0.45 psia), 8-13 (tvp testing)
S-1135-287	126,000 GALLON FIXED ROOF LACT TANK #8 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281	7 (vapor pressure 0.45 psia), 8-13 (tvp testing)
S-1135-301	281,400 GALLON FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)	4, 9, 11 (vapor pressure 0.45 psia), 12-15 (tvp testing)
S-1135-322	126,000 GALLON FIXED ROOF WASH TANK T-101, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY	6-17, leak free, I&M
S-1135-323	3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-129 - ANDERSON GOODWIN LEASE	4, 8,
S-1135-325	3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK, HANDLING MAXWELL LEASE PRODUCTION, SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W & S LEASE)	
S-1135-326	126,000 GALLON FIXED ROOF WASH TANK T-102, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY	5-15 (leak free I&M)
S-1135-327	905 BBL FWKO VESSEL (V-100) CONNECTED TO VAPOR RECOVERY SYSTEM LISTED ON S-1135-70	2-16 (leak free I&M)

S-1135-328	1,200 BBL FLOW SPLITTER PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1135-329	1,200 BBL FWKO PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1135-330	1,200 BBL "GAS BUSTER" PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1135-331	1,200 BBL UNFIRED TREATER #1 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1131-332	1,200 BBL UNFIRED TREATER #2 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1131-333	1,200 BBL UNFIRED TREATER #4 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1131-334	1,200 BBL UNFIRED TREATER #6 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1131-335	1,200 BBL UNFIRED TREATER #7 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1131-336	1,200 BBL UNFIRED TREATER #8 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)	Pressure vessel
S-1131-337	3,000 BBL (126,000 GALLON) FIXED ROOF STOCK TANK ID# WS-04, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)	3, 4 (leak free) 21 (records)

District Rule 4401

Outdated Rule 4401 conditions listed in the table below were replaced by conditions (following the table) reflecting the current rule requirements.

Permit (Conditions Replaced)	Equipment	Outdated Existing Rule 4401 Conditions
S-1135-230	1 MISC. STEAM DUMPING-ROCK BED MUFFLER OPERATION FOR MIDWAY SUNSET COGENERATION BLOWDOWN.	3, 5-15, 26
S-1135-17	STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION, SERVING 175 STEAM ENHANCED WELLS, INCLUDING PIPING TO INCINERATING STEAM GENERATORS, FOR REINJECTION OF NONCONDENSIBLE VAPORS, OR FOR BALANCING OF WELL VENTS.	5-15,
S-1135-18	STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 140 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (WILBERT LEASE)	6-41
S-1135-20	STEAM ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING 295 STEAM ENHANCED WELLS (KENDON LEASE), INCLUDING A FIN FAN COOLER, GAS/LIQUID SEPARATORS, AND ASSOCIATED PIPING	2, 4-14, 27,28
S-1135-21	STEAM-ENHANCED CRUDE OIL PRODUCTION OPERATION SERVING UP TO 153 STEAM-ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (BUENA FE FEE LEASE)	7, 12-13,4, 16-46
S-1135-22	STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 90 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (MOCAL LEASE)	8-43
S-1135-124	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 254 STEAM ENHANCED WELLS, AND TIED TO TEOR '293 INCLUDING PIPING TO BALANCED CGCS, RE-INJECTION COMPRESSORS OR INCINERATING STEAM GENERATORS (EXETER LEASE)	15-49
S-1135-125	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 144 STEAM ENHANCED CRUDE OIL PRODUCTION WELL VENTS, TIED TO TEOR '293 AND TVR '173 (W&S FEE LEASE)	17-51

S-1135-127	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION INCLUDING ONE TRANSPORTABLE FIN FAN COOLER AND ASSOCIATED PIPING SERVING 383 STEAM ENHANCED WELL VENTS (MAXWELL LEASE) CONNECTED TO TANK VAPOR CONTROL SYSTEM S-1135-118, COLLECTED VAPORS PIPED FROM VAPOR CONTROL COMPRESSOR SKIDS EITHER TO INJECTION COMPRESSORS FOR RE-INJECTION TO DOGGR WELLS, TO STEAM GENERATORS S-1135-9 AND '-10 FOR INCINERATION, OR CONTAINED WITHIN THE BALANCED CASING GAS COLLECTION SYSTEM (CGCS)	5-15
S-1135-128	THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 265 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, PIPING TO DISPOSAL WELLS, TIED TO TEOR S-1135-129, AND TVR S-1135-149 AND S-1135-281 (NEELY LEASE)	4-14
S-1135-129	THERMALLY ENHANCED OIL RECOVERY OPERATION AUTHORIZED FOR 425 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, VAPOR PIPING TO INJECTION WELLS (ANDERSON-GOODWIN LEASE)	11-26
S-1135-283	THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 90 STEAM ENHANCED WELLS WITH CLOSED CASING VENTS (ANDERSON LEASE)	11-35
S-1135-293	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 300 STEAM DRIVE WELLS WITH CASING VENTS TIED TO VAPOR CONTROL SYSTEM INCLUDING, THREE VAPOR CONTROL SKIDS WITH SEPARATOR(S), HEAT EXCHANGER(S), FAN(S), AND COMPRESSOR(S), WITH NON-CONDENSIBLE VAPOR PIPING SHARED WITH TEOR OPERATION S-1135-124 (EXETER LEASE) CONTROLLED BY BALANCED CASING VENT COLLECTION SYSTEM OR RE-INJECTION INTO DOGGR APPROVED DISPOSAL WELL (GLOBE LEASE)	4-14

The following updated conditions were added to the draft PTOs:

During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1]

An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, the steam-enhanced crude oil production well vent is open and the well vent is connected

to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.1.1 and 5.1.2]

An operator shall be in violation of this rule if any District inspection demonstrates that one or more of the following conditions in Section 5.2.2 exist at the facility or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates that one or more of the following conditions in Section 5.2.2 exist at the facility: Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines. [District Rule 4401 5.4.2]

An operator shall be in violation of this rule if any District inspection demonstrates that one or more of the following conditions exist at the facility or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates that one or more of the conditions in Section 5.2.2 exist at the facility: existence of a component with any of the following: a major liquid leak, a gas leak greater than 50,000 ppmv, a minor liquid leak or a minor gas leak in excess of the allowable number of leaks allowed by Table 3 of Rule 4401, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv in excess of the allowable number of leaks allowed by Table 3 of Rule 4401. [District Rule 4401 5.2.2]

An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401 5.3.1]

Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401 5.3.2]

An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401 5.3.3]

Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401 5.4.1]

An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.4.2]

An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3]

The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service,

and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4]

An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401 5.4.7]

District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401 5.4.8]

Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1]

The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2]

An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401 5.5.3]

Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 4 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401 5.5.4]

The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401 5.5.4]

The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.5.5]

The time of the initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.5.6]

If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401 5.5.7]

The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401 6.1.1]

An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401 6.1.3]

Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401 6.1.4]

Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401 6.1.5]

An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1.6]

Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401 6.1.7]

Operator shall submit to the APCO not later than June 14, 2007 a list of all gauge tanks, as defined in Section 3.17. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401 6.1.8]

The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401 6.1.9]

An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401 6.1.10]

An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401 6.2.1]

If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401 6.2.2]

If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 for a vapor control system which does not have a VOC destruction device. [District Rule 4401 6.2.3]

An operator seeking approval pursuant to Section 6.2.2 or Section 6.2.3 shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401 6.2.4]

An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank, the TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of

Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401 6.2.3]

The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401 6.3.1]

VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401 6.3.2]

Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401 6.3.3]

The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401 6.3.4]

Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401 6.4]

By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7]

Compliance is expected.

District Rule 4601

The purpose of this rule is to limit VOC emissions from architectural coatings. This rule specifies architectural coatings storage, cleanup, and labeling requirements.

This rule is applicable to any person who supplies, sells, offers for sale, applies, or solicits the application of any architectural coating, or who manufactures, blends or repackages any architectural coating for use within the District.

a. S-1121-0-1 – Facility-Wide Requirements

Conditions 23 – 27 on the proposed permit assure compliance with the requirements of this rule.

District Rules 4701 and 4702

Emergency IC engines S-1135-231 and 235 are currently in compliance with the rules.

Rule 4701 and 4702 requirements are listed as permit conditions.

Unit	Equipment	Rule 4701 and 4702 Conditions
S-1135-231	165 HP DIESEL-FIRED I.C. ENGINE POWERING A FIREWATER PUMP	2,3,5, 6
S-1135-235	2,520 BHP DIESEL FIRED I.C. ENGINE FOR EMERGENCY POWER GENERATION, INCLUDING: ONE CATERPILLAR MODEL #3516STD 16 CYLINDER I.C. ENGINE OPERATING A 1500 KW ELECTRIC GENERATOR, VALVE CONNECTING CRANKCASE TO INTAKE MANIFOLD, & ELAPSED OPERATING TIME METER	6

S-1135-235 Condition 5 was corrected as follows:

5. The sulfur content of the diesel fuel used shall not exceed ~~0.05%~~ 0.0015% by weight. [District NSR Rule] Y

District Rule 4703
Turbines S-1135-224 through '-226

The turbines are equipped with dry low NOx combustors and SCR and include an unfired heat recovery steam generator (HRSG):

The turbines meet the Section 5.1.3 and 5.2 exhaust limits of 5 ppmvd NO_X @ 15% O_2 and 200 ppmvd CO @ 15% O_2.

The turbines meet the Section 5.3 specific requirements for transitional periods.

The turbines meet the CEMs, annual source test, and recordkeeping requirements of Section 6.0.

Rule 4703 requirements are listed as permit conditions.

Unit	Equipment	Rule 4703 Conditions
S-1135-224	NOMINALLY RATED 78.2 MW COGENERATION UNIT A WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)	8, 22,23, 25, 27, 35, 50-53
S-1135-225	NOMINALLY RATED 78.2 MW COGENERATION UNIT B WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS, SELECTIVE CATALYTIC REDUCTION (SCR), AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)	8, 22,23, 25, 27, 35, 50-53
S-1135-226	NOMINALLY RATED 78.2 MW COGENERATION UNIT C WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)	8, 22,23, 25, 27, 35, 50-53

Regulation 8

Outdated conditions on the facility wide permit have been replaced by conditions included on Facility-Wide Umbrella Template #SJV-UM-0-3.

	Facility Wide Requirements
District Rule 8011 - General Requirements	The provisions of this rule are applicable to specified outdoor fugitive dust sources. The definitions, exemptions, requirements, administrative requirements, recordkeeping requirements, and test methods set forth in this rule are applicable to all Rules under Regulation VIII (Fugitive PM10 Prohibitions) of the Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. The rule was amended in August 19, 2004.
District Rule 8021 - Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities	The purpose of this rule is to limit fugitive dust emissions from construction, demolition, excavation, extraction, and other earthmoving activities. The rule was amended in August 19, 2004. This rule applies to any construction, demolition, excavation, extraction, and other earthmoving activities, including, but not limited to, land clearing, grubbing, scraping, travel on site, and travel on access roads to and from the site. This rule also applies to the construction of new landfill disposal sites or modification to existing landfill disposal sites prior to commencement of landfilling activities. Section 5.0 requires that no person shall perform any construction, demolition, excavation, extraction, or other earthmoving activities unless the appropriate requirements in sections 5.1 and 5.2 are sufficiently implemented to limit VDE to 20% opacity. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII.

District Rule 8031 - Bulk Materials	The purpose of this rule is to limit fugitive dust emissions from the outdoor handling, storage, and transport of bulk materials. The rule was amended in August 19, 2004. This rule applies to the outdoor handling, storage, and transport of any bulk material. Section 5.0 requires that no person shall perform any outdoor handling, storage, and transport of bulk materials unless the appropriate requirements in Table 8031-1 of this rule are sufficiently implemented to limit VDE to 20% opacity or to comply with the conditions for a stabilized surface as defined in Rule 8011. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII.
District Rule 8041 - Carryout and Trackout	The purpose of this rule is to limit fugitive dust emissions from carryout and trackout. The rule was amended in August 19, 2004. This rule applies to all sites that are subject to Rules 8021 (Construction, Demolition, Excavation, Extraction, and other Earthmoving Activities), 8031 (Bulk Materials), and 8071 (Unpaved Vehicle and Equipment Traffic Areas) where carryout or trackout has occurred or may occur. Section 5.0 requires that an owner/operator shall sufficiently prevent or cleanup carryout and trackout as specified in sections 5.1 through 5.8. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII. The use of blower devices, or dry rotary brushes or brooms, for removal of carryout and trackout on public roads is expressly prohibited. The removal of carryout and trackout from paved public roads does not exempt an owner/operator from obtaining state or local agency permits which may be required for the cleanup of mud and dirt on paved public roads.
District Rule 8051 - Open Areas	The purpose of this rule is to limit fugitive dust emissions from open areas. The rule was amended in August 19, 2004. This rule applies to any open area having 3.0 acres or more of disturbed surface area that has remained undeveloped, unoccupied, unused, or vacant for more than seven days. Section 5.0 requires that whenever open areas are disturbed or vehicles are used in open areas, the owner/operator shall implement one or a combination of control measures indicated in Table 8051-1 to comply with the conditions of a stabilized surface at all times and to limit VDE to 20% opacity. In addition to the requirements of this rule, a person shall comply with all other applicable requirements of Regulation VIII.

District Rule 8061 - Paved and Unpaved Roads	The purpose of this rule is to limit fugitive dust emissions from paved and unpaved roads by implementing control measures and design criteria. The rule was amended in August 19, 2004. This rule applies to any new or existing public or private paved or unpaved road, road construction project, or road modification project.
District Rule 8071 - Unpaved Vehicle/Equipment Traffic Area	The purpose of this rule is to limit fugitive dust emissions from unpaved vehicle and equipment traffic areas by implementing control measures and design criteria. The rule was amended in September 16, 2004. This rule applies to any unpaved vehicle/equipment traffic area of 1.0 acre or larger.

NSPS Requirements

40 CFR Part 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units

Subpart Dc applies to steam generating units for which construction, modification, or reconstruction is commenced after June 9, 1989 and that has a maximum design heat input capacity of 100 million Btu per hour or less, but greater than or equal to 10 million Btu per hour. Subpart Dc has no emission requirements for gas-fired units and therefore is not applicable.

40 CFR Part 82, Subpart B and F, Stratospheric Ozone

These regulations apply to servicing motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC). Sections of this regulation were amended in 2004 and 2008, and conditions 29 (Subpart F) and 30 (Subpart B) of C-1121-0-1 assure compliance with the requirements.

40 CFR 60, Subpart KKKK—Standards of Performance for Stationary Combustion Turbines

The requirements of the 40 CFR Part 60, Subpart KKKK apply to a stationary combustion turbine with heat input (at peak load) equal to or greater than 10 MMBtu/hr, and that commenced construction, modification or reconstruction after February 18, 2005. Units S-1135-224 through '-226 were installed before February 18, 2005 and therefore this section is not applicable.

40 CFR Part 64-CAM

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

1) the unit must have an emission limit for the pollutant;
2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

a. S-1135-70, '-71, '-72, '-149, '-150, '-151, '-152, '-155, '-173, '-174, '-175, '-178, '-270, '-281, '-284, '-285, '-286, '-287, '-301, '-322, '-323, '-325, '-326, '-327, '-328, '-328 through '-336 (heater treaters and pressure vessels) – <u>Vessels and Tanks</u> <u>with Vapor Recovery System</u>

§64.1 defines a control device as equipment, other than inherent process equipment, that is used to destroy or remove air pollutants prior to discharge to the atmosphere. For tanks equipped with a vapor control system, the District has determined that the vapor control system is "inherent process equipment, i.e. the vapor control system is used to increase the safe and proper functioning of the tank battery. Such a vapor control system serves to reduce emission of H2S (a toxic substance) from the tank(s) and to reduce corrosion in the tank(s) vapor space by eliminating the intrusion of ambient air. Inherent process equipment is explicitly excluded from the definition of control device as defined in 40 CFR 64.

b. S-<u>1135-82 and '-83 TVP < 0.5 psia – uncontrolled fixed-roof tanks</u>

These permit units are not subject to CAM since the units do not have add-on controls.

c. S-<u>1135-5 (optional FGR), '-6, '-12 (optional FGR), '-27, '-28, '-266, '-267, '-299, '-302, '-305 steam generators with low NOx burners and FGR</u>

Except for DEU units '-11 and '-12 these steam generators are equipped with FGR and are currently operating in compliance with Rule 4603 and therefore are

required to meet the NOx emissions limit of 0.018 lb/MMBtu. To assess whether CAM is triggered the emissions factor corresponding to pre add-on (FGR) was calculated.

AP-42 Table 1.4-1 (7/98) lists the following emissions factors for small boilers < 100 MMBtu/hr

	Emissions Factor ($lb/10^6$ scf)
Uncontrolled	100
Controlled – low NOx burners	50
Controlled – Low NOx burners/Flue gas recirculation	32

The control efficiency of FGR and corresponding emissions factor are

100 x (50 – 32)/50 = 36%

0.018/(1 – 0.36) = 0.028 lb/MMbtu

and the pre add-on control emissions are

0.028 lb/MMbtu x 62.5 MMBtu/hr x 8760 hr/yr x ton/2000 lb

= 7.7 tons/yr < 10 tons/yr

As pre-control annual emissions are less than 10 tons/yr enhanced CAM monitoring is not required. Note that units '-8, '-9, '-10, '-24, '-27, '-28, and '-30 are DEU and cannot be restarted until Rule 4306 requirements are met.

d. S-1135-12 (optional), '-13 (in conditions only – no longer has scrubber), '-24, '-26, '-27, '-28 steam generators with SO2 scrubbers

	MMBtu/yr permit limit	Maximum* vapor recovery gas volume (mscf/yr)	Maximum H_2S* content of vapor recovery gas (ppm)	Pre-Control SO_2 Emissions (tons/yr)**
'-12 and '-13	438,000	216,000	8,100	148 >70
'-24	30,000	0		
'-26	438,000	292,000	6450	159 >70
'-27	30,000	42,000	6450	23 < 70
'-28	30,000	42,000	6450	23 <70

*Applicant data used to calculate pre-control emissions
216,000,000 ft^3/yr x 8,100 $ft^3S/10^6$ ft^3 x lbmol/379 ft^3 x 64 lb SO2/lbmol x ton/2000 lb = 148 tons/yr*
** major source SO2 threshold is 140,000 lb/yr

Draft PTOs for the steam generators with scrubbers include the condition that scrubber pH must be maintained above pH 6.15 and be monitored continuously which provides exemption from CAM according to 40 CFR Subpart 64.2(b)(vi).

e. C-1121-33 and '-34 Turbines

The pre-control potentials to emit for the turbines are**

NOx: 0.038 lb NOx/MMBtu* x 920 MMBtu/hr x 8760 hr/yr x ton/2000 lb
= 153 tons/yr

CO: 0.057 lb NOx/MMBtu* x 920 MMBtu/hr x 8760 hr/yr x ton/2000 lb
= 230 tons/yr

*Manufacturer's Information (from Permittee Application) on Turbine and Dry Low NOx Combustors

The turbines are equipped with CEMs and are therefore exempt from CAM according to 40 CFR Subpart 64.2(b)(vi).

f. C-1121-38, '-39, '-114, and '-116 TEOR operations served by vapor control

Permit (Conditions Replaced)	
C-1121-38	CVR-1: 155 STEAM-DRIVE WELLS SERVED BY 170 HP CASING VAPOR RECOVERY SYSTEM WITH HEAT EXCHANGER E-100, FIN FAN COOLER E-110, SEPARATOR V-100, CONDENSATE PUMPS P-100 AND P-101, AND GAS COMPRESSOR SKID WITH COMPRESSOR C-10, FIN FAN COOLER E-10, SEPARATORS V-10 AND V-11 AND CONDENSATE PUMP P-10.
C-1121-39	CVR-2: 213 STEAM-DRIVE WELLS SERVED BY 140 HP CASING VAPOR RECOVERY SYSTEM WITH HEAT EXCHANGER E-200, FIN-FAN COOLER E-210, SEPARATOR V-200, CONDENSATE PUMPS P-200 & P-201, AND GAS COMPRESSOR SKID WITH COMPRESSOR C-20, FIN-FAN COOLER E-20, SEPARATORS V-20 & V-21, AND CONDENSATE PUMP P-20. RECOVERED VAPOR LINE CONNECTED TO RECOVERED VAPOR LINES OF PERMIT UNITS C-1121-116 & C-1121-114
C-1121-93	20 UNCONTROLLED CYCLIC/STEAM DRIVE WELLS.
C-1121-114	MS-714, CASING VAPOR RECOVERY SYSTEM WITH A CONDENSATE KNOCKOUT VESSEL SERVING 184 WELLS UTILIZING; A NORTH PENN ZEIR CVR SYSTEM WITH TWO CONDENSATE KO VESSELS, A CONDENSATE KO DRUM, TWO COMPRESSOR, TWO FIN FAN EXCHANGER AND CONNECTED TO CASING VAPOR RECOVERY SYSTEMS C-1121-39 & C-1121-116
C-1121-116	MS-717, VAPOR RECOVERY PLANT, FOR WELL CASING HEAD HYDROCARBON VAPOR RECOVERY, UTILIZING THE FOLLOWING EQUIPMENT: A CONDENSATE KO DRUM AND CONDENSATE PUMP SERVING 240 WELLS, RECOVERED VAPOR LINE CONNECTED TO RECOVERED VAPOR LINES OF PERMIT UNITS C-1121-39 AND C-1121-114

§64.1 defines a control device as equipment, other than inherent process equipment, that is used to destroy or remove air pollutants prior to discharge to the atmosphere. For TEOR operations equipped with a vapor control system, the District has determined that the vapor control system is "inherent process equipment, i.e. the vapor control system is used to increase the safe and proper functioning of the TEOR operation. Such a vapor control system serves to reduce emissions of H2S (a toxic substance) and to reduce corrosion in the tank(s) vapor space by eliminating the intrusion of ambient air. Inherent process equipment is explicitly excluded from the definition of control device as defined in 40 CFR 64.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit

is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

Conditions 39 and 40 on the proposed permit S-1135-0-3 are existing permit shields granted to the facility.

X. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit.

XI. ATTACHMENTS

A. Draft Renewed Title V Operating Permit
B. Previous Title V Operating Permit
C. Detailed Facility List

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley
Air Pollution Control District

FACILITY: S-1135-0-3 **EXPIRATION DATE:** 05/31/2007

DRAFT

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit

6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating not exempt as allowed by Sections 4.1 and 4.2 of Rule 4601 with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

42. Facilities S-1135 and S-1547 constitute one stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-3-23 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
8.4 MMBTU/HR (DERATED TO 5 MMBTU/HR) NATURAL GAS FIRED HEATER TREATER #1 WITH A MAXON MODEL M-PAKT BURNER WITH VARIABLE FREQUENCY DRIVE (VFD) BLOWER, SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE

PERMIT UNIT REQUIREMENTS

1. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas; or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels; or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2; District Rule 4301, 5.2.1; District Rule 4801, 3.1; and Kern County Rule 407] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 2520, 9.3.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

11. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf. [District NSR Rule] Federally Enforceable Through Title V Permit

12. {584} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. The rated heat input of the unit shall be reduced to no greater than 5.0 MMBtu/hr. [District NSR Rule] Federally Enforceable Through Title V Permit

16. Fuel consumption shall be verified by the use of a non-resettable, totalizing mass or volumetric flow meter. [District NSR Rule] Federally Enforceable Through Title V Permit

17. Emission rates, except during startup and shutdown shall not exceed the following: PM10: 0.0076 lb/MMBtu, SOx (as SO2): 0.00285 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC: 0.0055 lb/MMBtu, and CO: 0.033 lb/MMBtu or 45 ppmv @ 3% O2. [District NSR Rule, District Rule 4301, District Rule 4201, District Rule 4307, and Kern County Rule 404] Federally Enforceable Through Title V Permit

18. Emission rates shall not exceed any of the following: NOx (as NO2): 4.3 lb/day, SOx (as SO2): 0.3 lb/day, PM10: 0.9 lb/day, CO: 4.0 lb/day, VOC: 0.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

19. The permittee shall maintain records of fuel type and quantity for each day of operation, in the format approved by the District. [District NSR Rule] Federally Enforceable Through Title V Permit

20. The duration of start-up and shutdown shall not exceed one hour each per occurrence. [District Rule 4307] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of the duration of each start-up and shutdown that exceed one hour per occurrence for a period of five years and make such records readily available for District inspection upon request. [District Rule 4307] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall monitor, at least once per month, the units's operational characteristics recommended by the manufacturer and approved by the APCO. [District Rule 4307] Federally Enforceable Through Title V Permit

23. The permittee shall tune the unit at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year. The unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. In lieu of tuning the unit twice each calendar year, the owner/operator shall monitor the emissions with a portable NOx analyzer at least twice per calendar year and adjust the unit's operating parameters accordingly to assure compliance with the emission limits of this rule. [District Rule 4307] Federally Enforceable Through Title V Permit

24. If the unit is tuned for compliance, the permittee shall maintain records of: (1) the date that tune-ups are performed, (2) a description of any corrective action taken to maintain the emissions within the acceptable range, and (3) a record of the operational characteristics monitored. [District Rule 4307] Federally Enforceable Through Title V Permit

25. If NOx emissions are monitored for compliance, the permittee shall maintain records of: (1) the date and time of the NOx measurements, (2) the O2 concentration in percent and the measured NOx concentration corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, (5) a description of any corrective action taken to maintain the emissions within the acceptable range, and (6) a record of the operational characteristics monitored. [District Rules 4307] Federally Enforceable Through Title V Permit

26. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4307. Notwithstanding the requirements above and per Section 5.5.4 of Rule 4307, for units with a cyclical firing period that routinely interrupts fuel flow as part of its normal operation, source testing may commence sooner than specified above and continue through its normal cyclical firing period. [District Rule 4307] Federally Enforceable Through Title V Permit

27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4307] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-5-35 **EXPIRATION DATE:** 05/31/2007

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #41 DIS #11867-75 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR (BUENA FE LEASE)

PERMIT UNIT REQUIREMENTS

1. {518} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. {1677} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. {1678} This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District NSR Rule] Federally Enforceable Through Title V Permit

11. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Records of monthly and annual heat input of the unit shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 0.014 lb/MMBtu or SOx (as SO2): 0.001 lb/MMBtu. [District NSR Rule; District Rule 2520, 9.3.2; District Rule 4201, 3.0; District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit

14. Emission rates, except during startup and shutdown and refractory curing, shall not exceed any of the following: NOx (as NO2): 15 ppmv @ 3% O2, VOC: 0.003 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District NSR Rule and District Rules 2520, 9.3.2; 4301, 5.2; 4305, 5.1; 4306, 5.1.1and 4351, 5.1] Federally Enforceable Through Title V Permit

15. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306, 5.3.3.2] Federally Enforceable Through Title V Permit

16. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080, 3.0] Federally Enforceable Through Title V Permit

17. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080, 3.0 and 4306, 6.1.4] Federally Enforceable Through Title V Permit

18. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District NSR Rule and District Rules 4201, 3.0; 4301; 4405, 5.1; 4406, 5.1.1 and 4801, 3.1] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Measurement shall be made with the FGR system in the mode of operation (closed or open) in which it was used in the preceding 30 days. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 2520] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. If either the NOX and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

26. If the unit is equipped with flue gas recirculation (FGR), whenever the unit is switched to operate with the FGR system in the closed position, compliance source testing for NOx and CO shall be conducted within 60 days of cessation of FGR operation date unless source testing with FGR system in the closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

27. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

28. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

29. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

32. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

33. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

35. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-6-33 **EXPIRATION DATE:** 05/31/2007

SECTION: 35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #43 WITH A COEN QLN-ULN LOW NOX BURNER AND FLUE GAS RECIRCULATION (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculate emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculate emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2, 4305, 6.2.1, and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

8. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. {1678} This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.074 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406 and 4801, and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

15. Emission rates during startup, shutdown, and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406 and 4801, and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

16. Emission rates shall not exceed any of the following: PM10: 111.0 lb/day, SOx (as SO2): 7.5 lb/day, VOC: 10.5 lb/day, NOx (as NO2): 54.0 lb/day or 7,884 lb/year, or CO: 49.5 lb/day or 13,140 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

18. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Permittee shall maintain records of duration of each start-up, shutdown, and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306] Federally Enforceable Through Title V Permit

29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

33. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-8-34 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS FIRED NATIONAL STEAM GENERATOR #17, DIS# 9236-68, WITH NORTH AMERICAN BURNER (MAXWELL LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
2. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1, and 4306, 6.2.1] Federally Enforceable Through Title V Permit

11. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed the following: PM10: 0.102 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, NOx (as NO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201 and 4301, 5.2.2 and 5.2.3; Kern County Rule 424; and District Rule 4201] Federally Enforceable Through Title V Permit

16. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201, 4305, and 4306, 5.4.4] Federally Enforceable Through Title V Permit

17. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306, 5.2] Federally Enforceable Through Title V Permit

18. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

19. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

20. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306, 5.4.3] Federally Enforceable Through Title V Permit

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306, 6.1.2] Federally Enforceable Through Title V Permit

22. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306, 6.1.3] Federally Enforceable Through Title V Permit

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

25. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

26. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-9-32 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #18, DIS# 9237-68 (MAXWELL LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
2. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070]
3. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2; 4305, 6.2.1; and 4306, 6.2.1] Federally Enforceable Through Title V Permit

11. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306, 6.2] Federally Enforceable Through Title V Permit

12. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. Emission rates shall not exceed the following: PM10: 0.102 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, NOx (as NO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201 and Rule 4301, 5.2.2 and 5.2.3; Kern County Rule 424; and District Rule 4201] Federally Enforceable Through Title V Permit

17. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201, 4305, and 4306, 5.4.4] Federally Enforceable Through Title V Permit

18. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306, 5.2] Federally Enforceable Through Title V Permit

19. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

20. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

21. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306, 5.4.3] Federally Enforceable Through Title V Permit

22. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306, 6.1.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306, 6.1.3] Federally Enforceable Through Title V Permit

24. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306, 6.1] Federally Enforceable Through Title V Permit

25. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

27. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-10-31 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #19, DIS# 9238 68 (MAXWELL LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
2. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070]
3. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1, and 4306, 6.2.1] Federally Enforceable Through Title V Permit

11. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed the following: PM10: 0.102 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, NOx (as NO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201 and 4301, 5.2.2 and 5.2.3; Kern County Rule 424; and District Rule 4201] Federally Enforceable Through Title V Permit

16. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement.. [District Rules 2201, 4305, and 4306, 5.4.4] Federally Enforceable Through Title V Permit

17. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306, 5.2] Federally Enforceable Through Title V Permit

18. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

19. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

20. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306, 5.4.3] Federally Enforceable Through Title V Permit

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306, 6.1.2] Federally Enforceable Through Title V Permit

22. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306, 6.1.3] Federally Enforceable Through Title V Permit

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

25. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

26. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-12-38 **EXPIRATION DATE:** 05/31/2007

SECTION: 35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #45 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR AND OPTIONAL SO2 SCRUBBER (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

15. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

16. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Emission rates shall not exceed any of the following: PM10: 0.080 lb/MMBtu or SOx (as SO2): 0.080 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301] Federally Enforceable Through Title V Permit

18. Emission rates, except during startup and shutdown and refractory curing, shall not exceed any of the following: NOx (as NO2): 15 ppmv @ 3% O2, VOC: 0.007 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4301, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit

19. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 2201, 4201, 4301, 4405, 4406 and 4801] Federally Enforceable Through Title V Permit

20. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

21. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Measurement shall be made with the FGR system in the mode of operation (closed or open) in which it was used in the preceding 30 days. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 2520] Federally Enforceable Through Title V Permit

24. If periodic monitoring of NOX, CO, and O2 concentrations is utilized and the NOX and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

29. If the unit is equipped with flue gas recirculation (FGR), whenever the unit is switched to operate with the FGR system in the closed position, compliance source testing for NOx and CO shall be conducted within 60 days of cessation of FGR operation date unless source testing with FGR system in the closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

30. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

31. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

32. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

34. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

35. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

36. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

37. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

38. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-13-33 **EXPIRATION DATE:** 05/31/2007

SECTION: 26 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #44 WITH COEN QLN-ULN 3.2 BURNER (WILBERT LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit when it is dormant. [District Rule 4306] Federally Enforceable Through Title V Permit
2. Operator shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

11. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Scrubber liquor pH shall be maintained between 6.15 and 7.5 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

18. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District Rule 2201] Federally Enforceable Through Title V Permit

19. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

20. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rule 2201] Federally Enforceable Through Title V Permit

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

22. Emission rates shall not exceed either of the following: PM10: 0.080 lb/MMBtu or SOx (as SO2): 0.361 lb/MMBtu. [District Rules 2201, 2520, 4201, and 4301] Federally Enforceable Through Title V Permit

23. Emission rates, except during startup and shutdown and refractory curing, shall not exceed the following: NOx (as NO2): 15 ppmv @ 3% O2, VOC: 0.007 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4301, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit

24. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

27. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 2201, 4201, 4301, 4405, 4406 and 4801] Federally Enforceable Through Title V Permit

28. Permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Measurement shall be made with the FGR system in the mode of operation (closed or open) in which it was used in the preceding 30 days. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 2520] Federally Enforceable Through Title V Permit

29. If the NOx and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. Permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

32. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

34. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

36. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

37. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

38. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306, 6.2] Federally Enforceable Through Title V Permit

39. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

40. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

41. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

42. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

43. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-17-18 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION, SERVING 175 STEAM ENHANCED WELLS, INCLUDING PIPING TO INCINERATING STEAM GENERATORS, FOR REINJECTION OF NONCONDENSIBLE VAPORS, OR FOR BALANCING OF WELL VENTS.

PERMIT UNIT REQUIREMENTS

1. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. TEOR gases shall be re-injected to the formation, incinerated in steam generators #'s S-1135-26, -27,-28,-266 and S-1547-1089, contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
3. {1296} All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. {1309} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. Operation shall include gas/liquid separators, condensate knockouts, and compressor knockouts. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operation shall include, water-cooled heat exchanger, air-cooled heat exchangers, and gas compressors. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Operation shall include 3 pressure type condensate storage tanks (rated @ 50 psig 650 deg F), 3 - 25 bbl open top emergency drain tanks, and non condensible piping to approved incineration devices. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operation shall include vapor compressor bypass piping, and casing vapor collection piping to 175 wells. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. TEOR gas injection system shall include piping, reinjection knockout vessels, interstage coolers and gas/liquid separators, reinjection gas compressors, and liquid transfer pumps. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Operation shall include H2S chemical contractors/ scrubbing pressure vessels. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Casing vent vapor collection piping (includes M1, M2, and M3) shall be interconnected such that flow can be directed to all parts of system. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Water/VOCs condensate from all liquid knockout drums shall be pumped to production manifold. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Injection of collected vapors shall not commence until permittee has received valid Department of Oil & Gas (DOG) approval for injection of gases. [District Rule 2080] Federally Enforceable Through Title V Permit
16. TEOR gas injected into formation shall only be performed using DOGGR approved injection wells. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Permittee shall cease injecting vapors & notify the District immediately if DOG injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Gas compressor motors shall total at least 70 hp. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Block valve upstream of free condensate knockout shall activate and shut in casing vapor at 40 psig system pressure. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Non-condensibles shall be introduced only into gas section of dual fuel burners of steam generators for incineration. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Vapors extracted from Metson tank battery, tanks S-1135-70 shall be piped to casing vent collecting system. [District Rule 2201] Federally Enforceable Through Title V Permit
22. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
23. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
24. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
25. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit
26. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit
27. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

29. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

30. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

31. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

32. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

33. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

34. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

35. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

36. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

37. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

38. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

39. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

40. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

41. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

42. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

43. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

44. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

45. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

46. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

47. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

48. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

49. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

50. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

51. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

52. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401 I, 6.2.1] Federally Enforceable Through Title V Permit

53. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

54. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

55. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

56. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

57. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

58. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

59. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor; 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

60. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

61. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

62. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-18-17 **EXPIRATION DATE:** 05/31/2007

SECTION: 26 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 140 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (WILBERT LEASE)

PERMIT UNIT REQUIREMENTS

1. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. {1296} All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
3. {1309} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. TEOR gas VOC content shall not exceed 4.1% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Fugitive volatile organic compound (VOC) emissions from this steam-enhanced crude oil production operation shall not exceed 4.3 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts of components in gas service and resulting emissions calculated using the emission factors in the "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c, dated 2/99. (CAPCOA document). [District Rule 2201] Federally Enforceable Through Title V Permit
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

11. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

12. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

13. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

14. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

15. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

16. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

17. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

18. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

19. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

20. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

21. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

23. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

24. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

25. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

26. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

27. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

28. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

29. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

30. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

31. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

32. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

34. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

35. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

36. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

37. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

38. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

39. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

41. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

42. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

43. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

45. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

46. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

47. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

49. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-20-26 **EXPIRATION DATE:** 05/31/2007

SECTION: NE35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
STEAM ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING 295 STEAM ENHANCED WELLS (KENDON LEASE), INCLUDING A FIN FAN COOLER, GAS/LIQUID SEPARATORS, AND ASSOCIATED PIPING

PERMIT UNIT REQUIREMENTS

1. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. {1296} All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
3. {1297} The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
4. {1309} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. Operation shall include water-cooled heat exchangers, air-cooled heat exchangers, and gas compressors. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operation shall include pressure type condensate storage tanks, pressure type oil/water separators, vapor piping to vapor control system listed on S-1547-460 and uncondensed vapor piping to incineration in steam generators S-1135-12 and S-1135-24 or vapor disposal well(s) or to steam generators S-1547-234, S-1547-238 and S-1547-248. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Maximum VOC content of vapor in the vapor control system piping shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operation shall include H2S chemical contactor/scrubber vessels. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Condensate storage tanks and oil-water separator shall vent to vapor control system or be equipped with equivalent vapor control provisions approved by District. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Water/VOC condensate from all liquid knockout drums shall be pumped to production manifold. [District Rule 2201] Federally Enforceable Through Title V Permit
13. An I &M program consistent with Rule 4403 section 5.1 requirements shall be implemented for all new well stuffing boxes. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Permittee shall maintain with the permit an accurate listing of all steam enhanced wells connected to the casing vent control system. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Permittee shall make listing of all steam enhanced wells connected to the casing vent control system available upon District request. [District Rules 1070 and 2520, 9.4] Federally Enforceable Through Title V Permit
16. Injection of collected vapors shall only be conducted under a valid Department of Oil & Gas (DOG) approval for injection of gases. [District Rule 2080] Federally Enforceable Through Title V Permit
17. VOC emission rate shall not exceed 114.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
18. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
19. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
20. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
21. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit
22. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit
23. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit
24. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
25. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

27. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

28. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

29. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

30. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

31. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

32. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

33. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

34. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

35. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

36. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

37. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

38. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

39. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

40. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

41. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

42. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

43. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

44. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

45. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

46. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

47. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

48. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

49. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

51. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

52. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

53. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

54. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

55. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

56. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

57. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

58. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-21-12 **EXPIRATION DATE:** 05/31/2007

SECTION: 22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION OPERATION SERVING UP TO 153 STEAM-ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (BUENA FE FEE LEASE)

PERMIT UNIT REQUIREMENTS

1. Maximum VOC content of TEOR vapors shall not exceed 32.3% by weight of Total Organic Compounds (TOC). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed five (5). [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive volatile organic compound (VOC) emissions from this steam-enhanced crude oil production operation shall not exceed 14.6 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall maintain with the permit accurate fugitive component counts of components in gas service and resulting emissions calculated using the emission factors in the "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c, dated 2/99. (CAPCOA document). [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit a current listing of all steam-enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
6. {2441} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
7. {2443} All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
8. {2457} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed in compliance with District Rule 4401 (Amended December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
10. {2459} The requirements of District Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit because it is not an in situ combustion well vent. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

12. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

13. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

14. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

15. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

16. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

17. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

18. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

19. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

20. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

21. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

22. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

23. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

25. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

26. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

27. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

28. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

29. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

30. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

31. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

32. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

33. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

34. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

36. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

37. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

38. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

39. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

40. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

41. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

42. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

43. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

44. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

45. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

46. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

47. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

48. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

49. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

50. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

51. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-22-11 **EXPIRATION DATE:** 05/31/2007

SECTION: 26 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 90 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (MOCAL LEASE)

PERMIT UNIT REQUIREMENTS

1. {1296} All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
3. {1309} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. Fugitive volatile organic compound (VOC) emissions from this steam-enhanced crude oil production operation shall not exceed 61.3 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts of components in gas service and resulting emissions calculated using the emission factors in the "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c, dated 2/99. (CAPCOA document). [District Rule 2201] Federally Enforceable Through Title V Permit
8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
9. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

11. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

12. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

13. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

14. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

15. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

16. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

17. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

18. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

19. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

20. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

21. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

23. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

24. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

25. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

26. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

27. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

28. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

29. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

30. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

31. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

32. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

33. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

35. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

36. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

37. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

38. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

39. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

40. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

41. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

42. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

43. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

45. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

46. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

47. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

48. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-24-31 **EXPIRATION DATE:** 05/31/2007

SECTION: 35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
DORMANT 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #25, DIS# 26916 66, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND SO2 SCRUBBER (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification except for physically disconnecting the fuel supply line from this unit. [District Rules 2010 and 4306] Federally Enforceable Through Title V Permit
2. Operators shall notify the District at least seven calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove Dormant Emission Unit references. [District Rule 4306] Federally Enforceable Through Title V Permit
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. Upon recommencing operation, when complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Upon recommencing operation, when complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Upon recommencing operation, if the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Upon recommencing operation, if fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; 4306, and 4351, 6.2.1] Federally Enforceable Through Title V Permit

9. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

10. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, 4305, 6.2, and 4306] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. {534} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. {1677} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. {1678} This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District NSR Rule] Federally Enforceable Through Title V Permit

17. Upon recommencing operation, scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

18. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit

20. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

22. Emission rates shall not exceed any of the following: PM10: 0.075 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.033 lb/MMBtu or 44 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

23. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. If the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

29. Source testing to measure NOx and CO emissions shall be conducted within 60 days of recommencing operation of this unit. [District Rule 4306] Federally Enforceable Through Title V Permit

30. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

31. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by CARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
33. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit
34. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
35. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
36. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-26-40 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #32, DIS# 12051 71, WITH A COEN ULN 3.2 LOW-NOX BURNER AND OPTIONAL SO2 SCRUBBER - METSON LEASE

PERMIT UNIT REQUIREMENTS

1. {518} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2201, 2520 Section 9.3.2, and 4320] Federally Enforceable Through Title V Permit
4. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
6. {530} Sulfur emissions shall not exceed 0.11 lb of sulfur per million BTU of heat input, averaged over 3 - one hour periods. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas; multiplying the reported sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by a combination of source testing for sulfur compounds and fuel analysis. Compliance may be demonstrated for this unit individually, or by showing that the total emissions of sulfur compounds from all steam generators located at the stationary source with ATC or PTO issued prior to September 12, 1979 does not exceed the emissions that would result if each unit was operating in compliance with the specified limit. [Kern County Rule 424 and District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. {1677} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. The minimum scrubber recirculation liquid to gas ratio (recirculation rate) required to maintain compliance with the SO2 limit shall be 790 gpm/1000 acf. Compliance with the minimum recirculation rate requirement shall be determined by averaging the recirculation rate readings (calculated from hourly averages) during operation during the calendar day. [District Rule 2201] Federally Enforceable Through Title V Permit

9. When steam generator exhaust is routed through scrubber, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

10. When scrubber is bypassed, fuel gas sulfur content shall not exceed 5 grains of total sulfur per 100 dscf of fuel gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

11. When steam generator exhaust is routed through the scrubber, permittee shall monitor and record scrubber liquor recirculation rate and pH at least once per month. [District Rule 4320] Federally Enforceable Through Title V Permit

12. Source testing to demonstrate compliance with SOx emission limits (SOx emission concentration or control efficiency) in this permit shall be conducted annually. Source testing may be deferred if scrubber is bypassed as authorized by this permit. Whenever the unit is switched to scrubbed operation, compliance source testing for SOX shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. Source testing of scrubber exhaust during operation of any one of the steam generators S-1135-26 or S-1547-1089 shall satisfy the testing requirement for this unit. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

13. Source testing to demonstrate compliance with the PM10 emission limit (lb/MMBtu) included in this permit shall be conducted concurrently with the initial compliance test for SOx and every three years thereafter. Source testing of scrubber exhaust during operation of any one of the steam generators S-1135-26 or S-1547-1089 when firing the maximum available quantity of waste gas shall satisfy the PM10 testing requirement for this unit. [District Rule 2201]

14. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

15. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

16. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Emission rates, except during startup and shutdown and refractory curing, shall not exceed any of the following: PM10: 0.0266 lb/MMBtu, SOx (as SO2): 9 ppmv @ 3% O2, VOC: 0.007 lb/MMBtu, NOx (as NO2):15 ppmv @ 3% O2, or CO: 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4320, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

18. Emissions rates shall not exceed any of the following: PM10: 39.9 lb/day, SOx (as SO2): 23.3 lb/day, VOC: 10.5 lb/day, NOx (as NO2): 27.0 lb/day or 7884 lb/yr, or CO: 57.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

19. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 2201, 4201, 4301, 4405, 4406 and 4801] Federally Enforceable Through Title V Permit

20. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306 and 4320] Federally Enforceable Through Title V Permit

21. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080, 4306, and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, 4320, and 2520] Federally Enforceable Through Title V Permit

24. If the NOx and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

25. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

26. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

27. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. For the purposes of permittee-performed alternate monitoring, emissions measurements may be performed at any time after the unit reaches conditions representative of normal operation but no longer than 2 hrs after re-ignition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

28. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

32. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 6.1, 4306, 6.1,and 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-27-33 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #27, DIS# 12069-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. {518} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

11. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

12. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. {534} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. {1677} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. {1678} This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Upon recommencing operation, scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

20. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

21. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201 and 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

23. Upon recommencing operation, records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

24. Emission rates shall not exceed any of the following: PM10: 0.091 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.033 lb/MMBtu or 44 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

25. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306]

26. {2936} If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306]

27. {2937} All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306]

28. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306]

29. Upon recommencing operation, during the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

34. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

35. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

37. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

40. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-28-33 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #26, DIS# 12071-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. {518} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

11. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

12. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. {534} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. {1677} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. {1678} This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Upon recommencing operation, scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

20. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

21. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

23. Upon recommencing operation, records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

24. Emission rates shall not exceed any of the following: PM10: 0.091 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.033 lb/MMBtu or 44 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

25. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

29. Upon recommencing operation, during the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

34. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

35. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

37. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

39. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

40. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-29-29 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
NATURAL GAS-FIRED HEATER TREATER (#2) WITH A 4.2 MMBTU/HR MAXON MODEL M-PAKT BURNER SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. {520} The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit
3. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

14. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

15. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Emission rates, except during startup and shutdown shall not exceed any of the following: PM10: 0.136 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.037 lb/MMBtu or 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4307, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

17. Emission rates during startup and shutdown shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

18. {521} Particulate matter emissions shall not exceed 0.1 grain/dscf, calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit

19. Emission rates shall not exceed any of the following: PM10: 13.7 lb/day, SOx (as SO2): 0.5 lb/day, VOC: 0.7 lb/day, NOx (as NO2): 80.2 lb/day or 1080 lb/yr, or CO: 3.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Duration of start-up and shutdown shall not exceed one hour each per occurrence. [District Rule 4307] Federally Enforceable Through Title V Permit

21. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Permittee shall maintain records of duration of each start-up and shutdown that exceed one hour per occurrence, and refractory curing, for a period of five years and make such records readily available for District inspection upon request. [District Rule 4307] Federally Enforceable Through Title V Permit

23. The permittee shall monitor, at least once per month, the units's operational characteristics recommended by the manufacturer and approved by the APCO. [District Rule 4307] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. The permittee shall tune the unit at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year. The unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. In lieu of tuning the unit twice each calendar year, the owner/operator shall monitor the emissions with a portable NOx analyzer at least twice per calendar year and adjust the unit's operating parameters accordingly to assure compliance with the emission limits of this rule. [District Rule 4307] Federally Enforceable Through Title V Permit

25. If the unit is tuned for compliance, the permittee shall maintain records of: (1) the date that tune-ups are performed, (2) a description of any corrective action taken to maintain the emissions within the acceptable range, and (3) a record of the operational characteristics monitored. [District Rule 4307] Federally Enforceable Through Title V Permit

26. If NOx emissions are monitored for compliance, the permittee shall maintain records of: (1) the date and time of the NOx measurements, (2) the O2 concentration in percent and the measured NOx concentration corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, (5) a description of any corrective action taken to maintain the emissions within the acceptable range, and (6) a record of the operational characteristics monitored. [District Rule 4307] Federally Enforceable Through Title V Permit

27. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4307. Notwithstanding the requirements above and per Section 5.5.4 of Rule 4307, for units with a cyclical firing period that routinely interrupts fuel flow as part of its normal operation, source testing may commence sooner than specified above and continue through its normal cyclical firing period. [District Rule 4307] Federally Enforceable Through Title V Permit

28. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4307] Federally Enforceable Through Title V Permit

29. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

30. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081 and 4307] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 4307] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-30-18 **EXPIRATION DATE:** 05/31/2007

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
DORMANT 30 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #MO-2, DIS# 19961-68, WITH NORTH AMERICAN 5131-FACR BURNER - MOCAL LEASE

PERMIT UNIT REQUIREMENTS

1. No modification(s) to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. {593} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992), and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. {563} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera) 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. {565} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc (except 60.44c(g) and (h) and 60.48c). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. {1694} This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed the following: PM10: 0.005 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, NOx (as NO2): 0.133 lb/MMBtu, VOC: 0.003 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 4301, 5.2.2 and 5.2.3, and 4201] Federally Enforceable Through Title V Permit

14. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

15. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

16. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

17. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

18. The permittee shall monitor, at least on a monthly basis, the amount of water use, the amount of unit blow down, and the exhaust stack temperature or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

21. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-70-17 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
43,470 GALLON FIXED ROOF REJECT TANK T-110, WITH SHARED VAPOR RECOVERY SYSTEM - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Operation shall include two fin fan heat exchangers, two separators, two compressors, and two liquid transfer pumps, shared between tanks S-1135-70, '-71, '-72, '-322, ' -326, and '-327, and heater treaters S-1135-3 and '-29. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emissions rate calculated using EPA's Protocol for Equipment Leak Emission Estimates, Table 2-4, Oil and Gas Production Operations Average Emission Factors, shall not exceed 0.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All tanks and separators shall vent only to vapor control system. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 99% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rules 2201 and 4623, 5.6.1] Federally Enforceable Through Title V Permit
9. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
10. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

12. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

18. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. {2426} The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. The operator shall ensure that the vapor recovery system is functional and is operating as designed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-71-9 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF LACT TANK T-100 WITH VAPOR RECOVERY (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Operation shall include vapor recovery system described on the requirements for permit unit S-1135-70. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tanks and separators shall vent only to vapor control system. [District NSR Rule] Federally Enforceable Through Title V Permit
5. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. {2426} The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

18. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-72-9 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
210,000 GALLON FIXED ROOF STANDBY TANK T-120, WITH VAPOR RECOVERY SYSTEM (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Operation shall include vapor recovery system described on the requirements for permit unit S-1135-70. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
5. All tanks and separators shall vent only to vapor control system. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
7. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Permittee shall keep accurate records of throughput and storage temperature of liquids stored in each tank and such records shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

19. {2426} The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

20. The operator shall ensure that the vapor recovery system is functional and is operating as designed whenever organic liquids or organic liquid vapors are contained in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-82-11 **EXPIRATION DATE:** 05/31/2007

SECTION: 22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF STANDBY TANK #2179 (BUENA FE FEE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be equipped with a pressure relief device set to within 10% of the maximum allowable working pressure of the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This standby storage tank shall be equipped with an operational temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The temperature of any introduced or stored organic liquid shall not exceed 200 degrees F. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Organic liquids may not be introduced into the tank for more than 3 consecutive days and no more than 19 times in any consecutive 12-month period. No organic liquid may be removed from tank, except that which overflows to tank S-1135-83, until organic liquid ceases to be introduced into either tank. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The true vapor pressure of any introduced or stored organic liquid shall not exceed 0.19 psi. [District Rule 2201] Federally Enforceable Through Title V Permit
6. True vapor pressure of organic liquid introduced to tank shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatography" as approved by ARB, EPA, and the District. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall determine the true vapor pressure of the organic liquid stored in the tank at least once per year in accordance with methods described in section 6.2 of District Rule 4623 (amended 12/20/01). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall keep accurate records of the dates organic liquid is introduced into the tank and the dates organic liquids are stopped being introduced into the tank, the daily volume of organic liquids introduced into the tank, the true vapor pressure of the organic liquid introduced in the tank at least once per year and whenever there is a change in the source or type of petroleum introduced in the tank, and the number of times organic liquid has been introduced into the tank in the preceding 12 month period. All records shall be retained on site for at least 5 years and be made readily available for District inspection on request. [District Rule 1070]

11. The operator shall keep accurate records of types, storage temperature, and TVP of liquids stored to verify continued exemption from District Rule 4623 (as amended December 20, 2001). [District Rule 2520, 9.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-83-9 **EXPIRATION DATE:** 05/31/2007

SECTION: 22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF STANDBY TANK #2180 (BUENA FE FEE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be equipped with a pressure relief device set to within 10% of the maximum allowable working pressure of the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This standby storage tank shall be equipped with an operational temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The temperature of any introduced or stored organic liquid shall not exceed 200 degrees F. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Organic liquids may not be introduced into the tank for more than 3 consecutive days and no more than 19 times in any consecutive 12-month period. No organic liquid may be removed from tank, except that which overflows to tank S-1135-82, until organic liquid ceases to be introduced into either tank. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The true vapor pressure of any introduced or stored organic liquid shall not exceed 0.19 psi. [District Rule 2201] Federally Enforceable Through Title V Permit
6. True vapor pressure of organic liquid introduced to tank shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatography" as approved by ARB, EPA, and the District. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall determine the true vapor pressure of the organic liquid stored in the tank at least once per year in accordance with methods described in section 6.2 of District Rule 4623 (amended 12/20/01). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall keep accurate records of the dates organic liquid is introduced into the tank and the dates organic liquids are stopped being introduced into the tank, the daily volume of organic liquids introduced into the tank, the true vapor pressure of the organic liquid introduced in the tank at least once per year and whenever there is a change in the source or type of petroleum introduced in the tank, and the number of times organic liquid has been introduced into the tank in the preceding 12 month period. All records shall be retained on site for at least 5 years and be made readily available for District inspection on request. [District Rule 1070]

11. The operator shall keep accurate records of types, storage temperature, and TVP of liquids stored to verify continued exemption from District Rule 4623 (as amended December 20, 2001). [District Rule 2520, 9.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-115-23 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #1 (NEELY LEASE)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
4. This equipment shall not be operated for any reason until an Authority to Construct permit is implemented with all necessary retrofits required to comply with the applicable requirements of District Rule 4320 and all other applicable District regulations. [District Rule 4320] Federally Enforceable Through Title V Permit
5. {518} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. {534} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. {1677} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

16. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

17. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

18. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

19. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

21. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. Emission rates shall not exceed any of the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

24. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

25. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

26. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

27. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

28. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

29. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

30. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-119-25 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #5 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
3. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

14. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

15. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

16. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

17. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

18. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. No less than 9975 ft of presently unpaved dirt roadway shall be surfaced with SC hot mix asphalt paving. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Emission rates shall not exceed the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

21. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

23. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

24. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

25. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

26. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

27. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-122-26 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #6 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
3. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

14. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

15. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

16. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

17. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

18. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. Emission rates shall not exceed the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

20. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit
23. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit
24. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit
26. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-123-24 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #7 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
3. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; ~~4305~~, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

14. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

15. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

16. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

17. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

18. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. Emission rates shall not exceed the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

20. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

23. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

24. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

25. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

26. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-124-16 **EXPIRATION DATE:** 05/31/2007

SECTION: NW15 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 254 STEAM ENHANCED WELLS, AND TIED TO TEOR '293 INCLUDING PIPING TO BALANCED CGCS, RE-INJECTION COMPRESSORS OR INCINERATING STEAM GENERATORS (EXETER LEASE)

PERMIT UNIT REQUIREMENTS

1. Well vent vapor control system VOC fugitive emission rate shall not exceed 50.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit accurate fugitive component counts for well vent vapor control system and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production, Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
3. {1309} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. Operation shall include noncondensible vapor piping from vapor control skids to balanced system and re-injection compressors. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operation shall include vapor control skids including: various size knockout vessels with liquid pumps, gas scrubbers, heat exchangers, vapor compressors, and piping to District approved disposal devices. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Piping to re-injection system shall include re-injection knock out vessels, interstage coolers & gas/liquid separators, injection gas compressors and liquid transfer pumps, as needed. [District Rule 2201] Federally Enforceable Through Title V Permit
9. TEOR gas injected into formation shall only be performed using DOG approved injection wells. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Permittee shall cease injecting vapors and notify the District immediately if DOG injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. A listing of all steam enhanced wells connected to this system shall be maintained onsite and readily available to the District upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Vapor collection piping TEORs S-1135-124 and '-293 shall be contained in a balanced CGCS or collected at VR skid(s) and piped to approved injection wells. [District Rule 2201] Federally Enforceable Through Title V Permit
13. TEOR gas not re-injected to the formation shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Records shall be kept of injection well(s) utilized and volume of vapors injected. Records shall be made readily available to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
15. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
16. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
17. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
18. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit
19. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit
20. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit
21. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
22. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit
23. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
24. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

26. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

27. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

28. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

29. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

30. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

31. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

32. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

33. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

34. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

35. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

37. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

38. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

39. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

40. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

41. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

42. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

44. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

45. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

46. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

47. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

49. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

50. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

51. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

52. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

53. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

54. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

55. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-125-15 **EXPIRATION DATE:** 05/31/2007

SECTION: SW14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 144 STEAM ENHANCED CRUDE OIL PRODUCTION WELL VENTS, TIED TO TEOR '293 AND TVR '173 (W&S FEE LEASE)

PERMIT UNIT REQUIREMENTS

1. Well vent vapor control system VOC fugitive emission rate shall not exceed 38.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit accurate fugitive component counts for well vent vapor control system and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production, Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
3. {1309} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. {1296} All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Operation shall include three vapor control skids with casing vent collection piping serving 144 steam drive wells. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operation shall include noncondensible vapor piping from vapor control skids and W&S tank battery vapor collection system to balanced system and re-injection compressors. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operation shall include vapor control equipment which consists of miscellaneous knockout vessels & liquid removal pumps, gas coolers, heat exchangers, vapor compressors, condensate collection tanks & piping to approved injection well(s). [District Rule 2201] Federally Enforceable Through Title V Permit
9. TEOR gas injected into formation shall only be performed using DOGGR approved injection wells. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Permittee shall cease injecting vapors and notify the District immediately if DOGGR injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Piping to injection system shall include re-injection knockout vessels, interstage coolers & gas/liquid separators, injection gas compressors and liquid transfer pumps, as needed. [District Rule 2201] Federally Enforceable Through Title V Permit

12. A listing of all steam enhanced wells connected to this system shall be maintained onsite and readily available to the District upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Collected TEOR vapors shall be contained in a balanced CGCS or collected at VR skid(s) and piped to approved injection well(s). [District Rule 2201] Federally Enforceable Through Title V Permit

14. TEOR vapors not re-injected to the formation shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Collected liquids shall be handled, stored, and disposed of in a manner preventing air contaminant emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Records shall be kept of injection well(s) utilized and volume of vapors injected, for a period of five years. Records shall be made readily available to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

17. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

18. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

19. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

20. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

21. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

22. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

23. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

24. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

26. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

27. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

28. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

29. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

30. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

31. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

32. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

33. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

34. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

35. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

36. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

38. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

39. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

40. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

41. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

42. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

43. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

44. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

45. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

46. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

47. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

48. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

50. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

51. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

52. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

53. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

54. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

55. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

56. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

57. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-127-18 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION INCLUDING ONE TRANSPORTABLE FIN FAN COOLER AND ASSOCIATED PIPING SERVING 383 STEAM ENHANCED WELL VENTS (MAXWELL LEASE) CONNECTED TO TANK VAPOR CONTROL SYSTEM S-1135-118, COLLECTED VAPORS PIPED FROM VAPOR CONTROL COMPRESSOR SKIDS EITHER TO INJECTION COMPRESSORS FOR RE-INJECTION TO DOGGR WELLS, TO STEAM GENERATORS S-1135-9 AND '-10 FOR INCINERATION, OR CONTAINED WITHIN THE BALANCED CASING GAS COLLECTION SYSTEM (CGCS)

PERMIT UNIT REQUIREMENTS

1. Fin fan cooler may be transported to and installed at any vapor skid within the casing vent vapor collection system. [District Rule NSR] Federally Enforceable Through Title V Permit
2. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
3. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
4. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and Kern County Rule, 108.1] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: Kern County Rule, 108.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. Operation shall include noncondensible vapor piping from vapor recovery skids to balanced system, re-injection compressors, and scrubbed steam generators S-1135-9 and '10. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Operation shall include vapor control equipment which consists of miscellaneous knockout vessels & liquid removal pumps, condensate tanks, heat exchangers, gas coolers, vapor compressors, and piping to disposal devices. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Piping to re-injection system shall include re-injection knock out vessels, interstage coolers & gas/liquid separators, injection gas compressors and liquid transfer pumps, as needed. [District NSR Rule] Federally Enforceable Through Title V Permit

11. TEOR gas injected into formation shall only be performed using DOGGR approved disposal wells. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Permittee shall cease injecting vapors and notify the District immediately if DOGGR disposal approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit

13. A listing of all steam enhanced wells connected to this system shall be submitted to the District at least 60 days prior to the permit anniversary date. [District NSR Rule] Federally Enforceable Through Title V Permit

14. Vapor collection piping TEOR, also serving tank TVR system '118, shall be contained in a balanced CGCS or collected at VR skid(s) and piped to approved incinerating steam generators or DOGGR approved disposal wells. [District NSR Rule] Federally Enforceable Through Title V Permit

15. TEOR vapors not re-injected to the formation shall be contained within a balanced casing vent collection system, or well casing vents shall be closed and produced fluids shall be handled only in controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit

16. All wells producing from strata steamed by this unit shall be connected to a District-approved emissions control system or have District-approved closed casing vents. [District NSR Rule] Federally Enforceable Through Title V Permit

17. All produced fluids from any well served by vapor collection system which has had casing gas flow restricted or casing vent closed shall be handled only in closed and vapor controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit

18. Permittee shall maintain accurate component count for TEOR operation according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. Permittee shall update such records when new components are installed. [District NSR Rule]

19. Fugitive emissions from all components (except those operating under negative pressure at all times) in gas service including polish rods associated with this TEOR operation shall not exceed 140.1 lb VOC/ day. [District NSR Rule]

20. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

21. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

22. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

23. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

25. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

26. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

27. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

28. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

29. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

30. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

31. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

32. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

33. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

34. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

35. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

36. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

38. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

39. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

40. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

41. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

42. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

43. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

44. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

45. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

46. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

47. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

48. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

49. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

51. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

52. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

53. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

54. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

55. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

56. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

57. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

58. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

59. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

60. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

61. Records shall be kept of DOGGR injection well(s) utilized and volume of vapors injected. Records shall be made readily available to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-128-23 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 265 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, PIPING TO DISPOSAL WELLS, TIED TO TEOR S-1135-129, AND TVR S-1135-149 AND S-1135-281 (NEELY LEASE)

PERMIT UNIT REQUIREMENTS

1. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. TEOR gas injected into formation shall only be performed using Department of Oil, Gas & Geothermal (DOGGR) approved disposal wells. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Permittee shall cease injecting vapors and notify the District immediately if DOGGR disposal approval is revoked, denied, terminated, surrendered or altered to disallow disposal. This condition does not grant the permittee relief from any permit condition or other requirement of the Clean Air Act. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit a listing (updated annually within 60 days of permit anniversary) of all steam enhanced wells connected to the casing vent control system. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Permittee shall maintain with the permit an accurate fugitive component count and resulting emissions calculated using EPA Publication 453/R-95-017 November 1995. Permit count and resulting emissions shall be updated annually within 60 days of permit anniversary. [District NSR Rule] Federally Enforceable Through Title V Permit
10. An I &M program consistent with Rule 4403 light oil production Section 5.1 requirements shall be implemented for all new well stuffing boxes. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. TEOR vapors shall be injected to the formation (via DOGGR approved disposal wells) or shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Collected liquids shall be handled, stored, and disposed of in a manner preventing air contaminant emissions. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Well vent vapor control system VOC fugitive emission rate shall not exceed 133.9 lb/day and fugitive VOC emissions from new polish rods shall not exceed 2.3 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
14. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
15. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
16. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
17. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit
18. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit
19. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit
20. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
21. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit
22. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
23. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit
24. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

26. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

27. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

28. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

29. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

30. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

31. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

32. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

33. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

34. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

35. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

37. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

38. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

39. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

40. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

41. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

42. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

43. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

44. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

45. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

46. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

47. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

49. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

50. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

51. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

52. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

53. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

54. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-129-27 **EXPIRATION DATE:** 05/31/2007

SECTION: NW21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION AUTHORIZED FOR 425 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, VAPOR PIPING TO INJECTION WELLS (ANDERSON-GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
3. Volatile organic compound (VOC) emissions from the entire system (including fugitive emissions from components handling vapor and condensate) shall not exceed 143.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with the Kern County Rule 108.1. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. TEOR gas injected into formation shall only be performed using Department of Oil, Gas & Geothermal (DOGGR) approved injection wells. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Permit holder shall cease injecting vapors and notify the District immediately if DOGGR injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. This condition does not grant the permittee relief from any permit condition or other requirement of the Clean Air Act. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Permit holder shall maintain with the permit a listing (updated annually within 60 days of permit anniversary) of all steam enhanced wells connected to the casing vent control system. [District Rule 1070] Federally Enforceable Through Title V Permit
10. TEOR vapors shall be injected to the formation or shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Collected liquids shall be handled, stored, and disposed of in a manner preventing air contaminant emissions. [District NSR Rule] Federally Enforceable Through Title V Permit

12. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

13. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

14. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

15. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

16. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

17. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

18. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

19. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

20. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

21. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

22. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

23. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

25. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

26. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

27. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

28. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

29. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

30. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

31. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

32. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

33. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

34. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

36. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

37. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

38. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

39. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

40. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

41. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

42. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

43. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

44. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

45. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

46. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

47. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

48. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

49. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

50. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

51. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

52. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

53. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-149-19 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON CRUDE OIL LACT TANK ID# AG-01, WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-150, '151, '152, '155, '270, '301 AND '323 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Vapor control system shall contain vapor control system piping network and vapor compression system consisting of vapor compressor(s), air-cooled heat exchanger, inlet scrubber, pump, and discharge scrubber. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
6. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
7. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Compressor suction and knockout drum liquids shall be piped only to vapor-controlled tanks. [District NSR Rule] Federally Enforceable Through Title V Permit
9. The operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. Operator shall monitor vapor control system pressures on quarterly basis to ensure that system pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 10.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

15. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

16. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

18. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

19. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor recovery system and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit

20. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

21. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

23. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

24. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

25. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

26. The pressure transmitters shall be inspected and maintained in good operating conditions. The inspections shall be conducted on a quarterly basis. Replacing and repairing of each pressure transmitters shall not exceed one hour per day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

37. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-150-14 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON CRUDE OIL LACT TANK ID# AG-02, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 2.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-151-14 **EXPIRATION DATE:** 05/31/2007

DRAFT

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
210,000 GALLON REJECT TANK ID# AG-03, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 1.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-152-14 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
210,000 GALLON REJECT TANK ID# AG-04, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 1.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-155-16 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
281,400 GALLON (6,700 BBL) FIXED ROOF WASH TANK ID# AG-07, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 2.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-173-22 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,600 BBL (67,200 GALLON) FIXED ROOF LACT TANK ID# WS-01, HANDLING MAXWELL LEASE PRODUCTION, AND VESSELS V-101, V-102, V-103, AND V-104; WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-174, -175, -178, -325, AND -337 (W&S LEASE) DISCHARGING TO TEOR WVVCS S-1135-125

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Vapor control system shall contain vapor control system piping network and vapor compression system consisting of two vapor compressors, fin fan aerial cooler, and knockout vessels. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Vapor control system piping network shall include vapor space piping and make-up gas serving storage tanks S-1135-173, '-174, '-175, '-178, '-325, and '-337 with vapor control piping to W&S TEOR operation S-1135-125. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
5. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Compressor knock-out drum liquids shall be piped only to vapor controlled tanks or crude sales line. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. Operator shall monitor vapor control system pressures on quarterly basis to ensure that system pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 2.8 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

12. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

13. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

14. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

15. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

18. The pressure transmitters shall be inspected and maintained in good operating conditions. The inspections shall be conducted on a quarterly basis. Replacing and repairing of each pressure transmitters shall not exceed one hour per day. [District NSR Rule] Federally Enforceable Through Title V Permit

19. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-174-9 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
2,000 BBL (84,000 GALLON) FIXED ROOF LACT TANK ID# WS-02, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.1 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
8. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
9. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

13. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

14. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. True vapor pressure shall be measured at least once every 24 months during summer (July - September), and/or whenever these is a change in the source or type of organic liquid stored using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rules 2520, 9.3.2 and 4623, 6.2.2] Federally Enforceable Through Title V Permit

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Permittee shall keep accurate records of throughput and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-175-8 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,600 BBL (67,200 GALLON) FIXED ROOF WASH TANK ID# WS-03, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.1 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
8. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
9. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: t = 2.3 V / Q, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

13. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

14. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. True vapor pressure shall be measured at least once every 24 months during summer (July - September), and/or whenever these is a change in the source or type of organic liquid stored using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rules 2520, 9.3.2 and 4623, 6.2.2] Federally Enforceable Through Title V Permit

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Permittee shall keep accurate records of throughput and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-178-10 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
3,000 BBL (126,000 GALLON) FIXED ROOF SUMP PROCESS TANK ID# WS-06, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
2. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.1 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
8. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. True vapor pressure shall be measured at least once every 24 months during summer (July - September), and/or whenever these is a change in the source or type of organic liquid stored using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rules 2520, 9.3.2 and 4623, 6.2.2] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Permittee shall keep accurate records of throughput and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-224-26 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
NOMINALLY RATED 78.2 MW COGENERATION UNIT A WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)

PERMIT UNIT REQUIREMENTS

1. CTG exhaust after the SCR unit shall be equipped with continuously recording emissions monitors dedicated to this unit for NOx, CO, and O2. Continuous emissions monitors shall meet the requirements of 40 CFR Part 60, Appendices B and F, and 40 CFR Part 75, and shall be capable of monitoring emissions during startups and shutdowns as well as normal operating conditions. If relative accuracy of CEM(s) cannot be demonstrated during startup conditions, CEM results during startup and shutdown events shall be replaced with startup emission rates obtained from source testing to determine compliance with emission limits. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
2. CTG shall be equipped with a continuously recording emission monitor preceding the SCR module measuring NOx concentration for the purposes of calculating ammonia slip. Permittee shall check, record, and quantify the calibration drift (CD) at two concentration values at least once daily (approximately 24 hours). The calibration shall be adjusted whenever the daily zero or high-level CD exceeds 5%. If either the zero or high-level CD exceeds 5% for five consecutive daily periods, the analyzer shall be deemed out-of-control. If either the zero or high-level CD exceeds 10% during any CD check, analyzer shall be deemed out-of-control. If the analyzer is out-of-control, the permittee shall take appropriate corrective action and then repeat the CD check. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
3. Ammonia injection grid shall be equipped with operational ammonia flowmeter and injection pressure indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Heat recovery steam generator design shall provide space for additional selective catalytic reduction catalyst and oxidation catalyst if required to meet NOx and CO emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall monitor and record exhaust gas temperature at selective catalytic reduction and oxidation catalyst inlets. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Ammonia shall be injected whenever the selective catalytic reduction system catalyst temperature exceeds the minimum ammonia injection temperature recommended by the manufacturer. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas turbine engine shall be equipped with fuel consumption monitor recorder accurate to +/- 3%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. CEM for NOx (as NO2) and CO shall conform to Rule 1080 specifications. [District Rules 1080 and 4703] Federally Enforceable Through Title V Permit
9. HRSG exhaust stack shall be equipped with permanent stack sampling provisions adequate to facilitate testing consistent with EPA test methods. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Flue gas ducting from engine to HRSG shall have no provisions for introduction of dilution air. [District Rule 1110] Federally Enforceable Through Title V Permit

11. Lube oil cooler/accumulation vent shall be equipped with control device(s) approved by the APCO sufficient to prevent emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Lube oil cooler/accumulator vent(s) shall not have detectable emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Natural gas sulfur content shall not exceed 0.31 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Facility shall operate as a cogeneration facility pursuant to Public Resources Code section 25134 for TEOR operations unless prior District and CEC approval is granted to operate otherwise. [District Rule 2080] Federally Enforceable Through Title V Permit

15. All CEM's shall be calibrated and operated according to EPA guidelines as specified in 40 CFR 60 Appendix B. [District Rule 1080] Federally Enforceable Through Title V Permit

16. Quarterly CEM reports shall be submitted to the APCO according to EPA regulations as specified in 40 CFR 60 Appendix B. [District Rule 4001 and District rule 1080, 8.0] Federally Enforceable Through Title V Permit

17. Audits of all monitors shall be conducted by independent laboratory in accordance with EPA guidelines and witnessed by District. Reports shall be submitted to District within 60 days of audits. [District Rule 1080] Federally Enforceable Through Title V Permit

18. All notification, recordkeeping, performance tests, reporting requirements, and compliance testing requirements of Rule 4001 NSPS shall be satisfied. [District Rule 4001] Federally Enforceable Through Title V Permit

19. Operational records including fuel type, fuel characteristics, and consumption shall be maintained and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

20. Accurate records of NOx (as NO2) and CO flue gas concentration corrected to 15% O2 and fuel gas sulfur content shall be maintained and shall be reported as described in Rule 1080 upon request. [District Rule 1080] Federally Enforceable Through Title V Permit

21. Emission rates shall not exceed the following: PM10: 0.010 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu, VOC: 0.009 lb/MMBtu, CO: 0.057 lb/MMBtu, and ammonia - 10 ppmvd @ 15%O2. [District NSR Rule; District Rule 4201; and Kern County Rule 404] Federally Enforceable Through Title V Permit

22. Permittee shall comply with the following emission limit at all times except during periods of start-up, shutdown, or reduced load as defined in Rule 4703: NOx (as NO2): 5.0 ppmv, and CO: 25 ppmv, dry @ 15% O2 corrected to ISO conditions. [40 CFR 60.332(a)(1) & 60.332(a)(2) and District Rule 4703] Federally Enforceable Through Title V Permit

23. Gas turbine engine start-up is that period of time not exceeding two hours in duration during which the unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

24. Gas turbine engine shutdown it that period of time not exceeding two hours in duration during which the unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

25. Gas turbine reduced load period is that period not exceeding one hour in duration during which the unit is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

26. Compliance with NOx, CO and ammonia emission limits shall be demonstrated by District-witnessed sample collection by independent testing laboratory annually. [District Rules 4703 and 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used PM10: EPA method 5 (front half and back half), NOx: EPA Method 7E or 20, CO: EPA method 10 (or 10B) or CARB Method 100, O2: EPA Method 3, 3A, or 20, VOC: EPA method 18 or 25, ammonia: BAAQMD ST-1B, and fuel gas sulfur content: ASTM D3246. Alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rule 1081, 40 CFR 60.335 (b), and District Rule 4703, 6.4] Federally Enforceable Through Title V Permit

29. Compliance with ammonia slip limit shall be demonstrated by using the following calculation procedure: ammonia slip ppmv @ 15% O2 = ((a-(bxc/1,000,000)) x 1,000,000 / b) x d, where a = ammonia injection rate(lb/hr)/17(lb/lb. mol), b = dry exhaust gas flow rate (lb/hr)/(29(lb/lb. mol), c = change in measured NOx concentration ppmv at 15% O2 across catalyst, and d = correction factor. The correction factor shall be derived annually during compliance testing by comparing the measured and calculated ammonia slip. [District Rule 4102] Federally Enforceable Through Title V Permit

30. Official test results and field data shall be submitted within 60 days after collection. [District Rule 4703 and District Rule 1081] Federally Enforceable Through Title V Permit

31. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

33. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

34. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

35. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

36. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4703] Federally Enforceable Through Title V Permit

38. CEC emission rates, except during periods of startup, shutdown, or reduced load shall not exceed PM10: 9.98 lb/hr, SOx (as SO2): 0.92 lb/hr, NOx (as NO2): 17.66 lb/hr, VOC: 9.00 lb/hr, and CO: 54.91 lb/hr. [District Rules 2080 and 4703, and 40 CFR 60] Federally Enforceable Through Title V Permit

39. For CEC purposes, emissions during periods of startup and shutdown shall not exceed the following values average over 2 hours: NOx: 140 lb/hr, and CO: 94 lb/hr. [District Rule 2080] Federally Enforceable Through Title V Permit

40. The CEC shall be notified of any changes to the combined annual emission limits for steam generators S-1135-115, -119, -122, and -123, and cogeneration units S-1135-224, -225, and -226, only to the extent to be informed of their impact on the Midway-Sunset Cogeneration Facility. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [Kern County Rule 108 and District Rule 1080] Federally Enforceable Through Title V Permit

42. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [Kern County Rule 108; District Rules 1080 and 4703; 40 CFR 60.7 (b)] Federally Enforceable Through Title V Permit

43. The permittee shall maintain hourly average records of NOx and CO emissions. Compliance with the hourly, daily, and twelve month rolling average VOC emission limits shall be demonstrated by the CO CEM data and the VOC/CO relationship determined by annual CO and VOC source tests of NOx, CO, and ammonia emission concentrations (ppmv @ 15% O2), and hourly, daily, and twelve month rolling. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

44. A violation of NOx emission standards indicated by the NOx CEM shall be reported by the operator to the APCO within 96 hours. [Kern County Rule 108 and District Rule 1080, 9.0] Federally Enforceable Through Title V Permit

45. Operator shall notify the APCO no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [Kern County Rule 108 and District Rule 1080, 10.0] Federally Enforceable Through Title V Permit

46. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 1081] Federally Enforceable Through Title V Permit

47. Unit shall be fired on a natural gas which has a sulfur content of less than or equal to 0.017% by weight. [40 CFR 60.333 (a) & (b); 40 CFR 60.334 (c)(2); Kern County Rule 407; and District Rule 4801] Federally Enforceable Through Title V Permit

48. If the turbine is fired on PUC-regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

49. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using method(s) specified on this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

50. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using ASTM method D 1072, D 3031, D 4084 or D 3246, or double GC for H2S and mercaptans. [40 CFR 60.335 (d)] Federally Enforceable Through Title V Permit

51. If the turbine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be semi-annually. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334 (b)(2)] Federally Enforceable Through Title V Permit

52. Operator shall submit a semiannual report listing any daily period during which the sulfur content of the fuel being fired in the gas turbine exceeds 0.8% by weight. [40 CFR 60.334(a)(2)] Federally Enforceable Through Title V Permit

53. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, OR ASTM 1945. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

54. The operator shall provide source test information annually regarding the exhaust gas NOx concentration corrected to 15% O2 (dry). [40 CFR 60.332 (a),(b) and District Rule 4703, 5.1] Federally Enforceable Through Title V Permit

55. Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334 (a),(b),(c) and District Rule 4703, 5.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

56. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

57. This unit is a simple combustion turbine as defined in 40 CFR 72.6 (b)(1) and shall not be subject to the requirements of 40 CFR Part 72. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Kern County Rules 404, 108, and 108.1. A permit shield is granted from these requirements. [SJVUAPCD Rule 2520, 13.2] Federally Enforceable Through Title V Permit

59. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: Kern County Rule 407; District Rules 4801, 4201, 1081, and 1080, Sections 6.5, 7.2, 8.0, 9.0, and 10.0; 40 CFR 60.332 (c) and (d); 60.334 (b), (c)(2); 60.335(d). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: District Rule 4703, sections 5.0, 5.1.1, 6.2.1, 6.2.4, 6.3, 6.4.1, 6.4.3, 6.4.5, and 6.4.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: District Rules 1080, 7.3 and 4703, 6.2.2; 40 CFR 60.332(a), (b); 60.333(a) and (b), 60.334(a), (b), and (c)(1); 60.335(a), (b) and (c)(2). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

62. All equipment, facilities, and systems installed or used to achieve compliance with the terms and conditions of this permit shall at all times be maintained in good working order and be operated as efficiently as possible so as to minimize air pollutant emissions. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

63. The Permittee (MSCC) must notify EPA by telephone, facsimile, or electronic mail transmission within two (2) working days following the discovery of any failure of air pollution control equipment, process equipment, or of a process to operate in a normal manner, which results in an increase in emissions above any allowable emission limit stated in any conditions where PSD is cited as the basis of the condition. In addition, the Permittee (MSCC) must notify EPA in writing within fifteen (15) days of any such failure. The notification shall include a description of the malfunctioning equipment or abnormal operation, the date of the initial malfunction, the period of time over which emissions were increased due to the failure, the cause of the failure, the estimated resultant emissions in excess of those allowed in any conditions where PSD is cited as the basis of the condition, and the methods utilized to mitigate emissions and restore normal operations. Compliance with this malfunction notification provision shall not excuse or otherwise constitute a defense to any violation of this permit or of any law or regulation that such malfunction may cause, except as provided for in the conditions where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

64. A malfunction means a sudden and unavoidable breakdown of equipment or of a process beyond the reasonable control of the source. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

65. Emissions in excess of the limits specified in any conditions where PSD is cited as the basis of the condition shall constitute a violation of this permit and may be the subject of enforcement proceedings. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

66. Affirmative defense: In the context of an enforcement proceeding, emissions which are below the limits set forth in any condition where PSD is cited as the basis of the condition shall not be subject to penalty if the Permittee (MSCC) retains properly signed, contemporaneous operating logs or other relevant evidence and can demonstrate all of the following: i.) A malfunction caused the emissions in excess of the limits in any condition where PSD is cited as the basis of the condition; ii.) The permitted facility, including the air pollution control equipment and process equipment, was being properly operated at the time of the malfunction; iii.) Preventative maintenance was regularly performed in a manner consistent with good practice for minimizing emissions; iv.) The excess emissions were not part of a recurring pattern indicative of inadequate design, operation, or maintenance; v.) During the period of the malfunction, the permittee (MSCC) took all reasonable steps to minimize the amount and duration of emissions (including any bypass) that exceeded the emission limits provided in any condition where PSD is cited as the basis of the condition. Reasonable steps to minimize emissions could include, but are not limited to, reducing production to the lowest level practicable, reducing the material feed that results in the increased emissions, and switching to alternative, less polluting fuels. Where repairs were required, repairs were made in an expeditious fashion when the operator knew or should have known that applicable emission limitations were being exceeded. Off-shift labor and overtime must have been utilized, to the extent practicable, to ensure that such repairs were made as expeditiously as possible; and vi.) The permittee (MSCC) complied with the malfunction reporting requirements as specified in the condition where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

67. All emissions, including those associated with a malfunction which may be eligible for an affirmative defense, must be included in all emissions calculations and demonstrations of compliance with mass emission limits (e.g., daily, monthly, and annual emission limits) specified in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

68. This provision is in addition to any emergency or malfunction provision contained in any applicable requirement or elsewhere in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

69. The EPA Regional Administrator, and/or their authorized representative, upon the presentation of credential, must be permitted: (1) to enter the premises where the source is located or where any records are required to be kept under the terms and conditions of the PSD permit SJ-87-01; and (2) at reasonable times to have access to and copy any records required to be kept under the terms and conditions of PSD permit SJ 87-01; and (3) to inspect any equipment, operation, or method required in the PSD permit SJ-87-01; and (4) to sample emissions from source(s). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

70. In the event of any changes in control or ownership of facilities to be constructed or modified, this permit shall be binding on all subsequent owners and operators. The Permittee (MSCC) shall notify the succeeding owner and operator of the existence of the PSD permit SJ-87-01 and its conditions by letter, a copy of which shall be forwarded to the EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

71. The provisions of the PSD permit SJ-87-01 are severable, and , if any provisions of the permit is held invalid, the remainder of the permit must not be affected thereby. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

72. The permittee (MSCC) must construct and operate the proposed power plant in compliance with all other applicable provisions of 40 CFR Parts 52, 60, 62, and 63 and all other applicable Federal, State, and local air quality regulations. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

73. On or before the date of startup (as defined in 40 C.F.R. 60.2) of the Western Midway Sunset Cogeneration Project (WMSCP; PSD Permit No. SJ-00-01) and thereafter the Permittee (MSCC) must install, continuously operate, and maintain the Dry Low NOx (DLN) combustion systems to reduce NOx emissions from each of its three turbines. The Permittee (MSCC) shall also use proper combustion techniques for the control of CO emissions from the equipment at MSCP. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

74. Within 60 days after achieving the base load, but no later than 180 days after initial startup of all three modified turbines (as defined in 40 C.F.R. 60.2), and annually thereafter (at about the anniversary of the initial performance test), the Permittee (MSCC) must conduct performance tests (as described in 40 C.F.R. 60.8) for NOx, and CO on the exhaust stack gases. The Permittee (MSCC) must furnish the District, the California Air Resources Board (CARB), and the EPA a written report of the results of such tests. Upon written request from the Permittee (MSCC), and adequate justification, EPA may waive a specific annual test and/or allow for testing to be done at less than maximum operating capacity. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

75. Performance tests for the emissions of NOx, and CO must be conducted and the results reported in accordance with the test methods set forth in 40 C.F.R. 60.8 and 40 C.F.R. 60, Appendix A. The following test methods must be used: a.) Performance tests for the emissions of NOx must be conducted using EPA Method 1-4 and 7E. b.) Performance tests for the emissions of CO must be conducted using the EPA Methods 1-4 and 10. In lieu of the above-mentioned test methods, equivalent methods may be used with prior written approval from EPA. The Permittee (MSCC) must notify EPA in writing at least 30 days prior to such tests to allow time for the development of an approvable performance test plan and to arrange for an observer to be present at the test. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

76. For performance test purposes, sampling ports, platforms, and access must be provided by the Permittee on the emission unit exhaust system in accordance with 40 C.F.R. 60.8(e). [PSD SJ 87-01] Federally Enforceable Through Title V Permit

77. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of CO into the atmosphere in excess of the following emission limits per turbine: The more stringent of 25 ppmvd @ 15% O2 or 55 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

78. This condition applies prior to the startup of the WMSCP: On and after the date of start up any of the three turbines at MSCP must not discharge (per turbine, and based on 3-hour rolling average) into the atmosphere CO in excess of the following of any of: 1.) The more stringent of 52.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 75%. 2.) The more stringent of 62.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 35% but less than 75%. 3.) 94 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

79. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of NOx into the atmosphere in excess of the following emission limits per turbine: The more stringent of 10 ppmvd @ 15% O2 or 36.1 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

80. This condition applies prior to the startup of the WMSCP: On and after the date of start-up of any of the three turbines, MSCC must not discharge (per turbine, based on 3-hour rolling average) into the atmosphere NOx (as NO2) in excess of the following: 1.) The more stringent of 25.0 ppmvd @ 15% O2 or 85.0 pounds per hour for loads greater than or equal to 75%; 2.) The more stringent of 42.0 ppmvd @ 15% O2 or 85 pounds per hour for loads greater than or equal to 35% but less than 75%; 3.) 85 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

81. The hourly (3-hour averaging) emissions must not exceed: 1.) 94 pounds of CO and 85 pounds of NOx; 2.) All CEMs must be operating during startups and shut downs; 3.) The time, date and duration of each startup and shutdown event must be recorded. The records must include the lbs/hour calculations based on the CEM data. These records must be kept for five years following the date of such events. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

82. Prior to the date of startup and thereafter, the Permittee (MSCC) must install, maintain and operate the following continuous monitoring systems (CEMs) in the exhaust stacks: a.) Continuous monitoring systems to measure stack gas NOx , CO and O2 concentrations. The systems must meet EPA monitoring performance specification (40 C.F.R. 60.13 and 40 C.F.R. 60, Appendix B, Performance Specifications 2, 3 and 4); b.) A continuous monitoring system to measure stack gas and natural gas volumetric flow rates. The stack gas flow measurement system must meet EPA Performance Specifications for (40 C.F.R. Part 52, Appendix E). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

83. The Permittee (MSCC) must maintain a file of all measurements, including continuous monitoring systems evaluations; all continuous monitoring systems or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; performance and all other information required by 40 C.F.R. 60 Appendices A-B recorded in a permanent form suitable for inspection. The file must be retained for five years following the date of such measurements, maintenance, reports and records. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

84. The Permittee (MSCC) must notify EPA of the date on which demonstration for the continuous monitoring system performance commences (40 C.F.R. 60.13). This date must be no later than 60 days after full load operation but not later than 180 days after startup. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

85. The Permittee (MSCC) must submit a written report of all excess emissions to EPA for every calendar quarter. The quarterly report must include the following: a.) The magnitude of the excess emissions computed in accordance with 40 C.F.R. 60.13(h), any conversion factors used, and the date and time of commencement and compilation of each time period of excess emissions; b.) Specific identification of each period of excess emissions that occurs during startups, shutdowns, and malfunctions of any equipment. The nature and cause of any malfunction (if known) and the corrective action taken or preventative measures adopted must also be reported; c.) The date and time identifying each period during which the continuous monitoring system was inoperative except for zero and span checks, and the nature of the system repairs or adjustments; d.) When no excess emissions have occurred or the continuous monitoring system has not been inoperative, repaired, or adjusted, such information must be stated in the report; and e.) Excess emissions must be defined as any 3-hour period during which the average emissions of CO, as measured by the CEM exceeds the maximum emission limits set forth in the condition with a CO emission limit, where PSD is cited as the basis of the condition or any 3-hour period during which the average emissions of NOx exceed the maximum emission limits set forth in the condition with a NOx emission limit, where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

86. Excess emissions indicated by the CEM system must be considered violations of the applicable emission limit for the purpose of this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

87. The quality assurance project plan used by the Permittee (MSCC) for the certification and operation of the continuous emissions monitors, which meets the requirements of 40 C.F.R. Part 60, Appendix F, must be available upon request to EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

88. The Permittee (MSCC) must keep a monthly record of all fuel uses. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

89. The proposed power plant is subject to the federal regulations entitled Standards of Performance for New Stationary Sources (40 C.F.R. 60). The owner or operator must meet all applicable requirements of 40 C.F.R. 60 Subparts A and GG of this regulation. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

90. All three turbines will fire natural gas only. The Permittee (MSCC) must only combust pipeline quality natural gas with sulfur content (as S) below 0.75 grains per 100 dry standard cubic feet (dscf). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

91. MSCC shall have legal and operational responsibility and control of all air pollutant emitting activities of the MSCP. This responsibility shall include, but shall not be limited to the following: 1.) Operating and maintaining the project to comply with all federal, state, and local air pollution laws, regulations, orders, and other requirements; 2.) Ensuring the emissions offsets, tradeoffs, or other emission reductions required for this project under permits issued by the U.S. EPA, the District, and/or the California Energy Commission are obtained as required; or 3.) Any violations of any air pollution requirements are the legal responsibility of MSCC, in addition to any other legal responsible entity. Any proposed change to this condition shall require prior written concurrence of the US EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

92. In accordance with the emissions offset plan proposed by the applicant for the District (dated November 12, 1987) and the emissions offset plan for the U.S. EPA (dated July 21, 1987), Aera Energy LLC must not operate the following four steam generators (listed by District permit numbers S-1135-119, S-1135-122, S-1135-123, and S-1135-115) simultaneously with the firing of the MSCP turbines unless one or more of the MSCP turbines is shutdown: Andersen-Goodwin Lease: S-1135-119, S-1135-122, S-1135-123 and Neely Lease: S-1135-115 [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

93. MSCC shall maintain a record of the date(s), time(s), and duration(s) of the shutdown of any of the above mentioned steam generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

94. Aera Energy LLC shall not lease or modify the permit conditions for any of the above generators for use in the Midway Sunset Oil field, unless creditable emissions reductions (as defined in 40 C.F.R. 52.21), at a ratio of at least 1:1, are provided for emissions from those generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

95. Aera Energy LLC shall not modify any of the District Permit to Operate numbers. If any of the above steam generators are issued new Permit to Operate numbers by the District, Aera Energy LLC shall notify the U.S. EPA in writing of this action and shall make such notification upon issuance of a new Permit to Operate number. This letter shall include the original District Permit to Operate number(s) of the subject generator(s) and a copy of the new Permit to Operate issued by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

96. Aera Energy LLC shall notify the U.S. EPA in writing of the intention to sell, or potential sale, of any of the above generators and shall make such notification prior to the District's final action of the re-permitting process associated with the sale of a generators. This letter shall include the following: a.) The subject steam generator as identified by its District Permit to Operate number; b.) The name of the buyer (as identified by the company name) of the steam generator; and c.) An estimated date of the final action of the re-permitting process by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

97. The allowable incidental taking (killing, harming, or harassment) of San Joaquin kit foxes, blunt-nosed leopard lizards, and giant kangaroo rats is confined to the proposed cogeneration plant site one half mile radius around this site (on lands owned or leased by Aera Energy LLC), and associated subject cogeneration plant facilities (including pipelines, transmission lines, temporary equipment stockpiling areas, and access roads) as discussed in the project Application for Certification report (Sun Cogeneration Company and Southern Sierra Energy Company 1985). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

98. MSCC is required to implement the "Agreement on Conditions for Mitigation of the Biological Impacts of the Midway-Sunset Project" as required by the U.S. Fish and Wildlife Service (USFWS) (Memorandum dated March 16, 1987 from the USFWS to the US EPA). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

99. Any endangered species found dead should be turned in to the California Department of Fish and Game for Analysis. MSCC must also report this event to the USFWS. The USFWS may recommend amendment to the existing project actions pending results of the analysis. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

100. All correspondence as required by this permit shall be forwarded to: 1.) Director, Air Division (Attn: Air-3) EPA Region IX 75 Hawthorne Street San Francisco, CA 94105-3901 Tel: (415) 744-1291 Fax: (415) 744-1076; 2.) Chief, Stationary Source Division, California Air Resource Board P.O. Box 2815 Sacramento, CA 95812; and 3.) Air Pollution Control Officer, San Joaquin Valley Unified APCD 2700 M Street, Suite 275 Bakersfield, CA 93301-2370. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

101. Aera Energy LLC is the legal owner of the subject steam generators and of the leases on which the steam generators are located. MSCC is the legal owner of the gas turbine cogeneration facility. MSCC is jointly owned by Sun Cogeneration Limited Partnership (Sun Cogen LP) and San Joaquin Energy Company. Sun Cogen LP is managed and controlled by a wholly owned subsidiary of Aera Energy LLC. (See Condition 104) [PSD SJ-87-01] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-225-25 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
NOMINALLY RATED 78.2 MW COGENERATION UNIT B WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS, SELECTIVE CATALYTIC REDUCTION (SCR), AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)

PERMIT UNIT REQUIREMENTS

1. CTG exhaust after the SCR unit shall be equipped with continuously recording emissions monitors dedicated to this unit for NOx, CO, and O2. Continuous emissions monitors shall meet the requirements of 40 CFR Part 60, Appendices B and F, and 40 CFR Part 75, and shall be capable of monitoring emissions during startups and shutdowns as well as normal operating conditions. If relative accuracy of CEM(s) cannot be demonstrated during startup conditions, CEM results during startup and shutdown events shall be replaced with startup emission rates obtained from source testing to determine compliance with emission limits. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
2. CTG shall be equipped with a continuously recording emission monitor preceding the SCR module measuring NOx concentration for the purposes of calculating ammonia slip. Permittee shall check, record, and quantify the calibration drift (CD) at two concentration values at least once daily (approximately 24 hours). The calibration shall be adjusted whenever the daily zero or high-level CD exceeds 5%. If either the zero or high-level CD exceeds 5% for five consecutive daily periods, the analyzer shall be deemed out-of-control. If either the zero or high-level CD exceeds 10% during any CD check, analyzer shall be deemed out-of-control. If the analyzer is out-of-control, the permittee shall take appropriate corrective action and then repeat the CD check. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
3. Ammonia injection grid shall be equipped with operational ammonia flowmeter and injection pressure indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Heat recovery steam generator design shall provide space for additional selective catalytic reduction catalyst and oxidation catalyst if required to meet NOx and CO emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall monitor and record exhaust gas temperature at selective catalytic reduction and oxidation catalyst inlets. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Ammonia shall be injected whenever the selective catalytic reduction system catalyst temperature exceeds the minimum ammonia injection temperature recommended by the manufacturer. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas turbine engine shall be equipped with fuel consumption monitor recorder accurate to +/- 3%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. CEM for NOx (as NO2) and CO shall conform to Rule 1080 specifications. [District Rules 1080 and 4703] Federally Enforceable Through Title V Permit
9. HRSG exhaust stack shall be equipped with permanent stack sampling provisions adequate to facilitate testing consistent with EPA test methods. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Flue gas ducting from engine to HRSG shall have no provisions for introduction of dilution air. [District Rule 1110] Federally Enforceable Through Title V Permit

11. Lube oil cooler/accumulation vent shall be equipped with control device(s) approved by the APCO sufficient to prevent emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Lube oil cooler/accumulator vent(s) shall not have detectable emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Natural gas sulfur content shall not exceed 0.31 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Facility shall operate as a cogeneration facility pursuant to Public Resources Code section 25134 for TEOR operations unless prior District and CEC approval is granted to operate otherwise. [District Rule 2080] Federally Enforceable Through Title V Permit

15. All CEM's shall be calibrated and operated according to EPA guidelines as specified in 40 CFR 60 Appendix B. [District Rule 1080] Federally Enforceable Through Title V Permit

16. Quarterly CEM reports shall be submitted to the APCO according to EPA regulations as specified in 40 CFR 60 Appendix B. [District Rule 4001 and District rule 1080, 8.0] Federally Enforceable Through Title V Permit

17. Audits of all monitors shall be conducted by independent laboratory in accordance with EPA guidelines and witnessed by District. Reports shall be submitted to District within 60 days of audits. [District Rule 1080] Federally Enforceable Through Title V Permit

18. All notification, recordkeeping, performance tests, reporting requirements, and compliance testing requirements of Rule 4001 NSPS shall be satisfied. [District Rule 4001] Federally Enforceable Through Title V Permit

19. Operational records including fuel type, fuel characteristics, and consumption shall be maintained and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

20. Accurate records of NOx (as NO2) and CO flue gas concentration corrected to 15% O2 and fuel gas sulfur content shall be maintained and shall be reported as described in Rule 1080 upon request. [District Rule 1080] Federally Enforceable Through Title V Permit

21. Emission rates shall not exceed the following: PM10: 0.010 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu, VOC: 0.009 lb/MMBtu, CO: 0.057 lb/MMBtu, and ammonia - 10 ppmvd @ 15%O2. [District NSR Rule; District Rule 4201; and Kern County Rule 404] Federally Enforceable Through Title V Permit

22. Permittee shall comply with the following emission limit at all times except during periods of start-up, shutdown, or reduced load as defined in Rule 4703: NOx (as NO2): 5.0 ppmv, and CO: 25 ppmv, dry @ 15% O2 corrected to ISO conditions. [40 CFR 60.332(a)(1) & 60.332(a)(2) and District Rule 4703] Federally Enforceable Through Title V Permit

23. Gas turbine engine start-up is that period of time not exceeding two hours in duration during which the unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

24. Gas turbine engine shutdown it that period of time not exceeding two hours in duration during which the unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

25. Gas turbine reduced load period is that period not exceeding one hour in duration during which the unit is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

26. Compliance with NOx, CO and ammonia emission limits shall be demonstrated by District-witnessed sample collection by independent testing laboratory annually. [District Rules 4703 and 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used PM10: EPA method 5 (front half and back half), NOx: EPA Method 7E or 20, CO: EPA method 10 (or 10B) or CARB Method 100, O2: EPA Method 3, 3A, or 20, VOC: EPA method 18 or 25, ammonia: BAAQMD ST-1B, and fuel gas sulfur content: ASTM D3246. Alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rule 1081, 40 CFR 60.335 (b), and District Rule 4703, 6.4] Federally Enforceable Through Title V Permit

29. Compliance with ammonia slip limit shall be demonstrated by using the following calculation procedure: ammonia slip ppmv @ 15% O2 = ((a-(bxc/1,000,000)) x 1,000,000 / b) x d, where a = ammonia injection rate(lb/hr)/17(lb/lb. mol), b = dry exhaust gas flow rate (lb/hr)/(29(lb/lb. mol), c = change in measured NOx concentration ppmv at 15% O2 across catalyst, and d = correction factor. The correction factor shall be derived annually during compliance testing by comparing the measured and calculated ammonia slip. [District Rule 4102] Federally Enforceable Through Title V Permit

30. Official test results and field data shall be submitted within 60 days after collection. [District Rule 4703 and District Rule 1081] Federally Enforceable Through Title V Permit

31. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

33. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

34. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

35. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

36. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4703] Federally Enforceable Through Title V Permit

38. CEC emission rates, except during periods of startup, shutdown, or reduced load shall not exceed PM10: 9.98 lb/hr, SOx (as SO2): 0.92 lb/hr, NOx (as NO2): 17.66 lb/hr, VOC: 9.00 lb/hr, and CO: 54.91 lb/hr. [District Rules 2080 and 4703, and 40 CFR 60] Federally Enforceable Through Title V Permit

39. For CEC purposes, emissions during periods of startup and shutdown shall not exceed the following values average over 2 hours: NOx: 140 lb/hr, and CO: 94 lb/hr. [District Rule 2080] Federally Enforceable Through Title V Permit

40. The CEC shall be notified of any changes to the combined annual emission limits for steam generators S-1135-115, -119, -122, and -123, and cogeneration units S-1135-224, -225, and -226, only to the extent to be informed of their impact on the Midway-Sunset Cogeneration Facility. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [Kern County Rule 108 and District Rule 1080] Federally Enforceable Through Title V Permit

42. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [Kern County Rule 108; District Rules 1080 and 4703; 40 CFR 60.7 (b)] Federally Enforceable Through Title V Permit

43. The permittee shall maintain hourly average records of NOx and CO emissions. Compliance with the hourly, daily, and twelve month rolling average VOC emission limits shall be demonstrated by the CO CEM data and the VOC/CO relationship determined by annual CO and VOC source tests of NOx, CO, and ammonia emission concentrations (ppmv @ 15% O2), and hourly, daily, and twelve month rolling. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

44. A violation of NOx emission standards indicated by the NOx CEM shall be reported by the operator to the APCO within 96 hours. [Kern County Rule 108 and District Rule 1080, 9.0] Federally Enforceable Through Title V Permit

45. Operator shall notify the APCO no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [Kern County Rule 108 and District Rule 1080, 10.0] Federally Enforceable Through Title V Permit

46. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 1081] Federally Enforceable Through Title V Permit

47. Unit shall be fired on a natural gas which has a sulfur content of less than or equal to 0.017% by weight. [40 CFR 60.333 (a) & (b); 40 CFR 60.334 (c)(2); Kern County Rule 407; and District Rule 4801] Federally Enforceable Through Title V Permit

48. If the turbine is fired on PUC-regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

49. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using method(s) specified on this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

50. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using ASTM method D 1072, D 3031, D 4084 or D 3246, or double GC for H2S and mercaptans. [40 CFR 60.335 (d)] Federally Enforceable Through Title V Permit

51. If the turbine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be semi-annually. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334 (b)(2)] Federally Enforceable Through Title V Permit

52. Operator shall submit a semiannual report listing any daily period during which the sulfur content of the fuel being fired in the gas turbine exceeds 0.8% by weight. [40 CFR 60.334(a)(2)] Federally Enforceable Through Title V Permit

53. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, OR ASTM 1945. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

54. The operator shall provide source test information annually regarding the exhaust gas NOx concentration corrected to 15% O2 (dry). [40 CFR 60.332 (a),(b) and District Rule 4703, 5.1] Federally Enforceable Through Title V Permit

55. Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334 (a),(b),(c) and District Rule 4703, 5.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

56. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

57. This unit is a simple combustion turbine as defined in 40 CFR 72.6 (b)(1) and shall not be subject to the requirements of 40 CFR Part 72. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Kern County Rules 404, 108, and 108.1. A permit shield is granted from these requirements. [SJVUAPCD Rule 2520, 13.2] Federally Enforceable Through Title V Permit

59. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: Kern County Rule 407; District Rules 4801, 4201, 1081, and 1080, Sections 6.5, 7.2, 8.0, 9.0, and 10.0; 40 CFR 60.332 (c) and (d); 60.334 (b), (c)(2); 60.335(d). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: District Rule 4703, sections 5.0, 5.1.1, 6.2.1, 6.2.4, 6.3, 6.4.1, 6.4.3, 6.4.5, and 6.4.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: District Rules 1080, 7.3 and 4703, 6.2.2; 40 CFR 60.332(a), (b); 60.333(a) and (b), 60.334(a), (b), and (c)(1); 60.335(a), (b) and (c)(2). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

62. All equipment, facilities, and systems installed or used to achieve compliance with the terms and conditions of this permit shall at all times be maintained in good working order and be operated as efficiently as possible so as to minimize air pollutant emissions. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

63. The Permittee (MSCC) must notify EPA by telephone, facsimile, or electronic mail transmission within two (2) working days following the discovery of any failure of air pollution control equipment, process equipment, or of a process to operate in a normal manner, which results in an increase in emissions above any allowable emission limit stated in any conditions where PSD is cited as the basis of the condition. In addition, the Permittee (MSCC) must notify EPA in writing within fifteen (15) days of any such failure. The notification shall include a description of the malfunctioning equipment or abnormal operation, the date of the initial malfunction, the period of time over which emissions were increased due to the failure, the cause of the failure, the estimated resultant emissions in excess of those allowed in any conditions where PSD is cited as the basis of the condition, and the methods utilized to mitigate emissions and restore normal operations. Compliance with this malfunction notification provision shall not excuse or otherwise constitute a defense to any violation of this permit or of any law or regulation that such malfunction may cause, except as provided for in the conditions where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

64. A malfunction means a sudden and unavoidable breakdown of equipment or of a process beyond the reasonable control of the source. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

65. Emissions in excess of the limits specified in any conditions where PSD is cited as the basis of the condition shall constitute a violation of this permit and may be the subject of enforcement proceedings. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

66. Affirmative defense: In the context of an enforcement proceeding, emissions which are below the limits set forth in any condition where PSD is cited as the basis of the condition shall not be subject to penalty if the Permittee (MSCC) retains properly signed, contemporaneous operating logs or other relevant evidence and can demonstrate all of the following: i.) A malfunction caused the emissions in excess of the limits in any condition where PSD is cited as the basis of the condition; ii.) The permitted facility, including the air pollution control equipment and process equipment, was being properly operated at the time of the malfunction; iii.) Preventative maintenance was regularly performed in a manner consistent with good practice for minimizing emissions; iv.) The excess emissions were not part of a recurring pattern indicative of inadequate design, operation, or maintenance; v.) During the period of the malfunction, the permittee (MSCC) took all reasonable steps to minimize the amount and duration of emissions (including any bypass) that exceeded the emission limits provided in any condition where PSD is cited as the basis of the condition. Reasonable steps to minimize emissions could include, but are not limited to, reducing production to the lowest level practicable, reducing the material feed that results in the increased emissions, and switching to alternative, less polluting fuels. Where repairs were required, repairs were made in an expeditious fashion when the operator knew or should have known that applicable emission limitations were being exceeded. Off-shift labor and overtime must have been utilized, to the extent practicable, to ensure that such repairs were made as expeditiously as possible; and vi.) The permittee (MSCC) complied with the malfunction reporting requirements as specified in the condition where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

67. All emissions, including those associated with a malfunction which may be eligible for an affirmative defense, must be included in all emissions calculations and demonstrations of compliance with mass emission limits (e.g., daily, monthly, and annual emission limits) specified in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

68. This provision is in addition to any emergency or malfunction provision contained in any applicable requirement or elsewhere in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

69. The EPA Regional Administrator, and/or their authorized representative, upon the presentation of credential, must be permitted: (1) to enter the premises where the source is located or where any records are required to be kept under the terms and conditions of the PSD permit SJ-87-01; and (2) at reasonable times to have access to and copy any records required to be kept under the terms and conditions of PSD permit SJ 87-01; and (3) to inspect any equipment, operation, or method required in the PSD permit SJ-87-01; and (4) to sample emissions from source(s). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

70. In the event of any changes in control or ownership of facilities to be constructed or modified, this permit shall be binding on all subsequent owners and operators. The Permittee (MSCC) shall notify the succeeding owner and operator of the existence of the PSD permit SJ-87-01 and its conditions by letter, a copy of which shall be forwarded to the EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

71. The provisions of the PSD permit SJ-87-01 are severable, and , if any provisions of the permit is held invalid, the remainder of the permit must not be affected thereby. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

72. The permittee (MSCC) must construct and operate the proposed power plant in compliance with all other applicable provisions of 40 CFR Parts 52, 60, 62, and 63 and all other applicable Federal, State, and local air quality regulations. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

73. On or before the date of startup (as defined in 40 C.F.R. 60.2) of the Western Midway Sunset Cogeneration Project (WMSCP; PSD Permit No. SJ-00-01) and thereafter the Permittee (MSCC) must install, continuously operate, and maintain the Dry Low NOx (DLN) combustion systems to reduce NOx emissions from each of its three turbines. The Permittee (MSCC) shall also use proper combustion techniques for the control of CO emissions from the equipment at MSCP. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

74. Within 60 days after achieving the base load, but no later than 180 days after initial startup of all three modified turbines (as defined in 40 C.F.R. 60.2), and annually thereafter (at about the anniversary of the initial performance test), the Permittee (MSCC) must conduct performance tests (as described in 40 C.F.R. 60.8) for NOx, and CO on the exhaust stack gases. The Permittee (MSCC) must furnish the District, the California Air Resources Board (CARB), and the EPA a written report of the results of such tests. Upon written request from the Permittee (MSCC), and adequate justification, EPA may waive a specific annual test and/or allow for testing to be done at less than maximum operating capacity. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

75. Performance tests for the emissions of NOx, and CO must be conducted and the results reported in accordance with the test methods set forth in 40 C.F.R. 60.8 and 40 C.F.R. 60, Appendix A. The following test methods must be used: a.) Performance tests for the emissions of NOx must be conducted using EPA Method 1-4 and 7E. b.) Performance tests for the emissions of CO must be conducted using the EPA Methods 1-4 and 10. In lieu of the above-mentioned test methods, equivalent methods may be used with prior written approval from EPA. The Permittee (MSCC) must notify EPA in writing at least 30 days prior to such tests to allow time for the development of an approvable performance test plan and to arrange for an observer to be present at the test. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

76. For performance test purposes, sampling ports, platforms, and access must be provided by the Permittee on the emission unit exhaust system in accordance with 40 C.F.R. 60.8(e). [PSD SJ 87-01] Federally Enforceable Through Title V Permit

77. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of CO into the atmosphere in excess of the following emission limits per turbine: The more stringent of 25 ppmvd @ 15% O2 or 55 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

78. This condition applies prior to the startup of the WMSCP: On and after the date of start up any of the three turbines at MSCP must not discharge (per turbine, and based on 3-hour rolling average) into the atmosphere CO in excess of the following of any of: 1.) The more stringent of 52.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 75%. 2.) The more stringent of 62.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 35% but less than 75%. 3.) 94 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

79. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of NOx into the atmosphere in excess of the following emission limits per turbine: The more stringent of 10 ppmvd @ 15% O2 or 36.1 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

80. This condition applies prior to the startup of the WMSCP: On and after the date of start-up of any of the three turbines, MSCC must not discharge (per turbine, based on 3-hour rolling average) into the atmosphere NOx (as NO2) in excess of the following: 1.) The more stringent of 25.0 ppmvd @ 15% O2 or 85.0 pounds per hour for loads greater than or equal to 75%; 2.) The more stringent of 42.0 ppmvd @ 15% O2 or 85 pounds per hour for loads greater than or equal to 35% but less than 75%; 3.) 85 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

81. The hourly (3-hour averaging) emissions must not exceed: 1.) 94 pounds of CO and 85 pounds of NOx; 2.) All CEMs must be operating during startups and shut downs; 3.) The time, date and duration of each startup and shutdown event must be recorded. The records must include the lbs/hour calculations based on the CEM data. These records must be kept for five years following the date of such events. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

82. Prior to the date of startup and thereafter, the Permittee (MSCC) must install, maintain and operate the following continuous monitoring systems (CEMs) in the exhaust stacks: a.) Continuous monitoring systems to measure stack gas NOx , CO and O2 concentrations. The systems must meet EPA monitoring performance specification (40 C.F.R. 60.13 and 40 C.F.R. 60, Appendix B, Performance Specifications 2, 3 and 4); b.) A continuous monitoring system to measure stack gas and natural gas volumetric flow rates. The stack gas flow measurement system must meet EPA Performance Specifications for (40 C.F.R. Part 52, Appendix E). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

83. The Permittee (MSCC) must maintain a file of all measurements, including continuous monitoring systems evaluations; all continuous monitoring systems or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; performance and all other information required by 40 C.F.R. 60 Appendices A-B recorded in a permanent form suitable for inspection. The file must be retained for five years following the date of such measurements, maintenance, reports and records. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

84. The Permittee (MSCC) must notify EPA of the date on which demonstration for the continuous monitoring system performance commences (40 C.F.R. 60.13). This date must be no later than 60 days after full load operation but not later than 180 days after startup. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

85. The Permittee (MSCC) must submit a written report of all excess emissions to EPA for every calendar quarter. The quarterly report must include the following: a.) The magnitude of the excess emissions computed in accordance with 40 C.F.R. 60.13(h), any conversion factors used, and the date and time of commencement and compilation of each time period of excess emissions; b.) Specific identification of each period of excess emissions that occurs during startups, shutdowns, and malfunctions of any equipment. The nature and cause of any malfunction (if known) and the corrective action taken or preventative measures adopted must also be reported; c.) The date and time identifying each period during which the continuous monitoring system was inoperative except for zero and span checks, and the nature of the system repairs or adjustments; d.) When no excess emissions have occurred or the continuous monitoring system has not been inoperative, repaired, or adjusted, such information must be stated in the report; and e.) Excess emissions must be defined as any 3-hour period during which the average emissions of CO, as measured by the CEM exceeds the maximum emission limits set forth in the condition with a CO emission limit, where PSD is cited as the basis of the condition or any 3-hour period during which the average emissions of NOx exceed the maximum emission limits set forth in the condition with a NOx emission limit, where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

86. Excess emissions indicated by the CEM system must be considered violations of the applicable emission limit for the purpose of this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

87. The quality assurance project plan used by the Permittee (MSCC) for the certification and operation of the continuous emissions monitors, which meets the requirements of 40 C.F.R. Part 60, Appendix F, must be available upon request to EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

88. The Permittee (MSCC) must keep a monthly record of all fuel uses. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

89. The proposed power plant is subject to the federal regulations entitled Standards of Performance for New Stationary Sources (40 C.F.R. 60). The owner or operator must meet all applicable requirements of 40 C.F.R. 60 Subparts A and GG of this regulation. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

90. All three turbines will fire natural gas only. The Permittee (MSCC) must only combust pipeline quality natural gas with sulfur content (as S) below 0.75 grains per 100 dry standard cubic feet (dscf). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

91. MSCC shall have legal and operational responsibility and control of all air pollutant emitting activities of the MSCP. This responsibility shall include, but shall not be limited to the following: 1.) Operating and maintaining the project to comply with all federal, state, and local air pollution laws, regulations, orders, and other requirements; 2.) Ensuring the emissions offsets, tradeoffs, or other emission reductions required for this project under permits issued by the U.S. EPA, the District, and/or the California Energy Commission are obtained as required; or 3.) Any violations of any air pollution requirements are the legal responsibility of MSCC, in addition to any other legal responsible entity. Any proposed change to this condition shall require prior written concurrence of the US EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

92. In accordance with the emissions offset plan proposed by the applicant for the District (dated November 12, 1987) and the emissions offset plan for the U.S. EPA (dated July 21, 1987), Aera Energy LLC must not operate the following four steam generators (listed by District permit numbers S-1135-119, S-1135-122, S-1135-123, and S-1135-115) simultaneously with the firing of the MSCP turbines unless one or more of the MSCP turbines is shutdown: Andersen-Goodwin Lease: S-1135-119, S-1135-122, S-1135-123 and Neely Lease: S-1135-115 [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

93. MSCC shall maintain a record of the date(s), time(s), and duration(s) of the shutdown of any of the above mentioned steam generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

94. Aera Energy LLC shall not lease or modify the permit conditions for any of the above generators for use in the Midway Sunset Oil field, unless creditable emissions reductions (as defined in 40 C.F.R. 52.21), at a ratio of at least 1:1, are provided for emissions from those generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

95. Aera Energy LLC shall not modify any of the District Permit to Operate numbers. If any of the above steam generators are issued new Permit to Operate numbers by the District, Aera Energy LLC shall notify the U.S. EPA in writing of this action and shall make such notification upon issuance of a new Permit to Operate number. This letter shall include the original District Permit to Operate number(s) of the subject generator(s) and a copy of the new Permit to Operate issued by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

96. Aera Energy LLC shall notify the U.S. EPA in writing of the intention to sell, or potential sale, of any of the above generators and shall make such notification prior to the District's final action of the re-permitting process associated with the sale of a generators. This letter shall include the following: a.) The subject steam generator as identified by its District Permit to Operate number; b.) The name of the buyer (as identified by the company name) of the steam generator; and c.) An estimated date of the final action of the re-permitting process by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

97. The allowable incidental taking (killing, harming, or harassment) of San Joaquin kit foxes, blunt-nosed leopard lizards, and giant kangaroo rats is confined to the proposed cogeneration plant site one half mile radius around this site (on lands owned or leased by Aera Energy LLC), and associated subject cogeneration plant facilities (including pipelines, transmission lines, temporary equipment stockpiling areas, and access roads) as discussed in the project Application for Certification report (Sun Cogeneration Company and Southern Sierra Energy Company 1985). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

98. MSCC is required to implement the "Agreement on Conditions for Mitigation of the Biological Impacts of the Midway-Sunset Project" as required by the U.S. Fish and Wildlife Service (USFWS) (Memorandum dated March 16, 1987 from the USFWS to the US EPA). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

99. Any endangered species found dead should be turned in to the California Department of Fish and Game for Analysis. MSCC must also report this event to the USFWS. The USFWS may recommend amendment to the existing project actions pending results of the analysis. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

100. All correspondence as required by this permit shall be forwarded to: 1.) Director, Air Division (Attn: Air-3) EPA Region IX 75 Hawthorne Street San Francisco, CA 94105-3901 Tel: (415) 744-1291 Fax: (415) 744-1076; 2.) Chief, Stationary Source Division, California Air Resource Board P.O. Box 2815 Sacramento, CA 95812; and 3.) Air Pollution Control Officer, San Joaquin Valley Unified APCD 2700 M Street, Suite 275 Bakersfield, CA 93301-2370. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

101. Aera Energy LLC is the legal owner of the subject steam generators and of the leases on which the steam generators are located. MSCC is the legal owner of the gas turbine cogeneration facility. MSCC is jointly owned by Sun Cogeneration Limited Partnership (Sun Cogen LP) and San Joaquin Energy Company. Sun Cogen LP is managed and controlled by a wholly owned subsidiary of Aera Energy LLC. (See Condition 104) [PSD SJ-87-01] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-226-25 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
NOMINALLY RATED 78.2 MW COGENERATION UNIT C WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)

PERMIT UNIT REQUIREMENTS

1. CTG exhaust after the SCR unit shall be equipped with continuously recording emissions monitors dedicated to this unit for NOx, CO, and O2. Continuous emissions monitors shall meet the requirements of 40 CFR Part 60, Appendices B and F, and 40 CFR Part 75, and shall be capable of monitoring emissions during startups and shutdowns as well as normal operating conditions. If relative accuracy of CEM(s) cannot be demonstrated during startup conditions, CEM results during startup and shutdown events shall be replaced with startup emission rates obtained from source testing to determine compliance with emission limits. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
2. CTG shall be equipped with a continuously recording emission monitor preceding the SCR module measuring NOx concentration for the purposes of calculating ammonia slip. Permittee shall check, record, and quantify the calibration drift (CD) at two concentration values at least once daily (approximately 24 hours). The calibration shall be adjusted whenever the daily zero or high-level CD exceeds 5%. If either the zero or high-level CD exceeds 5% for five consecutive daily periods, the analyzer shall be deemed out-of-control. If either the zero or high-level CD exceeds 10% during any CD check, analyzer shall be deemed out-of-control. If the analyzer is out-of-control, the permittee shall take appropriate corrective action and then repeat the CD check. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
3. Ammonia injection grid shall be equipped with operational ammonia flowmeter and injection pressure indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Heat recovery steam generator design shall provide space for additional selective catalytic reduction catalyst and oxidation catalyst if required to meet NOx and CO emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall monitor and record exhaust gas temperature at selective catalytic reduction and oxidation catalyst inlets. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Ammonia shall be injected whenever the selective catalytic reduction system catalyst temperature exceeds the minimum ammonia injection temperature recommended by the manufacturer. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas turbine engine shall be equipped with fuel consumption monitor recorder accurate to +/- 3%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. CEM for NOx (as NO2) and CO shall conform to Rule 1080 specifications. [District Rules 1080 and 4703] Federally Enforceable Through Title V Permit
9. HRSG exhaust stack shall be equipped with permanent stack sampling provisions adequate to facilitate testing consistent with EPA test methods. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Flue gas ducting from engine to HRSG shall have no provisions for introduction of dilution air. [District Rule 1110] Federally Enforceable Through Title V Permit
11. Lube oil cooler/accumulation vent shall be equipped with control device(s) approved by the APCO sufficient to prevent emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Lube oil cooler/accumulator vent(s) shall not have detectable emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Natural gas sulfur content shall not exceed 0.31 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Facility shall operate as a cogeneration facility pursuant to Public Resources Code section 25134 for TEOR operations unless prior District and CEC approval is granted to operate otherwise. [District Rule 2080] Federally Enforceable Through Title V Permit
15. All CEM's shall be calibrated and operated according to EPA guidelines as specified in 40 CFR 60 Appendix B. [District Rule 1080] Federally Enforceable Through Title V Permit
16. Quarterly CEM reports shall be submitted to the APCO according to EPA regulations as specified in 40 CFR 60 Appendix B. [District Rule 4001 and District rule 1080, 8.0] Federally Enforceable Through Title V Permit
17. Audits of all monitors shall be conducted by independent laboratory in accordance with EPA guidelines and witnessed by District. Reports shall be submitted to District within 60 days of audits. [District Rule 1080] Federally Enforceable Through Title V Permit
18. All notification, recordkeeping, performance tests, reporting requirements, and compliance testing requirements of Rule 4001 NSPS shall be satisfied. [District Rule 4001] Federally Enforceable Through Title V Permit
19. Operational records including fuel type, fuel characteristics, and consumption shall be maintained and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
20. Accurate records of NOx (as NO2) and CO flue gas concentration corrected to 15% O2 and fuel gas sulfur content shall be maintained and shall be reported as described in Rule 1080 upon request. [District Rule 1080] Federally Enforceable Through Title V Permit
21. Emission rates shall not exceed the following: PM10: 0.010 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu, VOC: 0.009 lb/MMBtu, CO: 0.057 lb/MMBtu, and ammonia - 10 ppmvd @ 15%O2. [District NSR Rule; District Rule 4201; and Kern County Rule 404] Federally Enforceable Through Title V Permit
22. Permittee shall comply with the following emission limit at all times except during periods of start-up, shutdown, or reduced load as defined in Rule 4703: NOx (as NO2): 5.0 ppmv, and CO: 25 ppmv, dry @ 15% O2 corrected to ISO conditions. [40 CFR 60.332(a)(1) & 60.332(a)(2) and District Rule 4703] Federally Enforceable Through Title V Permit
23. Gas turbine engine start-up is that period of time not exceeding two hours in duration during which the unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
24. Gas turbine engine shutdown it that period of time not exceeding two hours in duration during which the unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
25. Gas turbine reduced load period is that period not exceeding one hour in duration during which the unit is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
26. Compliance with NOx, CO and ammonia emission limits shall be demonstrated by District-witnessed sample collection by independent testing laboratory annually. [District Rules 4703 and 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used PM10: EPA method 5 (front half and back half), NOx: EPA Method 7E or 20, CO: EPA method 10 (or 10B) or CARB Method 100, O2: EPA Method 3, 3A, or 20, VOC: EPA method 18 or 25, ammonia: BAAQMD ST-1B, and fuel gas sulfur content: ASTM D3246. Alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rule 1081, 40 CFR 60.335 (b), and District Rule 4703, 6.4] Federally Enforceable Through Title V Permit

29. Compliance with ammonia slip limit shall be demonstrated by using the following calculation procedure: ammonia slip ppmv @ 15% O2 = ((a-(bxc/1,000,000)) x 1,000,000 / b) x d, where a = ammonia injection rate(lb/hr)/17(lb/lb. mol), b = dry exhaust gas flow rate (lb/hr)/(29(lb/lb. mol), c = change in measured NOx concentration ppmv at 15% O2 across catalyst, and d = correction factor. The correction factor shall be derived annually during compliance testing by comparing the measured and calculated ammonia slip. [District Rule 4102] Federally Enforceable Through Title V Permit

30. Official test results and field data shall be submitted within 60 days after collection. [District Rule 4703 and District Rule 1081] Federally Enforceable Through Title V Permit

31. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

33. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

34. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

35. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

36. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4703] Federally Enforceable Through Title V Permit

38. CEC emission rates, except during periods of startup, shutdown, or reduced load shall not exceed PM10: 9.98 lb/hr, SOx (as SO2): 0.92 lb/hr, NOx (as NO2): 17.66 lb/hr, VOC: 9.00 lb/hr, and CO: 54.91 lb/hr. [District Rules 2080 and 4703, and 40 CFR 60] Federally Enforceable Through Title V Permit

39. For CEC purposes, emissions during periods of startup and shutdown shall not exceed the following values average over 2 hours: NOx: 140 lb/hr, and CO: 94 lb/hr. [District Rule 2080] Federally Enforceable Through Title V Permit

40. The CEC shall be notified of any changes to the combined annual emission limits for steam generators S-1135-115, -119, -122, and -123, and cogeneration units S-1135-224, -225, and -226, only to the extent to be informed of their impact on the Midway-Sunset Cogeneration Facility. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [Kern County Rule 108 and District Rule 1080] Federally Enforceable Through Title V Permit

42. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [Kern County Rule 108; District Rules 1080 and 4703; 40 CFR 60.7 (b)] Federally Enforceable Through Title V Permit

43. The permittee shall maintain hourly average records of NOx and CO emissions. Compliance with the hourly, daily, and twelve month rolling average VOC emission limits shall be demonstrated by the CO CEM data and the VOC/CO relationship determined by annual CO and VOC source tests of NOx, CO, and ammonia emission concentrations (ppmv @ 15% O2), and hourly, daily, and twelve month rolling. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

44. A violation of NOx emission standards indicated by the NOx CEM shall be reported by the operator to the APCO within 96 hours. [Kern County Rule 108 and District Rule 1080, 9.0] Federally Enforceable Through Title V Permit

45. Operator shall notify the APCO no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [Kern County Rule 108 and District Rule 1080, 10.0] Federally Enforceable Through Title V Permit

46. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 1081] Federally Enforceable Through Title V Permit

47. Unit shall be fired on a natural gas which has a sulfur content of less than or equal to 0.017% by weight. [40 CFR 60.333 (a) & (b); 40 CFR 60.334 (c)(2); Kern County Rule 407; and District Rule 4801] Federally Enforceable Through Title V Permit

48. If the turbine is fired on PUC-regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

49. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using method(s) specified on this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

50. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using ASTM method D 1072, D 3031, D 4084 or D 3246, or double GC for H2S and mercaptans. [40 CFR 60.335 (d)] Federally Enforceable Through Title V Permit

51. If the turbine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be semi-annually. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334 (b)(2)] Federally Enforceable Through Title V Permit

52. Operator shall submit a semiannual report listing any daily period during which the sulfur content of the fuel being fired in the gas turbine exceeds 0.8% by weight. [40 CFR 60.334(a)(2)] Federally Enforceable Through Title V Permit

53. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, OR ASTM 1945. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

54. The operator shall provide source test information annually regarding the exhaust gas NOx concentration corrected to 15% O2 (dry). [40 CFR 60.332 (a),(b) and District Rule 4703, 5.1] Federally Enforceable Through Title V Permit

55. Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334 (a),(b),(c) and District Rule 4703, 5.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

56. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

57. This unit is a simple combustion turbine as defined in 40 CFR 72.6 (b)(1) and shall not be subject to the requirements of 40 CFR Part 72. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Kern County Rules 404, 108, and 108.1. A permit shield is granted from these requirements. [SJVUAPCD Rule 2520, 13.2] Federally Enforceable Through Title V Permit

59. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: Kern County Rule 407; District Rules 4801, 4201, 1081, and 1080, Sections 6.5, 7.2, 8.0, 9.0, and 10.0; 40 CFR 60.332 (c) and (d); 60.334 (b), (c)(2); 60.335(d). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: District Rule 4703, sections 5.0, 5.1.1, 6.2.1, 6.2.4, 6.3, 6.4.1, 6.4.3, 6.4.5, and 6.4.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: District Rules 1080, 7.3 and 4703, 6.2.2; 40 CFR 60.332(a), (b); 60.333(a) and (b), 60.334(a), (b), and (c)(1); 60.335(a), (b) and (c)(2). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

62. All equipment, facilities, and systems installed or used to achieve compliance with the terms and conditions of this permit shall at all times be maintained in good working order and be operated as efficiently as possible so as to minimize air pollutant emissions. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

63. The Permittee (MSCC) must notify EPA by telephone, facsimile, or electronic mail transmission within two (2) working days following the discovery of any failure of air pollution control equipment, process equipment, or of a process to operate in a normal manner, which results in an increase in emissions above any allowable emission limit stated in any conditions where PSD is cited as the basis of the condition. In addition, the Permittee (MSCC) must notify EPA in writing within fifteen (15) days of any such failure. The notification shall include a description of the malfunctioning equipment or abnormal operation, the date of the initial malfunction, the period of time over which emissions were increased due to the failure, the cause of the failure, the estimated resultant emissions in excess of those allowed in any conditions where PSD is cited as the basis of the condition, and the methods utilized to mitigate emissions and restore normal operations. Compliance with this malfunction notification provision shall not excuse or otherwise constitute a defense to any violation of this permit or of any law or regulation that such malfunction may cause, except as provided for in the conditions where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

64. A malfunction means a sudden and unavoidable breakdown of equipment or of a process beyond the reasonable control of the source. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

65. Emissions in excess of the limits specified in any conditions where PSD is cited as the basis of the condition shall constitute a violation of this permit and may be the subject of enforcement proceedings. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

66. Affirmative defense: In the context of an enforcement proceeding, emissions which are below the limits set forth in any condition where PSD is cited as the basis of the condition shall not be subject to penalty if the Permittee (MSCC) retains properly signed, contemporaneous operating logs or other relevant evidence and can demonstrate all of the following: i.) A malfunction caused the emissions in excess of the limits in any condition where PSD is cited as the basis of the condition; ii.) The permitted facility, including the air pollution control equipment and process equipment, was being properly operated at the time of the malfunction; iii.) Preventative maintenance was regularly performed in a manner consistent with good practice for minimizing emissions; iv.) The excess emissions were not part of a recurring pattern indicative of inadequate design, operation, or maintenance; v.) During the period of the malfunction, the permittee (MSCC) took all reasonable steps to minimize the amount and duration of emissions (including any bypass) that exceeded the emission limits provided in any condition where PSD is cited as the basis of the condition. Reasonable steps to minimize emissions could include, but are not limited to, reducing production to the lowest level practicable, reducing the material feed that results in the increased emissions, and switching to alternative, less polluting fuels. Where repairs were required, repairs were made in an expeditious fashion when the operator knew or should have known that applicable emission limitations were being exceeded. Off-shift labor and overtime must have been utilized, to the extent practicable, to ensure that such repairs were made as expeditiously as possible; and vi.) The permittee (MSCC) complied with the malfunction reporting requirements as specified in the condition where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

67. All emissions, including those associated with a malfunction which may be eligible for an affirmative defense, must be included in all emissions calculations and demonstrations of compliance with mass emission limits (e.g., daily, monthly, and annual emission limits) specified in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

68. This provision is in addition to any emergency or malfunction provision contained in any applicable requirement or elsewhere in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

69. The EPA Regional Administrator, and/or their authorized representative, upon the presentation of credential, must be permitted: (1) to enter the premises where the source is located or where any records are required to be kept under the terms and conditions of the PSD permit SJ-87-01; and (2) at reasonable times to have access to and copy any records required to be kept under the terms and conditions of PSD permit SJ 87-01; and (3) to inspect any equipment, operation, or method required in the PSD permit SJ-87-01; and (4) to sample emissions from source(s). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

70. In the event of any changes in control or ownership of facilities to be constructed or modified, this permit shall be binding on all subsequent owners and operators. The Permittee (MSCC) shall notify the succeeding owner and operator of the existence of the PSD permit SJ-87-01 and its conditions by letter, a copy of which shall be forwarded to the EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

71. The provisions of the PSD permit SJ-87-01 are severable, and , if any provisions of the permit is held invalid, the remainder of the permit must not be affected thereby. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

72. The permittee (MSCC) must construct and operate the proposed power plant in compliance with all other applicable provisions of 40 CFR Parts 52, 60, 62, and 63 and all other applicable Federal, State, and local air quality regulations. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

73. On or before the date of startup (as defined in 40 C.F.R. 60.2) of the Western Midway Sunset Cogeneration Project (WMSCP; PSD Permit No. SJ-00-01) and thereafter the Permittee (MSCC) must install, continuously operate, and maintain the Dry Low NOx (DLN) combustion systems to reduce NOx emissions from each of its three turbines. The Permittee (MSCC) shall also use proper combustion techniques for the control of CO emissions from the equipment at MSCP. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

74. Within 60 days after achieving the base load, but no later than 180 days after initial startup of all three modified turbines (as defined in 40 C.F.R. 60.2), and annually thereafter (at about the anniversary of the initial performance test), the Permittee (MSCC) must conduct performance tests (as described in 40 C.F.R. 60.8) for NOx, and CO on the exhaust stack gases. The Permittee (MSCC) must furnish the District, the California Air Resources Board (CARB), and the EPA a written report of the results of such tests. Upon written request from the Permittee (MSCC), and adequate justification, EPA may waive a specific annual test and/or allow for testing to be done at less than maximum operating capacity. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

75. Performance tests for the emissions of NOx, and CO must be conducted and the results reported in accordance with the test methods set forth in 40 C.F.R. 60.8 and 40 C.F.R. 60, Appendix A. The following test methods must be used: a.) Performance tests for the emissions of NOx must be conducted using EPA Method 1-4 and 7E. b.) Performance tests for the emissions of CO must be conducted using the EPA Methods 1-4 and 10. In lieu of the above-mentioned test methods, equivalent methods may be used with prior written approval from EPA. The Permittee (MSCC) must notify EPA in writing at least 30 days prior to such tests to allow time for the development of an approvable performance test plan and to arrange for an observer to be present at the test. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

76. For performance test purposes, sampling ports, platforms, and access must be provided by the Permittee on the emission unit exhaust system in accordance with 40 C.F.R. 60.8(e). [PSD SJ 87-01] Federally Enforceable Through Title V Permit

77. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of CO into the atmosphere in excess of the following emission limits per turbine: The more stringent of 25 ppmvd @ 15% O2 or 55 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

78. This condition applies prior to the startup of the WMSCP: On and after the date of start up any of the three turbines at MSCP must not discharge (per turbine, and based on 3-hour rolling average) into the atmosphere CO in excess of the following of any of: 1.) The more stringent of 52.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 75%. 2.) The more stringent of 62.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 35% but less than 75%. 3.) 94 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

79. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of NOx into the atmosphere in excess of the following emission limits per turbine: The more stringent of 10 ppmvd @ 15% O2 or 36.1 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

80. This condition applies prior to the startup of the WMSCP: On and after the date of start-up of any of the three turbines, MSCC must not discharge (per turbine, based on 3-hour rolling average) into the atmosphere NOx (as NO2) in excess of the following: 1.) The more stringent of 25.0 ppmvd @ 15% O2 or 85.0 pounds per hour for loads greater than or equal to 75%; 2.) The more stringent of 42.0 ppmvd @ 15% O2 or 85 pounds per hour for loads greater than or equal to 35% but less than 75%; 3.) 85 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

81. The hourly (3-hour averaging) emissions must not exceed: 1.) 94 pounds of CO and 85 pounds of NOx; 2.) All CEMs must be operating during startups and shut downs; 3.) The time, date and duration of each startup and shutdown event must be recorded. The records must include the lbs/hour calculations based on the CEM data. These records must be kept for five years following the date of such events. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

82. Prior to the date of startup and thereafter, the Permittee (MSCC) must install, maintain and operate the following continuous monitoring systems (CEMs) in the exhaust stacks: a.) Continuous monitoring systems to measure stack gas NOx , CO and O2 concentrations. The systems must meet EPA monitoring performance specification (40 C.F.R. 60.13 and 40 C.F.R. 60, Appendix B, Performance Specifications 2, 3 and 4); b.) A continuous monitoring system to measure stack gas and natural gas volumetric flow rates. The stack gas flow measurement system must meet EPA Performance Specifications for (40 C.F.R. Part 52, Appendix E). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

83. The Permittee (MSCC) must maintain a file of all measurements, including continuous monitoring systems evaluations; all continuous monitoring systems or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; performance and all other information required by 40 C.F.R. 60 Appendices A-B recorded in a permanent form suitable for inspection. The file must be retained for five years following the date of such measurements, maintenance, reports and records. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

84. The Permittee (MSCC) must notify EPA of the date on which demonstration for the continuous monitoring system performance commences (40 C.F.R. 60.13). This date must be no later than 60 days after full load operation but not later than 180 days after startup. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

85. The Permittee (MSCC) must submit a written report of all excess emissions to EPA for every calendar quarter. The quarterly report must include the following: a.) The magnitude of the excess emissions computed in accordance with 40 C.F.R. 60.13(h), any conversion factors used, and the date and time of commencement and compilation of each time period of excess emissions; b.) Specific identification of each period of excess emissions that occurs during startups, shutdowns, and malfunctions of any equipment. The nature and cause of any malfunction (if known) and the corrective action taken or preventative measures adopted must also be reported; c.) The date and time identifying each period during which the continuous monitoring system was inoperative except for zero and span checks, and the nature of the system repairs or adjustments; d.) When no excess emissions have occurred or the continuous monitoring system has not been inoperative, repaired, or adjusted, such information must be stated in the report; and e.) Excess emissions must be defined as any 3-hour period during which the average emissions of CO, as measured by the CEM exceeds the maximum emission limits set forth in the condition with a CO emission limit, where PSD is cited as the basis of the condition or any 3-hour period during which the average emissions of NOx exceed the maximum emission limits set forth in the condition with a NOx emission limit, where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

86. Excess emissions indicated by the CEM system must be considered violations of the applicable emission limit for the purpose of this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

87. The quality assurance project plan used by the Permittee (MSCC) for the certification and operation of the continuous emissions monitors, which meets the requirements of 40 C.F.R. Part 60, Appendix F, must be available upon request to EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

88. The Permittee (MSCC) must keep a monthly record of all fuel uses. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

89. The proposed power plant is subject to the federal regulations entitled Standards of Performance for New Stationary Sources (40 C.F.R. 60). The owner or operator must meet all applicable requirements of 40 C.F.R. 60 Subparts A and GG of this regulation. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

90. All three turbines will fire natural gas only. The Permittee (MSCC) must only combust pipeline quality natural gas with sulfur content (as S) below 0.75 grains per 100 dry standard cubic feet (dscf). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

91. MSCC shall have legal and operational responsibility and control of all air pollutant emitting activities of the MSCP. This responsibility shall include, but shall not be limited to the following: 1.) Operating and maintaining the project to comply with all federal, state, and local air pollution laws, regulations, orders, and other requirements; 2.) Ensuring the emissions offsets, tradeoffs, or other emission reductions required for this project under permits issued by the U.S. EPA, the District, and/or the California Energy Commission are obtained as required; or 3.) Any violations of any air pollution requirements are the legal responsibility of MSCC, in addition to any other legal responsible entity. Any proposed change to this condition shall require prior written concurrence of the US EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

92. In accordance with the emissions offset plan proposed by the applicant for the District (dated November 12, 1987) and the emissions offset plan for the U.S. EPA (dated July 21, 1987), Aera Energy LLC must not operate the following four steam generators (listed by District permit numbers S-1135-119, S-1135-122, S-1135-123, and S-1135-115) simultaneously with the firing of the MSCP turbines unless one or more of the MSCP turbines is shutdown: Andersen-Goodwin Lease: S-1135-119, S-1135-122, S-1135-123 and Neely Lease: S-1135-115 [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

93. MSCC shall maintain a record of the date(s), time(s), and duration(s) of the shutdown of any of the above mentioned steam generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

94. Aera Energy LLC shall not lease or modify the permit conditions for any of the above generators for use in the Midway Sunset Oil field, unless creditable emissions reductions (as defined in 40 C.F.R. 52.21), at a ratio of at least 1:1, are provided for emissions from those generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

95. Aera Energy LLC shall not modify any of the District Permit to Operate numbers. If any of the above steam generators are issued new Permit to Operate numbers by the District, Aera Energy LLC shall notify the U.S. EPA in writing of this action and shall make such notification upon issuance of a new Permit to Operate number. This letter shall include the original District Permit to Operate number(s) of the subject generator(s) and a copy of the new Permit to Operate issued by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

96. Aera Energy LLC shall notify the U.S. EPA in writing of the intention to sell, or potential sale, of any of the above generators and shall make such notification prior to the District's final action of the re-permitting process associated with the sale of a generators. This letter shall include the following: a.) The subject steam generator as identified by its District Permit to Operate number; b.) The name of the buyer (as identified by the company name) of the steam generator; and c.) An estimated date of the final action of the re-permitting process by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

97. The allowable incidental taking (killing, harming, or harassment) of San Joaquin kit foxes, blunt-nosed leopard lizards, and giant kangaroo rats is confined to the proposed cogeneration plant site one half mile radius around this site (on lands owned or leased by Aera Energy LLC), and associated subject cogeneration plant facilities (including pipelines, transmission lines, temporary equipment stockpiling areas, and access roads) as discussed in the project Application for Certification report (Sun Cogeneration Company and Southern Sierra Energy Company 1985). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

98. MSCC is required to implement the "Agreement on Conditions for Mitigation of the Biological Impacts of the Midway-Sunset Project" as required by the U.S. Fish and Wildlife Service (USFWS) (Memorandum dated March 16, 1987 from the USFWS to the US EPA). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

99. Any endangered species found dead should be turned in to the California Department of Fish and Game for Analysis. MSCC must also report this event to the USFWS. The USFWS may recommend amendment to the existing project actions pending results of the analysis. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

100. All correspondence as required by this permit shall be forwarded to: 1.) Director, Air Division (Attn: Air-3) EPA Region IX 75 Hawthorne Street San Francisco, CA 94105-3901 Tel: (415) 744-1291 Fax: (415) 744-1076; 2.) Chief, Stationary Source Division, California Air Resource Board P.O. Box 2815 Sacramento, CA 95812; and 3.) Air Pollution Control Officer, San Joaquin Valley Unified APCD 2700 M Street, Suite 275 Bakersfield, CA 93301-2370. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

101. Aera Energy LLC is the legal owner of the subject steam generators and of the leases on which the steam generators are located. MSCC is the legal owner of the gas turbine cogeneration facility. MSCC is jointly owned by Sun Cogeneration Limited Partnership (Sun Cogen LP) and San Joaquin Energy Company. Sun Cogen LP is managed and controlled by a wholly owned subsidiary of Aera Energy LLC. (See Condition 104) [PSD SJ-87-01] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-230-3 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1 MISC. STEAM DUMPING-ROCK BED MUFFLER OPERATION FOR MIDWAY SUNSET COGENERATION BLOWDOWN.

PERMIT UNIT REQUIREMENTS

1. Unit shall receive steam only from cogeneration units S-1135-224, '-225, & '-226. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Steam pit shall not be used for more than 6 hours in any one day. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Only treated water shall be used as cogenerators steam generators feed water. [District Rule 2080] Federally Enforceable Through Title V Permit
4. This equipment shall not be used on any day when any of the 52 steam generators and heater treaters curtailed to provide cogeneration project offsets are operated unless these units are operated in accordance with District approval. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Permittee shall keep accurate daily records indicating hours of steam pit usage. Records shall be kept, maintained, and made readily available to District staff upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. H2S emissions shall not exceed 19 lb/hr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Emission sampling limits for the following shall not exceed any of the following: PM-10 - 8.40 lb/hr, SOx (as SO2) - 42.24 lb/hr, or VOC - 1.00 lb/hr. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-231-5 **EXPIRATION DATE:** 05/31/2007

DRAFT

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
165 HP DIESEL-FIRED I.C. ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District NSR Rule and District Rule 4702] Federally Enforceable Through Title V Permit
3. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115] Federally Enforceable Through Title V Permit
5. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201, 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-235-3 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
2,520 BHP DIESEL FIRED I.C. ENGINE FOR EMERGENCY POWER GENERATION, INCLUDING: ONE CATERPILLAR MODEL #3516STD 16 CYLINDER I.C. ENGINE OPERATING A 1500 KW ELECTRIC GENERATOR, VALVE CONNECTING CRANKCASE TO INTAKE MANIFOLD, & ELAPSED OPERATING TIME METER

PERMIT UNIT REQUIREMENTS

1. Engine shall be equipped with a turbocharger. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Engine shall be equipped with an aftercooler or intercooler. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The engine shall be equipped with a positive crankcase ventilation (PCV) system or a crankcase emissions control device of at least 90% control efficiency. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The engine shall be operated with the timing retarded four degrees from the manufacturer's standard recommended timing. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The sulfur content of the diesel fuel used shall not exceed 0.0015% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
6. The engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance and testing purposes shall not exceed 6 hours per year. [District NSR Rule and District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
7. The permittee shall maintain records of hours of non-emergency operation and of the sulfur content of the diesel fuel used. Such records shall be made available for District inspection upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 gr/dscf in concentration at the point of discharge. [District Rule 4201 and Kern County Rule 404] Federally Enforceable Through Title V Permit
9. If the IC engine is fired on CARB regulated diesel fuel, with a supplier certified sulfur content less than 0.0015% by weight, the operator shall maintain copies of all fuel invoices and supplier certifications. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. If the IC engine is not fired on CARB regulated diesel fuel, with a supplier certified sulfur content less than 0.0015% by weight, then the owner or operator shall determine the sulfur content of each delivery of diesel fuel being fired in the IC engine. The sulfur content shall be determined using ASTM method D 2880-71. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
11. If the IC engine is not fired on CARB regulated diesel fuel and the sulfur content of the fuel is determined using the method specified on this permit, the records of fuel sulfur content testing results shall be kept, maintained, and made available to the district upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-266-15 **EXPIRATION DATE:** 05/31/2007

SECTION: SE24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS STEAM GENERATOR, WITH A COEN QLN-ULN BURNER, O2 CONTROLLER, AND FLUE GAS RECIRCULATION (METSON 48)

PERMIT UNIT REQUIREMENTS

1. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. {1678} This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.001 lb/MMBtu, SOx (as SO2): 0.0016 lb/MMBtu, VOC: 0.0027 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

14. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 404, 424 and 425] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed any of the following: PM10: 1.5 lb/day, SOx (as SO2): 2.4 lb/day, VOC: 4.1 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 45.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

17. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. If the unit is equipped with flue gas recirculation (FGR), whenever the unit is switched to operate with the FGR system in the closed position, compliance source testing for NOx and CO shall be conducted within 60 days of cessation of FGR operation date unless source testing with FGR system in the closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

25. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit
29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
30. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit
31. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit
32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit
33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit
34. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-267-14 **EXPIRATION DATE:** 05/31/2007

SECTION: NE35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS GAS-FIRED STEAM GENERATOR (#49) WITH A COEN MODEL QLN-ULN BURNER WITH FLUE GAS RECIRCULATION (FGR) (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. {581} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. {585} Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. {1686} This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. {1678} This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.001 lb/MMBtu, SOx (as SO2): 0.0016 lb/MMBtu, VOC: 0.0027 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

14. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 404, 424 and 425] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed any of the following: PM10: 1.5 lb/day, SOx (as SO2): 2.4 lb/day, VOC: 4.1 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

17. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

33. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-270-12 **EXPIRATION DATE:** 05/31/2007

SECTION: NW21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
210,000 GALLON FIXED ROOF OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 3.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
9. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
10. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

13. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

14. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

16. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

21. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

30. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-281-13 **EXPIRATION DATE:** 05/31/2007

SECTION: 16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
3,000 BBL FIXED ROOF SUMP REPLACEMENT TANK WITH VAPOR CONTROL SYSTEM SHARED WITH S-1135-284, -285, -286, -287, -328, '-329, '-330, '-331, '-332, '-333, '-334, '-335, AND '-336

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Vapor control system shall discharge to unit S-1135-128. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All associated tanks shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall be equipped with stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Compressor suction and knockout drum liquids shall be piped only to vapor-controlled tanks. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. Operator shall monitor vapor control system compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. Tank vapor control system efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor control system. Emissions shall be determined based on tank emission factors in EPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. All non-condensible hydrocarbon vapors shall be directed to the vapor control system authorized by permit S-1135-128 either directly through bypass piping, or through tank battery vapor control skid. [District Rule 2201] Federally Enforceable Through Title V Permit

13. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

14. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit

16. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

18. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

19. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

20. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

21. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

23. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

24. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

26. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. The fugitive VOC emissions from this tank and tank vapor control system shall not exceed 3.1 lb/day [District Rule 2201] Federally Enforceable Through Title V Permit

37. Permittee shall maintain with the permit accurate fugitive component counts for tank and the tank vapor control system and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit

38. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-283-7 **EXPIRATION DATE:** 05/31/2007

SECTION: NW17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 90 STEAM ENHANCED WELLS WITH CLOSED CASING VENTS (ANDERSON LEASE)

PERMIT UNIT REQUIREMENTS

1. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
2. All valves, fittings and connectors serving closed well vents shall be constructed and maintained in a leak free condition except during periods of actual service and repair. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
3. Wells authorized by this permit shall only be operated with closed casing vents. Well casing vents shall remain closed at all times except during periods of actual service or repair provided such activity is attended and done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
4. All produced fluids from all wells authorized by this permit shall be handled only in closed production equipment served by a 99% efficient vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Total fugitive emission of volatile organic compounds (VOC) from entire operation shall not exceed 16.4 lbm/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Wellhead (polishing rod/stuffing box) fugitive emissions from new wells shall not exceed 0.00778 lbm VOC/well/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for well vent vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c(Feb 1999) Screening Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401, excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
10. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

12. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

13. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

14. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

15. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

16. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

17. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

18. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

19. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

20. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

21. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

22. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

23. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

25. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

26. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

27. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

28. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

29. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

30. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

31. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

32. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

33. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

34. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

36. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

37. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

38. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

39. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

40. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

41. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

42. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

43. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

44. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

45. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

46. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

47. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

48. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

49. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

50. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

51. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-284-14 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF RUN TANK #5, WITH VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.1 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-285-16 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF LACT TANK #6 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.2 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-286-16 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF LACT TANK #7 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.1 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-287-16 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF LACT TANK #8 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.1 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-293-8 **EXPIRATION DATE:** 05/31/2007

SECTION: 15 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 300 STEAM DRIVE WELLS WITH CASING VENTS TIED TO VAPOR CONTROL SYSTEM INCLUDING, THREE VAPOR CONTROL SKIDS WITH SEPARATOR(S), HEAT EXCHANGER(S), FAN(S), AND COMPRESSOR(S), WITH NON-CONDENSIBLE VAPOR PIPING SHARED WITH TEOR OPERATION S-1135-124 (EXETER LEASE) CONTROLLED BY BALANCED CASING VENT COLLECTION SYSTEM OR RE-INJECTION INTO DOGGR APPROVED DISPOSAL WELL (GLOBE LEASE)

PERMIT UNIT REQUIREMENTS

1. {1294} The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. {1296} All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. {1309} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. {1769} The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. Collected liquids shall be handled, stored, and disposed of in a manner preventing detectable volatile organic compound (VOC) to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Total number of vapor collection system leaks shall not exceed 15, as per Rule 4401 - Steam-Enhanced Crude Oil Production Well Vents. [District Rule 4401] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of dates and well identifications where steam injection or well stimulation occurs and shall make such records available for District inspection. [District Rule 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall maintain an inspection and maintenance program consistent with Rule 4403 (Components Serving Light Crude Oil or Gases) for those stuffing boxes on wells which commence steam-enhancement operations on or after April 11, 1991. [District NSR Rule and District Rule 4403] Federally Enforceable Through Title V Permit

11. Volatile organic compound (VOC) emissions shall not exceed 2.32 lb/hr for casing collection fugitives and 0.33 lb/hr for polished rod fugitives. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 4401] Federally Enforceable Through Title V Permit

13. Well casing vent collection system shall also include non-condensible vapor piping from vapor control skids to re-injection skid. [District Rule 2201] Federally Enforceable Through Title V Permit

14. TEOR vapors shall be injected only in DOGGR-approved gas disposal wells. [District NSR Rule] Federally Enforceable Through Title V Permit

15. Permittee shall submit a copy of the DOGGR gas disposal well approval to the District prior to injection of any TEOR gas. [District NSR Rule] Federally Enforceable Through Title V Permit

16. Permittee shall cease injection of vapors and notify the District immediately if DOGGR disposal well approval is revoked, denied, terminated, surrendered, or otherwise altered to disallow gas disposal. [District NSR Rule] Federally Enforceable Through Title V Permit

17. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the requirements of District Rule 4401. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

18. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

19. An operator shall not operate a steam-enhanced crude oil production well unless either of the following two conditions are met: 1) The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids is connected to a VOC collection and control system as defined in Section 3.0 of this Rule or 2) the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit

20. There shall be no open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.2.2.1] Federally Enforceable Through Title V Permit

21. There shall be no components with a major liquid leak as defined in Section 3.20.2 of Rule 4401. [District Rule 4401, 5.2.2.2] Federally Enforceable Through Title V Permit

22. There shall be no components with a gas leak of greater than 50,000 ppmv. [District Rule 4401, 5.2.2.3] Federally Enforceable Through Title V Permit

23. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit

24. No leaking components (as defined in Section 5.2.2 of Rule 4401) may be used unless they have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Each hatch shall be closed at all times except during attended repair, replacement, or maintenance operations, providing such activities are done as expeditiously as possible with minimal spillage or material and VOC emissions into the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit

26. The operator shall comply with the requirements of Section 6.7 if there is any change in the description of major components or critical components. [District Rule 4401, 5.3.3] Federally Enforceable Through Title V Permit

27. Unless otherwise specified in Section 5.4, an operator shall perform all component inspections and gas leak measurements pursuant to the requirements of Section 6.3.3. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

28. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year. [District Rule 4401, 5.4.1] Federally Enforceable Through Title V Permit

29. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.2] Federally Enforceable Through Title V Permit

30. An operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: 1) An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. 2) Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of this Rule. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit

31. The operator shall also perform the following inspections: 1) An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. 2) An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service, and 3) Except for PRDs subject to the requirements of Section 5.4.4.1 of this Rule, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit

32. Components located in unsafe areas shall be inspected and repaired at the next process unit turnaround and inaccessible components shall be inspected at least annually. [District Rule 4401, 5.4.7] Federally Enforceable Through Title V Permit

33. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.4.8] Federally Enforceable Through Title V Permit

34. Upon detection of a leak, an operator shall affix a readily visible weatherproof tag to that leaking component that includes the following information: 1) The date and time of leak detection; 2) The date and time of the leak measurement; 3) For a gaseous leak, the leak concentration in ppmv; 4) For a liquid leak, whether it is a major or minor liquid leak; and 5) Whether the component is an essential component, and unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

35. The tag shall remain affixed to the leaky component until all the following requirements are met: 1) The component is repaired or replaced, 2) The component is re-inspected as set forth in Section 6.3, and 3) The component is found to be in compliance with this Rule. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit

36. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0, an operator shall comply with at least one of the following three requirements as soon as practicable but not later than the time period specified in Table 4: 1) Repair or replace the leaking component, 2) Vent the leaking component to a VOC collection and control system as defined in Section 3.0, or 3) Remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

38. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit

39. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4. [District Rule 4401, 5.5.5] Federally Enforceable Through Title V Permit

40. The time of the initial leak detection shall be the start of the repair period specified in Table 4. [District Rule 4401, 5.5.6] Federally Enforceable Through Title V Permit

41. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit

42. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

43. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

44. The operator of any steam-enhanced crude oil production well shall maintain an inspection log pursuant to Section 6.4 of Rule 4401. [District Rule 4401, 6.1.4] Federally Enforceable Through Title V Permit

45. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration [District Rule 4401, 6.1.5] Federally Enforceable Through Title V Permit

46. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

47. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 44011, 6.2.1] Federally Enforceable Through Title V Permit

48. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401, 6.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401, 6.2.3] Federally Enforceable Through Title V Permit

50. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

51. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

52. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

53. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.4] Federally Enforceable Through Title V Permit

54. The operator shall maintain an inspection log in which the operator records at least all of the following for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type, 2) The location, type and name or description of each leaking component and description of any unit where the leaking component is found, 3) The date of leak detection and the method of leak detection, 4) For gaseous leaks, the leak concentration in ppmv and, for liquids leaks, whether the leak is major or minor, 5) The date of repair, replacement or removal from operation of leaking components, 6) The identity and location of essential components and critical components as defined in this Rule, found leaking, that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than 1 year after detection, whichever comes earlier, 8) The date or re-inspection and the leak concentration in ppmv after the component is repaired or replaced, 9) The inspectors name, business mailing address, and business telephone number, and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

55. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

56. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

57. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

58. A listing of steam enhanced wells connected to this system and DOGGR wells used for re-injection of TEOR vapors shall be made availible for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-299-11 **EXPIRATION DATE:** 05/31/2007

SECTION: NE35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR GAS-/LPG-FIRED STEAM GENERATOR #50 WITH A COEN MODEL QLN-ULN LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM AND AN OXYGEN CONTROLLER (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. {518} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.014 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, VOC: 0.003 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

12. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 21.0 lb/day, SOx (as SO2): 1.5 lb/day, VOC: 4.5 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

15. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

24. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, and 4306] Federally Enforceable Through Title V Permit

25. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

27. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

29. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

31. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-301-13 **EXPIRATION DATE:** 05/31/2007

SECTION: NW21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
281,400 GALLON FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 4.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
11. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

13. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

14. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

15. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

17. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080]

20. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

22. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

31. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-302-10 **EXPIRATION DATE:** 05/31/2007

SECTION: SE22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR (#5) WITH A COEN MODEL QLN-ULN ULTRA LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) (BUENA FE LEASE)

PERMIT UNIT REQUIREMENTS

1. {518} All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.005 lb/MMBtu, SOx (as SO2): 0.0006 lb/MMBtu, VOC: 0.0028 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

12. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 7.5 lb/day, SOx (as SO2): 0.9 lb/day, VOC: 4.2 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

15. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

17. Permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

18. If the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. Permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, and 4306] Federally Enforceable Through Title V Permit

25. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, and 4306, 6.2] Federally Enforceable Through Title V Permit

27. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

29. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

31. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.005 lb/MMBtu, SOx (as SO2): 0.0006 lb/MMBtu, VOC: 0.0028 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

12. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 7.5 lb/day, SOx (as SO2): 0.9 lb/day, VOC: 4.2 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

15. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-305-9 **EXPIRATION DATE:** 05/31/2007

SECTION: NW36 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NAT GAS-FIRED STEAM GENERATOR # 52, WITH A COEN QLN-ULN LOW NOX BURNER, WITH FLUE GAS RECIRCULATION, (PRU LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rule 108.1 (Kern)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

24. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, and 4306] Federally Enforceable Through Title V Permit

25. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

27. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

29. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320] Federally Enforceable Through Title V Permit

31. On and after July 1, 2010, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-322-3 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF WASH TANK T-101, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emissions rate calculated using EPA's Protocol for Equipment Leak Emission Estimates, Table 2-4, Oil and Gas Production Operations Average Emission Factors, shall not exceed 3.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation shall include vapor recovery system described on the requirements for permit unit S-1135-70. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All tanks and separators shall vent only to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
6. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
7. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. {2426} The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

19. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-323-4 **EXPIRATION DATE:** 05/31/2007

DRAFT

EQUIPMENT DESCRIPTION:
3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-129 - ANDERSON GOODWIN LEASE

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall vent only to the vapor control skid inlet in permit S-1135-129. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule and District Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.26 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule and District Rule 4623] Federally Enforceable Through Title V Permit
9. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
10. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
11. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: t = 2.3 V / Q, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

13. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

14. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons (1,589.874 cubic meters) and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-325-2 **EXPIRATION DATE:** 05/31/2007

EQUIPMENT DESCRIPTION:
3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK, HANDLING MAXWELL LEASE PRODUCTION, SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W & S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.47 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
8. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. This unit has a storage capacity less than 420,000 gallons (1,589.874 cubic meters) and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-326-3 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF WASH TANK T-102, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Fugitive emissions calculated using EPA's Protocol for Equipment Leak Emission Estimates, Table 2-4, Oil and Gas Production Operations Average Emission Factors, shall not exceed 3.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank shall vent only to the vapor recovery system described in the requirements for permit unit S-1135-70. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623] Federally Enforceable Through Title V Permit
6. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
7. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

18. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-327-2 **EXPIRATION DATE:** 05/31/2007

EQUIPMENT DESCRIPTION:
905 BBL FWKO VESSEL (V-100) CONNECTED TO VAPOR RECOVERY SYSTEM LISTED ON S-1135-70

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102] Federally Enforceable Through Title V Permit
2. The tank shall vent only to the vapor control system listed on S-1135-70. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank using California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2C: Oil and Gas Production Screening Value Ranges (<10,000 ppmv) Emission Factors. [District Rule 4623] Federally Enforceable Through Title V Permit
4. There shall be no leaks exceeding 10,000 ppmv from fugitive emissions components associated with tank. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 4623] Federally Enforceable Through Title V Permit
6. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.11, 3.17, and 3.18] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 4623] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
14. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive quarterly inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
18. Permittee shall maintain records of annual tank inspections, maintenance, and cleaning to document the participation in the Rule 4623 Fixed Roof Tank Preventative Inspection, Maintenance and Tank Interior Cleaning Program. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
19. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 3 of Rule 4623. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
20. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-328-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL FLOW SPLITTER PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-329-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL FWKO PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-330-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL "GAS BUSTER" PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-331-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #1 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-332-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #2 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-333-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #4 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-334-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #6 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-335-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #7 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-336-1 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #8 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-337-2 **EXPIRATION DATE:** 05/31/2007

EQUIPMENT DESCRIPTION:
3,000 BBL (126,000 GALLON) FIXED ROOF STOCK TANK ID# WS-04, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.2 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
8. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. This unit has a storage capacity less than 420,000 gallons (1,589.874 cubic meters) and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40 CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

21. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

ATTACHMENT B

Previous Title V Operating Permit

San Joaquin Valley
Air Pollution Control District

FACILITY: S-1135-0-2 **EXPIRATION DATE:** 05/31/2007

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020. [District Rule 2010, 3.0 and 4.0; 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring, where applicable, that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.6.1] Federally Enforceable Through Title V Permit

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520. [District Rules 2520, 9.6.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.8] Federally Enforceable Through Title V Permit

13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.9.1] Federally Enforceable Through Title V Permit

14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.9.3] Federally Enforceable Through Title V Permit

15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.9.4] Federally Enforceable Through Title V Permit

16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.9.5] Federally Enforceable Through Title V Permit

17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.10] Federally Enforceable Through Title V Permit

18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.14.2.1] Federally Enforceable Through Title V Permit

19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.14.2.2] Federally Enforceable Through Title V Permit

20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.14.2.3] Federally Enforceable Through Title V Permit

21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.14.2.4] Federally Enforceable Through Title V Permit

22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101, by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

23. No person shall supply, sell, solicit or apply any architectural coating, except specialty coatings, that contains more than 250 grams of VOC per liter of coating (less water and exempt compounds, and excluding any colorant added to tint bases), or manufacture, blend, or repackage such coating with more than 250 grams of VOC per liter (less water and exempt compounds, and excluding any colorant added to tint bases) for use within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. Special Coating Limitations: No person shall apply, sell, solicit, or offer for sale any specialty architectural coating listed in the Table of Standards (District Rule 4601, Table 1 and Table 2), nor manufacture, blend, or repackage such coating for use within the District, which contains VOCs (less water and exempt compounds, excluding any colorant added to tint bases) in excess of the specified limits listed in Table 1 (grams of VOC per liter of coating as applied less water and exempt compounds, excluding any colorant added to tint bases) and in Table 2 (grams of VOC per liter of material), except as provided in Section 5.3 of Rule 4601. [District Rule 4601, 5.2] Federally Enforceable Through Title V Permit

25. All VOC-containing materials shall be stored in closed containers when not in use. In use includes, but is not limited to: being accessed, filled, emptied, maintained or repaired. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

26. A person shall not use VOCs for the cleanup of spray equipment unless equipment for collection of the cleaning compounds and minimizing its evaporation to the atmosphere is used. [District Rule 4601, 5.5] Federally Enforceable Through Title V Permit

27. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.2. [District Rule 4601, 6.1 and 6.2] Federally Enforceable Through Title V Permit

28. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

29. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

30. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

31. Disturbances of soil related to any construction, demolition, excavation, extraction, or water mining activities shall comply with the requirements for fugitive dust control in SJVUAPCD District Rule 8020, unless specifically exempted under section 4 of Rule 8020. [District Rule 8020] Federally Enforceable Through Title V Permit

32. Outdoor handling and storage of any bulk material which emits dust shall comply with the requirements of SJVUAPCD Rule 8030, unless specifically exempted under section 4 of Rule 8030. [District Rule 8030] Federally Enforceable Through Title V Permit

33. Any paved road over 3 miles in length, and any unpaved roads over half a mile in length, constructed after October 10, 1993 shall use the design criteria and dust control measures of, and comply with the administrative requirements of, SJVUAPCD Rule 8060 unless specifically exempted under section 4 of Rule 8060. [District Rule 8060] Federally Enforceable Through Title V Permit

34. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

35. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.17] Federally Enforceable Through Title V Permit

36. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

37. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permit shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

38. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92);2070 , section 7.0 (12/17/92); 2080 (12/17/92); 4101 (12/17/92); 4601, sections 5.1, 5.2, 5.4, 5.5, 6.1, and 6.2 (9/17/97); 8020 (4/25/96); 8030 (4/25/96); 8060 (4/25/96); A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

41. Should the facility, as defined in 40 CFR 68.3, become subject to Part 68, then the owner or operator shall submit a risk management plan (RMP) by the date specified in 40 CFR 68.10. The facility shall certify compliance as part of the annual certification as required by 40 CFR part 70. [40 CFR 68] Federally Enforceable Through Title V Permit

42. On August 31, 2002, the initial Title V permit was issued, the reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of reporting period. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

43. Facilities S-1135 and S-1547 constitute one stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-3-22 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
8.4 MMBTU/HR (DERATED TO 5 MMBTU/HR) NATURAL GAS FIRED HEATER TREATER #1 WITH A MAXON MODEL M-PAKT BURNER WITH VARIABLE FREQUENCY DRIVE (VFD) BLOWER, SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
5. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. To demonstrate compliance with this requirement the operator shall do one of the following: fire the unit only on PUC or FERC regulated natural gas; or test the sulfur content of each fuel source and demonstrate the sulfur content does not exceed 3.3% by weight for gaseous fuels; or determine that the concentration of sulfur compounds in the exhaust does not exceed the concentration limit by a combination of source testing and fuel analysis. [District Rule 2520, 9.3.2; District Rule 4301, 5.2.1; District Rule 4801, 3.1; and Kern County Rule 407] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 2520, 9.3.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

11. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements of SJVUAPCD Rules 4201 (Amended December 17, 1992), and 4301 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. The rated heat input of the unit shall be reduced to no greater than 5.0 MMBtu/hr. [District NSR Rule] Federally Enforceable Through Title V Permit

16. Fuel consumption shall be verified by the use of a non-resettable, totalizing mass or volumetric flow meter. [District NSR Rule] Federally Enforceable Through Title V Permit

17. Emission rates, except during startup and shutdown shall not exceed the following: PM10: 0.0076 lb/MMBtu, SOx (as SO2): 0.00285 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, VOC: 0.0055 lb/MMBtu, and CO: 0.033 lb/MMBtu or 45 ppmv @ 3% O2. [District NSR Rule, District Rule 4301, District Rule 4201, District Rule 4307, and Kern County Rule 404]

18. Emission rates shall not exceed any of the following: NOx (as NO2): 4.3 lb/day, SOx (as SO2): 0.3 lb/day, PM10: 0.9 lb/day, CO: 4.0 lb/day, VOC: 0.7 lb/day. [District Rule 2201]

19. The permittee shall maintain records of fuel type and quantity for each day of operation, in the format approved by the District. [District NSR Rule] Federally Enforceable Through Title V Permit

20. The duration of start-up and shutdown shall not exceed one hour each per occurrence. [District Rule 4307]

21. The permittee shall maintain records of the duration of each start-up and shutdown that exceed one hour per occurrence for a period of five years and make such records readily available for District inspection upon request. [District Rule 4307]

22. The permittee shall monitor, at least once per month, the units's operational characteristics recommended by the manufacturer and approved by the APCO. [District Rule 4307]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The permittee shall tune the unit at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year. The unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. In lieu of tuning the unit twice each calendar year, the owner/operator shall monitor the emissions with a portable NOx analyzer at least twice per calendar year and adjust the unit's operating parameters accordingly to assure compliance with the emission limits of this rule. [District Rule 4307]

24. If the unit is tuned for compliance, the permittee shall maintain records of: (1) the date that tune-ups are performed, (2) a description of any corrective action taken to maintain the emissions within the acceptable range, and (3) a record of the operational characteristics monitored. [District Rule 4307]

25. If NOx emissions are monitored for compliance, the permittee shall maintain records of: (1) the date and time of the NOx measurements, (2) the O2 concentration in percent and the measured NOx concentration corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, (5) a description of any corrective action taken to maintain the emissions within the acceptable range, and (6) a record of the operational characteristics monitored. [District Rules 4307]

26. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4307. Notwithstanding the requirements above and per Section 5.5.4 of Rule 4307, for units with a cyclical firing period that routinely interrupts fuel flow as part of its normal operation, source testing may commence sooner than specified above and continue through its normal cyclical firing period. [District Rule 4307]

27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4307]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-5-29 **EXPIRATION DATE:** 05/31/2007

SECTION: SW22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #41 DIS #11867-75 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR (BUENA FE LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District NSR Rule] Federally Enforceable Through Title V Permit

11. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District NSR Rule] Federally Enforceable Through Title V Permit

12. Records of monthly and annual heat input of the unit shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 0.014 lb/MMBtu or SOx (as SO2): 0.001 lb/MMBtu. [District NSR Rule; District Rule 2520, 9.3.2; District Rule 4201, 3.0; District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit

14. Emission rates, except during startup and shutdown and refractory curing, shall not exceed any of the following: NOx (as NO2): 15 ppmv @ 3% O2, VOC: 0.003 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District NSR Rule and District Rules 2520, 9.3.2; 4301, 5.2; 4305, 5.1; 4306, 5.1.1and 4351, 5.1] Federally Enforceable Through Title V Permit

15. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306, 5.3.3.2] Federally Enforceable Through Title V Permit

16. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080, 3.0] Federally Enforceable Through Title V Permit

17. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080, 3.0 and 4306, 6.1.4] Federally Enforceable Through Title V Permit

18. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District NSR Rule and District Rules 4201, 3.0; 4301; 4405, 5.1; 4406, 5.1.1 and 4801, 3.1] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Measurement shall be made with the FGR system in the mode of operation (closed or open) in which it was used in the preceding 30 days. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 2520] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. If either the NOX and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. Source testing to measure NOx, and CO emissions shall be conducted within 60 days of initial start-up of this unit. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit

26. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

27. If the unit is equipped with flue gas recirculation (FGR), whenever the unit is switched to operate with the FGR system in the closed position, compliance source testing for NOx and CO shall be conducted within 60 days of cessation of FGR operation date unless source testing with FGR system in the closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

28. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

29. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

30. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306, 6.2] Federally Enforceable Through Title V Permit

32. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

33. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

34. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-6-27 **EXPIRATION DATE:** 05/31/2007

SECTION: 35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #43 WITH A COEN QLN-ULN LOW NOX BURNER AND FLUE GAS RECIRCULATION (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculate emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculate emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2, 4305, 6.2.1, and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.074 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406 and 4801, and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

15. Emission rates during startup, shutdown, and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406 and 4801, and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

16. Emission rates shall not exceed any of the following: PM10: 111.0 lb/day, SOx (as SO2): 7.5 lb/day, VOC: 10.5 lb/day, NOx (as NO2): 54.0 lb/day or 7,884 lb/year, or CO: 49.5 lb/day or 13,140 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

18. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Permittee shall maintain records of duration of each start-up, shutdown, and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081 and 4305, 6.2] Federally Enforceable Through Title V Permit

29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-8-33 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS FIRED NATIONAL STEAM GENERATOR #17, DIS# 9236-68, WITH NORTH AMERICAN BURNER (MAXWELL LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
2. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1, and 4306, 6.2.1] Federally Enforceable Through Title V Permit

11. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed the following: PM10: 0.102 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, NOx (as NO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201 and 4301, 5.2.2 and 5.2.3; Kern County Rule 424; and District Rule 4201] Federally Enforceable Through Title V Permit

16. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201, 4305, and 4306, 5.4.4] Federally Enforceable Through Title V Permit

17. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306, 5.2] Federally Enforceable Through Title V Permit

18. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

19. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

20. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306, 5.4.3] Federally Enforceable Through Title V Permit

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306, 6.1.2] Federally Enforceable Through Title V Permit

22. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306, 6.1.3] Federally Enforceable Through Title V Permit

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-9-31 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #18, DIS# 9237-68 (MAXWELL LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
2. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2; 4305, 6.2.1; and 4306, 6.2.1] Federally Enforceable Through Title V Permit

11. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306, 6.2] Federally Enforceable Through Title V Permit

12. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. Emission rates shall not exceed the following: PM10: 0.102 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, NOx (as NO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201 and Rule 4301, 5.2.2 and 5.2.3; Kern County Rule 424; and District Rule 4201] Federally Enforceable Through Title V Permit

17. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201, 4305, and 4306, 5.4.4] Federally Enforceable Through Title V Permit

18. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306, 5.2] Federally Enforceable Through Title V Permit

19. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

20. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

21. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306, 5.4.3] Federally Enforceable Through Title V Permit

22. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306, 6.1.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306, 6.1.3] Federally Enforceable Through Title V Permit

24. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306, 6.1] Federally Enforceable Through Title V Permit

25. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-10-30 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #19, DIS# 9238 68 (MAXWELL LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
2. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3246, D 4084, or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2, 4305, 6.2.1, and 4306, 6.2.1] Federally Enforceable Through Title V Permit

11. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed the following: PM10: 0.102 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, NOx (as NO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201 and 4301, 5.2.2 and 5.2.3; Kern County Rule 424; and District Rule 4201] Federally Enforceable Through Title V Permit

16. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement.. [District Rules 2201, 4305, and 4306, 5.4.4] Federally Enforceable Through Title V Permit

17. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306, 5.2] Federally Enforceable Through Title V Permit

18. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

19. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306, 5.2.1] Federally Enforceable Through Title V Permit

20. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306, 5.4.3] Federally Enforceable Through Title V Permit

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306, 6.1.2] Federally Enforceable Through Title V Permit

22. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306, 6.1.3] Federally Enforceable Through Title V Permit

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306, 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-12-31 **EXPIRATION DATE:** 05/31/2007

SECTION: 35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #45 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR AND OPTIONAL SO2 SCRUBBER (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

13. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

15. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

16. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

17. During a "shakedown" period not to exceed 60 calendar days from initial operation of the modifications authorized by this ATC, NOx emission rate shall not exceed 30 ppmvd @ 3% O2 or 0.036 lb/MMBtu. The shakedown period shall be concluded prior to the applicable Rule 4306 compliance deadline selected for this unit. Permittee shall maintain a record of the date of initial operation and shall make such records readily available for District inspection upon request. [District Rule 4306] Federally Enforceable Through Title V Permit

18. Emission rates shall not exceed any of the following: PM10: 0.080 lb/MMBtu or SOx (as SO2): 0.080 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301] Federally Enforceable Through Title V Permit

19. Emission rates, except during startup and shutdown and refractory curing, shall not exceed any of the following: NOx (as NO2): 15 ppmv @ 3% O2, VOC: 0.007 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4301, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit

20. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 2201, 4201, 4301, 4405, 4406 and 4801] Federally Enforceable Through Title V Permit

21. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

22. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

24. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Measurement shall be made with the FGR system in the mode of operation (closed or open) in which it was used in the preceding 30 days. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 2520] Federally Enforceable Through Title V Permit

25. If periodic monitoring of NOX, CO, and O2 concentrations is utilized and the NOX and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

29. Source testing to measure NOx, and CO emissions shall be conducted within 60 days of initial start-up of this unit. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit

30. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

31. If the unit is equipped with flue gas recirculation (FGR), whenever the unit is switched to operate with the FGR system in the closed position, compliance source testing for NOx and CO shall be conducted within 60 days of cessation of FGR operation date unless source testing with FGR system in the closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

32. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

34. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

35. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306, 6.2] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-13-32 **EXPIRATION DATE:** 05/31/2007

SECTION: 26 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #44 WITH COEN QLN-ULN 3.2 BURNER (WILBERT LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit when it is dormant. [District Rule 4306] Federally Enforceable Through Title V Permit
2. Operator shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

11. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Scrubber liquor pH shall be maintained between 6.15 and 7.5 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

18. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District Rule 2201] Federally Enforceable Through Title V Permit

19. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

20. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rule 2201] Federally Enforceable Through Title V Permit

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

22. Emission rates shall not exceed either of the following: PM10: 0.080 lb/MMBtu or SOx (as SO2): 0.361 lb/MMBtu. [District Rules 2201, 2520, 4201, and 4301] Federally Enforceable Through Title V Permit

23. Emission rates, except during startup and shutdown and refractory curing, shall not exceed the following: NOx (as NO2): 15 ppmv @ 3% O2, VOC: 0.007 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4301, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit

24. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

27. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 2201, 4201, 4301, 4405, 4406 and 4801] Federally Enforceable Through Title V Permit

28. Permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Measurement shall be made with the FGR system in the mode of operation (closed or open) in which it was used in the preceding 30 days. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 2520] Federally Enforceable Through Title V Permit

29. If the NOx and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. Permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

32. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

33. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

34. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

36. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

37. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

38. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306, 6.2] Federally Enforceable Through Title V Permit

39. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

40. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

41. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-17-17 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION, SERVING 175 STEAM ENHANCED WELLS, INCLUDING PIPING TO INCINERATING STEAM GENERATORS, FOR REINJECTION OF NONCONDENSIBLE VAPORS, OR FOR BALANCING OF WELL VENTS.

PERMIT UNIT REQUIREMENTS

1. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. TEOR gases shall be re-injected to the formation, incinerated in steam generators #'s S-1135-26, -27,-28,-266 and S-1547-1089, contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
3. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
4. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
5. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
6. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
7. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
8. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended December 14, 2006) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
9. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
10. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

12. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

13. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components; and the efficiency of destruction devices determined by USEPA Method 18 as applicable. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

14. VOC content shall be determined using ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by CARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

15. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

18. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

19. Operation shall include gas/liquid separators, condensate knockouts, and compressor knockouts. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Operation shall include, water-cooled heat exchanger, air-cooled heat exchangers, and gas compressors. [District Rule 2201] Federally Enforceable Through Title V Permit

21. Operation shall include 3 pressure type condensate storage tanks (rated @ 50 psig 650 deg F), 3 - 25 bbl open top emergency drain tanks, and non condensible piping to approved incineration devices. [District Rule 2201] Federally Enforceable Through Title V Permit

22. Operation shall include vapor compressor bypass piping, and casing vapor collection piping to 175 wells. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. TEOR gas injection system shall include piping, reinjection knockout vessels, interstage coolers and gas/liquid separators, reinjection gas compressors, and liquid transfer pumps. [District Rule 2201] Federally Enforceable Through Title V Permit
24. Operation shall include H2S chemical contractors/ scrubbing pressure vessels. [District Rule 2201] Federally Enforceable Through Title V Permit
25. Permittee shall maintain a listing of all steam enhanced wells connected to this system. [District Rule 2080] Federally Enforceable Through Title V Permit
26. All components of well vent vapor collection and control systems shall be maintained in good working condition. [District Rule 4401] Federally Enforceable Through Title V Permit
27. Casing vent vapor collection piping (includes M1, M2, and M3) shall be interconnected such that flow can be directed to all parts of system. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Water/VOCs condensate from all liquid knockout drums shall be pumped to production manifold. [District Rule 2201] Federally Enforceable Through Title V Permit
29. Injection of collected vapors shall not commence until permittee has received valid Department of Oil & Gas (DOG) approval for injection of gases. [District Rule 2080] Federally Enforceable Through Title V Permit
30. TEOR gas injected into formation shall only be performed using DOGGR approved injection wells. [District Rule 2080] Federally Enforceable Through Title V Permit
31. Permittee shall cease injecting vapors & notify the District immediately if DOG injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit
32. Gas compressor motors shall total at least 70 hp. [District Rule 2201] Federally Enforceable Through Title V Permit
33. Block valve upstream of free condensate knockout shall activate and shut in casing vapor at 40 psig system pressure. [District Rule 2201] Federally Enforceable Through Title V Permit
34. Non-condensibles shall be introduced only into gas section of dual fuel burners of steam generators for incineration. [District Rule 2201] Federally Enforceable Through Title V Permit
35. Vapors extracted from Metson tank battery, tanks S-1135-70 shall be piped to casing vent collecting system. [District Rule 2201] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-18-16 **EXPIRATION DATE:** 05/31/2007

SECTION: 26 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 140 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (WILBERT LEASE)

PERMIT UNIT REQUIREMENTS

1. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
3. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. Steam-enhanced crude oil production well vents shall be closed, except when temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, and the front line production equipment downstream of the wells that carry produced fluids be connected to a VOC collection and control system. Alternatively, steam-enhanced crude oil production well vents shall be open and the well vents connected to a VOC collection and control system. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit
8. The operator shall be in violation of Rule 4401 if any District inspection or operator inspection, conducted as a requirement of this rule, demonstrates that one or more of the leak standard conditions set forth in section 5.6.2 exists. [District Rule 4401, 5.6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. There shall not be an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.6.2.1] Federally Enforceable Through Title V Permit

10. For pressure relief devices (PRDs) a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 400 to 10,000 ppmv. For components other than PRDs a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 2,000 to 10,000 ppmv. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak, except seal lubricant, that is not a major liquid leak and drips liquid at a rate of more than three drops per minute. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component into a container is not considered a leak provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 3.20] Federally Enforceable Through Title V Permit

11. There shall be no components with major liquid leaks or with gas leaks greater than 50,000 ppmv. [District Rule 4401, 5.6.2.2 and 5.6.2.3] Federally Enforceable Through Title V Permit

12. There shall not be more minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv than the following: 3 leaks for 1 - 25 wells, 6 leaks for 26 - 50 wells, 8 leaks for 51 - 100 wells, 10 leaks for 101 - 250 wells, 15 leaks for 251 - 500 wells, and 1 leak for each 20 wells (with a minimum of 50 wells test) for more than 500 wells connected to a VOC collection and control system. [District Rule 4401, 5.6.2.4] Federally Enforceable Through Title V Permit

13. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

14. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.7.2] Federally Enforceable Through Title V Permit

15. Except for pipes and unsafe-to-monitor components, all other components shall be inspected pursuant to the requirements of section 6.3.3 at least once every year. [District Rule 4401,5.8.1] Federally Enforceable Through Title V Permit

16. All pipes shall be visually inspected at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.2] Federally Enforceable Through Title V Permit

17. The operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. [District Rule 4401, 5.8.3.1] Federally Enforceable Through Title V Permit

18. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.3.2] Federally Enforceable Through Title V Permit

19. The operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. The operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.8.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. The operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. The operator shall inspect a component, other than PRDs, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. The operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.8.4.2, 5.8.4.3, 5.8.5] Federally Enforceable Through Title V Permit

21. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.8.6] Federally Enforceable Through Title V Permit

22. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.1, 5.9.2] Federally Enforceable Through Title V Permit

23. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. Except for leaking critical components or leaking essential components, if the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4401, 5.9.3, 5.9.4] Federally Enforceable Through Title V Permit

24. The operator shall repair minor gas leaks within 14 days, major gas leaks which less than or equal to 50,000 ppmv within 5 days., major gas leaks which are greater than 50,000 ppmv within two days, minor liquid leaks within 3 days, and major liquid leaks within 2 days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4401, 5.9.4, 5.9.5, and 5.9.6] Federally Enforceable Through Title V Permit

25. If a leaking component is an essential component or a critical component which cannot be shut down immediately for repairs, and after being minimized still exceeds the applicable leak standard, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround or no later than one year from the date of original leak detection, which ever is earlier. [District Rule 4401, 5.9.7] Federally Enforceable Through Title V Permit

26. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

27. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

29. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 44019, 6.1.6] Federally Enforceable Through Title V Permit

30. The operator shall maintain a copies of training records and of the latest APCO-approved Operator Management Plan (OMP) at the facility and make such available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.7, 6.1.8] Federally Enforceable Through Title V Permit

31. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. The operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.11] Federally Enforceable Through Title V Permit

32. Except as set forth elsewhere in this permit, the operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

33. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual control efficiency testing requirement if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare, or if the vapor collection and control does not have a VOC destruction device. [District Rule 4401, 6.2.2, 6.2.3] Federally Enforceable Through Title V Permit

34. An operator seeking approval of a waiver of the annual control efficiency testing requirement shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401, 6.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

36. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

37. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

38. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

39. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

40. The operator shall maintain an APCO approved Operator Management Plan (OMP). The OMP shall include, at a minimum, a description of all wells and all associated VOC collection and control systems subject to this rule, and all wells and all associated VOC collection and control systems that are exempt; an identification and description of any known hazard that might affect the safety of an inspector; except for pipes, the number of components that are subject to this rule by component type; except for pipes, the number and types of major components, inaccessible components, unsafe-to-monitor components, critical components, and essential components that are subject to this rule and the reason(s) for such designation; except for pipes, the location of components subject to the rule (components may be grouped together functionally by process unit or facility description); except for pipes, components exempt pursuant to Section 4.8 (except for components buried below ground) may be described in the OMP by grouping them functionally by process unit or facility description (the results of any laboratory testing or other pertinent information to demonstrate compliance with the applicable exemption criteria for components for which an exemption is being claimed pursuant to Sections 4.8 shall be submitted with the OMP); a detailed schedule of an operator's inspections of components to be conducted as required by this rule and whether the operator inspections of components required by this rule will be performed by a qualified contractor or by an in-house team; a description of the training standards for personnel that inspect and repair components; and a description of the leak detection training for conducting the test method specified in Section 6.3.3 for new operators, and for experienced operators, as necessary. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

41. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

42. TEOR gas VOC content shall not exceed 4.1% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit

43. Fugitive volatile organic compound (VOC) emissions from this steam-enhanced crude oil production operation shall not exceed 4.3 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

44. Permittee shall maintain with the permit accurate fugitive component counts of components in gas service and resulting emissions calculated using the emission factors in the "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c, dated 2/99. (CAPCOA document). [District Rule 2201] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-20-25 **EXPIRATION DATE:** 05/31/2007

SECTION: NE35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
STEAM ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING 295 STEAM ENHANCED WELLS (KENDON LEASE), INCLUDING A FIN FAN COOLER, GAS/LIQUID SEPARATORS, AND ASSOCIATED PIPING

PERMIT UNIT REQUIREMENTS

1. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
5. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
6. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
7. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
8. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
9. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

11. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

12. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components; and the efficiency of destruction devices determined by USEPA Method 18. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

13. VOC content shall be determined using ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by CARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

14. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

15. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

18. Operation shall include water-cooled heat exchangers, air-cooled heat exchangers, and gas compressors. [District Rule 2201] Federally Enforceable Through Title V Permit

19. Operation shall include pressure type condensate storage tanks, pressure type oil/water separators, vapor piping to vapor control system listed on S-1547-460 and uncondensed vapor piping to incineration in steam generators S-1135-12 and S-1135-24 or vapor disposal well(s) or to steam generators S-1547-234, S-1547-238 and S-1547-248. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Maximum VOC content of vapor in the vapor control system piping shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit

21. Operation shall include H2S chemical contactor/scrubber vessels. [District Rule 2201] Federally Enforceable Through Title V Permit

22. Condensate storage tanks and oil-water separator shall vent to vapor control system or be equipped with equivalent vapor control provisions approved by District. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Water/VOC condensate from all liquid knockout drums shall be pumped to production manifold. [District Rule 2201] Federally Enforceable Through Title V Permit
24. An I &M program consistent with Rule 4403 section 5.1 requirements shall be implemented for all new well stuffing boxes. [District Rule 2201] Federally Enforceable Through Title V Permit
25. Permittee shall maintain with the permit an accurate listing of all steam enhanced wells connected to the casing vent control system. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Permittee shall make listing of all steam enhanced wells connected to the casing vent control system available upon District request. [District Rules 1070 and 2520, 9.4] Federally Enforceable Through Title V Permit
27. Well casing vents may be closed provided produced fluids are handled only in production facilities with District approved emission control systems achieving at least 99% control. [District Rule 4401] Federally Enforceable Through Title V Permit
28. Well vent vapor collection system piping may be isolated from steam generators and injection compressors for balanced operation between wells provided all produced fluids are handled only in production facilities with District approved emission control systems achieving at least 99% control. [District Rule 4401] Federally Enforceable Through Title V Permit
29. Injection of collected vapors shall only be conducted under a valid Department of Oil & Gas (DOG) approval for injection of gases. [District Rule 2080] Federally Enforceable Through Title V Permit
30. VOC emission rate shall not exceed 114.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-21-11 **EXPIRATION DATE:** 05/31/2007

SECTION: 22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION OPERATION SERVING UP TO 153 STEAM-ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (BUENA FE FEE LEASE)

PERMIT UNIT REQUIREMENTS

1. Maximum VOC content of TEOR vapors shall not exceed 32.3% by weight of Total Organic Compounds (TOC). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed five (5). [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive volatile organic compound (VOC) emissions from this steam-enhanced crude oil production operation shall not exceed 14.6 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Permittee shall maintain with the permit accurate fugitive component counts of components in gas service and resulting emissions calculated using the emission factors in the "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c, dated 2/99. (CAPCOA document). [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain with the permit a current listing of all steam-enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
7. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
8. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
10. Compliance with permit conditions in the Title V permit shall be deemed in compliance with District Rule 4401 (Amended December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The requirements of District Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit because it is not an in situ combustion well vent. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. Steam-enhanced crude oil production well vents shall be closed, except when temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, and the front line production equipment downstream of the wells that carry produced fluids be connected to a VOC collection and control system. Alternatively, steam-enhanced crude oil production well vents shall be open and the well vents connected to a VOC collection and control system. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

13. The operator shall be in violation of Rule 4401 if any District inspection or operator inspection, conducted as a requirement of this rule, demonstrates that one or more of the leak standard conditions set forth in section 5.6.2 exists. [District Rule 4401, 5.6.1] Federally Enforceable Through Title V Permit

14. There shall not be an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.6.2.1] Federally Enforceable Through Title V Permit

15. For pressure relief devices (PRDs) a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 400 to 10,000 ppmv. For components other than PRDs a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 2,000 to 10,000 ppmv. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak, except seal lubricant, that is not a major liquid leak and drips liquid at a rate of more than three drops per minute. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component into a container is not considered a leak provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 3.20] Federally Enforceable Through Title V Permit

16. There shall be no components with major liquid leaks or with gas leaks greater than 50,000 ppmv. [District Rule 4401, 5.6.2.2 and 5.6.2.3] Federally Enforceable Through Title V Permit

17. There shall not be more minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv than the following: 3 leaks for 1 - 25 wells, 6 leaks for 26 - 50 wells, 8 leaks for 51 - 100 wells, 10 leaks for 101 - 250 wells, 15 leaks for 251 - 500 wells, and 1 leak for each 20 wells (with a minimum of 50 wells test) for more than 500 wells connected to a VOC collection and control system. [District Rule 4401, 5.6.2.4] Federally Enforceable Through Title V Permit

18. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

19. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.7.2] Federally Enforceable Through Title V Permit

20. Except for pipes and unsafe-to-monitor components, all other components shall be inspected pursuant to the requirements of section 6.3.3 at least once every year. [District Rule 4401,5.8.1] Federally Enforceable Through Title V Permit

21. All pipes shall be visually inspected at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. [District Rule 4401, 5.8.3.1] Federally Enforceable Through Title V Permit

23. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.3.2] Federally Enforceable Through Title V Permit

24. The operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. The operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.8.4.1] Federally Enforceable Through Title V Permit

25. The operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. The operator shall inspect a component, other than PRDs, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. The operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.8.4.2, 5.8.4.3, 5.8.5] Federally Enforceable Through Title V Permit

26. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.8.6] Federally Enforceable Through Title V Permit

27. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.1, 5.9.2] Federally Enforceable Through Title V Permit

28. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. Except for leaking critical components or leaking essential components, if the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4401, 5.9.3, 5.9.4] Federally Enforceable Through Title V Permit

29. The operator shall repair minor gas leaks within 14 days, major gas leaks which less than or equal to 50,000 ppmv within 5 days., major gas leaks which are greater than 50,000 ppmv within two days, minor liquid leaks within 3 days, and major liquid leaks within 2 days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4401, 5.9.4, 5.9.5, and 5.9.6] Federally Enforceable Through Title V Permit

30. If a leaking component is an essential component or a critical component which cannot be shut down immediately for repairs, and after being minimized still exceeds the applicable leak standard, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround or no later than one year from the date of original leak detection, which ever is earlier. [District Rule 4401, 5.9.7] Federally Enforceable Through Title V Permit

31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

33. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

34. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 44019, 6.1.6] Federally Enforceable Through Title V Permit

35. The operator shall maintain a copies of training records and of the latest APCO-approved Operator Management Plan (OMP) at the facility and make such available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.7, 6.1.8] Federally Enforceable Through Title V Permit

36. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. The operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.11] Federally Enforceable Through Title V Permit

37. Except as set forth elsewhere in this permit, the operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

38. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual control efficiency testing requirement if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare, or if the vapor collection and control does not have a VOC destruction device. [District Rule 4401, 6.2.2, 6.2.3] Federally Enforceable Through Title V Permit

39. An operator seeking approval of a waiver of the annual control efficiency testing requirement shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401, 6.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

41. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

42. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

43. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

44. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

45. The operator shall maintain an APCO approved Operator Management Plan (OMP). The OMP shall include, at a minimum, a description of all wells and all associated VOC collection and control systems subject to this rule, and all wells and all associated VOC collection and control systems that are exempt; an identification and description of any known hazard that might affect the safety of an inspector; except for pipes, the number of components that are subject to this rule by component type; except for pipes, the number and types of major components, inaccessible components, unsafe-to-monitor components, critical components, and essential components that are subject to this rule and the reason(s) for such designation; except for pipes, the location of components subject to the rule (components may be grouped together functionally by process unit or facility description); except for pipes, components exempt pursuant to Section 4.8 (except for components buried below ground) may be described in the OMP by grouping them functionally by process unit or facility description (the results of any laboratory testing or other pertinent information to demonstrate compliance with the applicable exemption criteria for components for which an exemption is being claimed pursuant to Sections 4.8 shall be submitted with the OMP); a detailed schedule of an operator's inspections of components to be conducted as required by this rule and whether the operator inspections of components required by this rule will be performed by a qualified contractor or by an in-house team; a description of the training standards for personnel that inspect and repair components; and a description of the leak detection training for conducting the test method specified in Section 6.3.3 for new operators, and for experienced operators, as necessary. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

46. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-22-10 **EXPIRATION DATE:** 05/31/2007

SECTION: 26 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 90 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (MOCAL LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
3. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (December 14, 2006), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. Fugitive volatile organic compound (VOC) emissions from this steam-enhanced crude oil production operation shall not exceed 61.3 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts of components in gas service and resulting emissions calculated using the emission factors in the "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c, dated 2/99. (CAPCOA document). [District Rule 2201] Federally Enforceable Through Title V Permit
8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
9. Steam-enhanced crude oil production well vents shall be closed, except when temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, and the front line production equipment downstream of the wells that carry produced fluids be connected to a VOC collection and control system. Alternatively, steam-enhanced crude oil production well vents shall be open and the well vents connected to a VOC collection and control system. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall be in violation of Rule 4401 if any District inspection or operator inspection, conducted as a requirement of this rule, demonstrates that one or more of the leak standard conditions set forth in section 5.6.2 exists. [District Rule 4401, 5.6.1] Federally Enforceable Through Title V Permit

11. There shall not be an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.6.2.1] Federally Enforceable Through Title V Permit

12. For pressure relief devices (PRDs) a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 400 to 10,000 ppmv. For components other than PRDs a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 2,000 to 10,000 ppmv. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak, except seal lubricant, that is not a major liquid leak and drips liquid at a rate of more than three drops per minute. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component into a container is not considered a leak provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit

13. There shall be no components with major liquid leaks or with gas leaks greater than 50,000 ppmv. [District Rule 4401, 5.6.2.2 and 5.6.2.3] Federally Enforceable Through Title V Permit

14. There shall not be more minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv than the following: 3 leaks for 1 - 25 wells, 6 leaks for 26 - 50 wells, 8 leaks for 51 - 100 wells, 10 leaks for 101 - 250 wells, 15 leaks for 251 - 500 wells, and 1 leak for each 20 wells (with a minimum of 50 wells test) for more than 500 wells connected to a VOC collection and control system. [District Rule 4401, 5.6.2.4] Federally Enforceable Through Title V Permit

15. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

16. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.7.2] Federally Enforceable Through Title V Permit

17. Except for pipes and unsafe-to-monitor components, all other components shall be inspected pursuant to the requirements of section 6.3.3 at least once every year. [District Rule 4401,5.8.1] Federally Enforceable Through Title V Permit

18. All pipes shall be visually inspected at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.2] Federally Enforceable Through Title V Permit

19. The operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. [District Rule 4401, 5.8.3.1] Federally Enforceable Through Title V Permit

20. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. The operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.8.4.1] Federally Enforceable Through Title V Permit

22. The operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. The operator shall inspect a component, other than PRDs, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. The operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.8.4.2, 5.8.4.3, 5.8.5] Federally Enforceable Through Title V Permit

23. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.8.6] Federally Enforceable Through Title V Permit

24. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.1, 5.9.2] Federally Enforceable Through Title V Permit

25. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. Except for leaking critical components or leaking essential components, if the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4401, 5.9.3, 5.9.4] Federally Enforceable Through Title V Permit

26. The operator shall repair minor gas leaks within 14 days, major gas leaks which less than or equal to 50,000 ppmv within 5 days., major gas leaks which are greater than 50,000 ppmv within two days, minor liquid leaks within 3 days, and major liquid leaks within 2 days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4401, 5.9.4, 5.9.5, and 5.9.6] Federally Enforceable Through Title V Permit

27. If a leaking component is an essential component or a critical component which cannot be shut down immediately for repairs, and after being minimized still exceeds the applicable leak standard, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround or no later than one year from the date of original leak detection, which ever is earlier. [District Rule 4401, 5.9.7] Federally Enforceable Through Title V Permit

28. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

29. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

31. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit

32. The operator shall maintain a copies of training records and of the latest APCO-approved Operator Management Plan (OMP) at the facility and make such available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.7, 6.1.8] Federally Enforceable Through Title V Permit

33. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. The operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.11] Federally Enforceable Through Title V Permit

34. Except as set forth elsewhere in this permit, the operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

35. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual control efficiency testing requirement if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare, or if the vapor collection and control does not have a VOC destruction device. [District Rule 4401, 6.2.2, 6.2.3] Federally Enforceable Through Title V Permit

36. An operator seeking approval of a waiver of the annual control efficiency testing requirement shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401, 6.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

38. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

39. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

40. The VOC content by weight percent (wt.%) of TEOR vapor shall be determined annually using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

41. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

42. The operator shall maintain an APCO approved Operator Management Plan (OMP). The OMP shall include, at a minimum, a description of all wells and all associated VOC collection and control systems subject to this rule, and all wells and all associated VOC collection and control systems that are exempt; an identification and description of any known hazard that might affect the safety of an inspector; except for pipes, the number of components that are subject to this rule by component type; except for pipes, the number and types of major components, inaccessible components, unsafe-to-monitor components, critical components, and essential components that are subject to this rule and the reason(s) for such designation; except for pipes, the location of components subject to the rule (components may be grouped together functionally by process unit or facility description); except for pipes, components exempt pursuant to Section 4.8 (except for components buried below ground) may be described in the OMP by grouping them functionally by process unit or facility description (the results of any laboratory testing or other pertinent information to demonstrate compliance with the applicable exemption criteria for components for which an exemption is being claimed pursuant to Sections 4.8 shall be submitted with the OMP); a detailed schedule of an operator's inspections of components to be conducted as required by this rule and whether the operator inspections of components required by this rule will be performed by a qualified contractor or by an in-house team; a description of the training standards for personnel that inspect and repair components; and a description of the leak detection training for conducting the test method specified in Section 6.3.3 for new operators, and for experienced operators, as necessary. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

43. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-24-30 **EXPIRATION DATE:** 05/31/2007

SECTION: 35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
DORMANT 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #25, DIS# 26916 66, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND SO2 SCRUBBER (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification except for physically disconnecting the fuel supply line from this unit. [District Rules 2010 and 4306] Federally Enforceable Through Title V Permit
2. Operators shall notify the District at least seven calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove Dormant Emission Unit references. [District Rule 4306] Federally Enforceable Through Title V Permit
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and Kern County Rule 108.1] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. Upon recommencing operation, when complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Upon recommencing operation, when complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Upon recommencing operation, if the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Upon recommencing operation, if fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

9. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

10. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District NSR Rule] Federally Enforceable Through Title V Permit

17. Upon recommencing operation, scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

18. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit

20. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

22. Emission rates shall not exceed any of the following: PM10: 0.075 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.033 lb/MMBtu or 44 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

23. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. If the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

26. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

29. Source testing to measure NOx and CO emissions shall be conducted within 60 days of recommencing operation of this unit. [District Rule 4306] Federally Enforceable Through Title V Permit

30. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

31. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by CARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

33. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

34. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

35. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

36. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-26-29 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #32, DIS# 12051 71, WITH A COEN ULN 3.2 LOW-NOX BURNER AND OPTIONAL SO2 SCRUBBER - METSON LEASE

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Sulfur emissions shall not exceed 0.11 lb of sulfur per million BTU of heat input, averaged over 3 - one hour periods. Compliance with this requirement may be demonstrated by firing the unit only on PUC or FERC regulated natural gas; multiplying the reported sulfur content of each fuel in lb/MMBtu by the maximum heat input rating of the unit; or by a combination of source testing for sulfur compounds and fuel analysis. Compliance may be demonstrated for this unit individually, or by showing that the total emissions of sulfur compounds from all steam generators located at the stationary source with ATC or PTO issued prior to September 12, 1979 does not exceed the emissions that would result if each unit was operating in compliance with the specified limit. [Kern County Rule 424 and District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

14. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District NSR Rule] Federally Enforceable Through Title V Permit

15. Scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

17. Maximum annual heat input of the unit shall not exceed 438,000 MMBtu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

18. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

19. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Emission rates shall not exceed any of the following: PM10: 0.092 lb/MMBtu or SOx (as SO2): 0.940 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Emission rates, except during startup and shutdown and refractory curing, shall not exceed any of the following: NOx (as NO2): 15 ppmv @ 3% O2, VOC: 0.007 lb/MMBtu, or CO: 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4301, 4305, 4306, and 4351] Federally Enforceable Through Title V Permit

22. Emission rates during refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 2201, 4201, 4301, 4405, 4406 and 4801] Federally Enforceable Through Title V Permit

23. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

24. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

25. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

26. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 2520] Federally Enforceable Through Title V Permit

27. If the NOx and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306]

28. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

29. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

33. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

34. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

35. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 100 or EPA Method 6 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans performed in a laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, 6.2, and 4306, 6.2] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-27-32 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #27, DIS# 12069-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

11. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

12. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Upon recommencing operation, scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

20. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

21. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

23. Upon recommencing operation, records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

24. Emission rates shall not exceed any of the following: PM10: 0.091 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.033 lb/MMBtu or 44 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

25. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306]

26. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306]

27. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306]

28. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306]

29. Upon recommencing operation, during the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

34. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

35. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

37. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-28-32 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #26, DIS# 12071-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District at least seven calendar days prior to the designation of this permit unit as a dormant emissions unit or an active emissions unit. [District Rule 1070] Federally Enforceable Through Title V Permit
2. When designated as a dormant emissions unit the fuel supply line shall be physically disconnected from the emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306] Federally Enforceable Through Title V Permit
4. A source test to demonstrate compliance with the NOx and CO emission limits shall be performed within 60 days of recommencing operation of the dormant emissions unit. [District Rule 4306] Federally Enforceable Through Title V Permit
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit

11. Whenever the unit is switched to scrubbed operation, compliance source testing for SOx shall be conducted within 60 days of initial scrubbing date unless source testing under scrubbed operation has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

12. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. Scrubber shall be located on site. Duct work to steam generators may be blinded off or removed. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Scrubber recirculation liquid pH shall be maintained only by the addition of caustic unless prior approval for an alternative pH maintenance method is received from the District. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Upon recommencing operation, scrubber liquor pH shall be maintained above 6.15 and shall be continuously monitored. [District Rule 2201] Federally Enforceable Through Title V Permit

20. When scrubber is in operation, steam generator firebox convection section, scrubber bypass valve, and all flue gas ductwork shall be maintained with no detectable leaks. [District NSR Rule] Federally Enforceable Through Title V Permit

21. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rules 2201, 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas/vapor recovery gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

23. Upon recommencing operation, records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

24. Emission rates shall not exceed any of the following: PM10: 0.091 lb/MMBtu, SOx (as SO2): 0.080 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.033 lb/MMBtu or 44 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

25. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306]

26. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305 and 4306]

27. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306]

28. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306]

29. Upon recommencing operation, during the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

30. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

32. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

34. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

35. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

36. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

37. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

38. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-29-28 **EXPIRATION DATE:** 05/31/2007

SECTION: 24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
NATURAL GAS-FIRED HEATER TREATER (#2) WITH A 4.2 MMBTU/HR MAXON MODEL M-PAKT BURNER SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
2. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.5.2] Federally Enforceable Through Title V Permit
3. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. Fuel gas sulfur content shall not exceed 0.5 gr/100 scf (as sulfur). [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 30 billion Btu per calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

14. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201] Federally Enforceable Through Title V Permit

15. Records of monthly and annual heat input of the unit shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Emission rates, except during startup and shutdown shall not exceed any of the following: PM10: 0.136 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, VOC: 0.007 lb/MMBtu, NOx (as NO2): 0.036 lb/MMBtu or 30 ppmv @ 3% O2, or CO: 0.037 lb/MMBtu or 50 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4307, 4405, 4406, 4801 and Kern County Rules 424 and 425]

17. Emission rates during startup and shutdown shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

18. Particulate matter emissions shall not exceed 0.1 grain/dscf, calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 3.1 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit

19. Emission rates shall not exceed any of the following: PM10: 13.7 lb/day, SOx (as SO2): 0.5 lb/day, VOC: 0.7 lb/day, NOx (as NO2): 80.2 lb/day or 1080 lb/yr, or CO: 3.7 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Duration of start-up and shutdown shall not exceed one hour each per occurrence. [District Rule 4307]

21. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Permittee shall maintain records of duration of each start-up and shutdown that exceed one hour per occurrence, and refractory curing, for a period of five years and make such records readily available for District inspection upon request. [District Rule 4307] Federally Enforceable Through Title V Permit

23. The permittee shall monitor, at least once per month, the units's operational characteristics recommended by the manufacturer and approved by the APCO. [District Rule 4307]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. The permittee shall tune the unit at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year. The unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. In lieu of tuning the unit twice each calendar year, the owner/operator shall monitor the emissions with a portable NOx analyzer at least twice per calendar year and adjust the unit's operating parameters accordingly to assure compliance with the emission limits of this rule. [District Rule 4307]

25. If the unit is tuned for compliance, the permittee shall maintain records of: (1) the date that tune-ups are performed, (2) a description of any corrective action taken to maintain the emissions within the acceptable range, and (3) a record of the operational characteristics monitored. [District Rule 4307]

26. If NOx emissions are monitored for compliance, the permittee shall maintain records of: (1) the date and time of the NOx measurements, (2) the O2 concentration in percent and the measured NOx concentration corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, (5) a description of any corrective action taken to maintain the emissions within the acceptable range, and (6) a record of the operational characteristics monitored. [District Rule 4307]

27. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4307. Notwithstanding the requirements above and per Section 5.5.4 of Rule 4307, for units with a cyclical firing period that routinely interrupts fuel flow as part of its normal operation, source testing may commence sooner than specified above and continue through its normal cyclical firing period. [District Rule 4307]

28. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4307]

29. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

30. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081 and 4307]

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rule 4307]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-30-17 **EXPIRATION DATE:** 05/31/2007

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
DORMANT 30 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #MO-2, DIS# 19961-68, WITH NORTH AMERICAN 5131-FACR BURNER - MOCAL LEASE

PERMIT UNIT REQUIREMENTS

1. No modification(s) to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4306] Federally Enforceable Through Title V Permit
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4306 and all other applicable District regulations. [District Rule 4306] Federally Enforceable Through Title V Permit
4. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Method 6 or CARB Method 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.4.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992), and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera) 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc (except 60.44c(g) and (h) and 60.48c). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed the following: PM10: 0.005 lb/MMBtu, SOx (as SO2): 0.005 lb/MMBtu, NOx (as NO2): 0.133 lb/MMBtu, VOC: 0.003 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 4301, 5.2.2 and 5.2.3, and 4201] Federally Enforceable Through Title V Permit

14. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. Use of an alternate system consisting of calibrated orifice plates, transmitters, and a programmable logic controller (PLC) may be used to meet this requirement. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

15. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

16. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

17. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

18. The permittee shall monitor, at least on a monthly basis, the amount of water use, the amount of unit blow down, and the exhaust stack temperature or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

21. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-70-15 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
43,470 GALLON FIXED ROOF REJECT TANK T-110, WITH SHARED VAPOR RECOVERY SYSTEM - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Operation shall include two fin fan heat exchangers, two separators, two compressors, and two liquid transfer pumps, shared between tanks S-1135-70, '-71, '-72, '-322, ' -326, and '-327, and heater treaters S-1135-3 and '-29. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive VOC emissions rate calculated using EPA's Protocol for Equipment Leak Emission Estimates, Table 2-4, Oil and Gas Production Operations Average Emission Factors, shall not exceed 0.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All tanks and separators shall vent only to vapor control system. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 99% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rules 2201 and 4623, 5.6.1] Federally Enforceable Through Title V Permit
9. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
10. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

12. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

18. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

19. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. The operator shall ensure that the vapor recovery system is functional and is operating as designed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-71-8 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF LACT TANK T-100 WITH VAPOR RECOVERY (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Operation shall include vapor recovery system described on the requirements for permit unit S-1135-70. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tanks and separators shall vent only to vapor control system. [District NSR Rule] Federally Enforceable Through Title V Permit
5. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

18. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-72-7 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
210,000 GALLON FIXED ROOF STANDBY TANK T-120, WITH VAPOR RECOVERY SYSTEM (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Operation shall include vapor recovery system described on the requirements for permit unit S-1135-70. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
5. All tanks and separators shall vent only to vapor control system. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
7. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Permittee shall keep accurate records of throughput and storage temperature of liquids stored in each tank and such records shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

19. The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

20. The operator shall ensure that the vapor recovery system is functional and is operating as designed whenever organic liquids or organic liquid vapors are contained in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-82-10 **EXPIRATION DATE:** 05/31/2007

SECTION: 22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF STANDBY TANK #2179 (BUENA FE FEE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be equipped with a pressure relief device set to within 10% of the maximum allowable working pressure of the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This standby storage tank shall be equipped with an operational temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The temperature of any introduced or stored organic liquid shall not exceed 200 degrees F. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Organic liquids may not be introduced into the tank for more than 3 consecutive days and no more than 19 times in any consecutive 12-month period. No organic liquid may be removed from tank, except that which overflows to tank S-1135-83, until organic liquid ceases to be introduced into either tank. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The true vapor pressure of any introduced or stored organic liquid shall not exceed 0.19 psi. [District Rule 2201] Federally Enforceable Through Title V Permit
6. True vapor pressure of organic liquid introduced to tank shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatography" as approved by ARB, EPA, and the District. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall determine the true vapor pressure of the organic liquid stored in the tank at least once per year in accordance with methods described in section 6.2 of District Rule 4623 (amended 12/20/01). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall keep accurate records of the dates organic liquid is introduced into the tank and the dates organic liquids are stopped being introduced into the tank, the daily volume of organic liquids introduced into the tank, the true vapor pressure of the organic liquid introduced in the tank at least once per year and whenever there is a change in the source or type of petroleum introduced in the tank, and the number of times organic liquid has been introduced into the tank in the preceding 12 month period. All records shall be retained on site for at least 5 years and be made readily available for District inspection on request. [District Rule 1070]

11. The operator shall keep accurate records of types, storage temperature, and TVP of liquids stored to verify continued exemption from District Rule 4623 (as amended December 20, 2001). [District Rule 2520, 9.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-83-8 **EXPIRATION DATE:** 05/31/2007

SECTION: 22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,000 GALLON FIXED ROOF STANDBY TANK #2180 (BUENA FE FEE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be equipped with a pressure relief device set to within 10% of the maximum allowable working pressure of the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This standby storage tank shall be equipped with an operational temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The temperature of any introduced or stored organic liquid shall not exceed 200 degrees F. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Organic liquids may not be introduced into the tank for more than 3 consecutive days and no more than 19 times in any consecutive 12-month period. No organic liquid may be removed from tank, except that which overflows to tank S-1135-82, until organic liquid ceases to be introduced into either tank. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The true vapor pressure of any introduced or stored organic liquid shall not exceed 0.19 psi. [District Rule 2201] Federally Enforceable Through Title V Permit
6. True vapor pressure of organic liquid introduced to tank shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatography" as approved by ARB, EPA, and the District. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall determine the true vapor pressure of the organic liquid stored in the tank at least once per year in accordance with methods described in section 6.2 of District Rule 4623 (amended 12/20/01). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall keep accurate records of the dates organic liquid is introduced into the tank and the dates organic liquids are stopped being introduced into the tank, the daily volume of organic liquids introduced into the tank, the true vapor pressure of the organic liquid introduced in the tank at least once per year and whenever there is a change in the source or type of petroleum introduced in the tank, and the number of times organic liquid has been introduced into the tank in the preceding 12 month period. All records shall be retained on site for at least 5 years and be made readily available for District inspection on request. [District Rule 1070]

11. The operator shall keep accurate records of types, storage temperature, and TVP of liquids stored to verify continued exemption from District Rule 4623 (as amended December 20, 2001). [District Rule 2520, 9.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-115-22 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #1 (NEELY LEASE)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320]
3. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320]
4. This equipment shall not be operated for any reason until an Authority to Construct permit is implemented with all necessary retrofits required to comply with the applicable requirements of District Rule 4320 and all other applicable District regulations. [District Rule 4320]
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

16. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

17. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

18. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

19. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

21. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. Emission rates shall not exceed any of the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

24. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

25. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

26. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

27. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

28. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

29. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

30. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-119-24 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #5 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320]
2. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320]
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2 and 4305, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

14. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

15. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

16. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

17. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

18. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. No less than 9975 ft of presently unpaved dirt roadway shall be surfaced with SC hot mix asphalt paving. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Emission rates shall not exceed the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

21. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
23. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit
24. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit
25. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit
26. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit
27. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-122-25 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #6 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320]
2. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320]
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

14. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

15. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

16. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

17. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

18. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. Emission rates shall not exceed the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

20. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit
23. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit
24. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit
26. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-123-23 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #7 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The fuel supply line shall be physically disconnected from this unit. [District Rule 4320]
2. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4320]
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of natural gas combusted in the unit shall be installed, utilized and maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

13. Maximum annual heat input of the unit shall not exceed 9 billion Btu per calendar year. [District Rule 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

14. Owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4306] Federally Enforceable Through Title V Permit

15. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4306] Federally Enforceable Through Title V Permit

16. The permittee shall monitor, at least on a monthly basis, the exhaust oxygen content or other operational characteristics recommended by the unit manufacturer. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 day of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

17. Records of monthly and annual heat input of the unit shall be maintained. [District Rules 2201, 4305, and 4306] Federally Enforceable Through Title V Permit

18. Records of tune-up and monitoring of the operational characteristics of the unit shall be maintained. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

19. Emission rates shall not exceed the following: PM10: 0.008 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.098 lb/MMBtu, VOC: 0.005 lb/MMBtu, and CO: 0.033 lb/MMBtu. [District Rules 2201, 2520, 4201, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

20. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit
23. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit
24. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit
26. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-124-15 **EXPIRATION DATE:** 05/31/2007

SECTION: NW15 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 254 STEAM ENHANCED WELLS, AND TIED TO TEOR '293 INCLUDING PIPING TO BALANCED CGCS, RE-INJECTION COMPRESSORS OR INCINERATING STEAM GENERATORS (EXETER LEASE)

PERMIT UNIT REQUIREMENTS

1. Well vent vapor control system VOC fugitive emission rate shall not exceed 50.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit accurate fugitive component counts for well vent vapor control system and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production, Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. Operation shall include noncondensible vapor piping from vapor control skids to balanced system and re-injection compressors. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operation shall include vapor control skids including: various size knockout vessels with liquid pumps, gas scrubbers, heat exchangers, vapor compressors, and piping to District approved disposal devices. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Piping to re-injection system shall include re-injection knock out vessels, interstage coolers & gas/liquid separators, injection gas compressors and liquid transfer pumps, as needed. [District Rule 2201] Federally Enforceable Through Title V Permit
9. TEOR gas injected into formation shall only be performed using DOG approved injection wells. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Permittee shall cease injecting vapors and notify the District immediately if DOG injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. A listing of all steam enhanced wells connected to this system shall be maintained onsite and readily available to the District upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Vapor collection piping TEORs S-1135-124 and '-293 shall be contained in a balanced CGCS or collected at VR skid(s) and piped to approved injection wells. [District Rule 2201] Federally Enforceable Through Title V Permit

13. TEOR gas not re-injected to the formation shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records shall be kept of injection well(s) utilized and volume of vapors injected. Records shall be made readily available to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

15. Steam-enhanced crude oil production well vents shall be closed, except when temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, and the front line production equipment downstream of the wells that carry produced fluids be connected to a VOC collection and control system. Alternatively, steam-enhanced crude oil production well vents shall be open and the well vents connected to a VOC collection and control system. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

16. The operator shall be in violation of Rule 4401 if any District inspection or operator inspection, conducted as a requirement of this rule, demonstrates that one or more of the leak standard conditions set forth in section 5.6.2 exists. [District Rule 4401, 5.6.1] Federally Enforceable Through Title V Permit

17. There shall not be an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.6.2.1] Federally Enforceable Through Title V Permit

18. For pressure relief devices (PRDs) a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 400 to 10,000 ppmv. For components other than PRDs a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 2,000 to 10,000 ppmv. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak, except seal lubricant, that is not a major liquid leak and drips liquid at a rate of more than three drops per minute. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component into a container is not considered a leak provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 3.20] Federally Enforceable Through Title V Permit

19. There shall be no components with major liquid leaks or with gas leaks greater than 50,000 ppmv. [District Rule 4401, 5.6.2.2 and 5.6.2.3] Federally Enforceable Through Title V Permit

20. There shall not be more minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv than the following: 3 leaks for 1 - 25 wells, 6 leaks for 26 - 50 wells, 8 leaks for 51 - 100 wells, 10 leaks for 101 - 250 wells, 15 leaks for 251 - 500 wells, and 1 leak for each 20 wells (with a minimum of 50 wells test) for more than 500 wells connected to a VOC collection and control system. [District Rule 4401, 5.6.2.4] Federally Enforceable Through Title V Permit

21. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

22. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.7.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Except for pipes and unsafe-to-monitor components, all other components shall be inspected pursuant to the requirements of section 6.3.3 at least once every year. [District Rule 4401,5.8.1] Federally Enforceable Through Title V Permit

24. All pipes shall be visually inspected at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.2] Federally Enforceable Through Title V Permit

25. The operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. [District Rule 4401, 5.8.3.1] Federally Enforceable Through Title V Permit

26. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.3.2] Federally Enforceable Through Title V Permit

27. The operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. The operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.8.4.1] Federally Enforceable Through Title V Permit

28. The operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. The operator shall inspect a component, other than PRDs, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. The operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.8.4.2, 5.8.4.3, 5.8.5] Federally Enforceable Through Title V Permit

29. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.8.6] Federally Enforceable Through Title V Permit

30. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.1, 5.9.2] Federally Enforceable Through Title V Permit

31. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. Except for leaking critical components or leaking essential components, if the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4401, 5.9.3, 5.9.4] Federally Enforceable Through Title V Permit

32. The operator shall repair minor gas leaks within 14 days, major gas leaks which less than or equal to 50,000 ppmv within 5 days., major gas leaks which are greater than 50,000 ppmv within two days, minor liquid leaks within 3 days, and major liquid leaks within 2 days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4401, 5.9.4, 5.9.5, and 5.9.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. If a leaking component is an essential component or a critical component which cannot be shut down immediately for repairs, and after being minimized still exceeds the applicable leak standard, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround or no later than one year from the date of original leak detection, which ever is earlier. [District Rule 4401, 5.9.7] Federally Enforceable Through Title V Permit

34. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

35. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

36. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

37. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 44019, 6.1.6] Federally Enforceable Through Title V Permit

38. The operator shall maintain a copies of training records and of the latest APCO-approved Operator Management Plan (OMP) at the facility and make such available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.7, 6.1.8] Federally Enforceable Through Title V Permit

39. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. The operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.11] Federally Enforceable Through Title V Permit

40. Except as set forth elsewhere in this permit, the operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

41. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual control efficiency testing requirement if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare, or if the vapor collection and control does not have a VOC destruction device. [District Rule 4401, 6.2.2, 6.2.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

42. An operator seeking approval of a waiver of the annual control efficiency testing requirement shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401, 6.2.4] Federally Enforceable Through Title V Permit

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

46. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

47. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

48. The operator shall maintain an APCO approved Operator Management Plan (OMP). The OMP shall include, at a minimum, a description of all wells and all associated VOC collection and control systems subject to this rule, and all wells and all associated VOC collection and control systems that are exempt; an identification and description of any known hazard that might affect the safety of an inspector; except for pipes, the number of components that are subject to this rule by component type; except for pipes, the number and types of major components, inaccessible components, unsafe-to-monitor components, critical components, and essential components that are subject to this rule and the reason(s) for such designation; except for pipes, the location of components subject to the rule (components may be grouped together functionally by process unit or facility description); except for pipes, components exempt pursuant to Section 4.8 (except for components buried below ground) may be described in the OMP by grouping them functionally by process unit or facility description (the results of any laboratory testing or other pertinent information to demonstrate compliance with the applicable exemption criteria for components for which an exemption is being claimed pursuant to Sections 4.8 shall be submitted with the OMP); a detailed schedule of an operator's inspections of components to be conducted as required by this rule and whether the operator inspections of components required by this rule will be performed by a qualified contractor or by an in-house team; a description of the training standards for personnel that inspect and repair components; and a description of the leak detection training for conducting the test method specified in Section 6.3.3 for new operators, and for experienced operators, as necessary. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

49. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-125-14 **EXPIRATION DATE:** 05/31/2007

SECTION: SW14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 144 STEAM ENHANCED CRUDE OIL PRODUCTION WELL VENTS, TIED TO TEOR '293 AND TVR '173 (W&S FEE LEASE)

PERMIT UNIT REQUIREMENTS

1. Well vent vapor control system VOC fugitive emission rate shall not exceed 38.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall maintain with the permit accurate fugitive component counts for well vent vapor control system and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production, Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
4. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
6. Operation shall include three vapor control skids with casing vent collection piping serving 144 steam drive wells. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operation shall include noncondensible vapor piping from vapor control skids and W&S tank battery vapor collection system to balanced system and re-injection compressors. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operation shall include vapor control equipment which consists of miscellaneous knockout vessels & liquid removal pumps, gas coolers, heat exchangers, vapor compressors, condensate collection tanks & piping to approved injection well(s). [District Rule 2201] Federally Enforceable Through Title V Permit
9. TEOR gas injected into formation shall only be performed using DOGGR approved injection wells. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Permittee shall cease injecting vapors and notify the District immediately if DOGGR injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Piping to injection system shall include re-injection knockout vessels, interstage coolers & gas/liquid separators, injection gas compressors and liquid transfer pumps, as needed. [District Rule 2201] Federally Enforceable Through Title V Permit

12. A listing of all steam enhanced wells connected to this system shall be maintained onsite and readily available to the District upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Collected TEOR vapors shall be contained in a balanced CGCS or collected at VR skid(s) and piped to approved injection well(s). [District Rule 2201] Federally Enforceable Through Title V Permit

14. TEOR vapors not re-injected to the formation shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Collected liquids shall be handled, stored, and disposed of in a manner preventing air contaminant emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Records shall be kept of injection well(s) utilized and volume of vapors injected, for a period of five years. Records shall be made readily available to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

17. Steam-enhanced crude oil production well vents shall be closed, except when temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, and the front line production equipment downstream of the wells that carry produced fluids be connected to a VOC collection and control system. Alternatively, steam-enhanced crude oil production well vents shall be open and the well vents connected to a VOC collection and control system. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

18. The operator shall be in violation of Rule 4401 if any District inspection or operator inspection, conducted as a requirement of this rule, demonstrates that one or more of the leak standard conditions set forth in section 5.6.2 exists. [District Rule 4401, 5.6.1] Federally Enforceable Through Title V Permit

19. There shall not be an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.6.2.1] Federally Enforceable Through Title V Permit

20. For pressure relief devices (PRDs) a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 400 to 10,000 ppmv. For components other than PRDs a major gas leak is greater than 10,000 ppmv and a minor gas leak is from 2,000 to 10,000 ppmv. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak, except seal lubricant, that is not a major liquid leak and drips liquid at a rate of more than three drops per minute. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component into a container is not considered a leak provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 3.20] Federally Enforceable Through Title V Permit

21. There shall be no components with major liquid leaks or with gas leaks greater than 50,000 ppmv. [District Rule 4401, 5.6.2.2 and 5.6.2.3] Federally Enforceable Through Title V Permit

22. There shall not be more minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv than the following: 3 leaks for 1 - 25 wells, 6 leaks for 26 - 50 wells, 8 leaks for 51 - 100 wells, 10 leaks for 101 - 250 wells, 15 leaks for 251 - 500 wells, and 1 leak for each 20 wells (with a minimum of 50 wells test) for more than 500 wells connected to a VOC collection and control system. [District Rule 4401, 5.6.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

24. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.7.2] Federally Enforceable Through Title V Permit

25. Except for pipes and unsafe-to-monitor components, all other components shall be inspected pursuant to the requirements of section 6.3.3 at least once every year. [District Rule 4401,5.8.1] Federally Enforceable Through Title V Permit

26. All pipes shall be visually inspected at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.2] Federally Enforceable Through Title V Permit

27. The operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. [District Rule 4401, 5.8.3.1] Federally Enforceable Through Title V Permit

28. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.3.2] Federally Enforceable Through Title V Permit

29. The operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. The operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.8.4.1] Federally Enforceable Through Title V Permit

30. The operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. The operator shall inspect a component, other than PRDs, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. The operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.8.4.2, 5.8.4.3, 5.8.5] Federally Enforceable Through Title V Permit

31. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.8.6] Federally Enforceable Through Title V Permit

32. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.1, 5.9.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. Except for leaking critical components or leaking essential components, if the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4401, 5.9.3, 5.9.4] Federally Enforceable Through Title V Permit

34. The operator shall repair minor gas leaks within 14 days, major gas leaks which less than or equal to 50,000 ppmv within 5 days., major gas leaks which are greater than 50,000 ppmv within two days, minor liquid leaks within 3 days, and major liquid leaks within 2 days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4401, 5.9.4, 5.9.5, and 5.9.6] Federally Enforceable Through Title V Permit

35. If a leaking component is an essential component or a critical component which cannot be shut down immediately for repairs, and after being minimized still exceeds the applicable leak standard, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround or no later than one year from the date of original leak detection, which ever is earlier. [District Rule 4401, 5.9.7] Federally Enforceable Through Title V Permit

36. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

37. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

38. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

39. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 44019, 6.1.6] Federally Enforceable Through Title V Permit

40. The operator shall maintain copies of training records and of the latest APCO-approved Operator Management Plan (OMP) at the facility and make such available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.7, 6.1.8] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. The operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401, 6.1.11] Federally Enforceable Through Title V Permit

42. Except as set forth elsewhere in this permit, the operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401, 6.2.1] Federally Enforceable Through Title V Permit

43. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual control efficiency testing requirement if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare, or if the vapor collection and control does not have a VOC destruction device. [District Rule 4401, 6.2.2, 6.2.3] Federally Enforceable Through Title V Permit

44. An operator seeking approval of a waiver of the annual control efficiency testing requirement shall submit a written request and supporting information to the APCO. The District shall evaluate the request and if approved by the APCO, the District shall provide EPA and ARB with a copy of the evaluation and shall request EPA and ARB approval. The District evaluation and the APCO request shall be deemed approved unless EPA or ARB objects to such approval in writing within 45 days of the receipt of the APCO request. [District Rule 4401, 6.2.4] Federally Enforceable Through Title V Permit

45. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

46. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

47. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

48. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

49. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. The operator shall maintain an APCO approved Operator Management Plan (OMP). The OMP shall include, at a minimum, a description of all wells and all associated VOC collection and control systems subject to this rule, and all wells and all associated VOC collection and control systems that are exempt; an identification and description of any known hazard that might affect the safety of an inspector; except for pipes, the number of components that are subject to this rule by component type; except for pipes, the number and types of major components, inaccessible components, unsafe-to-monitor components, critical components, and essential components that are subject to this rule and the reason(s) for such designation; except for pipes, the location of components subject to the rule (components may be grouped together functionally by process unit or facility description); except for pipes, components exempt pursuant to Section 4.8 (except for components buried below ground) may be described in the OMP by grouping them functionally by process unit or facility description (the results of any laboratory testing or other pertinent information to demonstrate compliance with the applicable exemption criteria for components for which an exemption is being claimed pursuant to Sections 4.8 shall be submitted with the OMP); a detailed schedule of an operator's inspections of components to be conducted as required by this rule and whether the operator inspections of components required by this rule will be performed by a qualified contractor or by an in-house team; a description of the training standards for personnel that inspect and repair components; and a description of the leak detection training for conducting the test method specified in Section 6.3.3 for new operators, and for experienced operators, as necessary. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

51. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-127-17 **EXPIRATION DATE:** 05/31/2007

SECTION: NE27 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION INCLUDING ONE TRANSPORTABLE FIN FAN COOLER AND ASSOCIATED PIPING SERVING 383 STEAM ENHANCED WELL VENTS (MAXWELL LEASE) CONNECTED TO TANK VAPOR CONTROL SYSTEM S-1135-118, COLLECTED VAPORS PIPED FROM VAPOR CONTROL COMPRESSOR SKIDS EITHER TO INJECTION COMPRESSORS FOR RE-INJECTION TO DOGGR WELLS, TO STEAM GENERATORS S-1135-9 AND '-10 FOR INCINERATION, OR CONTAINED WITHIN THE BALANCED CASING GAS COLLECTION SYSTEM (CGCS)

PERMIT UNIT REQUIREMENTS

1. Fin fan cooler may be transported to and installed at any vapor skid within the casing vent vapor collection system. [District Rule NSR] Federally Enforceable Through Title V Permit
2. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
3. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
4. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and Kern County Rule, 108.1] Federally Enforceable Through Title V Permit
5. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
6. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
7. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
8. There shall be no more than 15 leaks from the well vent vapor collection and control system, including condensate handling and wellhead connections, at any one time. [District NSR Rule and Rule 4401] Federally Enforceable Through Title V Permit
9. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

11. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

12. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

13. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components; and the efficiency of destruction devices determined by USEPA Method 18. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

14. VOC content shall be determined using ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by CARB Method 422. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

15. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.4.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: Kern County Rule, 108.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

18. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

19. Operation shall include noncondensible vapor piping from vapor recovery skids to balanced system, re-injection compressors, and scrubbed steam generators S-1135-9 and '10. [District NSR Rule] Federally Enforceable Through Title V Permit

20. Operation shall include vapor control equipment which consists of miscellaneous knockout vessels & liquid removal pumps, condensate tanks, heat exchangers, gas coolers, vapor compressors, and piping to disposal devices. [District NSR Rule] Federally Enforceable Through Title V Permit

21. Piping to re-injection system shall include re-injection knock out vessels, interstage coolers & gas/liquid separators, injection gas compressors and liquid transfer pumps, as needed. [District NSR Rule] Federally Enforceable Through Title V Permit

22. TEOR gas injected into formation shall only be performed using DOGGR approved disposal wells. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Permittee shall cease injecting vapors and notify the District immediately if DOGGR disposal approval is revoked, denied, terminated, surrendered or altered to disallow injection. [District Rule 2080] Federally Enforceable Through Title V Permit

24. A listing of all steam enhanced wells connected to this system shall be submitted to the District at least 60 days prior to the permit anniversary date. [District NSR Rule] Federally Enforceable Through Title V Permit

25. Vapor collection piping TEOR, also serving tank TVR system '118, shall be contained in a balanced CGCS or collected at VR skid(s) and piped to approved incinerating steam generators or DOGGR approved disposal wells. [District NSR Rule] Federally Enforceable Through Title V Permit

26. TEOR vapors not re-injected to the formation shall be contained within a balanced casing vent collection system, or well casing vents shall be closed and produced fluids shall be handled only in controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit

27. All wells producing from strata steamed by this unit shall be connected to a District-approved emissions control system or have District-approved closed casing vents. [District NSR Rule] Federally Enforceable Through Title V Permit

28. All produced fluids from any well served by vapor collection system which has had casing gas flow restricted or casing vent closed shall be handled only in closed and vapor controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit

29. Permittee shall maintain accurate component count for TEOR operation according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. Permittee shall update such records when new components are installed. [District NSR Rule]

30. Fugitive emissions from all components (except those operating under negative pressure at all times) in gas service including polish rods associated with this TEOR operation shall not exceed 140.1 lb VOC/ day. [District NSR Rule]

31. Records shall be kept of DOGGR injection well(s) utilized and volume of vapors injected. Records shall be made readily available to the District upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-128-21 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 265 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, PIPING TO DISPOSAL WELLS, TIED TO TEOR S-1135-129, AND TVR S-1135-149 AND S-1135-281 (NEELY LEASE)

PERMIT UNIT REQUIREMENTS

1. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
4. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
5. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
6. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
7. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
8. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
9. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
10. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

12. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components; and the efficiency of destruction devices determined by USEPA Method 18. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

13. VOC content shall be determined using ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by CARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

14. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

15. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. TEOR gas injected into formation shall only be performed using Department of Oil, Gas & Geothermal (DOGGR) approved disposal wells. [District NSR Rule] Federally Enforceable Through Title V Permit

18. Permittee shall cease injecting vapors and notify the District immediately if DOGGR disposal approval is revoked, denied, terminated, surrendered or altered to disallow disposal. This condition does not grant the permittee relief from any permit condition or other requirement of the Clean Air Act. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Permittee shall maintain with the permit a listing (updated annually within 60 days of permit anniversary) of all steam enhanced wells connected to the casing vent control system. [District NSR Rule] Federally Enforceable Through Title V Permit

20. Permittee shall maintain with the permit an accurate fugitive component count and resulting emissions calculated using EPA Publication 453/R-95-017 November 1995. Permit count and resulting emissions shall be updated annually within 60 days of permit anniversary. [District NSR Rule] Federally Enforceable Through Title V Permit

21. An I &M program consistent with Rule 4403 light oil production Section 5.1 requirements shall be implemented for all new well stuffing boxes. [District NSR Rule] Federally Enforceable Through Title V Permit

22. TEOR vapors shall be injected to the formation (via DOGGR approved disposal wells) or shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit

23. Collected liquids shall be handled, stored, and disposed of in a manner preventing air contaminant emissions. [District NSR Rule] Federally Enforceable Through Title V Permit

24. Well vent vapor control system VOC fugitive emission rate shall not exceed 133.9 lb/day and fugitive VOC emissions from new polish rods shall not exceed 2.3 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-129-26 **EXPIRATION DATE:** 05/31/2007

SECTION: NW21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION AUTHORIZED FOR 425 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, VAPOR PIPING TO INJECTION WELLS (ANDERSON-GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
3. Volatile organic compound (VOC) emissions from the entire system (including fugitive emissions from components handling vapor and condensate) shall not exceed 143.0 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Compliance with permit conditions in the Title V permit shall be deemed compliance with the Kern County Rule 108.1. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
5. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
6. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. TEOR gas injected into formation shall only be performed using Department of Oil, Gas & Geothermal (DOGGR) approved injection wells. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Permit holder shall cease injecting vapors and notify the District immediately if DOGGR injection approval is revoked, denied, terminated, surrendered or altered to disallow injection. This condition does not grant the permittee relief from any permit condition or other requirement of the Clean Air Act. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Permit holder shall maintain with the permit a listing (updated annually within 60 days of permit anniversary) of all steam enhanced wells connected to the casing vent control system. [District Rule 1070] Federally Enforceable Through Title V Permit
10. TEOR vapors shall be injected to the formation or shall be contained within balanced casing vent collection system, or well casing vents shall be closed and produced fluids handled only in controlled production equipment. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

12. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

13. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

14. Total number of leaks from the well vent vapor control system, including condensate handling, shall not exceed the number of allowable leaks allowed by Rule 4401 at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

15. Units consisting of more than 500 wells shall not exceed one leak detected for each 20 wells tested with a minimum of 50 wells tested. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

16. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

17. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

18. Operator shall repair each leak within 15 calendar days of detection. The APCO may grant a 10 calendar day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

19. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

20. All records of required monitoring data and support information shall be maintained, retained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit

21. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

22. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source testers certified by the California Air Resources Board (CARB) during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the annual testing requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless open flare, and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components and number of components; and the efficiency of destruction devices determined by USEPA Method 18, 25, 25a, or 25b as applicable. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

24. Leak inspection and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

25. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

26. Unless waived by the District, the operator shall maintain source test records which show that the control efficiency requirements have been satisfied. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

27. Collected liquids shall be handled, stored, and disposed of in a manner preventing air contaminant emissions. [District NSR Rule] Federally Enforceable Through Title V Permit

28. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-149-18 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON CRUDE OIL LACT TANK ID# AG-01, WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-150, '151, '152, '155, '270, '301 AND '323 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Vapor control system shall contain vapor control system piping network and vapor compression system consisting of vapor compressor(s), air-cooled heat exchanger, inlet scrubber, pump, and discharge scrubber. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
6. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
7. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Compressor suction and knockout drum liquids shall be piped only to vapor-controlled tanks. [District NSR Rule] Federally Enforceable Through Title V Permit
9. The operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. Operator shall monitor vapor control system pressures on quarterly basis to ensure that system pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 10.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

15. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

16. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

18. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

19. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor recovery system and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit

20. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

21. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

23. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

24. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

25. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

26. The pressure transmitters shall be inspected and maintained in good operating conditions. The inspections shall be conducted on a quarterly basis. Replacing and repairing of each pressure transmitters shall not exceed one hour per day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

35. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

37. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-150-12 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON CRUDE OIL LACT TANK ID# AG-02, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 2.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-151-12 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
210,000 GALLON REJECT TANK ID# AG-03, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 1.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-152-12 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
210,000 GALLON REJECT TANK ID# AG-04, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 1.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-155-14 **EXPIRATION DATE:** 05/31/2007

SECTION: 21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
281,400 GALLON (6,700 BBL) FIXED ROOF WASH TANK ID# AG-07, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All collected vapors shall be compressed to the Andersen-Goodwin Lease TEOR skid S-1135-129 for disposal. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 2.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
11. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
12. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

18. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

23. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

32. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-173-21 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,600 BBL (67,200 GALLON) FIXED ROOF LACT TANK ID# WS-01, HANDLING MAXWELL LEASE PRODUCTION, AND VESSELS V-101, V-102, V-103, AND V-104; WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-174, -175, -178, -325, AND -337 (W&S LEASE) DISCHARGING TO TEOR WVVCS S-1135-125

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Vapor control system shall contain vapor control system piping network and vapor compression system consisting of two vapor compressors, fin fan aerial cooler, and knockout vessels. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Vapor control system piping network shall include vapor space piping and make-up gas serving storage tanks S-1135-173, '-174, '-175, '-178, '-325, and '-337 with vapor control piping to W&S TEOR operation S-1135-125. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
5. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Compressor knock-out drum liquids shall be piped only to vapor controlled tanks or crude sales line. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. Operator shall monitor vapor control system pressures on quarterly basis to ensure that system pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 2.8 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

12. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

13. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

14. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

15. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

18. The pressure transmitters shall be inspected and maintained in good operating conditions. The inspections shall be conducted on a quarterly basis. Replacing and repairing of each pressure transmitters shall not exceed one hour per day. [District NSR Rule] Federally Enforceable Through Title V Permit

19. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-174-8 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
2,000 BBL (84,000 GALLON) FIXED ROOF LACT TANK ID# WS-02, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.1 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
8. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
9. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: t = 2.3 V / Q, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

13. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

14. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. True vapor pressure shall be measured at least once every 24 months during summer (July - September), and/or whenever these is a change in the source or type of organic liquid stored using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rules 2520, 9.3.2 and 4623, 6.2.2] Federally Enforceable Through Title V Permit

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Permittee shall keep accurate records of throughput and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-175-7 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,600 BBL (67,200 GALLON) FIXED ROOF WASH TANK ID# WS-03, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.1 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
8. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
9. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

13. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

14. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. True vapor pressure shall be measured at least once every 24 months during summer (July - September), and/or whenever these is a change in the source or type of organic liquid stored using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rules 2520, 9.3.2 and 4623, 6.2.2] Federally Enforceable Through Title V Permit

21. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Permittee shall keep accurate records of throughput and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-178-9 **EXPIRATION DATE:** 05/31/2007

SECTION: 14 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
3,000 BBL (126,000 GALLON) FIXED ROOF SUMP PROCESS TANK ID# WS-06, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
2. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.1 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
5. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
8. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. True vapor pressure shall be measured at least once every 24 months during summer (July - September), and/or whenever these is a change in the source or type of organic liquid stored using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rules 2520, 9.3.2 and 4623, 6.2.2] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Permittee shall keep accurate records of throughput and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-224-25 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
NOMINALLY RATED 78.2 MW COGENERATION UNIT A WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)

PERMIT UNIT REQUIREMENTS

1. CTG exhaust after the SCR unit shall be equipped with continuously recording emissions monitors dedicated to this unit for NOx, CO, and O2. Continuous emissions monitors shall meet the requirements of 40 CFR Part 60, Appendices B and F, and 40 CFR Part 75, and shall be capable of monitoring emissions during startups and shutdowns as well as normal operating conditions. If relative accuracy of CEM(s) cannot be demonstrated during startup conditions, CEM results during startup and shutdown events shall be replaced with startup emission rates obtained from source testing to determine compliance with emission limits. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
2. CTG shall be equipped with a continuously recording emission monitor preceding the SCR module measuring NOx concentration for the purposes of calculating ammonia slip. Permittee shall check, record, and quantify the calibration drift (CD) at two concentration values at least once daily (approximately 24 hours). The calibration shall be adjusted whenever the daily zero or high-level CD exceeds 5%. If either the zero or high-level CD exceeds 5% for five consecutive daily periods, the analyzer shall be deemed out-of-control. If either the zero or high-level CD exceeds 10% during any CD check, analyzer shall be deemed out-of-control. If the analyzer is out-of-control, the permittee shall take appropriate corrective action and then repeat the CD check. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
3. Ammonia injection grid shall be equipped with operational ammonia flowmeter and injection pressure indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Heat recovery steam generator design shall provide space for additional selective catalytic reduction catalyst and oxidation catalyst if required to meet NOx and CO emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall monitor and record exhaust gas temperature at selective catalytic reduction and oxidation catalyst inlets. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Ammonia shall be injected whenever the selective catalytic reduction system catalyst temperature exceeds the minimum ammonia injection temperature recommended by the manufacturer. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas turbine engine shall be equipped with fuel consumption monitor recorder accurate to +/- 3%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. CEM for NOx (as NO2) and CO shall conform to Rule 1080 specifications. [District Rules 1080 and 4703] Federally Enforceable Through Title V Permit
9. HRSG exhaust stack shall be equipped with permanent stack sampling provisions adequate to facilitate testing consistent with EPA test methods. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Flue gas ducting from engine to HRSG shall have no provisions for introduction of dilution air. [District Rule 1110] Federally Enforceable Through Title V Permit
11. Lube oil cooler/accumulation vent shall be equipped with control device(s) approved by the APCO sufficient to prevent emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Lube oil cooler/accumulator vent(s) shall not have detectable emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Natural gas sulfur content shall not exceed 0.31 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Facility shall operate as a cogeneration facility pursuant to Public Resources Code section 25134 for TEOR operations unless prior District and CEC approval is granted to operate otherwise. [District Rule 2080] Federally Enforceable Through Title V Permit
15. All CEM's shall be calibrated and operated according to EPA guidelines as specified in 40 CFR 60 Appendix B. [District Rule 1080] Federally Enforceable Through Title V Permit
16. Quarterly CEM reports shall be submitted to the APCO according to EPA regulations as specified in 40 CFR 60 Appendix B. [District Rule 4001 and District rule 1080, 8.0] Federally Enforceable Through Title V Permit
17. Audits of all monitors shall be conducted by independent laboratory in accordance with EPA guidelines and witnessed by District. Reports shall be submitted to District within 60 days of audits. [District Rule 1080] Federally Enforceable Through Title V Permit
18. All notification, recordkeeping, performance tests, reporting requirements, and compliance testing requirements of Rule 4001 NSPS shall be satisfied. [District Rule 4001] Federally Enforceable Through Title V Permit
19. Operational records including fuel type, fuel characteristics, and consumption shall be maintained and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
20. Accurate records of NOx (as NO2) and CO flue gas concentration corrected to 15% O2 and fuel gas sulfur content shall be maintained and shall be reported as described in Rule 1080 upon request. [District Rule 1080] Federally Enforceable Through Title V Permit
21. Emission rates shall not exceed the following: PM10: 0.010 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu, VOC: 0.009 lb/MMBtu, CO: 0.057 lb/MMBtu, and ammonia - 10 ppmvd @ 15%O2. [District NSR Rule; District Rule 4201; and Kern County Rule 404] Federally Enforceable Through Title V Permit
22. Permittee shall comply with the following emission limit at all times except during periods of start-up, shutdown, or reduced load as defined in Rule 4703: NOx (as NO2): 5.0 ppmv, and CO: 25 ppmv, dry @ 15% O2 corrected to ISO conditions. [40 CFR 60.332(a)(1) & 60.332(a)(2) and District Rule 4703] Federally Enforceable Through Title V Permit
23. Gas turbine engine start-up is that period of time not exceeding two hours in duration during which the unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
24. Gas turbine engine shutdown it that period of time not exceeding two hours in duration during which the unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
25. Gas turbine reduced load period is that period not exceeding one hour in duration during which the unit is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
26. Compliance with NOx, CO and ammonia emission limits shall be demonstrated by District-witnessed sample collection by independent testing laboratory annually. [District Rules 4703 and 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used PM10: EPA method 5 (front half and back half), NOx: EPA Method 7E or 20, CO: EPA method 10 (or 10B) or CARB Method 100, O2: EPA Method 3, 3A, or 20, VOC: EPA method 18 or 25, ammonia: BAAQMD ST-1B, and fuel gas sulfur content: ASTM D3246. Alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rule 1081, 40 CFR 60.335 (b), and District Rule 4703, 6.4] Federally Enforceable Through Title V Permit

29. Compliance with ammonia slip limit shall be demonstrated by using the following calculation procedure: ammonia slip ppmv @ 15% O2 = ((a-(bxc/1,000,000)) x 1,000,000 / b) x d, where a = ammonia injection rate(lb/hr)/17(lb/lb. mol), b = dry exhaust gas flow rate (lb/hr)/(29(lb/lb. mol), c = change in measured NOx concentration ppmv at 15% O2 across catalyst, and d = correction factor. The correction factor shall be derived annually during compliance testing by comparing the measured and calculated ammonia slip. [District Rule 4102] Federally Enforceable Through Title V Permit

30. Official test results and field data shall be submitted within 60 days after collection. [District Rule 4703 and District Rule 1081] Federally Enforceable Through Title V Permit

31. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

33. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

34. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

35. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

36. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4703] Federally Enforceable Through Title V Permit

38. CEC emission rates, except during periods of startup, shutdown, or reduced load shall not exceed PM10: 9.98 lb/hr, SOx (as SO2): 0.92 lb/hr, NOx (as NO2): 17.66 lb/hr, VOC: 9.00 lb/hr, and CO: 54.91 lb/hr. [District Rules 2080 and 4703, and 40 CFR 60] Federally Enforceable Through Title V Permit

39. For CEC purposes, emissions during periods of startup and shutdown shall not exceed the following values average over 2 hours: NOx: 140 lb/hr, and CO: 94 lb/hr. [District Rule 2080] Federally Enforceable Through Title V Permit

40. The CEC shall be notified of any changes to the combined annual emission limits for steam generators S-1135-115, -119, -122, and -123, and cogeneration units S-1135-224, -225, and -226, only to the extent to be informed of their impact on the Midway-Sunset Cogeneration Facility. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [Kern County Rule 108 and District Rule 1080] Federally Enforceable Through Title V Permit

42. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [Kern County Rule 108; District Rules 1080 and 4703; 40 CFR 60.7 (b)] Federally Enforceable Through Title V Permit

43. The permittee shall maintain hourly average records of NOx and CO emissions. Compliance with the hourly, daily, and twelve month rolling average VOC emission limits shall be demonstrated by the CO CEM data and the VOC/CO relationship determined by annual CO and VOC source tests of NOx, CO, and ammonia emission concentrations (ppmv @ 15% O2), and hourly, daily, and twelve month rolling. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

44. A violation of NOx emission standards indicated by the NOx CEM shall be reported by the operator to the APCO within 96 hours. [Kern County Rule 108 and District Rule 1080, 9.0] Federally Enforceable Through Title V Permit

45. Operator shall notify the APCO no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [Kern County Rule 108 and District Rule 1080, 10.0] Federally Enforceable Through Title V Permit

46. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 1081] Federally Enforceable Through Title V Permit

47. Unit shall be fired on a natural gas which has a sulfur content of less than or equal to 0.017% by weight. [40 CFR 60.333 (a) & (b); 40 CFR 60.334 (c)(2); Kern County Rule 407; and District Rule 4801] Federally Enforceable Through Title V Permit

48. If the turbine is fired on PUC-regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

49. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using method(s) specified on this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

50. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using ASTM method D 1072, D 3031, D 4084 or D 3246, or double GC for H2S and mercaptans. [40 CFR 60.335 (d)] Federally Enforceable Through Title V Permit

51. If the turbine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be semi-annually. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334 (b)(2)] Federally Enforceable Through Title V Permit

52. Operator shall submit a semiannual report listing any daily period during which the sulfur content of the fuel being fired in the gas turbine exceeds 0.8% by weight. [40 CFR 60.334(a)(2)] Federally Enforceable Through Title V Permit

53. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, OR ASTM 1945. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

54. The operator shall provide source test information annually regarding the exhaust gas NOx concentration corrected to 15% O2 (dry). [40 CFR 60.332 (a),(b) and District Rule 4703, 5.1] Federally Enforceable Through Title V Permit

55. Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334 (a),(b),(c) and District Rule 4703, 5.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

56. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

57. This unit is a simple combustion turbine as defined in 40 CFR 72.6 (b)(1) and shall not be subject to the requirements of 40 CFR Part 72. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Kern County Rules 404, 108, and 108.1. A permit shield is granted from these requirements. [SJVUAPCD Rule 2520, 13.2] Federally Enforceable Through Title V Permit

59. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: Kern County Rule 407; District Rules 4801, 4201, 1081, and 1080, Sections 6.5, 7.2, 8.0, 9.0, and 10.0; 40 CFR 60.332 (c) and (d); 60.334 (b), (c)(2); 60.335(d). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: District Rule 4703, sections 5.0, 5.1.1, 6.2.1, 6.2.4, 6.3, 6.4.1, 6.4.3, 6.4.5, and 6.4.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: District Rules 1080, 7.3 and 4703, 6.2.2; 40 CFR 60.332(a), (b); 60.333(a) and (b), 60.334(a), (b), and (c)(1); 60.335(a), (b) and (c)(2). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

62. All equipment, facilities, and systems installed or used to achieve compliance with the terms and conditions of this permit shall at all times be maintained in good working order and be operated as efficiently as possible so as to minimize air pollutant emissions. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

63. The Permittee (MSCC) must notify EPA by telephone, facsimile, or electronic mail transmission within two (2) working days following the discovery of any failure of air pollution control equipment, process equipment, or of a process to operate in a normal manner, which results in an increase in emissions above any allowable emission limit stated in any conditions where PSD is cited as the basis of the condition. In addition, the Permittee (MSCC) must notify EPA in writing within fifteen (15) days of any such failure. The notification shall include a description of the malfunctioning equipment or abnormal operation, the date of the initial malfunction, the period of time over which emissions were increased due to the failure, the cause of the failure, the estimated resultant emissions in excess of those allowed in any conditions where PSD is cited as the basis of the condition, and the methods utilized to mitigate emissions and restore normal operations. Compliance with this malfunction notification provision shall not excuse or otherwise constitute a defense to any violation of this permit or of any law or regulation that such malfunction may cause, except as provided for in the conditions where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

64. A malfunction means a sudden and unavoidable breakdown of equipment or of a process beyond the reasonable control of the source. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

65. Emissions in excess of the limits specified in any conditions where PSD is cited as the basis of the condition shall constitute a violation of this permit and may be the subject of enforcement proceedings. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

66. Affirmative defense: In the context of an enforcement proceeding, emissions which are below the limits set forth in any condition where PSD is cited as the basis of the condition shall not be subject to penalty if the Permittee (MSCC) retains properly signed, contemporaneous operating logs or other relevant evidence and can demonstrate all of the following: i.) A malfunction caused the emissions in excess of the limits in any condition where PSD is cited as the basis of the condition; ii.) The permitted facility, including the air pollution control equipment and process equipment, was being properly operated at the time of the malfunction; iii.) Preventative maintenance was regularly performed in a manner consistent with good practice for minimizing emissions; iv.) The excess emissions were not part of a recurring pattern indicative of inadequate design, operation, or maintenance; v.) During the period of the malfunction, the permittee (MSCC) took all reasonable steps to minimize the amount and duration of emissions (including any bypass) that exceeded the emission limits provided in any condition where PSD is cited as the basis of the condition. Reasonable steps to minimize emissions could include, but are not limited to, reducing production to the lowest level practicable, reducing the material feed that results in the increased emissions, and switching to alternative, less polluting fuels. Where repairs were required, repairs were made in an expeditious fashion when the operator knew or should have known that applicable emission limitations were being exceeded. Off-shift labor and overtime must have been utilized, to the extent practicable, to ensure that such repairs were made as expeditiously as possible; and vi.) The permittee (MSCC) complied with the malfunction reporting requirements as specified in the condition where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

67. All emissions, including those associated with a malfunction which may be eligible for an affirmative defense, must be included in all emissions calculations and demonstrations of compliance with mass emission limits (e.g., daily, monthly, and annual emission limits) specified in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

68. This provision is in addition to any emergency or malfunction provision contained in any applicable requirement or elsewhere in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

69. The EPA Regional Administrator, and/or their authorized representative, upon the presentation of credential, must be permitted: (1) to enter the premises where the source is located or where any records are required to be kept under the terms and conditions of the PSD permit SJ-87-01; and (2) at reasonable times to have access to and copy any records required to be kept under the terms and conditions of PSD permit SJ 87-01; and (3) to inspect any equipment, operation, or method required in the PSD permit SJ-87-01; and (4) to sample emissions from source(s). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

70. In the event of any changes in control or ownership of facilities to be constructed or modified, this permit shall be binding on all subsequent owners and operators. The Permittee (MSCC) shall notify the succeeding owner and operator of the existence of the PSD permit SJ-87-01 and its conditions by letter, a copy of which shall be forwarded to the EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

71. The provisions of the PSD permit SJ-87-01 are severable, and , if any provisions of the permit is held invalid, the remainder of the permit must not be affected thereby. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

72. The permittee (MSCC) must construct and operate the proposed power plant in compliance with all other applicable provisions of 40 CFR Parts 52, 60, 62, and 63 and all other applicable Federal, State, and local air quality regulations. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

73. On or before the date of startup (as defined in 40 C.F.R. 60.2) of the Western Midway Sunset Cogeneration Project (WMSCP; PSD Permit No. SJ-00-01) and thereafter the Permittee (MSCC) must install, continuously operate, and maintain the Dry Low NOx (DLN) combustion systems to reduce NOx emissions from each of its three turbines. The Permittee (MSCC) shall also use proper combustion techniques for the control of CO emissions from the equipment at MSCP. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

74. Within 60 days after achieving the base load, but no later than 180 days after initial startup of all three modified turbines (as defined in 40 C.F.R. 60.2), and annually thereafter (at about the anniversary of the initial performance test), the Permittee (MSCC) must conduct performance tests (as described in 40 C.F.R. 60.8) for NOx, and CO on the exhaust stack gases. The Permittee (MSCC) must furnish the District, the California Air Resources Board (CARB), and the EPA a written report of the results of such tests. Upon written request from the Permittee (MSCC), and adequate justification, EPA may waive a specific annual test and/or allow for testing to be done at less than maximum operating capacity. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

75. Performance tests for the emissions of NOx, and CO must be conducted and the results reported in accordance with the test methods set forth in 40 C.F.R. 60.8 and 40 C.F.R. 60, Appendix A. The following test methods must be used: a.) Performance tests for the emissions of NOx must be conducted using EPA Method 1-4 and 7E. b.) Performance tests for the emissions of CO must be conducted using the EPA Methods 1-4 and 10. In lieu of the above-mentioned test methods, equivalent methods may be used with prior written approval from EPA. The Permittee (MSCC) must notify EPA in writing at least 30 days prior to such tests to allow time for the development of an approvable performance test plan and to arrange for an observer to be present at the test. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

76. For performance test purposes, sampling ports, platforms, and access must be provided by the Permittee on the emission unit exhaust system in accordance with 40 C.F.R. 60.8(e). [PSD SJ 87-01] Federally Enforceable Through Title V Permit

77. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of CO into the atmosphere in excess of the following emission limits per turbine: The more stringent of 25 ppmvd @ 15% O2 or 55 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

78. This condition applies prior to the startup of the WMSCP: On and after the date of start up any of the three turbines at MSCP must not discharge (per turbine, and based on 3-hour rolling average) into the atmosphere CO in excess of the following of any of: 1.) The more stringent of 52.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 75%. 2.) The more stringent of 62.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 35% but less than 75%. 3.) 94 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

79. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of NOx into the atmosphere in excess of the following emission limits per turbine: The more stringent of 10 ppmvd @ 15% O2 or 36.1 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

80. This condition applies prior to the startup of the WMSCP: On and after the date of start-up of any of the three turbines, MSCC must not discharge (per turbine, based on 3-hour rolling average) into the atmosphere NOx (as NO2) in excess of the following: 1.) The more stringent of 25.0 ppmvd @ 15% O2 or 85.0 pounds per hour for loads greater than or equal to 75%; 2.) The more stringent of 42.0 ppmvd @ 15% O2 or 85 pounds per hour for loads greater than or equal to 35% but less than 75%; 3.) 85 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

81. The hourly (3-hour averaging) emissions must not exceed: 1.) 94 pounds of CO and 85 pounds of NOx; 2.) All CEMs must be operating during startups and shut downs; 3.) The time, date and duration of each startup and shutdown event must be recorded. The records must include the lbs/hour calculations based on the CEM data. These records must be kept for five years following the date of such events. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

82. Prior to the date of startup and thereafter, the Permittee (MSCC) must install, maintain and operate the following continuous monitoring systems (CEMs) in the exhaust stacks: a.) Continuous monitoring systems to measure stack gas NOx , CO and O2 concentrations. The systems must meet EPA monitoring performance specification (40 C.F.R. 60.13 and 40 C.F.R. 60, Appendix B, Performance Specifications 2, 3 and 4); b.) A continuous monitoring system to measure stack gas and natural gas volumetric flow rates. The stack gas flow measurement system must meet EPA Performance Specifications for (40 C.F.R. Part 52, Appendix E). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

83. The Permittee (MSCC) must maintain a file of all measurements, including continuous monitoring systems evaluations; all continuous monitoring systems or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; performance and all other information required by 40 C.F.R. 60 Appendices A-B recorded in a permanent form suitable for inspection. The file must be retained for five years following the date of such measurements, maintenance, reports and records. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

84. The Permittee (MSCC) must notify EPA of the date on which demonstration for the continuous monitoring system performance commences (40 C.F.R. 60.13). This date must be no later than 60 days after full load operation but not later than 180 days after startup. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

85. The Permittee (MSCC) must submit a written report of all excess emissions to EPA for every calendar quarter. The quarterly report must include the following: a.) The magnitude of the excess emissions computed in accordance with 40 C.F.R. 60.13(h), any conversion factors used, and the date and time of commencement and compilation of each time period of excess emissions; b.) Specific identification of each period of excess emissions that occurs during startups, shutdowns, and malfunctions of any equipment. The nature and cause of any malfunction (if known) and the corrective action taken or preventative measures adopted must also be reported; c.) The date and time identifying each period during which the continuous monitoring system was inoperative except for zero and span checks, and the nature of the system repairs or adjustments; d.) When no excess emissions have occurred or the continuous monitoring system has not been inoperative, repaired, or adjusted, such information must be stated in the report; and e.) Excess emissions must be defined as any 3-hour period during which the average emissions of CO, as measured by the CEM exceeds the maximum emission limits set forth in the condition with a CO emission limit, where PSD is cited as the basis of the condition or any 3-hour period during which the average emissions of NOx exceed the maximum emission limits set forth in the condition with a NOx emission limit, where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

86. Excess emissions indicated by the CEM system must be considered violations of the applicable emission limit for the purpose of this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

87. The quality assurance project plan used by the Permittee (MSCC) for the certification and operation of the continuous emissions monitors, which meets the requirements of 40 C.F.R. Part 60, Appendix F, must be available upon request to EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

88. The Permittee (MSCC) must keep a monthly record of all fuel uses. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

89. The proposed power plant is subject to the federal regulations entitled Standards of Performance for New Stationary Sources (40 C.F.R. 60). The owner or operator must meet all applicable requirements of 40 C.F.R. 60 Subparts A and GG of this regulation. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

90. All three turbines will fire natural gas only. The Permittee (MSCC) must only combust pipeline quality natural gas with sulfur content (as S) below 0.75 grains per 100 dry standard cubic feet (dscf). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

91. MSCC shall have legal and operational responsibility and control of all air pollutant emitting activities of the MSCP. This responsibility shall include, but shall not be limited to the following: 1.) Operating and maintaining the project to comply with all federal, state, and local air pollution laws, regulations, orders, and other requirements; 2.) Ensuring the emissions offsets, tradeoffs, or other emission reductions required for this project under permits issued by the U.S. EPA, the District, and/or the California Energy Commission are obtained as required; or 3.) Any violations of any air pollution requirements are the legal responsibility of MSCC, in addition to any other legal responsible entity. Any proposed change to this condition shall require prior written concurrence of the US EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

92. In accordance with the emissions offset plan proposed by the applicant for the District (dated November 12, 1987) and the emissions offset plan for the U.S. EPA (dated July 21, 1987), Aera Energy LLC must not operate the following four steam generators (listed by District permit numbers S-1135-119, S-1135-122, S-1135-123, and S-1135-115) simultaneously with the firing of the MSCP turbines unless one or more of the MSCP turbines is shutdown: Andersen-Goodwin Lease: S-1135-119, S-1135-122, S-1135-123 and Neely Lease: S-1135-115 [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

93. MSCC shall maintain a record of the date(s), time(s), and duration(s) of the shutdown of any of the above mentioned steam generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

94. Aera Energy LLC shall not lease or modify the permit conditions for any of the above generators for use in the Midway Sunset Oil field, unless creditable emissions reductions (as defined in 40 C.F.R. 52.21), at a ratio of at least 1:1, are provided for emissions from those generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

95. Aera Energy LLC shall not modify any of the District Permit to Operate numbers. If any of the above steam generators are issued new Permit to Operate numbers by the District, Aera Energy LLC shall notify the U.S. EPA in writing of this action and shall make such notification upon issuance of a new Permit to Operate number. This letter shall include the original District Permit to Operate number(s) of the subject generator(s) and a copy of the new Permit to Operate issued by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

96. Aera Energy LLC shall notify the U.S. EPA in writing of the intention to sell, or potential sale, of any of the above generators and shall make such notification prior to the District's final action of the re-permitting process associated with the sale of a generators. This letter shall include the following: a.) The subject steam generator as identified by its District Permit to Operate number; b.) The name of the buyer (as identified by the company name) of the steam generator; and c.) An estimated date of the final action of the re-permitting process by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

97. The allowable incidental taking (killing, harming, or harassment) of San Joaquin kit foxes, blunt-nosed leopard lizards, and giant kangaroo rats is confined to the proposed cogeneration plant site one half mile radius around this site (on lands owned or leased by Aera Energy LLC), and associated subject cogeneration plant facilities (including pipelines, transmission lines, temporary equipment stockpiling areas, and access roads) as discussed in the project Application for Certification report (Sun Cogeneration Company and Southern Sierra Energy Company 1985). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

98. MSCC is required to implement the "Agreement on Conditions for Mitigation of the Biological Impacts of the Midway-Sunset Project" as required by the U.S. Fish and Wildlife Service (USFWS) (Memorandum dated March 16, 1987 from the USFWS to the US EPA). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

99. Any endangered species found dead should be turned in to the California Department of Fish and Game for Analysis. MSCC must also report this event to the USFWS. The USFWS may recommend amendment to the existing project actions pending results of the analysis. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

100. All correspondence as required by this permit shall be forwarded to: 1.) Director, Air Division (Attn: Air-3) EPA Region IX 75 Hawthorne Street San Francisco, CA 94105-3901 Tel: (415) 744-1291 Fax: (415) 744-1076; 2.) Chief, Stationary Source Division, California Air Resource Board P.O. Box 2815 Sacramento, CA 95812; and 3.) Air Pollution Control Officer, San Joaquin Valley Unified APCD 2700 M Street, Suite 275 Bakersfield, CA 93301-2370. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

101. Aera Energy LLC is the legal owner of the subject steam generators and of the leases on which the steam generators are located. MSCC is the legal owner of the gas turbine cogeneration facility. MSCC is jointly owned by Sun Cogeneration Limited Partnership (Sun Cogen LP) and San Joaquin Energy Company. Sun Cogen LP is managed and controlled by a wholly owned subsidiary of Aera Energy LLC. (See Condition 104) [PSD SJ-87-01] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-225-23 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
NOMINALLY RATED 78.2 MW COGENERATION UNIT B WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS, SELECTIVE CATALYTIC REDUCTION (SCR), AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)

PERMIT UNIT REQUIREMENTS

1. CTG exhaust after the SCR unit shall be equipped with continuously recording emissions monitors dedicated to this unit for NOx, CO, and O2. Continuous emissions monitors shall meet the requirements of 40 CFR Part 60, Appendices B and F, and 40 CFR Part 75, and shall be capable of monitoring emissions during startups and shutdowns as well as normal operating conditions. If relative accuracy of CEM(s) cannot be demonstrated during startup conditions, CEM results during startup and shutdown events shall be replaced with startup emission rates obtained from source testing to determine compliance with emission limits. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
2. CTG shall be equipped with a continuously recording emission monitor preceding the SCR module measuring NOx concentration for the purposes of calculating ammonia slip. Permittee shall check, record, and quantify the calibration drift (CD) at two concentration values at least once daily (approximately 24 hours). The calibration shall be adjusted whenever the daily zero or high-level CD exceeds 5%. If either the zero or high-level CD exceeds 5% for five consecutive daily periods, the analyzer shall be deemed out-of-control. If either the zero or high-level CD exceeds 10% during any CD check, analyzer shall be deemed out-of-control. If the analyzer is out-of-control, the permittee shall take appropriate corrective action and then repeat the CD check. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
3. Ammonia injection grid shall be equipped with operational ammonia flowmeter and injection pressure indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Heat recovery steam generator design shall provide space for additional selective catalytic reduction catalyst and oxidation catalyst if required to meet NOx and CO emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall monitor and record exhaust gas temperature at selective catalytic reduction and oxidation catalyst inlets. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Ammonia shall be injected whenever the selective catalytic reduction system catalyst temperature exceeds the minimum ammonia injection temperature recommended by the manufacturer. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas turbine engine shall be equipped with fuel consumption monitor recorder accurate to +/- 3%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. CEM for NOx (as NO2) and CO shall conform to Rule 1080 specifications. [District Rules 1080 and 4703] Federally Enforceable Through Title V Permit
9. HRSG exhaust stack shall be equipped with permanent stack sampling provisions adequate to facilitate testing consistent with EPA test methods. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Flue gas ducting from engine to HRSG shall have no provisions for introduction of dilution air. [District Rule 1110] Federally Enforceable Through Title V Permit
11. Lube oil cooler/accumulation vent shall be equipped with control device(s) approved by the APCO sufficient to prevent emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Lube oil cooler/accumulator vent(s) shall not have detectable emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Natural gas sulfur content shall not exceed 0.31 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Facility shall operate as a cogeneration facility pursuant to Public Resources Code section 25134 for TEOR operations unless prior District and CEC approval is granted to operate otherwise. [District Rule 2080] Federally Enforceable Through Title V Permit
15. All CEM's shall be calibrated and operated according to EPA guidelines as specified in 40 CFR 60 Appendix B. [District Rule 1080] Federally Enforceable Through Title V Permit
16. Quarterly CEM reports shall be submitted to the APCO according to EPA regulations as specified in 40 CFR 60 Appendix B. [District Rule 4001 and District rule 1080, 8.0] Federally Enforceable Through Title V Permit
17. Audits of all monitors shall be conducted by independent laboratory in accordance with EPA guidelines and witnessed by District. Reports shall be submitted to District within 60 days of audits. [District Rule 1080] Federally Enforceable Through Title V Permit
18. All notification, recordkeeping, performance tests, reporting requirements, and compliance testing requirements of Rule 4001 NSPS shall be satisfied. [District Rule 4001] Federally Enforceable Through Title V Permit
19. Operational records including fuel type, fuel characteristics, and consumption shall be maintained and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
20. Accurate records of NOx (as NO2) and CO flue gas concentration corrected to 15% O2 and fuel gas sulfur content shall be maintained and shall be reported as described in Rule 1080 upon request. [District Rule 1080] Federally Enforceable Through Title V Permit
21. Emission rates shall not exceed the following: PM10: 0.010 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu, VOC: 0.009 lb/MMBtu, CO: 0.057 lb/MMBtu, and ammonia - 10 ppmvd @ 15%O2. [District NSR Rule; District Rule 4201; and Kern County Rule 404] Federally Enforceable Through Title V Permit
22. Permittee shall comply with the following emission limit at all times except during periods of start-up, shutdown, or reduced load as defined in Rule 4703: NOx (as NO2): 5.0 ppmv, and CO: 25 ppmv, dry @ 15% O2 corrected to ISO conditions. [40 CFR 60.332(a)(1) & 60.332(a)(2) and District Rule 4703] Federally Enforceable Through Title V Permit
23. Gas turbine engine start-up is that period of time not exceeding two hours in duration during which the unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
24. Gas turbine engine shutdown it that period of time not exceeding two hours in duration during which the unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
25. Gas turbine reduced load period is that period not exceeding one hour in duration during which the unit is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
26. Compliance with NOx, CO and ammonia emission limits shall be demonstrated by District-witnessed sample collection by independent testing laboratory annually. [District Rules 4703 and 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used PM10: EPA method 5 (front half and back half), NOx: EPA Method 7E or 20, CO: EPA method 10 (or 10B) or CARB Method 100, O2: EPA Method 3, 3A, or 20, VOC: EPA method 18 or 25, ammonia: BAAQMD ST-1B, and fuel gas sulfur content: ASTM D3246. Alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rule 1081, 40 CFR 60.335 (b), and District Rule 4703, 6.4] Federally Enforceable Through Title V Permit

29. Compliance with ammonia slip limit shall be demonstrated by using the following calculation procedure: ammonia slip ppmv @ 15% O2 = ((a-(bxc/1,000,000)) x 1,000,000 / b) x d, where a = ammonia injection rate(lb/hr)/17(lb/lb. mol), b = dry exhaust gas flow rate (lb/hr)/(29(lb/lb. mol), c = change in measured NOx concentration ppmv at 15% O2 across catalyst, and d = correction factor. The correction factor shall be derived annually during compliance testing by comparing the measured and calculated ammonia slip. [District Rule 4102] Federally Enforceable Through Title V Permit

30. Official test results and field data shall be submitted within 60 days after collection. [District Rule 4703 and District Rule 1081] Federally Enforceable Through Title V Permit

31. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

33. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

34. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

35. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

36. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4703] Federally Enforceable Through Title V Permit

38. CEC emission rates, except during periods of startup, shutdown, or reduced load shall not exceed PM10: 9.98 lb/hr, SOx (as SO2): 0.92 lb/hr, NOx (as NO2): 17.66 lb/hr, VOC: 9.00 lb/hr, and CO: 54.91 lb/hr. [District Rules 2080 and 4703, and 40 CFR 60] Federally Enforceable Through Title V Permit

39. For CEC purposes, emissions during periods of startup and shutdown shall not exceed the following values average over 2 hours: NOx: 140 lb/hr, and CO: 94 lb/hr. [District Rule 2080] Federally Enforceable Through Title V Permit

40. The CEC shall be notified of any changes to the combined annual emission limits for steam generators S-1135-115, -119, -122, and -123, and cogeneration units S-1135-224, -225, and -226, only to the extent to be informed of their impact on the Midway-Sunset Cogeneration Facility. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [Kern County Rule 108 and District Rule 1080] Federally Enforceable Through Title V Permit

42. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [Kern County Rule 108; District Rules 1080 and 4703; 40 CFR 60.7 (b)] Federally Enforceable Through Title V Permit

43. The permittee shall maintain hourly average records of NOx and CO emissions. Compliance with the hourly, daily, and twelve month rolling average VOC emission limits shall be demonstrated by the CO CEM data and the VOC/CO relationship determined by annual CO and VOC source tests of NOx, CO, and ammonia emission concentrations (ppmv @ 15% O2), and hourly, daily, and twelve month rolling. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

44. A violation of NOx emission standards indicated by the NOx CEM shall be reported by the operator to the APCO within 96 hours. [Kern County Rule 108 and District Rule 1080, 9.0] Federally Enforceable Through Title V Permit

45. Operator shall notify the APCO no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [Kern County Rule 108 and District Rule 1080, 10.0] Federally Enforceable Through Title V Permit

46. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 1081] Federally Enforceable Through Title V Permit

47. Unit shall be fired on a natural gas which has a sulfur content of less than or equal to 0.017% by weight. [40 CFR 60.333 (a) & (b); 40 CFR 60.334 (c)(2); Kern County Rule 407; and District Rule 4801] Federally Enforceable Through Title V Permit

48. If the turbine is fired on PUC-regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

49. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using method(s) specified on this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

50. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using ASTM method D 1072, D 3031, D 4084 or D 3246, or double GC for H2S and mercaptans. [40 CFR 60.335 (d)] Federally Enforceable Through Title V Permit

51. If the turbine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be semi-annually. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334 (b)(2)] Federally Enforceable Through Title V Permit

52. Operator shall submit a semiannual report listing any daily period during which the sulfur content of the fuel being fired in the gas turbine exceeds 0.8% by weight. [40 CFR 60.334(a)(2)] Federally Enforceable Through Title V Permit

53. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, OR ASTM 1945. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

54. The operator shall provide source test information annually regarding the exhaust gas NOx concentration corrected to 15% O2 (dry). [40 CFR 60.332 (a),(b) and District Rule 4703, 5.1] Federally Enforceable Through Title V Permit

55. Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334 (a),(b),(c) and District Rule 4703, 5.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

56. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

57. This unit is a simple combustion turbine as defined in 40 CFR 72.6 (b)(1) and shall not be subject to the requirements of 40 CFR Part 72. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Kern County Rules 404, 108, and 108.1. A permit shield is granted from these requirements. [SJVUAPCD Rule 2520, 13.2] Federally Enforceable Through Title V Permit

59. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: Kern County Rule 407; District Rules 4801, 4201, 1081, and 1080, Sections 6.5, 7.2, 8.0, 9.0, and 10.0; 40 CFR 60.332 (c) and (d); 60.334 (b), (c)(2); 60.335(d). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: District Rule 4703, sections 5.0, 5.1.1, 6.2.1, 6.2.4, 6.3, 6.4.1, 6.4.3, 6.4.5, and 6.4.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: District Rules 1080, 7.3 and 4703, 6.2.2; 40 CFR 60.332(a), (b); 60.333(a) and (b), 60.334(a), (b), and (c)(1); 60.335(a), (b) and (c)(2). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

62. All equipment, facilities, and systems installed or used to achieve compliance with the terms and conditions of this permit shall at all times be maintained in good working order and be operated as efficiently as possible so as to minimize air pollutant emissions. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

63. The Permittee (MSCC) must notify EPA by telephone, facsimile, or electronic mail transmission within two (2) working days following the discovery of any failure of air pollution control equipment, process equipment, or of a process to operate in a normal manner, which results in an increase in emissions above any allowable emission limit stated in any conditions where PSD is cited as the basis of the condition. In addition, the Permittee (MSCC) must notify EPA in writing within fifteen (15) days of any such failure. The notification shall include a description of the malfunctioning equipment or abnormal operation, the date of the initial malfunction, the period of time over which emissions were increased due to the failure, the cause of the failure, the estimated resultant emissions in excess of those allowed in any conditions where PSD is cited as the basis of the condition, and the methods utilized to mitigate emissions and restore normal operations. Compliance with this malfunction notification provision shall not excuse or otherwise constitute a defense to any violation of this permit or of any law or regulation that such malfunction may cause, except as provided for in the conditions where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

64. A malfunction means a sudden and unavoidable breakdown of equipment or of a process beyond the reasonable control of the source. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

65. Emissions in excess of the limits specified in any conditions where PSD is cited as the basis of the condition shall constitute a violation of this permit and may be the subject of enforcement proceedings. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

66. Affirmative defense: In the context of an enforcement proceeding, emissions which are below the limits set forth in any condition where PSD is cited as the basis of the condition shall not be subject to penalty if the Permittee (MSCC) retains properly signed, contemporaneous operating logs or other relevant evidence and can demonstrate all of the following: i.) A malfunction caused the emissions in excess of the limits in any condition where PSD is cited as the basis of the condition; ii.) The permitted facility, including the air pollution control equipment and process equipment, was being properly operated at the time of the malfunction; iii.) Preventative maintenance was regularly performed in a manner consistent with good practice for minimizing emissions; iv.) The excess emissions were not part of a recurring pattern indicative of inadequate design, operation, or maintenance; v.) During the period of the malfunction, the permittee (MSCC) took all reasonable steps to minimize the amount and duration of emissions (including any bypass) that exceeded the emission limits provided in any condition where PSD is cited as the basis of the condition. Reasonable steps to minimize emissions could include, but are not limited to, reducing production to the lowest level practicable, reducing the material feed that results in the increased emissions, and switching to alternative, less polluting fuels. Where repairs were required, repairs were made in an expeditious fashion when the operator knew or should have known that applicable emission limitations were being exceeded. Off-shift labor and overtime must have been utilized, to the extent practicable, to ensure that such repairs were made as expeditiously as possible; and vi.) The permittee (MSCC) complied with the malfunction reporting requirements as specified in the condition where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

67. All emissions, including those associated with a malfunction which may be eligible for an affirmative defense, must be included in all emissions calculations and demonstrations of compliance with mass emission limits (e.g., daily, monthly, and annual emission limits) specified in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

68. This provision is in addition to any emergency or malfunction provision contained in any applicable requirement or elsewhere in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

69. The EPA Regional Administrator, and/or their authorized representative, upon the presentation of credential, must be permitted: (1) to enter the premises where the source is located or where any records are required to be kept under the terms and conditions of the PSD permit SJ-87-01; and (2) at reasonable times to have access to and copy any records required to be kept under the terms and conditions of PSD permit SJ 87-01; and (3) to inspect any equipment, operation, or method required in the PSD permit SJ-87-01; and (4) to sample emissions from source(s). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

70. In the event of any changes in control or ownership of facilities to be constructed or modified, this permit shall be binding on all subsequent owners and operators. The Permittee (MSCC) shall notify the succeeding owner and operator of the existence of the PSD permit SJ-87-01 and its conditions by letter, a copy of which shall be forwarded to the EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

71. The provisions of the PSD permit SJ-87-01 are severable, and , if any provisions of the permit is held invalid, the remainder of the permit must not be affected thereby. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

72. The permittee (MSCC) must construct and operate the proposed power plant in compliance with all other applicable provisions of 40 CFR Parts 52, 60, 62, and 63 and all other applicable Federal, State, and local air quality regulations. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

73. On or before the date of startup (as defined in 40 C.F.R. 60.2) of the Western Midway Sunset Cogeneration Project (WMSCP; PSD Permit No. SJ-00-01) and thereafter the Permittee (MSCC) must install, continuously operate, and maintain the Dry Low NOx (DLN) combustion systems to reduce NOx emissions from each of its three turbines. The Permittee (MSCC) shall also use proper combustion techniques for the control of CO emissions from the equipment at MSCP. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

74. Within 60 days after achieving the base load, but no later than 180 days after initial startup of all three modified turbines (as defined in 40 C.F.R. 60.2), and annually thereafter (at about the anniversary of the initial performance test), the Permittee (MSCC) must conduct performance tests (as described in 40 C.F.R. 60.8) for NOx, and CO on the exhaust stack gases. The Permittee (MSCC) must furnish the District, the California Air Resources Board (CARB), and the EPA a written report of the results of such tests. Upon written request from the Permittee (MSCC), and adequate justification, EPA may waive a specific annual test and/or allow for testing to be done at less than maximum operating capacity. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

75. Performance tests for the emissions of NOx, and CO must be conducted and the results reported in accordance with the test methods set forth in 40 C.F.R. 60.8 and 40 C.F.R. 60, Appendix A. The following test methods must be used: a.) Performance tests for the emissions of NOx must be conducted using EPA Method 1-4 and 7E. b.) Performance tests for the emissions of CO must be conducted using the EPA Methods 1-4 and 10. In lieu of the above-mentioned test methods, equivalent methods may be used with prior written approval from EPA. The Permittee (MSCC) must notify EPA in writing at least 30 days prior to such tests to allow time for the development of an approvable performance test plan and to arrange for an observer to be present at the test. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

76. For performance test purposes, sampling ports, platforms, and access must be provided by the Permittee on the emission unit exhaust system in accordance with 40 C.F.R. 60.8(e). [PSD SJ 87-01] Federally Enforceable Through Title V Permit

77. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of CO into the atmosphere in excess of the following emission limits per turbine: The more stringent of 25 ppmvd @ 15% O2 or 55 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

78. This condition applies prior to the startup of the WMSCP: On and after the date of start up any of the three turbines at MSCP must not discharge (per turbine, and based on 3-hour rolling average) into the atmosphere CO in excess of the following of any of: 1.) The more stringent of 52.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 75%. 2.) The more stringent of 62.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 35% but less than 75%. 3.) 94 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

79. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of NOx into the atmosphere in excess of the following emission limits per turbine: The more stringent of 10 ppmvd @ 15% O2 or 36.1 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

80. This condition applies prior to the startup of the WMSCP: On and after the date of start-up of any of the three turbines, MSCC must not discharge (per turbine, based on 3-hour rolling average) into the atmosphere NOx (as NO2) in excess of the following: 1.) The more stringent of 25.0 ppmvd @ 15% O2 or 85.0 pounds per hour for loads greater than or equal to 75%; 2.) The more stringent of 42.0 ppmvd @ 15% O2 or 85 pounds per hour for loads greater than or equal to 35% but less than 75%; 3.) 85 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

81. The hourly (3-hour averaging) emissions must not exceed: 1.) 94 pounds of CO and 85 pounds of NOx; 2.) All CEMs must be operating during startups and shut downs; 3.) The time, date and duration of each startup and shutdown event must be recorded. The records must include the lbs/hour calculations based on the CEM data. These records must be kept for five years following the date of such events. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

82. Prior to the date of startup and thereafter, the Permittee (MSCC) must install, maintain and operate the following continuous monitoring systems (CEMs) in the exhaust stacks: a.) Continuous monitoring systems to measure stack gas NOx , CO and O2 concentrations. The systems must meet EPA monitoring performance specification (40 C.F.R. 60.13 and 40 C.F.R. 60, Appendix B, Performance Specifications 2, 3 and 4); b.) A continuous monitoring system to measure stack gas and natural gas volumetric flow rates. The stack gas flow measurement system must meet EPA Performance Specifications for (40 C.F.R. Part 52, Appendix E). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

83. The Permittee (MSCC) must maintain a file of all measurements, including continuous monitoring systems evaluations; all continuous monitoring systems or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; performance and all other information required by 40 C.F.R. 60 Appendices A-B recorded in a permanent form suitable for inspection. The file must be retained for five years following the date of such measurements, maintenance, reports and records. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

84. The Permittee (MSCC) must notify EPA of the date on which demonstration for the continuous monitoring system performance commences (40 C.F.R. 60.13). This date must be no later than 60 days after full load operation but not later than 180 days after startup. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

85. The Permittee (MSCC) must submit a written report of all excess emissions to EPA for every calendar quarter. The quarterly report must include the following: a.) The magnitude of the excess emissions computed in accordance with 40 C.F.R. 60.13(h), any conversion factors used, and the date and time of commencement and compilation of each time period of excess emissions; b.) Specific identification of each period of excess emissions that occurs during startups, shutdowns, and malfunctions of any equipment. The nature and cause of any malfunction (if known) and the corrective action taken or preventative measures adopted must also be reported; c.) The date and time identifying each period during which the continuous monitoring system was inoperative except for zero and span checks, and the nature of the system repairs or adjustments; d.) When no excess emissions have occurred or the continuous monitoring system has not been inoperative, repaired, or adjusted, such information must be stated in the report; and e.) Excess emissions must be defined as any 3-hour period during which the average emissions of CO, as measured by the CEM exceeds the maximum emission limits set forth in the condition with a CO emission limit, where PSD is cited as the basis of the condition or any 3-hour period during which the average emissions of NOx exceed the maximum emission limits set forth in the condition with a NOx emission limit, where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

86. Excess emissions indicated by the CEM system must be considered violations of the applicable emission limit for the purpose of this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

87. The quality assurance project plan used by the Permittee (MSCC) for the certification and operation of the continuous emissions monitors, which meets the requirements of 40 C.F.R. Part 60, Appendix F, must be available upon request to EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

88. The Permittee (MSCC) must keep a monthly record of all fuel uses. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

89. The proposed power plant is subject to the federal regulations entitled Standards of Performance for New Stationary Sources (40 C.F.R. 60). The owner or operator must meet all applicable requirements of 40 C.F.R. 60 Subparts A and GG of this regulation. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

90. All three turbines will fire natural gas only. The Permittee (MSCC) must only combust pipeline quality natural gas with sulfur content (as S) below 0.75 grains per 100 dry standard cubic feet (dscf). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

91. MSCC shall have legal and operational responsibility and control of all air pollutant emitting activities of the MSCP. This responsibility shall include, but shall not be limited to the following: 1.) Operating and maintaining the project to comply with all federal, state, and local air pollution laws, regulations, orders, and other requirements; 2.) Ensuring the emissions offsets, tradeoffs, or other emission reductions required for this project under permits issued by the U.S. EPA, the District, and/or the California Energy Commission are obtained as required; or 3.) Any violations of any air pollution requirements are the legal responsibility of MSCC, in addition to any other legal responsible entity. Any proposed change to this condition shall require prior written concurrence of the US EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

92. In accordance with the emissions offset plan proposed by the applicant for the District (dated November 12, 1987) and the emissions offset plan for the U.S. EPA (dated July 21, 1987), Aera Energy LLC must not operate the following four steam generators (listed by District permit numbers S-1135-119, S-1135-122, S-1135-123, and S-1135-115) simultaneously with the firing of the MSCP turbines unless one or more of the MSCP turbines is shutdown: Andersen-Goodwin Lease: S-1135-119, S-1135-122, S-1135-123 and Neely Lease: S-1135-115 [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

93. MSCC shall maintain a record of the date(s), time(s), and duration(s) of the shutdown of any of the above mentioned steam generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

94. Aera Energy LLC shall not lease or modify the permit conditions for any of the above generators for use in the Midway Sunset Oil field, unless creditable emissions reductions (as defined in 40 C.F.R. 52.21), at a ratio of at least 1:1, are provided for emissions from those generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

95. Aera Energy LLC shall not modify any of the District Permit to Operate numbers. If any of the above steam generators are issued new Permit to Operate numbers by the District, Aera Energy LLC shall notify the U.S. EPA in writing of this action and shall make such notification upon issuance of a new Permit to Operate number. This letter shall include the original District Permit to Operate number(s) of the subject generator(s) and a copy of the new Permit to Operate issued by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

96. Aera Energy LLC shall notify the U.S. EPA in writing of the intention to sell, or potential sale, of any of the above generators and shall make such notification prior to the District's final action of the re-permitting process associated with the sale of a generators. This letter shall include the following: a.) The subject steam generator as identified by its District Permit to Operate number; b.) The name of the buyer (as identified by the company name) of the steam generator; and c.) An estimated date of the final action of the re-permitting process by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

97. The allowable incidental taking (killing, harming, or harassment) of San Joaquin kit foxes, blunt-nosed leopard lizards, and giant kangaroo rats is confined to the proposed cogeneration plant site one half mile radius around this site (on lands owned or leased by Aera Energy LLC), and associated subject cogeneration plant facilities (including pipelines, transmission lines, temporary equipment stockpiling areas, and access roads) as discussed in the project Application for Certification report (Sun Cogeneration Company and Southern Sierra Energy Company 1985). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

98. MSCC is required to implement the "Agreement on Conditions for Mitigation of the Biological Impacts of the Midway-Sunset Project" as required by the U.S. Fish and Wildlife Service (USFWS) (Memorandum dated March 16, 1987 from the USFWS to the US EPA). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

99. Any endangered species found dead should be turned in to the California Department of Fish and Game for Analysis. MSCC must also report this event to the USFWS. The USFWS may recommend amendment to the existing project actions pending results of the analysis. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

100. All correspondence as required by this permit shall be forwarded to: 1.) Director, Air Division (Attn: Air-3) EPA Region IX 75 Hawthorne Street San Francisco, CA 94105-3901 Tel: (415) 744-1291 Fax: (415) 744-1076; 2.) Chief, Stationary Source Division, California Air Resource Board P.O. Box 2815 Sacramento, CA 95812; and 3.) Air Pollution Control Officer, San Joaquin Valley Unified APCD 2700 M Street, Suite 275 Bakersfield, CA 93301-2370. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

101. Aera Energy LLC is the legal owner of the subject steam generators and of the leases on which the steam generators are located. MSCC is the legal owner of the gas turbine cogeneration facility. MSCC is jointly owned by Sun Cogeneration Limited Partnership (Sun Cogen LP) and San Joaquin Energy Company. Sun Cogen LP is managed and controlled by a wholly owned subsidiary of Aera Energy LLC. (See Condition 104) [PSD SJ-87-01] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-226-24 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
NOMINALLY RATED 78.2 MW COGENERATION UNIT C WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)

PERMIT UNIT REQUIREMENTS

1. CTG exhaust after the SCR unit shall be equipped with continuously recording emissions monitors dedicated to this unit for NOx, CO, and O2. Continuous emissions monitors shall meet the requirements of 40 CFR Part 60, Appendices B and F, and 40 CFR Part 75, and shall be capable of monitoring emissions during startups and shutdowns as well as normal operating conditions. If relative accuracy of CEM(s) cannot be demonstrated during startup conditions, CEM results during startup and shutdown events shall be replaced with startup emission rates obtained from source testing to determine compliance with emission limits. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
2. CTG shall be equipped with a continuously recording emission monitor preceding the SCR module measuring NOx concentration for the purposes of calculating ammonia slip. Permittee shall check, record, and quantify the calibration drift (CD) at two concentration values at least once daily (approximately 24 hours). The calibration shall be adjusted whenever the daily zero or high-level CD exceeds 5%. If either the zero or high-level CD exceeds 5% for five consecutive daily periods, the analyzer shall be deemed out-of-control. If either the zero or high-level CD exceeds 10% during any CD check, analyzer shall be deemed out-of-control. If the analyzer is out-of-control, the permittee shall take appropriate corrective action and then repeat the CD check. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
3. Ammonia injection grid shall be equipped with operational ammonia flowmeter and injection pressure indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Heat recovery steam generator design shall provide space for additional selective catalytic reduction catalyst and oxidation catalyst if required to meet NOx and CO emission limits. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall monitor and record exhaust gas temperature at selective catalytic reduction and oxidation catalyst inlets. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Ammonia shall be injected whenever the selective catalytic reduction system catalyst temperature exceeds the minimum ammonia injection temperature recommended by the manufacturer. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas turbine engine shall be equipped with fuel consumption monitor recorder accurate to +/- 3%. [District Rule 2201] Federally Enforceable Through Title V Permit
8. CEM for NOx (as NO2) and CO shall conform to Rule 1080 specifications. [District Rules 1080 and 4703] Federally Enforceable Through Title V Permit
9. HRSG exhaust stack shall be equipped with permanent stack sampling provisions adequate to facilitate testing consistent with EPA test methods. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Flue gas ducting from engine to HRSG shall have no provisions for introduction of dilution air. [District Rule 1110] Federally Enforceable Through Title V Permit
11. Lube oil cooler/accumulation vent shall be equipped with control device(s) approved by the APCO sufficient to prevent emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Lube oil cooler/accumulator vent(s) shall not have detectable emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Natural gas sulfur content shall not exceed 0.31 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Facility shall operate as a cogeneration facility pursuant to Public Resources Code section 25134 for TEOR operations unless prior District and CEC approval is granted to operate otherwise. [District Rule 2080] Federally Enforceable Through Title V Permit
15. All CEM's shall be calibrated and operated according to EPA guidelines as specified in 40 CFR 60 Appendix B. [District Rule 1080] Federally Enforceable Through Title V Permit
16. Quarterly CEM reports shall be submitted to the APCO according to EPA regulations as specified in 40 CFR 60 Appendix B. [District Rule 4001 and District rule 1080, 8.0] Federally Enforceable Through Title V Permit
17. Audits of all monitors shall be conducted by independent laboratory in accordance with EPA guidelines and witnessed by District. Reports shall be submitted to District within 60 days of audits. [District Rule 1080] Federally Enforceable Through Title V Permit
18. All notification, recordkeeping, performance tests, reporting requirements, and compliance testing requirements of Rule 4001 NSPS shall be satisfied. [District Rule 4001] Federally Enforceable Through Title V Permit
19. Operational records including fuel type, fuel characteristics, and consumption shall be maintained and shall be made readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
20. Accurate records of NOx (as NO2) and CO flue gas concentration corrected to 15% O2 and fuel gas sulfur content shall be maintained and shall be reported as described in Rule 1080 upon request. [District Rule 1080] Federally Enforceable Through Title V Permit
21. Emission rates shall not exceed the following: PM10: 0.010 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu, VOC: 0.009 lb/MMBtu, CO: 0.057 lb/MMBtu, and ammonia - 10 ppmvd @ 15%O2. [District NSR Rule; District Rule 4201; and Kern County Rule 404] Federally Enforceable Through Title V Permit
22. Permittee shall comply with the following emission limit at all times except during periods of start-up, shutdown, or reduced load as defined in Rule 4703: NOx (as NO2): 5.0 ppmv, and CO: 25 ppmv, dry @ 15% O2 corrected to ISO conditions. [40 CFR 60.332(a)(1) & 60.332(a)(2) and District Rule 4703] Federally Enforceable Through Title V Permit
23. Gas turbine engine start-up is that period of time not exceeding two hours in duration during which the unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
24. Gas turbine engine shutdown it that period of time not exceeding two hours in duration during which the unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
25. Gas turbine reduced load period is that period not exceeding one hour in duration during which the unit is operated at less than rated capacity in order to change the position of the exhaust gas diverter gate. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit
26. Compliance with NOx, CO and ammonia emission limits shall be demonstrated by District-witnessed sample collection by independent testing laboratory annually. [District Rules 4703 and 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used PM10: EPA method 5 (front half and back half), NOx: EPA Method 7E or 20, CO: EPA method 10 (or 10B) or CARB Method 100, O2: EPA Method 3, 3A, or 20, VOC: EPA method 18 or 25, ammonia: BAAQMD ST-1B, and fuel gas sulfur content: ASTM D3246. Alternative test methods as approved by the District may also be used to address the source testing requirements of this permit. [District Rule 1081, 40 CFR 60.335 (b), and District Rule 4703, 6.4] Federally Enforceable Through Title V Permit

29. Compliance with ammonia slip limit shall be demonstrated by using the following calculation procedure: ammonia slip ppmv @ 15% O2 = ((a-(bxc/1,000,000)) x 1,000,000 / b) x d, where a = ammonia injection rate(lb/hr)/17(lb/lb. mol), b = dry exhaust gas flow rate (lb/hr)/(29(lb/lb. mol), c = change in measured NOx concentration ppmv at 15% O2 across catalyst, and d = correction factor. The correction factor shall be derived annually during compliance testing by comparing the measured and calculated ammonia slip. [District Rule 4102] Federally Enforceable Through Title V Permit

30. Official test results and field data shall be submitted within 60 days after collection. [District Rule 4703 and District Rule 1081] Federally Enforceable Through Title V Permit

31. Combined annual emissions from units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, S-1135-226 shall not exceed any of the following: PM10 - 262,360 lb/yr, SOx (as SO2) - 24,200 lb/yr, NOx (as NO2) - 464,170 lb/yr, VOC - 236,520 lb/yr, or CO - 1,443,101 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

32. The permittee shall maintain records of fuel type, quantity, heating value of gas burned, permitted emission factors and annual emissions for each unit. For units equipped with continuous emissions monitors (CEMs), CEM data may be used in place of calculated emissions. If CEM shows a violation, CEM data shall be used. Records shall be updated at least monthly. Reports of annual emissions and fuel usage shall be submitted within 30 days after the end of the calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit

33. If fuel use monitoring provisions fail, emissions shall be calculated based on operational data, or if not available, on set equal to the average of four days prior to failure. [District NSR Rule] Federally Enforceable Through Title V Permit

34. When three gas turbine engines S-1135-224, '-225, and '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 shall be shut down. [District NSR Rule] Federally Enforceable Through Title V Permit

35. When up to two gas turbine engines S-1135-224, '-225, or '-226 are operating, four steam generators S-1135-115, '-119, '-122, and '-123 may be operated. [District NSR Rule] Federally Enforceable Through Title V Permit

36. The permittee shall maintain records of operational status of units S-1135-115, S-1135-119, S-1135-122, S1135-123, S-1135-224, S-1135-225, and S-1135-226 on a daily basis. [District Rule 2201] Federally Enforceable Through Title V Permit

37. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4703] Federally Enforceable Through Title V Permit

38. CEC emission rates, except during periods of startup, shutdown, or reduced load shall not exceed PM10: 9.98 lb/hr, SOx (as SO2): 0.92 lb/hr, NOx (as NO2): 17.66 lb/hr, VOC: 9.00 lb/hr, and CO: 54.91 lb/hr. [District Rules 2080 and 4703, and 40 CFR 60] Federally Enforceable Through Title V Permit

39. For CEC purposes, emissions during periods of startup and shutdown shall not exceed the following values average over 2 hours: NOx: 140 lb/hr, and CO: 94 lb/hr. [District Rule 2080] Federally Enforceable Through Title V Permit

40. The CEC shall be notified of any changes to the combined annual emission limits for steam generators S-1135-115, -119, -122, and -123, and cogeneration units S-1135-224, -225, and -226, only to the extent to be informed of their impact on the Midway-Sunset Cogeneration Facility. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. Results of continuous emissions monitoring must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the CARB, and the EPA. [Kern County Rule 108 and District Rule 1080] Federally Enforceable Through Title V Permit

42. Records shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of any CEM's that have been installed pursuant to District Rule 1080, and emission measurements. [Kern County Rule 108; District Rules 1080 and 4703; 40 CFR 60.7 (b)] Federally Enforceable Through Title V Permit

43. The permittee shall maintain hourly average records of NOx and CO emissions. Compliance with the hourly, daily, and twelve month rolling average VOC emission limits shall be demonstrated by the CO CEM data and the VOC/CO relationship determined by annual CO and VOC source tests of NOx, CO, and ammonia emission concentrations (ppmv @ 15% O2), and hourly, daily, and twelve month rolling. [District Rules 2201 and 4703] Federally Enforceable Through Title V Permit

44. A violation of NOx emission standards indicated by the NOx CEM shall be reported by the operator to the APCO within 96 hours. [Kern County Rule 108 and District Rule 1080, 9.0] Federally Enforceable Through Title V Permit

45. Operator shall notify the APCO no later than eight hours after the detection of a breakdown of the CEM. The operator shall inform the APCO of the intent to shut down the CEM at least 24 hours prior to the event. [Kern County Rule 108 and District Rule 1080, 10.0] Federally Enforceable Through Title V Permit

46. Emissions for this unit shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty-minute test runs for NOx and CO. [District Rule 1081] Federally Enforceable Through Title V Permit

47. Unit shall be fired on a natural gas which has a sulfur content of less than or equal to 0.017% by weight. [40 CFR 60.333 (a) & (b); 40 CFR 60.334 (c)(2); Kern County Rule 407; and District Rule 4801] Federally Enforceable Through Title V Permit

48. If the turbine is fired on PUC-regulated natural gas, then maintain on file copies of natural gas bills. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

49. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using method(s) specified on this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

50. If the turbine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the turbine shall be determined using ASTM method D 1072, D 3031, D 4084 or D 3246, or double GC for H2S and mercaptans. [40 CFR 60.335 (d)] Federally Enforceable Through Title V Permit

51. If the turbine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be semi-annually. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [40 CFR 60.334 (b)(2)] Federally Enforceable Through Title V Permit

52. Operator shall submit a semiannual report listing any daily period during which the sulfur content of the fuel being fired in the gas turbine exceeds 0.8% by weight. [40 CFR 60.334(a)(2)] Federally Enforceable Through Title V Permit

53. HHV and LHV of the fuel shall be determined using ASTM D3588, ASTM 1826, OR ASTM 1945. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.4.5] Federally Enforceable Through Title V Permit

54. The operator shall provide source test information annually regarding the exhaust gas NOx concentration corrected to 15% O2 (dry). [40 CFR 60.332 (a),(b) and District Rule 4703, 5.1] Federally Enforceable Through Title V Permit

55. Results of continuous emission monitoring must be averaged in accordance with the requirements of 40 CFR 60.13. [40 CFR 60.334 (a),(b),(c) and District Rule 4703, 5.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

56. Operator shall maintain a stationary gas turbine operating log that includes, on a daily basis the actual local start-up and stop time, length and reason for reduced load periods, total hours of operation and quantity of fuel used. [40 CFR 60.332 (a),(b) and District Rule 4703, 6.2.4] Federally Enforceable Through Title V Permit

57. This unit is a simple combustion turbine as defined in 40 CFR 72.6 (b)(1) and shall not be subject to the requirements of 40 CFR Part 72. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Kern County Rules 404, 108, and 108.1. A permit shield is granted from these requirements. [SJVUAPCD Rule 2520, 13.2] Federally Enforceable Through Title V Permit

59. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: Kern County Rule 407; District Rules 4801, 4201, 1081, and 1080, Sections 6.5, 7.2, 8.0, 9.0, and 10.0; 40 CFR 60.332 (c) and (d); 60.334 (b), (c)(2); 60.335(d). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: District Rule 4703, sections 5.0, 5.1.1, 6.2.1, 6.2.4, 6.3, 6.4.1, 6.4.3, 6.4.5, and 6.4.6. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: District Rules 1080, 7.3 and 4703, 6.2.2; 40 CFR 60.332(a), (b); 60.333(a) and (b), 60.334(a), (b), and (c)(1); 60.335(a), (b) and (c)(2). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

62. All equipment, facilities, and systems installed or used to achieve compliance with the terms and conditions of this permit shall at all times be maintained in good working order and be operated as efficiently as possible so as to minimize air pollutant emissions. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

63. The Permittee (MSCC) must notify EPA by telephone, facsimile, or electronic mail transmission within two (2) working days following the discovery of any failure of air pollution control equipment, process equipment, or of a process to operate in a normal manner, which results in an increase in emissions above any allowable emission limit stated in any conditions where PSD is cited as the basis of the condition. In addition, the Permittee (MSCC) must notify EPA in writing within fifteen (15) days of any such failure. The notification shall include a description of the malfunctioning equipment or abnormal operation, the date of the initial malfunction, the period of time over which emissions were increased due to the failure, the cause of the failure, the estimated resultant emissions in excess of those allowed in any conditions where PSD is cited as the basis of the condition, and the methods utilized to mitigate emissions and restore normal operations. Compliance with this malfunction notification provision shall not excuse or otherwise constitute a defense to any violation of this permit or of any law or regulation that such malfunction may cause, except as provided for in the conditions where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

64. A malfunction means a sudden and unavoidable breakdown of equipment or of a process beyond the reasonable control of the source. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

65. Emissions in excess of the limits specified in any conditions where PSD is cited as the basis of the condition shall constitute a violation of this permit and may be the subject of enforcement proceedings. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

66. Affirmative defense: In the context of an enforcement proceeding, emissions which are below the limits set forth in any condition where PSD is cited as the basis of the condition shall not be subject to penalty if the Permittee (MSCC) retains properly signed, contemporaneous operating logs or other relevant evidence and can demonstrate all of the following: i.) A malfunction caused the emissions in excess of the limits in any condition where PSD is cited as the basis of the condition; ii.) The permitted facility, including the air pollution control equipment and process equipment, was being properly operated at the time of the malfunction; iii.) Preventative maintenance was regularly performed in a manner consistent with good practice for minimizing emissions; iv.) The excess emissions were not part of a recurring pattern indicative of inadequate design, operation, or maintenance; v.) During the period of the malfunction, the permittee (MSCC) took all reasonable steps to minimize the amount and duration of emissions (including any bypass) that exceeded the emission limits provided in any condition where PSD is cited as the basis of the condition. Reasonable steps to minimize emissions could include, but are not limited to, reducing production to the lowest level practicable, reducing the material feed that results in the increased emissions, and switching to alternative, less polluting fuels. Where repairs were required, repairs were made in an expeditious fashion when the operator knew or should have known that applicable emission limitations were being exceeded. Off-shift labor and overtime must have been utilized, to the extent practicable, to ensure that such repairs were made as expeditiously as possible; and vi.) The permittee (MSCC) complied with the malfunction reporting requirements as specified in the condition where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

67. All emissions, including those associated with a malfunction which may be eligible for an affirmative defense, must be included in all emissions calculations and demonstrations of compliance with mass emission limits (e.g., daily, monthly, and annual emission limits) specified in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

68. This provision is in addition to any emergency or malfunction provision contained in any applicable requirement or elsewhere in this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

69. The EPA Regional Administrator, and/or their authorized representative, upon the presentation of credential, must be permitted: (1) to enter the premises where the source is located or where any records are required to be kept under the terms and conditions of the PSD permit SJ-87-01; and (2) at reasonable times to have access to and copy any records required to be kept under the terms and conditions of PSD permit SJ 87-01; and (3) to inspect any equipment, operation, or method required in the PSD permit SJ-87-01; and (4) to sample emissions from source(s). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

70. In the event of any changes in control or ownership of facilities to be constructed or modified, this permit shall be binding on all subsequent owners and operators. The Permittee (MSCC) shall notify the succeeding owner and operator of the existence of the PSD permit SJ-87-01 and its conditions by letter, a copy of which shall be forwarded to the EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

71. The provisions of the PSD permit SJ-87-01 are severable, and , if any provisions of the permit is held invalid, the remainder of the permit must not be affected thereby. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

72. The permittee (MSCC) must construct and operate the proposed power plant in compliance with all other applicable provisions of 40 CFR Parts 52, 60, 62, and 63 and all other applicable Federal, State, and local air quality regulations. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

73. On or before the date of startup (as defined in 40 C.F.R. 60.2) of the Western Midway Sunset Cogeneration Project (WMSCP; PSD Permit No. SJ-00-01) and thereafter the Permittee (MSCC) must install, continuously operate, and maintain the Dry Low NOx (DLN) combustion systems to reduce NOx emissions from each of its three turbines. The Permittee (MSCC) shall also use proper combustion techniques for the control of CO emissions from the equipment at MSCP. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

74. Within 60 days after achieving the base load, but no later than 180 days after initial startup of all three modified turbines (as defined in 40 C.F.R. 60.2), and annually thereafter (at about the anniversary of the initial performance test), the Permittee (MSCC) must conduct performance tests (as described in 40 C.F.R. 60.8) for NOx, and CO on the exhaust stack gases. The Permittee (MSCC) must furnish the District, the California Air Resources Board (CARB), and the EPA a written report of the results of such tests. Upon written request from the Permittee (MSCC), and adequate justification, EPA may waive a specific annual test and/or allow for testing to be done at less than maximum operating capacity. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

75. Performance tests for the emissions of NOx, and CO must be conducted and the results reported in accordance with the test methods set forth in 40 C.F.R. 60.8 and 40 C.F.R. 60, Appendix A. The following test methods must be used: a.) Performance tests for the emissions of NOx must be conducted using EPA Method 1-4 and 7E. b.) Performance tests for the emissions of CO must be conducted using the EPA Methods 1-4 and 10. In lieu of the above-mentioned test methods, equivalent methods may be used with prior written approval from EPA. The Permittee (MSCC) must notify EPA in writing at least 30 days prior to such tests to allow time for the development of an approvable performance test plan and to arrange for an observer to be present at the test. [PSD SJ 87-01] Federally Enforceable Through Title V Permit

76. For performance test purposes, sampling ports, platforms, and access must be provided by the Permittee on the emission unit exhaust system in accordance with 40 C.F.R. 60.8(e). [PSD SJ 87-01] Federally Enforceable Through Title V Permit

77. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of CO into the atmosphere in excess of the following emission limits per turbine: The more stringent of 25 ppmvd @ 15% O2 or 55 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

78. This condition applies prior to the startup of the WMSCP: On and after the date of start up any of the three turbines at MSCP must not discharge (per turbine, and based on 3-hour rolling average) into the atmosphere CO in excess of the following of any of: 1.) The more stringent of 52.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 75%. 2.) The more stringent of 62.0 ppmvd @ 15% O2 or 94 pounds for loads greater than or equal to 35% but less than 75%. 3.) 94 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

79. On and after the date of startup of the WMSCP (PSD Permit No. SJ-00-01), the Permittee (MSCC) must not discharge or cause the discharge of NOx into the atmosphere in excess of the following emission limits per turbine: The more stringent of 10 ppmvd @ 15% O2 or 36.1 pounds per hour, based on 3-hour rolling average. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

80. This condition applies prior to the startup of the WMSCP: On and after the date of start-up of any of the three turbines, MSCC must not discharge (per turbine, based on 3-hour rolling average) into the atmosphere NOx (as NO2) in excess of the following: 1.) The more stringent of 25.0 ppmvd @ 15% O2 or 85.0 pounds per hour for loads greater than or equal to 75%; 2.) The more stringent of 42.0 ppmvd @ 15% O2 or 85 pounds per hour for loads greater than or equal to 35% but less than 75%; 3.) 85 pounds per hour for loads less than 35%. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

81. The hourly (3-hour averaging) emissions must not exceed: 1.) 94 pounds of CO and 85 pounds of NOx; 2.) All CEMs must be operating during startups and shut downs; 3.) The time, date and duration of each startup and shutdown event must be recorded. The records must include the lbs/hour calculations based on the CEM data. These records must be kept for five years following the date of such events. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

82. Prior to the date of startup and thereafter, the Permittee (MSCC) must install, maintain and operate the following continuous monitoring systems (CEMs) in the exhaust stacks: a.) Continuous monitoring systems to measure stack gas NOx , CO and O2 concentrations. The systems must meet EPA monitoring performance specification (40 C.F.R. 60.13 and 40 C.F.R. 60, Appendix B, Performance Specifications 2, 3 and 4); b.) A continuous monitoring system to measure stack gas and natural gas volumetric flow rates. The stack gas flow measurement system must meet EPA Performance Specifications for (40 C.F.R. Part 52, Appendix E). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

83. The Permittee (MSCC) must maintain a file of all measurements, including continuous monitoring systems evaluations; all continuous monitoring systems or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; performance and all other information required by 40 C.F.R. 60 Appendices A-B recorded in a permanent form suitable for inspection. The file must be retained for five years following the date of such measurements, maintenance, reports and records. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

84. The Permittee (MSCC) must notify EPA of the date on which demonstration for the continuous monitoring system performance commences (40 C.F.R. 60.13). This date must be no later than 60 days after full load operation but not later than 180 days after startup. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

85. The Permittee (MSCC) must submit a written report of all excess emissions to EPA for every calendar quarter. The quarterly report must include the following: a.) The magnitude of the excess emissions computed in accordance with 40 C.F.R. 60.13(h), any conversion factors used, and the date and time of commencement and compilation of each time period of excess emissions; b.) Specific identification of each period of excess emissions that occurs during startups, shutdowns, and malfunctions of any equipment. The nature and cause of any malfunction (if known) and the corrective action taken or preventative measures adopted must also be reported; c.) The date and time identifying each period during which the continuous monitoring system was inoperative except for zero and span checks, and the nature of the system repairs or adjustments; d.) When no excess emissions have occurred or the continuous monitoring system has not been inoperative, repaired, or adjusted, such information must be stated in the report; and e.) Excess emissions must be defined as any 3-hour period during which the average emissions of CO, as measured by the CEM exceeds the maximum emission limits set forth in the condition with a CO emission limit, where PSD is cited as the basis of the condition or any 3-hour period during which the average emissions of NOx exceed the maximum emission limits set forth in the condition with a NOx emission limit, where PSD is cited as the basis of the condition. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

86. Excess emissions indicated by the CEM system must be considered violations of the applicable emission limit for the purpose of this permit. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

87. The quality assurance project plan used by the Permittee (MSCC) for the certification and operation of the continuous emissions monitors, which meets the requirements of 40 C.F.R. Part 60, Appendix F, must be available upon request to EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

88. The Permittee (MSCC) must keep a monthly record of all fuel uses. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

89. The proposed power plant is subject to the federal regulations entitled Standards of Performance for New Stationary Sources (40 C.F.R. 60). The owner or operator must meet all applicable requirements of 40 C.F.R. 60 Subparts A and GG of this regulation. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

90. All three turbines will fire natural gas only. The Permittee (MSCC) must only combust pipeline quality natural gas with sulfur content (as S) below 0.75 grains per 100 dry standard cubic feet (dscf). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

91. MSCC shall have legal and operational responsibility and control of all air pollutant emitting activities of the MSCP. This responsibility shall include, but shall not be limited to the following: 1.) Operating and maintaining the project to comply with all federal, state, and local air pollution laws, regulations, orders, and other requirements; 2.) Ensuring the emissions offsets, tradeoffs, or other emission reductions required for this project under permits issued by the U.S. EPA, the District, and/or the California Energy Commission are obtained as required; or 3.) Any violations of any air pollution requirements are the legal responsibility of MSCC, in addition to any other legal responsible entity. Any proposed change to this condition shall require prior written concurrence of the US EPA. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

92. In accordance with the emissions offset plan proposed by the applicant for the District (dated November 12, 1987) and the emissions offset plan for the U.S. EPA (dated July 21, 1987), Aera Energy LLC must not operate the following four steam generators (listed by District permit numbers S-1135-119, S-1135-122, S-1135-123, and S-1135-115) simultaneously with the firing of the MSCP turbines unless one or more of the MSCP turbines is shutdown: Andersen-Goodwin Lease: S-1135-119, S-1135-122, S-1135-123 and Neely Lease: S-1135-115 [PSD SJ-87-01] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

93. MSCC shall maintain a record of the date(s), time(s), and duration(s) of the shutdown of any of the above mentioned steam generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

94. Aera Energy LLC shall not lease or modify the permit conditions for any of the above generators for use in the Midway Sunset Oil field, unless creditable emissions reductions (as defined in 40 C.F.R. 52.21), at a ratio of at least 1:1, are provided for emissions from those generators. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

95. Aera Energy LLC shall not modify any of the District Permit to Operate numbers. If any of the above steam generators are issued new Permit to Operate numbers by the District, Aera Energy LLC shall notify the U.S. EPA in writing of this action and shall make such notification upon issuance of a new Permit to Operate number. This letter shall include the original District Permit to Operate number(s) of the subject generator(s) and a copy of the new Permit to Operate issued by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

96. Aera Energy LLC shall notify the U.S. EPA in writing of the intention to sell, or potential sale, of any of the above generators and shall make such notification prior to the District's final action of the re-permitting process associated with the sale of a generators. This letter shall include the following: a.) The subject steam generator as identified by its District Permit to Operate number; b.) The name of the buyer (as identified by the company name) of the steam generator; and c.) An estimated date of the final action of the re-permitting process by the District. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

97. The allowable incidental taking (killing, harming, or harassment) of San Joaquin kit foxes, blunt-nosed leopard lizards, and giant kangaroo rats is confined to the proposed cogeneration plant site one half mile radius around this site (on lands owned or leased by Aera Energy LLC), and associated subject cogeneration plant facilities (including pipelines, transmission lines, temporary equipment stockpiling areas, and access roads) as discussed in the project Application for Certification report (Sun Cogeneration Company and Southern Sierra Energy Company 1985). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

98. MSCC is required to implement the "Agreement on Conditions for Mitigation of the Biological Impacts of the Midway-Sunset Project" as required by the U.S. Fish and Wildlife Service (USFWS) (Memorandum dated March 16, 1987 from the USFWS to the US EPA). [PSD SJ-87-01] Federally Enforceable Through Title V Permit

99. Any endangered species found dead should be turned in to the California Department of Fish and Game for Analysis. MSCC must also report this event to the USFWS. The USFWS may recommend amendment to the existing project actions pending results of the analysis. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

100. All correspondence as required by this permit shall be forwarded to: 1.) Director, Air Division (Attn: Air-3) EPA Region IX 75 Hawthorne Street San Francisco, CA 94105-3901 Tel: (415) 744-1291 Fax: (415) 744-1076; 2.) Chief, Stationary Source Division, California Air Resource Board P.O. Box 2815 Sacramento, CA 95812; and 3.) Air Pollution Control Officer, San Joaquin Valley Unified APCD 2700 M Street, Suite 275 Bakersfield, CA 93301-2370. [PSD SJ-87-01] Federally Enforceable Through Title V Permit

101. Aera Energy LLC is the legal owner of the subject steam generators and of the leases on which the steam generators are located. MSCC is the legal owner of the gas turbine cogeneration facility. MSCC is jointly owned by Sun Cogeneration Limited Partnership (Sun Cogen LP) and San Joaquin Energy Company. Sun Cogen LP is managed and controlled by a wholly owned subsidiary of Aera Energy LLC. (See Condition 104) [PSD SJ-87-01] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-230-2 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1 MISC. STEAM DUMPING-ROCK BED MUFFLER OPERATION FOR MIDWAY SUNSET COGENERATION BLOWDOWN.

PERMIT UNIT REQUIREMENTS

1. Unit shall receive steam only from cogeneration units S-1135-224, '-225, & '-226. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Steam pit shall not be used for more than 6 hours in any one day. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Only treated water shall be used as cogenerators steam generators feed water. [District Rule 2080] Federally Enforceable Through Title V Permit
4. This equipment shall not be used on any day when any of the 52 steam generators and heater treaters curtailed to provide cogeneration project offsets are operated unless these units are operated in accordance with District approval. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Permittee shall keep accurate daily records indicating hours of steam pit usage. Records shall be kept, maintained, and made readily available to District staff upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. H2S emissions shall not exceed 19 lb/hr. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Emission sampling limits for the following shall not exceed any of the following: PM-10 - 8.40 lb/hr, SOx (as SO2) - 42.24 lb/hr, or VOC - 1.00 lb/hr. [District NSR Rule] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-231-4 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
165 HP DIESEL-FIRED I.C. ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District NSR Rule and District Rule 4702] Federally Enforceable Through Title V Permit
3. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115] Federally Enforceable Through Title V Permit
5. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201, 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-235-1 **EXPIRATION DATE:** 05/31/2007

SECTION: 17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
2,520 BHP DIESEL FIRED I.C. ENGINE FOR EMERGENCY POWER GENERATION, INCLUDING: ONE CATERPILLAR MODEL #3516STD 16 CYLINDER I.C. ENGINE OPERATING A 1500 KW ELECTRIC GENERATOR, VALVE CONNECTING CRANKCASE TO INTAKE MANIFOLD, & ELAPSED OPERATING TIME METER

PERMIT UNIT REQUIREMENTS

1. Engine shall be equipped with a turbocharger. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Engine shall be equipped with an aftercooler or intercooler. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The engine shall be equipped with a positive crankcase ventilation (PCV) system or a crankcase emissions control device of at least 90% control efficiency. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The engine shall be operated with the timing retarded four degrees from the manufacturer's standard recommended timing. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The sulfur content of the diesel fuel used shall not exceed 0.05% by weight. [District NSR Rule] Federally Enforceable Through Title V Permit
6. The engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance and testing purposes shall not exceed 6 hours per year. [District NSR Rule and District Rule 4701] Federally Enforceable Through Title V Permit
7. The permittee shall maintain records of hours of non-emergency operation and of the sulfur content of the diesel fuel used. Such records shall be made available for District inspection upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 gr/dscf in concentration at the point of discharge. [District Rule 4201 and Kern County Rule 404] Federally Enforceable Through Title V Permit
9. If the IC engine is fired on CARB regulated diesel fuel, with a supplier certified sulfur content less than 0.05% by weight, the operator shall maintain copies of all fuel invoices and supplier certifications. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. If the IC engine is not fired on CARB regulated diesel fuel, with a supplier certified sulfur content less than 0.05% by weight, then the owner or operator shall determine the sulfur content of each delivery of diesel fuel being fired in the IC engine. The sulfur content shall be determined using ASTM method D 2880-71. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
11. If the IC engine is not fired on CARB regulated diesel fuel and the sulfur content of the fuel is determined using the method specified on this permit, the records of fuel sulfur content testing results shall be kept, maintained, and made available to the district upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-266-8 **EXPIRATION DATE:** 05/31/2007

SECTION: SE24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS STEAM GENERATOR, WITH A COEN QLN-ULN BURNER, O2 CONTROLLER, AND FLUE GAS RECIRCULATION (METSON 48)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.001 lb/MMBtu, SOx (as SO2): 0.0016 lb/MMBtu, VOC: 0.0027 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

14. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 404, 424 and 425] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed any of the following: PM10: 1.5 lb/day, SOx (as SO2): 2.4 lb/day, VOC: 4.1 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 45.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

17. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

23. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

25. If the unit is equipped with flue gas recirculation (FGR), whenever the unit is switched to operate with the FGR system in the closed position, compliance source testing for NOx and CO shall be conducted within 60 days of cessation of FGR operation date unless source testing with FGR system in the closed position has occurred within the previous 12 months. [District Rule 1070] Federally Enforceable Through Title V Permit

26. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

30. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

32. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

33. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

34. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-267-8 **EXPIRATION DATE:** 05/31/2007

SECTION: NE35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR STRUTHERS GAS-FIRED STEAM GENERATOR (#49) WITH A COEN MODEL QLN-ULN BURNER WITH FLUE GAS RECIRCULATION (FGR) (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Amended December 16, 1993). [District Rule 1081, and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.4.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera), 402 (Madera), 404 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 405 (Madera), 408 (Fresno, Kern, Tulare, Kings, Stanislaus, Merced, and San Joaquin), 407.2 (Kern, Tulare, Kings, Stanislaus, and San Joaquin), and 408.2 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit commenced construction, modification, or reconstruction prior to June 19, 1984. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit is located west of interstate 5 in Kern county. Therefore, the requirements of District Rule 4351(Amended October 19, 1995) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.001 lb/MMBtu, SOx (as SO2): 0.0016 lb/MMBtu, VOC: 0.0027 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

14. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 404, 424 and 425] Federally Enforceable Through Title V Permit

15. Emission rates shall not exceed any of the following: PM10: 1.5 lb/day, SOx (as SO2): 2.4 lb/day, VOC: 4.1 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

17. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

19. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

20. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

22. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

24. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

25. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

26. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months (no more than 30 days before or after the required annual source test date). After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months (no more than 30 days before or after the required 36-month source test date). If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

27. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

30. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

31. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

32. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

33. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-270-10 **EXPIRATION DATE:** 05/31/2007

SECTION: NW21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
210,000 GALLON FIXED ROOF OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control system listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 3.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
9. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
10. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

13. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

14. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

16. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

20. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

21. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

30. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-281-12 **EXPIRATION DATE:** 05/31/2007

SECTION: 16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
3,000 BBL FIXED ROOF SUMP REPLACEMENT TANK WITH VAPOR CONTROL SYSTEM SHARED WITH S-1135-284, -285, -286, -287, -328, '-329, '-330, '-331, '-332, '-333, '-334, '-335, AND '-336

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Vapor control system shall discharge to unit S-1135-128. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All associated tanks shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank shall be equipped with stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Compressor suction and knockout drum liquids shall be piped only to vapor-controlled tanks. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. Operator shall monitor vapor control system compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. Tank vapor control system efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor control system. Emissions shall be determined based on tank emission factors in EPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. All non-condensible hydrocarbon vapors shall be directed to the vapor control system authorized by permit S-1135-128 either directly through bypass piping, or through tank battery vapor control skid. [District Rule 2201] Federally Enforceable Through Title V Permit

13. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

14. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

15. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit

16. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

18. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

19. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

20. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

21. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

22. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

23. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

24. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

26. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

33. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

36. The fugitive VOC emissions from this tank and tank vapor control system shall not exceed 3.1 lb/day [District Rule 2201] Federally Enforceable Through Title V Permit

37. Permittee shall maintain with the permit accurate fugitive component counts for tank and the tank vapor control system and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit

38. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-283-6 **EXPIRATION DATE:** 05/31/2007

SECTION: NW17 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 90 STEAM ENHANCED WELLS WITH CLOSED CASING VENTS (ANDERSON LEASE)

PERMIT UNIT REQUIREMENTS

1. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
2. All valves, fittings and connectors serving closed well vents shall be constructed and maintained in a leak free condition except during periods of actual service and repair. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
3. Wells authorized by this permit shall only be operated with closed casing vents. Well casing vents shall remain closed at all times except during periods of actual service or repair provided such activity is attended and done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
4. All produced fluids from all wells authorized by this permit shall be handled only in closed production equipment served by a 99% efficient vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Total fugitive emission of volatile organic compounds (VOC) from entire operation shall not exceed 16.4 lbm/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Wellhead (polishing rod/stuffing box) fugitive emissions from new wells shall not exceed 0.00778 lbm VOC/well/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for well vent vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c(Feb 1999) Screening Range emission factors. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401, excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
10. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Steam-enhanced crude oil production well vents shall be closed, except when temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, and the front line production equipment downstream of the wells that carry produced fluids be connected to a VOC collection and control system. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

12. The operator shall be in violation of Rule 4401 if any District inspection or operator inspection, conducted as a requirement of this rule, are found to be leaking in excess of the applicable leak standards in section 5.6.2. [District Rule 4401, 5.6.1] Federally Enforceable Through Title V Permit

13. There shall not be an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.6.2.1] Federally Enforceable Through Title V Permit

14. There shall be no components with major liquid leaks or with gas leaks greater than 50,000 ppmv. [District Rule 4401, 5.6.2.2 and 5.6.2.3] Federally Enforceable Through Title V Permit

15. There shall not be more minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv than the following: 3 leaks for 1 - 25 wells, 6 leaks for 26 - 50 wells, 8 leaks for 51 - 100 wells, 10 leaks for 101 - 250 wells, 15 leaks for 251 - 500 wells, and 1 leak for each 20 wells (with a minimum of 50 wells test) for more than 500 wells connected to a VOC collection and control system. [District Rule 4401, 5.6.2.4] Federally Enforceable Through Title V Permit

16. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.7.1] Federally Enforceable Through Title V Permit

17. Except for pipes and unsafe-to-monitor components, all other components shall be inspected pursuant to the requirements of section 6.3.3 at least once every year. [District Rule 4401,5.8.1] Federally Enforceable Through Title V Permit

18. All pipes shall be visually inspected at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than as allowed by Rule 4401 and specified in this permit. [District Rule 4401, 5.8.2] Federally Enforceable Through Title V Permit

19. The operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. The operator shall inspect a component, other than PRDs, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. The operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.8.4.2, 5.8.4.3, 5.8.5] Federally Enforceable Through Title V Permit

20. A District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401, 5.8.6] Federally Enforceable Through Title V Permit

21. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.1, 5.9.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. Except for leaking critical components or leaking essential components, if the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4401, 5.9.3, 5.9.4] Federally Enforceable Through Title V Permit

23. The operator shall repair minor gas leaks within 14 days, major gas leaks which less than or equal to 50,000 ppmv within 5 days., major gas leaks which are greater than 50,000 ppmv within two days, minor liquid leaks within 3 days, and major liquid leaks within 2 days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4401, 5.9.4, 5.9.5, and 5.9.6] Federally Enforceable Through Title V Permit

24. If a leaking component is an essential component or a critical component which cannot be shut down immediately for repairs, and after being minimized still exceeds the applicable leak standard, the operator shall repair or replace the component to eliminate the leak during the next process unit turnaround or no later than one year from the date of original leak detection, which ever is earlier. [District Rule 4401, 5.9.7] Federally Enforceable Through Title V Permit

25. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

26. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401, 6.1.3] Federally Enforceable Through Title V Permit

27. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 44019, 6.1.6] Federally Enforceable Through Title V Permit

28. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit

29. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4401, 6.4] Federally Enforceable Through Title V Permit

31. The operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401, 6.5] Federally Enforceable Through Title V Permit

32. The operator shall maintain copies of training records and a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make such available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.7, 6.1.8] Federally Enforceable Through Title V Permit

33. The operator shall maintain an APCO approved Operator Management Plan (OMP). The OMP shall include, at a minimum, a description of all wells and all associated VOC collection and control systems subject to this rule, and all wells and all associated VOC collection and control systems that are exempt; an identification and description of any known hazard that might affect the safety of an inspector; except for pipes, the number of components that are subject to this rule by component type; except for pipes, the number and types of major components, inaccessible components, unsafe-to-monitor components, critical components, and essential components that are subject to this rule and the reason(s) for such designation; except for pipes, the location of components subject to the rule (components may be grouped together functionally by process unit or facility description); except for pipes, components exempt pursuant to Section 4.8 (except for components buried below ground) may be described in the OMP by grouping them functionally by process unit or facility description (the results of any laboratory testing or other pertinent information to demonstrate compliance with the applicable exemption criteria for components for which an exemption is being claimed pursuant to Sections 4.8 shall be submitted with the OMP); a detailed schedule of an operator's inspections of components to be conducted as required by this rule and whether the operator inspections of components required by this rule will be performed by a qualified contractor or by an in-house team; a description of the training standards for personnel that inspect and repair components; and a description of the leak detection training for conducting the test method specified in Section 6.3.3 for new operators, and for experienced operators, as necessary. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

34. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4401, 6.7] Federally Enforceable Through Title V Permit

35. Permittee shall maintain with the permit a listing (updated annually within 60 day of permit anniversary) of all steam-enhanced wells authorized by this permit and such listing shall be made available for District inspection upon request. [District Rules 2201 and 1070] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-284-12 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF RUN TANK #5, WITH VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.1 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-285-14 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF LACT TANK #6 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.2 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-286-14 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF LACT TANK #7 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.1 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-287-14 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF LACT TANK #8 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor control system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauge hatches, thief hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and gas-tight (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rules 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rules 4623] Federally Enforceable Through Title V Permit

13. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rules 4623] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor control system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor control system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

20. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. The fugitive VOC emissions from this tank shall not exceed 0.1 lb/day [District NSR Rule] Federally Enforceable Through Title V Permit

31. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Oil and Gas Production Screening Value Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit

32. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-293-7 **EXPIRATION DATE:** 05/31/2007

SECTION: 15 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 300 STEAM DRIVE WELLS WITH CASING VENTS TIED TO VAPOR CONTROL SYSTEM INCLUDING, THREE VAPOR CONTROL SKIDS WITH SEPARATOR(S), HEAT EXCHANGER(S), FAN(S), AND COMPRESSOR(S), WITH NON-CONDENSIBLE VAPOR PIPING SHARED WITH TEOR OPERATION S-1135-124 (EXETER LEASE) CONTROLLED BY BALANCED CASING VENT COLLECTION SYSTEM OR RE-INJECTION INTO DOGGR APPROVED DISPOSAL WELL (GLOBE LEASE)

PERMIT UNIT REQUIREMENTS

1. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
2. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
3. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
4. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
5. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
6. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
7. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
8. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
9. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

11. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

12. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components; and the efficiency of destruction devices determined by USEPA Method 18. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

13. VOC content shall be determined using ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by CARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit

14. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.4.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

15. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. The crude oil production wells associated with this unit do not have production enhanced by in-situ combustion. Therefore, the requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

18. Collected liquids shall be handled, stored, and disposed of in a manner preventing detectable volatile organic compound (VOC) to the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit

19. Total number of vapor collection system leaks shall not exceed 15, as per Rule 4401 - Steam-Enhanced Crude Oil Production Well Vents. [District Rule 4401] Federally Enforceable Through Title V Permit

20. Permittee shall maintain records of dates and well identifications where steam injection or well stimulation occurs and shall make such records available for District inspection. [District Rule 1070] Federally Enforceable Through Title V Permit

21. Permittee shall maintain an inspection and maintenance program consistent with Rule 4403 (Components Serving Light Crude Oil or Gases) for those stuffing boxes on wells which commence steam-enhancement operations on or after April 11, 1991. [District NSR Rule and District Rule 4403] Federally Enforceable Through Title V Permit

22. Volatile organic compound (VOC) emissions shall not exceed 2.32 lb/hr for casing collection fugitives and 0.33 lb/hr for polished rod fugitives. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Total uncontrolled VOC emissions from all well vents shall be reduced by at least 99%. [District Rule 4401] Federally Enforceable Through Title V Permit
24. Well casing vent collection system shall also include non-condensible vapor piping from vapor control skids to re-injection skid. [District Rule 2201] Federally Enforceable Through Title V Permit
25. TEOR vapors shall be injected only in DOGGR-approved gas disposal wells. [District NSR Rule] Federally Enforceable Through Title V Permit
26. Permittee shall submit a copy of the DOGGR gas disposal well approval to the District prior to injection of any TEOR gas. [District NSR Rule] Federally Enforceable Through Title V Permit
27. Permittee shall cease injection of vapors and notify the District immediately if DOGGR disposal well approval is revoked, denied, terminated, surrendered, or otherwise altered to disallow gas disposal. [District NSR Rule] Federally Enforceable Through Title V Permit
28. A listing of steam enhanced wells connected to this system and DOGGR wells used for re-injection of TEOR vapors shall be made availible for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-299-5 **EXPIRATION DATE:** 05/31/2007

SECTION: NE35 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR GAS-/LPG-FIRED STEAM GENERATOR #50 WITH A COEN MODEL QLN-ULN LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM AND AN OXYGEN CONTROLLER (KENDON LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.014 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, VOC: 0.003 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

12. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 21.0 lb/day, SOx (as SO2): 1.5 lb/day, VOC: 4.5 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

15. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rule 2080 & 4306] Federally Enforceable Through Title V Permit

17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

24. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

25. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

26. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

27. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-301-11 **EXPIRATION DATE:** 05/31/2007

SECTION: NW21 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
281,400 GALLON FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall be vented only to vapor control listed on S-1135-149. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenances allowed by this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 4.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum VOC content of hydrocarbons in tank vapor shall not exceed 20% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District Rule 2201 and District Rule 4623] Federally Enforceable Through Title V Permit
10. Tank shall be equipped with stored liquid temperature indicator. [District NSR Rule] Federally Enforceable Through Title V Permit
11. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) not exceeding 0.45 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit

13. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit

14. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit

15. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit

16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

17. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit

18. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

19. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080]

20. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

21. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

22. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

26. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall keep accurate records of throughput, storage temperature, and TVP of liquids stored in each tank and such records shall be made readily available for District inspection at any time for a time period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

29. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

31. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-302-4 **EXPIRATION DATE:** 05/31/2007

SECTION: SE22 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR (#5) WITH A COEN MODEL QLN-ULN ULTRA LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) (BUENA FE LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.005 lb/MMBtu, SOx (as SO2): 0.0006 lb/MMBtu, VOC: 0.0028 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

12. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 7.5 lb/day, SOx (as SO2): 0.9 lb/day, VOC: 4.2 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

15. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

17. Permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

18. If the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. Permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

24. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

25. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

26. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rules 1081, 4305, and 4306, 6.2] Federally Enforceable Through Title V Permit

27. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

29. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

30. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-305-3 **EXPIRATION DATE:** 05/31/2007

SECTION: NW36 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
62.5 MMBTU/HR NAT GAS-FIRED STEAM GENERATOR # 52, WITH A COEN QLN-ULN LOW NOX BURNER, WITH FLUE GAS RECIRCULATION, (PRU LEASE)

PERMIT UNIT REQUIREMENTS

1. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (Last Amended December 16, 1993). [District Rule 1081 and County Rule 108.1 (Kern)] Federally Enforceable Through Title V Permit
2. Copies of all fuel invoices showing quantity and delivery points of gas delivered and copies of quality terms of gas delivery contracts shall be maintained. The operator shall record daily amount and type(s) of fuel(s) combusted and all dates on which unit is fired on any noncertified fuel and record specific type of noncertified fuel used. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. When complying with sulfur emission limits by fuel analysis or by a combination of source testing and fuel analysis, each fuel source shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for a fuel source, then the fuel testing frequency shall be semi-annually. If a semi-annual fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
4. When complying with SOx emission limits by testing of stack emissions, testing shall be performed not less than once every 12 months using EPA Methods 6, 6B, 8 or CARB Method 8 or 100; or, for units using gaseous fuel scrubbed for sulfur pre-combustion, a grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. Gaseous fuel fired units demonstrating compliance on two consecutive annual source tests shall be tested not less than once every thirty-six months; however, annual source testing shall resume if any test fails to show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 4468, D 4084, D 3246 or grab sample analysis by double GC for H2S and mercaptans performed in the laboratory and EPA Method 19 to calculated emissions. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2520, 9.3.2; 4305, 6.2.1; and 4351, 6.2.1] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201 (Amended December 17, 1992), 4301 (Amended December 17, 1992), 4406 (Amended December 17, 1992, and Rule 4801 (Amended December 17, 1992). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of Kern County Rules 108.1, 404, 408, and 407.2. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

9. This unit is fired only on gaseous fuel and has no provisions of firing on oil or coal. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of 40 CFR 60, Subpart Dc. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

10. This unit has not been used to produce electricity for sale in 1985 or on or after November 15, 1990. Therefore, the requirements of 40 CFR 72.6(b) do not apply to this source. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

11. Emission rates, except during startup, shutdown, and refractory curing shall not exceed any of the following: PM10: 0.005 lb/MMBtu, SOx (as SO2): 0.0006 lb/MMBtu, VOC: 0.0028 lb/MMBtu, NOx (as NO2): 0.018 lb/MMBtu or 15 ppmv @ 3% O2, or CO: 0.030 lb/MMBtu or 40 ppmv @ 3% O2. [District Rules 2201, 2520, 4201, 4301, 4305, 4306, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

12. Emission rates during startup, shutdown and refractory curing shall not exceed any of the following: particulate matter - 10 pounds per hour, or 0.1 grains/dscf calculated to 12% CO2; sulfur - 200 pounds of SO2 per hour, or 2000 ppmv as SO2, or 0.11 pounds sulfur (as S) per MMBtu on average-wide basis for all units in Rule 4406 plan ; NO2 - 140 pounds per hour or 0.14 pounds per MMBtu. [District Rules 4101, 4102, 4301, 4405, 4406, 4801 and Kern County Rules 424 and 425] Federally Enforceable Through Title V Permit

13. Emission rates shall not exceed any of the following: PM10: 7.5 lb/day, SOx (as SO2): 0.9 lb/day, VOC: 4.2 lb/day, NOx (as NO2): 54.0 lb/day or 9855 lb/yr, or CO: 55.5 lb/day or 16,425 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Duration of start-up and shutdown shall not exceed 2 hours each per occurrence. [District Rule 4306] Federally Enforceable Through Title V Permit

15. Duration of refractory curing shall not exceed 30 hours each per occurrence. Permittee shall notify the District in writing prior to refractory curing. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Permittee shall maintain records of duration of each start-up, shutdown and refractory curing, per a period of five years and make such records readily available for District inspection upon request. [District Rules 2080 and 4306] Federally Enforceable Through Title V Permit

17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

21. During the 36-month source testing interval, the operator shall tune the unit at least twice per calendar year, (from four to eight months apart) by a qualified technician in accordance with the procedure described in Rule 4304, and shall monitor, on a monthly basis, the unit's operational characteristics recommended by the manufacturer. Semi-annual tuning is not required if emissions are monitored monthly with a portable analyzer. [District Rule 4306] Federally Enforceable Through Title V Permit

22. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

23. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rule 4305 and 4306] Federally Enforceable Through Title V Permit

24. Performance testing for NOx and CO emissions shall be conducted not less than once every 12 months, except as provided below. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

25. Performance testing for NOx and CO emissions shall be conducted not less than once every 36 months if compliance is demonstrated on two consecutive annual tests. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

26. If permittee fails any performance testing for NOx or CO emissions when testing not less than once every 36 months, compliance with NOx and CO emissions testing shall be less than once every 12 months. [District Rules 4305, 6.3 and 4306, 6.3] Federally Enforceable Through Title V Permit

27. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

28. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or 10B or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, SOx (lb/MMBtu) - ARB Method 8 or 100 or EPA Method 6, 6B or 8 or fuel gas sulfur content analysis and EPA Method 19, fuel gas sulfur content - ASTM D1072, D4468, D3246, D3246, D4084 or double GC for H2S and mercaptans performed in laboratory, fuel gas hhv - ASTM D1826 or D1945 in conjunction with ASTM D3588. [District Rule 1081, and 4305, 6.2] Federally Enforceable Through Title V Permit

29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit

30. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, and 4306] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

31. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

32. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-322-2 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF WASH TANK T-101, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Fugitive VOC emissions rate calculated using EPA's Protocol for Equipment Leak Emission Estimates, Table 2-4, Oil and Gas Production Operations Average Emission Factors, shall not exceed 3.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Operation shall include vapor recovery system described on the requirements for permit unit S-1135-70. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All tanks and separators shall vent only to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
6. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
7. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
8. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.17 and 6.4.8] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

16. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

19. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-323-3 **EXPIRATION DATE:** 05/31/2007

EQUIPMENT DESCRIPTION:
3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-129 - ANDERSON GOODWIN LEASE

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall vent only to the vapor control skid inlet in permit S-1135-129. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. [District NSR Rule and District Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.26 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall measure VOC content of tank vapor annually using EPA Method 18, 25, 25a, 25b, or ASTM D-1945. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Permittee shall maintain with the permit accurate fugitive component counts for tank and resulting emissions calculated using using Table 2-4 Oil and Gas Production Operations Average Emissions factors from the EPA Protocol for Equipment Leak Emissions Estimates EPA-453/R-95-017. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule and District Rule 4623] Federally Enforceable Through Title V Permit
9. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
10. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
11. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed (except for PV valve venting on tanks not required to have a vapor recovery system). Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: t = 2.3 V / Q, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

13. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

14. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

15. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Permittee shall maintain records of the date and duration of the vapor control system maintenance operation. Such records shall be made available for district inspection upon request for a period of at least five years. [District NSR Rule and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. Permittee shall keep records of VOC content of tank vapor and such records shall be made available for District inspection upon request for a period of 5 years. [District Rule 1070] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons (1,589.874 cubic meters) and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-325-2 **EXPIRATION DATE:** 05/31/2007

EQUIPMENT DESCRIPTION:
3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK, HANDLING MAXWELL LEASE PRODUCTION, SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W & S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.47 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
8. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. This unit has a storage capacity less than 420,000 gallons (1,589.874 cubic meters) and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-326-2 **EXPIRATION DATE:** 05/31/2007

SECTION: SW24 **TOWNSHIP:** 11N **RANGE:** 23W

EQUIPMENT DESCRIPTION:
126,000 GALLON FIXED ROOF WASH TANK T-102, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY

PERMIT UNIT REQUIREMENTS

1. Fugitive emissions calculated using EPA's Protocol for Equipment Leak Emission Estimates, Table 2-4, Oil and Gas Production Operations Average Emission Factors, shall not exceed 3.0 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank shall vent only to the vapor recovery system described in the requirements for permit unit S-1135-70. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Operation shall include provisions for connecting tank to existing TEOR operation and Vapor Control System. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This tank shall only vent to a vapor recovery system. The vapor recovery system shall be an APCO-approved system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be maintained in a leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4 of District Rule 4623 (amended May 19, 2005). [District Rule 4623] Federally Enforceable Through Title V Permit
6. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
7. A leak-free condition is a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of District Rule 4623. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of District Rule 4623. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2520, 9.3.2 and 4623, Table 3] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. Operator shall maintain an inspection log containing the following: 1) Date of all inspections; 2) Type and identification of leaking components; 3) Date of leak detection and method of detection; 4) Method used to minimize leak; and 5) Date and emission level of recheck after leak is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. The permittee shall maintain, and make available for District inspection, all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

18. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-327-1 **EXPIRATION DATE:** 05/31/2007

EQUIPMENT DESCRIPTION:
905 BBL FWKO VESSEL (V-100) CONNECTED TO VAPOR RECOVERY SYSTEM LISTED ON S-1135-70

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102] Federally Enforceable Through Title V Permit
2. The tank shall vent only to the vapor control system listed on S-1135-70. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions from tank using California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2C: Oil and Gas Production Screening Value Ranges (<10,000 ppmv) Emission Factors. [District Rule 4623] Federally Enforceable Through Title V Permit
4. There shall be no leaks exceeding 10,000 ppmv from fugitive emissions components associated with tank. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Gas-leak concentration shall be determined by EPA Method 21. [District Rule 4623] Federally Enforceable Through Title V Permit
6. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.11, 3.17, and 3.18] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 4623] Federally Enforceable Through Title V Permit

12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit

13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit

14. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit

15. Any component found to be leaking on two consecutive quarterly inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit

16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit

18. Permittee shall maintain records of annual tank inspections, maintenance, and cleaning to document the participation in the Rule 4623 Fixed Roof Tank Preventative Inspection, Maintenance and Tank Interior Cleaning Program. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit

19. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 3 of Rule 4623. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit

20. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-328-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL FLOW SPLITTER PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-329-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL FWKO PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-330-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL "GAS BUSTER" PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-331-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #1 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-332-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #2 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-333-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #4 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-334-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #6 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-335-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #7 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-336-0 **EXPIRATION DATE:** 05/31/2007

SECTION: SW16 **TOWNSHIP:** 31S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,200 BBL UNFIRED TREATER #8 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)

PERMIT UNIT REQUIREMENTS

1. The pressure vessel shall only vent to the vapor control system listed on permit S-1135-281. [District Rule 2080] Federally Enforceable Through Title V Permit
2. All piping, fittings, and valves shall be constructed and maintained in a leak-free condition. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Vessel covers, inspection hatches, etc. shall be maintained in a leak-free condition except during vessel cleaning, repair, or maintenance. [District Rule 2080] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 2080] Federally Enforceable Through Title V Permit
5. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2080] Federally Enforceable Through Title V Permit
6. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2080] Federally Enforceable Through Title V Permit
7. An operator shall reinspect a component for leaks within 30 working days after the date on which the component is repaired. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 95 percent efficient as measured by EPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 95% control efficiency as measured by EPA Method 25 at least annually. [District Rule2080] Federally Enforceable Through Title V Permit

10. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2080] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1135-337-1 **EXPIRATION DATE:** 05/31/2007

EQUIPMENT DESCRIPTION:
3,000 BBL (126,000 GALLON) FIXED ROOF STOCK TANK ID# WS-04, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Tank shall be designed and maintained to vent only to vapor control system, except during the period of tank cleaning, inspections, and maintenance allowed by this permit. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All tank gauging, hatches, sampling ports, pressure relief valves, vapor control system components, etc. shall be closed and leak-free (as defined in Rule 4623) except during sampling or attended maintenance. Leak-free is a condition without a gas leak or a liquid leak. A gas leak is a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with EPA Method 21. A liquid leak is the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
4. Tanks seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free (as defined in Rule 4623) condition. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
5. The fugitive VOC emissions from this tank and the vapor control system shall not exceed 0.2 lb/day. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall maintain with the permit accurate fugitive component counts for tank and associated vapor control systems and resulting emissions calculated using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999) Screening Range emission factors. [District NSR Rule] Federally Enforceable Through Title V Permit
7. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
8. There shall be no throughput during cleaning of this tank. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning, the following procedure must be followed: Operate PV valve and vapor control system during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Prior to opening the tank to allow tank cleaning, one of the following options must be followed: 1) operate the vapor control system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V / Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Tank pressure/vacuum valve (Varec) shall be inspected on an annual basis. During the varec inspections, the varec can be removed from the tank and replaced if necessary. The permittee shall minimize emissions from the opening by plugging the opening during the removal of varec valve. [District Rule 2080] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by EPA Method 18 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by EPA Method 18 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. This unit has a storage capacity less than 420,000 gallons (1,589.874 cubic meters) and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40 CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

21. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

ATTACHMENT C

Detailed Facility List

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

AERA ENERGY LLC	FAC # **S 1135**	TYPE: **TitleV**	EXPIRE ON: 05/31/2007
HEAVY OIL WESTERN STATIONARY SOURCE	STATUS: **A**	TOXIC ID: **50002**	AREA: 7 / 31
MIDWAY-SUNSET	TELEPHONE: **6616655279**		INSP. DATE: 01/12
KERN COUNTY, CA			

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-1-25	31,500 kBtu/hr burner	3020-02 H	1	1,030.00	1,030.00	D	DORMANT 31.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #14, DIS# 9175-68, W/ NORTH AMERICAN BURNER AND OPTIONAL SO2 SCRUBBER (WILBERT LEASE)
S-1135-2-5	4,200,000 BTU/HR	3020-02 F	1	607.00	607.00	D	4.2 MMBTU/HR OIL/NATURAL GAS FIRED HEATER TREATER - WILBERT LEASE. CANCELLED BY APPLICANT ON 1995 RENEWALS, ANNUAL FEES NOT PAID, MRB.
S-1135-3-22	5 MMBtu/hr	3020-02 F	1	607.00	607.00	A	8.4 MMBTU/HR (DERATED TO 5 MMBTU/HR) NATURAL GAS FIRED HEATER TREATER #1 WITH A MAXON MODEL M-PAKT BURNER WITH VARIABLE FREQUENCY DRIVE (VFD) BLOWER, SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE
S-1135-4-21	25,200 kBtu/hr burner	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #30, DIS# 12055 70 (PRU LEASE)
S-1135-5-29	6,250 KBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #41 DIS #11867-75 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR (BUENA FE LEASE)
S-1135-6-27	62.5 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #43 WITH A COEN QLN-ULN LOW NOX BURNER AND FLUE GAS RECIRCULATION (KENDON LEASE)
S-1135-7-6	8,400,000 BTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR OIL/NATURAL GAS FIRED HEATER TREATER TULARE #2 - MAXWELL
S-1135-8-33	25.2 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS FIRED NATIONAL STEAM GENERATOR #17, DIS# 9236-68, WITH NORTH AMERICAN BURNER (MAXWELL LEASE)
S-1135-9-31	25.2 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #18, DIS# 9237-68 (MAXWELL LEASE)
S-1135-10-30	25.2 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #19, DIS# 9238 68 (MAXWELL LEASE)
S-1135-11-6	8.4 MMBTU/HR HEATER TREATER	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR OIL/NATURAL GAS FIRED HEATER TREATER #6 - MAXWELL
S-1135-12-31	62,500 KBtu/hr Burner	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #45 WITH A COEN ULN LOW-NOX BURNER WITH OPTIONAL-USE FGR AND OPTIONAL SO2 SCRUBBER (KENDON LEASE)
S-1135-13-32	62.5 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #44 WITH COEN QLN-ULN 3.2 BURNER (WILBERT LEASE)

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-14-5	8.4 MMBTU/HR HEATER TREATER	3020-03 G	1	1,030.00	1,030.00	D	8.4 MMBTU/HR OIL/NATURAL GAS FIRED HEATER TREATER #5 WITH NORTH AMERICAN 6131-C-CR 8.4 BURNER - MAXWELL
S-1135-15-30	2.5 MW	3020-08A C	1	1,533.00	1,533.00	D	NONCOMPLIANT DORMANT 2.5 MW COMBINED CYCLE GAS TURBINE TOPPING CYCLE COGENERATION UNIT TG-1 INCLUDING SOLAR TURBINE INC. CENTAUR MODEL GSC-400G, 38.5 MMBTU/HR GAS FIRED TURBINE ENGINE AND 2.5 MW ELECTRICAL GENERATOR (MAXWELL LEASE)
S-1135-16-30	2.5 MW	3020-08A C	1	1,533.00	1,533.00	D	NONCOMPLIANT DORMANT 2.5 MW COMBINED CYCLE GAS TURBINE TOPPING CYCLE COGENERATION UNIT TG-2 INCLUDING A SOLAR TURBINE INC. CENTAUR MODEL GSC-400G, 38.5 MMBTU/HR GAS FIRED TURBINE ENGINE AND A 2.5 MW ELECTRICAL GENERATOR (MAXWELL LEASE)
S-1135-17-17	175 wells with vapor recovery	3020-09 A	175	9.34	1,634.50	A	STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION, SERVING 175 STEAM ENHANCED WELLS, INCLUDING PIPING TO INCINERATING STEAM GENERATORS, FOR REINJECTION OF NONCONDENSIBLE VAPORS, OR FOR BALANCING OF WELL VENTS.
S-1135-18-16	140 wells	3020-09 A	140	9.34	1,307.60	A	STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 140 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (WILBERT LEASE)
S-1135-19-6	130 WELLS	3020-09 A	13	9.34	121.42	D	130 WELL CASING COLLECTION SYSTEM. PTO CANCELLED UPON IMPLEMENTATION OF PROJECT 930245 (COMBINE WITH OXFORD, S-1135 127-8 TEOR). 8/31/1993 MRB
S-1135-20-25	295 wells	3020-09 A	295	9.34	2,755.30	A	STEAM ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING 295 STEAM ENHANCED WELLS (KENDON LEASE), INCLUDING A FIN FAN COOLER, GAS/LIQUID SEPARATORS, AND ASSOCIATED PIPING
S-1135-21-11	153 wells	3020-09 A	153	9.34	1,429.02	A	STEAM-ENHANCED CRUDE OIL PRODUCTION OPERATION SERVING UP TO 153 STEAM-ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (BUENA FE FEE LEASE)
S-1135-22-10	90 wells	3020-09 A	90	9.34	840.60	A	STEAM-ENHANCED CRUDE OIL PRODUCTION WELL OPERATION SERVING UP TO 90 STEAM ENHANCED WELLS, INCLUDING PIPING FOR BALANCING OF WELL VENTS OR CLOSED CASING VENTS (MOCAL LEASE)
S-1135-23-9	25,200,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #23, DIS# 20628-66, WITH NORTH AMERICAN BURNER AND SO2 SCRUBBER - WILBERT. CANCELLED BY APPLICANT ON 1995 RENEWALS, MRB.
S-1135-24-30	25,200 kBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	DORMANT 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #25, DIS# 26916 66, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND SO2 SCRUBBER (KENDON LEASE)

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-25-11	25,200,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	INOPERABLE 25.2 MMBTU/HR STEAM GENERATOR WITH SO2 SCRUBBER - METSON
S-1135-26-38	62,500 kBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #32, DIS# 12051 71, WITH A COEN ULN 3.2 LOW-NOX BURNER AND SO2 SCRUBBER SHARED BETWEEN UNITS S-1135-26 AND S-1547-1089 (METSON LEASE)
S-1135-27-32	25.2 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #27, DIS# 12069-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)
S-1135-28-32	25.2 MMBtu/hour	3020-02 H	1	1,030.00	1,030.00	A	COMPLIANT DORMANT EMISSIONS UNIT - 25.2 MMBTU/HR NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #26, DIS# 12071-69, WITH NORTH AMERICAN BURNER, FLUE GAS RECIRCULATION, AND OPTIONAL SO2 SCRUBBER (METSON LEASE)
S-1135-29-28	4.2 MMBtu/hr	3020-02 F	1	607.00	607.00	A	NATURAL GAS-FIRED HEATER TREATER (#2) WITH A 4.2 MMBTU/HR MAXON MODEL M-PAKT BURNER SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1135-70 - METSON LEASE
S-1135-30-17	30,000 kBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	DORMANT 30 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR #MO-2, DIS# 19961-68, WITH NORTH AMERICAN 5131-FACR BURNER - MOCAL LEASE
S-1135-32-0	25,200,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR NATIONAL STEAM GENERATOR #BF1
S-1135-33-1	25,200,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR STRUTHERS STEAM GENERATOR WITH NORTH AMERICAN BURNER ASSEMBLY, INCLUDING NON-CONDENSIBLE PIPING FROM TEOR S- 1135-21, SHARED WITH STEAM GENERATOR S-1135-34. THIS PTO SURRENDERED WITH PROJECT 990991 10/8/99 - MRB.
S-1135-34-6	25,200 KBTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR STRUTHERS STEAM GENERATOR WITH NORTH AMERICAN BURNER ASSEMBLY, TELEDYNE OXYGEN CONTROLLER, INCLUDING NON- CONDENSIBLE PIPING FROM TEOR SYSTEM S-1135-21, SHARED WITH STEAM GENERATOR S-1135-33.
S-1135-36-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF SHIPPING TANK, P/0 #4007772, PRU LEASE
S-1135-37-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF SHIPPING TANK, P/O #4007773, PRU LEASE
S-1135-38-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF SHIPPING TANK P/O #4007774, PRU LEASE
S-1135-39-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF WASH TANK P/O#4007775, PRU LEASE
S-1135-40-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF WATER TANK P/O#4007776, PRU LEASE
S-1135-41-0	10,500 GALLONS	3020-05 B	1	93.00	93.00	D	10,500 GALLON FIXED ROOF SKIM TANK P/O#4007777, PRU LEASE
S-1135-42-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF FUEL TANK P/O#4007778, PRU LEASE

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-43-3	126,924 GALLONS	3020-05 E	1	246.00	246.00	D	126,924 GALLON FIXED ROOF WATER TANK P/O#4007779, WITH VAPOR CONTROL SYSTEM (KENDON LEASE)
S-1135-44-1	214,452 GALLONS	3020-05 E	1	246.00	246.00	D	214,452 GALLON FIXED ROOF WATER TANK P/O#4007780, WITH VAPOR CONTROL SYSTEM (KENDON LEASE)
S-1135-45-1	84,588 GALLONS	3020-05 D	1	185.00	185.00	D	84,588 GALLON FIXED ROOF LACT TANK P/O# 4007781 WITH VAPOR CONTORL SYSTEM (KENDON LEASE)
S-1135-46-1	84,588 GALLONS	3020-05 D	1	185.00	185.00	D	84,588 GALLON FIXED ROOF REJECT TANK P/O#4007782 WITH VAPOR CONTROL SYSTEM (KENDON LEASE)
S-1135-47-1	84,588 GALLONS	3020-05 D	1	185.00	185.00	D	84,588 GALLON FIXED ROOF REJECT TANK P/O#4007783 WITH VAPOR CONTROL SYSTEM (KENDON LEASE)
S-1135-48-0	42,000 GALLONS	3020-05 C	1	135.00	135.00	D	42,000 GALLON FIXED ROOF FUEL TANK P/O#4007784, KENDON LEASE
S-1135-49-0	8,400 GALLONS	3020-05 B	1	93.00	93.00	D	8,400 GALLON FIXED ROOF TEST TANK P/O#4007735, KENDON LEASE
S-1135-50-1	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF SKIM TANK P/O#4007736 WITH VAPOR CONTROL SYSTEM (KENDON LEASE)
S-1135-51-5	68,544 GALLON	3020-05 D	1	185.00	185.00	D	68,544 GALLON FIXED ROOF EMERGENCY STORAGE TANK (P/O#4007787) EQUIPPED WITH PRESSURE-VACUUM RELIEF VALVE LOCATED AT MIDWAY SUNSET FIELD, WILBERT FEE.
S-1135-52-5	68,544 GALLON	3020-05 D	1	185.00	185.00	D	68,544 GALLON FIXED ROOF EMERGENCY STORAGE TANK (P/O#4007788) EQUIPPED WITH PRESSURE-VACUUM RELIEF VALVE LOCATED AT MIDWAY SUNSET FIELD, WILBERT FEE.
S-1135-53-5	68,544 GALLON	3020-05 D	1	185.00	185.00	D	68,544 GALLON FIXED ROOF EMERGENCY STORAGE TANK (P/O#4007789, ID#10745) EQUIPPED WITH PRESSURE-VACUUM RELIEF VALVE LOCATED AT MIDWAY SUNSET FIELD, WILBERT FEE.
S-1135-54-0	84,588 GALLONS	3020-05 D	1	185.00	185.00	D	84,588 GALLON FIXED ROOF WASTE TANK P/O#4007790, WILBERT LEASE
S-1135-55-1	84,588 GALLONS	3020-05 D	1	185.00	185.00	D	84,588 GALLON FIXED ROOF WASTE TANK (P/O#4007791) EQUIPPED WITH VAPOR RECOVERY. (WILBERT LEASE)
S-1135-56-1	45,486 GALLONS	3020-05 C	1	135.00	135.00	D	45,486 GALLON FIXED ROOF STORAGE TANK (P/O#4007792) EQUIPPED WITH VAPOR RECOVERY. (WILBERT LEASE)
S-1135-57-0	45,486 GALLONS	3020-05 D	1	185.00	185.00	D	45,486 GALLON FIXED ROOF WASH TANK P/O#4007793, WILBERT LEASE
S-1135-58-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF SKIM TANK P/O#4007794, WILBERT LEASE
S-1135-59-1	51,198 GALLON TANK	3020-05 D	1	185.00	185.00	D	51,198 GALLON FIXED ROOF STORAGE TANK. MAXWELL LEASE
S-1135-60-2	225,624 GALLONS	3020-05 E	1	246.00	246.00	D	225,624 GALLON REJECT TANK. MAXWELL LEASE. CANCELLED BY APPLICANT IN LIEW OF 1995 RENEWAL. MRB
S-1135-61-2	216,594 GALLON STORAGE TANK	3020-05 E	1	246.00	246.00	D	216,594 GALLON FIXED ROOF STORAGE TANK. MAXWELL LEASE.

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-62-1	84,588 GALLON STORAGE TANK	3020-05 D	1	185.00	185.00	D	84,588 GALLON FIXED ROOF WATER TANK. MAXWELL LEASE.
S-1135-63-2	84,588 GALLON STORAGE TANK	3020-05 D	1	185.00	185.00	D	84,588 GALLON FIXED ROOF REJECT TANK T103. MAXWELL LEASE.
S-1135-64-1	45,484 GALLON STORAGE TANK	3020-05 C	1	135.00	135.00	D	45,486 GALLON FIXED ROOF LACT TANK #8484. MAXWELL LEASE.
S-1135-65-1	51,198 GALLON STORAGE TANK	3020-05 D	1	185.00	185.00	D	51,198 GALLON FIXED ROOF WASH TANK. MAXWELL LEASE.
S-1135-66-2	142,968 GALLON STORAGE TANK	3020-05 E	1	246.00	246.00	D	142,968 GALLON FIXED ROOF WATER TANK T700. MAXWELL LEASE.
S-1135-67-2	142,968 GALLON STORAGE TANK	3020-05 E	1	246.00	246.00	D	142,968 GALLON FIXED ROOF STORAGE TANK #T200. MAXWELL LEASE.
S-1135-68-1	45,486 GALLON STORAGE TANK	3020-05 C	1	135.00	135.00	D	45,486 GALLON FIXED ROOF SLOP TANK #T300. MAXWELL LEASE.
S-1135-69-2	126,924 GALLON STORAGE TANK	3020-05 E	1	246.00	246.00	D	126,924 GALLON FIXED ROOF WASH TANK. MAXWELL LEASE.
S-1135-70-15	43,470 gallons	3020-05 C	1	135.00	135.00	A	43,470 GALLON FIXED ROOF REJECT TANK T-110, WITH SHARED VAPOR RECOVERY SYSTEM - METSON LEASE TANK BATTERY
S-1135-71-8	84,000 gallons	3020-05 D	1	185.00	185.00	A	84,000 GALLON FIXED ROOF LACT TANK T-100 WITH VAPOR RECOVERY (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY
S-1135-72-7	210,000 GALLONS	3020-05 E	1	246.00	246.00	A	210,000 GALLON FIXED ROOF STANDBY TANK T-120, WITH VAPOR RECOVERY SYSTEM (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY
S-1135-73-1	43,470 GALLONS	3020-05 C	1	135.00	135.00	D	43,470 GALLON FIXED ROOF FUEL TANK P/O#4007836, METSON LEASE
S-1135-74-1	43,470 GALLONS	3020-05 C	1	135.00	135.00	D	43,470 GALLONS FIXED ROOF SKIM TANK ID#103, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY
S-1135-75-7	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF WASH TANK M-101, WITH VAPOR RECOVERY (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY
S-1135-76-7	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF WASH TANK M-102, WITH VAPOR RECOVERY (LISTED ON S-1135-70) - METSON LEASE TANK BATTERY
S-1135-77-2	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF WATER TANK P/O#4007840, METSON LEASE
S-1135-78-2	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF STANDBY TANK P/O#4007841, METSON LEASE
S-1135-79-0	43,470 GALLONS	3020-05 C	1	135.00	135.00	D	43,470 GALLON FIXED ROOF FUEL TANK P/O#4007842, METSON LEASE***TANK REMOVED PER COMPLIANCE, CANCELLED ON 7/21/99, DBT***
S-1135-80-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF SKIM TANK ID#SOUTH, METSON LEASE ***TANK REMOVED PER COMPLIANCE, CANCELLED ON 7/21/99,DBT***
S-1135-81-0	10,500 GALLONS	3020-05 B	1	93.00	93.00	D	10,500 GALLON FIXED ROOF SKIM TANK ID#NORTH, METSON LEASE ***TANK REMOVED PER COMPLIANCE, CANCELLED ON 7/21/99,DBT***
S-1135-82-10	84,000 gallons	3020-05 D	1	185.00	185.00	A	84,000 GALLON FIXED ROOF STANDBY TANK #2179 (BUENA FE FEE)

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-83-8	84,000 gallons	3020-05 D	1	185.00	185.00	A	84,000 GALLON FIXED ROOF STANDBY TANK #2180 (BUENA FE FEE)
S-1135-84-2	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	52,500 GALLON FIXED ROOF WASH TANK (P/O#4007847) EQUIPPED WITH VAPOR RECOVERY. (BUENA FE LEASE)
S-1135-85-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	42,000 GALLON FIXED ROOF WASH TANK P/O#4007848, BUENA FE LEASE
S-1135-86-2	42,000 GALLONS	3020-05 C	1	135.00	135.00	D	42,000 GALLON FIXED ROOF SKIM TANK (P/O#4007849) EQUIPPED WITH VAPOR RECOVERY. (BUENA FE LEASE)
S-1135-87-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF WATER TANK P/O#4007850, BUENA FE LEASE
S-1135-88-0	10,500 GALLONS	3020-05 B	1	93.00	93.00	D	10,500 GALLON FIXED ROOF TEST #1 TANK ID#482, BUENA FE LEASE
S-1135-89-1	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF SKIM TANK P/O#4007852, BUENA FE LEASE
S-1135-90-0	10,500 GALLONS	3020-05 B	1	93.00	93.00	D	10,500 GALLON FIXED ROOF TEST #6 TANK ID#481, BUENA FE LEASE
S-1135-91-5	68,544 GALLONS	3020-05 D	1	185.00	185.00	D	68,544 GALLON EMERGENCY USE FIXED ROOF TANK ID #133170 WITH P/V VENT
S-1135-92-5	68,544 GALLONS	3020-05 D	1	185.00	185.00	D	68,544 GALLON EMERGENCY USE FIXED ROOF TANK ID #133169 WITH P/V VENT
S-1135-93-6	84,588 GALLONS	3020-05 D	1	185.00	185.00	D	84,588 GALLON EMERGENCY USE FIXED ROOF TANK #133171 WITH P/V VENT
S-1135-94-1	43,470 GALLONS	3020-05 C	1	135.00	135.00	D	43,470 GALLON FIXED ROOF WASH #2 TANK P/O#4007954, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-95 AND '-96. MOCAL LEASE TANK BATTERY
S-1135-95-1	43,470 GALLONS	3020-05 C	1	135.00	135.00	D	43,470 GALLON FIXED ROOF WASH TANK P/O#4007955, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-94 AND '-96. MOCAL LEASE TANK BATTERY
S-1135-96-1	8,400 GALLONS	3020-05 B	1	93.00	93.00	D	8,400 GALLON FIXED ROOF SKIM TANK P/O#4007956, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-94 AND '-95. MOCAL LEASE TANK BATTERY.
S-1135-97-5	16 UNCONTROLLED WELLS	3020-09 A	16	9.34	149.44	D	16 UNCONTROLLED CYCLICLY STEAMED OIL WELLS HEAVY OIL WESTERN ***CANCELLED PER LETTER FROM PERMITTEE. ALREADY PERMITTED FOR 40 CYCLICS IN H.O.W. PER S-1547-838-1. DBT, 4/19/99***
S-1135-98-0	8,400,000 BTU/HR	3020-02 G	1	815.00	815.00	D	8,400,000 BTU/HR HEATER TREATER
S-1135-99-11	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPORRECOVERY GAS FIRED STEAM GENERATOR #1 WITH SO2 SCRUBBER - MAXWELL
S-1135-100-0	6,300,000 BTU/HR	3020-02 G	1	815.00	815.00	D	6,300,000 BTU/HR FREE WATER KNOCKOUT VESSEL
S-1135-102-0	8,400,000 BTU/HR	3020-02 G	1	815.00	815.00	D	8,400,000 BTU/HR HEATER TREATER

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-103-1	8,400,000 BTU/HR	3020-02 G	1	815.00	815.00	D	8,400,000 BTU/HR HEATER TREATER
S-1135-104-15	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #7 WITH PCC BURNER AND SO2 SCRUBBER - MAXWELL
S-1135-105-8	25,000,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR OIL/NATURAL GAS FIRED STEAM GENERATOR #3 WITH SO2 SCRUBBER - W & S
S-1135-106-8	60,800,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #2 WITH NORTH AMERICAN BURNER AND SO2 SCRUBBER - W & S. CANCELLED BY APPLICANT IN LIEU OF 1995 RENEWAL. MRB
S-1135-107-0	8,400,000 BTU/HR	3020-02 G	1	815.00	815.00	D	8,400,000 BTU/HR HEATER TREATER
S-1135-109-6	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #1 WITH NORTH AMERICAN BURNER, STAGED COMBUSTION, AND SO2 SCRUBBER - EXETER
S-1135-110-6	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #2 WITH NORTH AMERICAN BURNER, STAGED COMBUSTION, AND SO2 SCRUBBER - EXETER
S-1135-111-8	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #3 WITH NORTH AMERICAN BURNER, STAGED COMBUSTION, AND SO2 SCRUBBER - ANDERSON
S-1135-112-6	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #4 WITH NORTH AMERICAN BURNER, STAGED COMBUSTION, AND SO2 SCRUBBER - EXETER
S-1135-113-2	62.5 MMBTU/HR STEAM GENERATOR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL FIRED STEAM GENERATOR #6 - EXETER
S-1135-115-22	62.5 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #1 (NEELY LEASE)
S-1135-116-9	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS FIRED STEAM GENERATOR #2 WITH STAGED COMBUSTION AND SO2 SCRUBBER - NEELY LEASE **PERMANENTLY REMOVED PER 3/9/99 LETTER, HAR**
S-1135-117-6	25,200,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR OIL FIRED STEAM GENERATOR #3 WITH SO2 SCRUBBER - NEELY
S-1135-118-14	100,800 gallons	3020-05 E	1	246.00	246.00	D	100,800 GALLON FIXED ROOF WASH TANK WITH VAPOR CONTROL SYSTEM CONSISTING OF VAPOR COMPRESSORS, PRE-COOLER, FIN-FAN COOLER, FREEWATER KNOCKOUTS #1, #2, AND #3, VARIOUS PUMPS AND PIPING, AND HEATER TREATERS #1, #2, #4, #5, #6, #7, AND #8 VENTED TO APPROVED INCINERATION DEVICES S-1135-9 AND -10 OR TEOR VAPOR CONTROL SKID INLET ON PERMIT S-1135-127 FOR RE-INJECTION TO DOGGR APPROVED WELL(S), SERVING TANKS S-1135-118, -146, -147, -148, -180, -181, -182, AND -296 (MAXWELL LEASE)

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-119-24	62.5 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #5 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)
S-1135-120-8	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS FIRED STEAM GENERATOR #5 WITH NORTH AMERICAN BURNER AND SO2 SCRUBBER - NEELY LEASE **PERMANENTLY REMOVED PER 3/9/99 LETTER, HAR**
S-1135-121-7	62,500,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	62.5 MMBTU/HR OIL/NATURAL GAS/VAPOR RECOVERY GAS FIRED STEAM GENERATOR #5 WITH NORTH AMERICAN BURNER, STAGED COMBUSTION, AND SO2 SCRUBBER - EXETER
S-1135-122-25	62.5 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #6 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)
S-1135-123-23	62.5 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR #7 WITH NORTH AMERICAN BURNER (ANDERSON GOODWIN LEASE)
S-1135-124-15	254 wells	3020-09 A	254	9.34	2,372.36	A	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 254 STEAM ENHANCED WELLS, AND TIED TO TEOR '293 INCLUDING PIPING TO BALANCED CGCS, RE-INJECTION COMPRESSORS OR INCINERATING STEAM GENERATORS (EXETER LEASE)
S-1135-125-14	144 wells	3020-09 A	144	9.34	1,344.96	A	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 144 STEAM ENHANCED CRUDE OIL PRODUCTION WELL VENTS, TIED TO TEOR '293 AND TVR '173 (W&S FEE LEASE)
S-1135-126-3	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF WASH TANK, INCLUDING: VAPOR CONTROL SYSTEM, 1 AIR COOLED HEAT EXCHANGER, 1 INLET SCRUBBER, ONE 1 HP PUMP, 1 DISCHARGE SCRUBBER, AND ONE 30 HP COMPRESSOR. EXETER & BOAC LEASE TANK BATTERY.
S-1135-127-17	383 TEOR Wells	3020-09 A	383	9.34	3,577.22	A	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION INCLUDING ONE TRANSPORTABLE FIN FAN COOLER AND ASSOCIATED PIPING SERVING 383 STEAM ENHANCED WELL VENTS (MAXWELL LEASE) CONNECTED TO TANK VAPOR CONTROL SYSTEM S-1135-118, COLLECTED VAPORS PIPED FROM VAPOR CONTROL COMPRESSOR SKIDS EITHER TO INJECTION COMPRESSORS FOR RE-INJECTION TO DOGGR WELLS, TO STEAM GENERATORS S-1135-9 AND '-10 FOR INCINERATION, OR CONTAINED WITHIN THE BALANCED CASING GAS COLLECTION SYSTEM (CGCS)
S-1135-128-21	265 wells	3020-09 A	265	9.34	2,475.10	A	THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 265 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, PIPING TO DISPOSAL WELLS, TIED TO TEOR S-1135-129, AND TVR S-1135-149 AND S-1135-281 (NEELY LEASE)
S-1135-129-26	425 Wells	3020-09 A	425	9.34	3,969.50	A	THERMALLY ENHANCED OIL RECOVERY OPERATION AUTHORIZED FOR 425 STEAM ENHANCED WELLS INCLUDING BALANCED WELL VENT CONTROL SYSTEM, VAPOR PIPING TO INJECTION WELLS (ANDERSON-GOODWIN LEASE)

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-130-4	5.3 MMBTU/HR	3020-02 G	1	815.00	815.00	D	MAXWELL LEASE, 5.3 MMBTU/HR JOHN ZINC CO. WASTE GAS INCINERATOR WITH ANDERSEN 2000 SO2 SCRUBBER SERVING TEOR OPERATION S-1135-127 AND TANK BATTERY VAPOR CONTROL SYSTEM S-1135-118. CANCELLED BY APPLICANT ON 95 RENEWALS,MRB.
S-1135-131-1	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF WASH TANK, INCLUDING VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-126 (EXETER & BOAC LEASES)
S-1135-132-1	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF WASH TANK, INCLUDING: VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-126 (EXETER AND BOAC LEASES)
S-1135-133-1	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF WASH TANK, INCLUDING: VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-126 (EXETER AND BOAC LEASES)
S-1135-134-1	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF REJECT TANK, INCLUDING VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-126 (EXETER AND BOAC LEASES)
S-1135-135-1	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF REJECT TANK, INCLUDING VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-126 (EXETER AND BOAC LEASES)
S-1135-136-0	16,800 GALLONS	3020-05 B	1	93.00	93.00	D	16,800 GALLON FIXED ROOF WATER TANK, INCLUDING VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-126, '-131, '-132, '-133, ' 134, '-135, AND '-137. EXETER AND BOAC LEASE TANK BATTERY. ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-137-0	16,800 GALLONS	3020-05 B	1	93.00	93.00	D	16,800 GALLON FIXED ROOF WATER TANK, INCLUDING VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-126, '-131, '-132, '-133, ' 134, '-135, AND '-136. EXETER AND BOAC LEASE TANK BATTERY. ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-138-4	11,260,000 BTU/HR	3020-02 G	1	815.00	815.00	D	NEELY INCINERATOR - 11.26 MMBTU/HR J.T THORP INC. WASTE GAS INCINERATOR WITH IN-LINE SULFUR SCAVENGER SYSTEM (SHARED WITH A/G S-1135-141) & ANDERSEN 2000 SO2 SCRUBBER. CANCELLED BY APPLICANT ON 1995 RENEWALS, MRB.
S-1135-139-3	15,540,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	W & S LEASE, 15.54 MMBTU/HR J.T. THORP WASTE GAS INCINERATOR WITH ANDERSEN 2000 SO2 SCRUBBER. CANCELLED BY APPLICANT ON 1995 RENEWALS - ANNUAL FEES NOT PAID. MRB.
S-1135-140-2	5,910,000 BTU/HR	3020-02 G	1	815.00	815.00	D	EXETER - 5.91 MMBTU/HR J.T. THORP WASTE GAS INCINERATOR WITH ANDERSEN 2000 SO2 SCRUBBER, INCLUDING: NONCONDENSIBLE VAPOR PIPING FROM TEOR OPERATION S-1135-124 AND TANK BATTERY S-1135-126.CANCELLED BY APPLICANT W 1995 RENEWALS, MRB.
S-1135-141-4	5,910,000 BTU/HR	3020-02 G	1	815.00	815.00	D	A/G LEASE - 5.91 MMBTU/HR J.T. THORP WASTE GAS INCINERATOR WITH ANDERSEN 2000 SO2 SCRUBBER. CANCELLED BY APPLICANT ON 1995 RENEWALS, MRB.

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-142-0	8,400,000 BTU/HR	3020-02 G	1	815.00	815.00	D	8,400,000 BTU/HR HEATER TREATER
S-1135-143-2	25,000,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR NATURAL GAS FIRED STEAM GENERATOR WITH NORTH AMERICAN BURNER - DICKENSON TRUST
S-1135-144-0	25,000,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR STRUTHERS STEAM GENERATOR WITH NORTH AMERICAN BURNER, ANDERSON LEASE
S-1135-145-0	25,000,000 BTU/HR	3020-02 H	1	1,030.00	1,030.00	D	25.2 MMBTU/HR BRINDLE STEAM GENERATOR WITH NORTH AMERICAN BURNER, ANDERSON LEASE
S-1135-146-6	67,200 gallons	3020-05 D	1	185.00	185.00	D	67,200 GALLON FIXED ROOF NET TANK SERVED BY VAPOR CONTROL SYSTEM LISTED S-1135-118 (MAXWELL LEASE)
S-1135-147-6	84,000 gallons	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF NET TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-118 (MAXWELL LEASE)
S-1135-148-6	420,000 gallons	3020-05 E	1	246.00	246.00	D	420,000 GALLON FIXED ROOF REJECT STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-118 (MAXWELL LEASE)
S-1135-149-18	126,000 gallons	3020-05 E	1	246.00	246.00	A	126,000 GALLON CRUDE OIL LACT TANK ID# AG-01, WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-150, '151, '152, '155, '270, '301 AND '323 (ANDERSON/GOODWIN LEASE)
S-1135-150-12	126,000 gallon	3020-05 E	1	246.00	246.00	A	126,000 GALLON CRUDE OIL LACT TANK ID# AG-02, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)
S-1135-151-12	210,000 gallon	3020-05 E	1	246.00	246.00	A	210,000 GALLON REJECT TANK ID# AG-03, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)
S-1135-152-12	210,000 gallon	3020-05 E	1	246.00	246.00	A	210,000 GALLON REJECT TANK ID# AG-04, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)
S-1135-153-1	9,450 GALLONS	3020-05 B	1	93.00	93.00	D	9,450 GALLON WASH TANK ID# AG-05, ANDERSON/GOODWIN LEASE
S-1135-154-1	16,000 GALLONS	3020-05 B	1	93.00	93.00	D	16,000 GALLON FIXED ROOF POLISH TANK ID# AG-06, ANDERSON/ GOODWIN LEASE.
S-1135-155-14	281,400 gallon	3020-05 E	1	246.00	246.00	A	281,400 GALLON (6,700 BBL) FIXED ROOF WASH TANK ID# AG-07, WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-149 (ANDERSON/GOODWIN LEASE)
S-1135-156-0	10,500 GALLONS	3020-05 C	1	135.00	135.00	D	10,500 GALLON FIXED ROOF CONDENSATE TANK ID# AG-08, ANDERSON/GOODWIN LEASE.
S-1135-157-8	420,000 gallon	3020-05 E	1	246.00	246.00	D	420,000 GALLON FIXED ROOF PROCESS TANK ID# AG-09 VENTED TO VAPOR CONTROL SKID LISTED ON S-1135-129 (ANDERSON/GOODWIN LEASE)
S-1135-158-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF GENERATOR FUEL TANK ID# AG-10, ANDERSON/GOODWIN LEASE

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-159-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF GENERATOR FUEL TANK ID# AG-11, ANDERSON/GOODWIN LEASE
S-1135-160-0	10,500 GALLONS	3020-05 B	1	93.00	93.00	D	10,500 GALLON WASH TANK ID# AG-12, ANDERSON/GOODWIN LEASE
S-1135-161-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF REJECT OIL STORAGE TANK ID# AG-13, ANDERSON/GOODWIN LEASE
S-1135-162-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF REJECT OIL STORAGE TANK ID# AG-14, ANDERSON/GOODWIN LEASE
S-1135-163-1	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF #1 WASH TANK(WEST) ID# A-01, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-164, '-165, AND '-166. ANDERSON LEASE.
S-1135-164-1	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF WASH TANK(WEST) ID# A-02, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-163, '-165, AND '-166. ANDERSON LEASE TANK BATTERY
S-1135-165-1	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF LACT STORAGE TANK(EAST) ID# A-03, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-163, '-164, AND '-166. ANDERSON LEASE TANK BATTERY
S-1135-166-1	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF REJECT OIL STORAGE TANK(WEST) ID# A-04, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-163, '-164, AND '-165. ANDERSON LEASE TANK BATTERY
S-1135-168-0	42,000 GALLONS	3020-05 C	1	135.00	135.00	D	42,000 GALLON FIXED ROOF PRODUCED WATER TANK ID# A-06, ANDERSON LEASE
S-1135-169-2	546,000 gallons	3020-05 F	1	301.00	301.00	D	546,000 GALLON FIXED ROOF T100 PRODUCED WATER TANK ID# VWP-01, VICTORY WATER PLANT
S-1135-170-2	126,000 gallons	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF T101 PRODUCED WATER TANK ID# VWP-02, VICTORY WATER PLANT
S-1135-171-0	8,400 GALLONS	3020-05 B	1	93.00	93.00	D	8,400 GALLON FIXED ROOF T102 PRODUCED WATER TANK ID# VWP-03, VICTORY WATER PLANT
S-1135-172-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF T103 PRODUCED WATER TANK ID# VWP-04, VICTORY WATER PLANT
S-1135-173-21	67,200 gallon tank	3020-05 D	1	185.00	185.00	A	1,600 BBL (67,200 GALLON) FIXED ROOF LACT TANK ID# WS-01, HANDLING MAXWELL LEASE PRODUCTION, AND VESSELS V-101, V-102, V-103, AND V-104; WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-174, -175, -178, -325, AND -337 (W&S LEASE) DISCHARGING TO TEOR WVVCS S-1135-125
S-1135-174-8	84,000 GALLONS	3020-05 D	1	185.00	185.00	A	2,000 BBL (84,000 GALLON) FIXED ROOF LACT TANK ID# WS-02, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)
S-1135-175-7	67,200 GALLONS	3020-05 D	1	185.00	185.00	A	1,600 BBL (67,200 GALLON) FIXED ROOF WASH TANK ID# WS-03, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-176-8	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	5,000 BBL (210,000 GALLON) FIXED ROOF STOCK TANK ID# WS-04, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)
S-1135-177-8	420,000 GALLONS	3020-05 E	1	246.00	246.00	D	10,000 BBL (420,000 GALLON) FIXED ROOF WASH TANK ID# WS-05, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)
S-1135-178-9	126,000 GALLON	3020-05 E	1	246.00	246.00	A	3,000 BBL (126,000 GALLON) FIXED ROOF SUMP PROCESS TANK ID# WS-06, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)
S-1135-179-1	126,000 GALLONS	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF WASH TANK WITH VAPOR RECOVERY SYSTEM SHARED BY TANK S-1135-173, W & S LEASE TANK BATTERY. ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-180-6	63,000 gallons	3020-05 D	1	185.00	185.00	D	63,000 GALLON FIXED ROOF SLOP OIL TANK ID# M-05 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-118 (MAXWELL LEASE)
S-1135-181-6	210,000 gallons	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF SUMP PROCESS TANK ID# M-06 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-118 (MAXWELL LEASE)
S-1135-182-6	420,000 gallons	3020-05 E	1	246.00	246.00	D	420,000 GALLON FIXED ROOF SUMP PROCESS TANK ID# M-07 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-118 (MAXWELL LEASE)
S-1135-183-3	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF LACT TANK (ID# GU-01) WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-184, '186, AND '192, AND TIE INTO TEOR SYSTEM S-1135-293 (GLOBE LEASE)
S-1135-184-2	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF LACT TANK (ID# GV-02), WITH VAPOR CONTROL SHARED WITH S-1135-183 (GLOBE LEASE)
S-1135-185-0	67,200 GALLONS	3020-05 D	1	185.00	185.00	D	67,200 GALLON FIXED ROOF SAND TANK ID# GV-03, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-186-2	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF REJECT TANK (ID# GV-04), WITH VAPOR VAPOR CONTROL SHARED WITH S-1135-183 (GLOBE LEASE)
S-1135-187-0	63,000 GALLONS	3020-05 D	1	185.00	185.00	D	63,000 GALLON FIXED ROOF REJECT TANK ID# GV-05, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-188-0	63,000 GALLONS	3020-05 D	1	185.00	185.00	D	63,000 GALLON FIXED ROOF REJECT TANK ID# GV-06, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-189-1	63,000 GALLONS	3020-05 D	1	185.00	185.00	D	63,000 GALLON FIXED ROOF SLOP OIL TANK ID# GV-07, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-183, '-184, '-186, '-192, AND '-197.GLOBE LEASE TANK BATTERY ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-190-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF REJECT TANK ID# GV-08, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-191-0	8,400 GALLONS	3020-05 B	1	93.00	93.00	D	8,400 GALLON FIXED ROOF FUEL OIL STORAGE TANK ID# GV-09, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-192-2	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF WASH TANK (ID# GV-10), WITH VAPOR CONTROL SHARED WITH S-1135-183 (GLOBE LEASE)
S-1135-193-0	63,000 GALLONS	3020-05 D	1	185.00	185.00	D	63,000 GALLON FIXED ROOF WASH TANK ID# GV-11, GLOBE LEASE
S-1135-194-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF #6 WASH TANK ID# GV-12, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-195-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF CONDENSATE TANK ID# GV-13, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-196-0	63,000 GALLONS	3020-05 D	1	185.00	185.00	D	63,000 GALLON FIXED ROOF SHIPPING TANK ID# GV-14, GLOBE LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-197-1	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF WASH TANK ID# GV-15, WITH VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1135-183, '-184, '-186, '-189, AND '-192. GLOBE LEASE TANK BATTERY ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-198-0	42,000 GALLONS	3020-05 C	1	135.00	135.00	D	42,000 GALLON FIXED ROOF TANK ID# DT-01, DICKINSON TRUST LEASE.
S-1135-199-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF RUN TANK ID# DT-02, DICKINSON TRUST LEASE
S-1135-200-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF RUN TANK ID# DT-03, DICKINSON TRUST LEASE
S-1135-201-0	31,500 GALLONS	3020-05 C	1	135.00	135.00	D	31,500 GALLON FIXED ROOF WASH TANK ID# DT-04, DICKINSON TRUST LEASE
S-1135-202-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF POLISH TANK ID# E-09, EXETER LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-203-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF POLISH TANK ID# E-10, EXETER LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-204-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF FUEL STORAGE TANK ID# E-11, EXETER LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-205-0	8,400 GALLONS	3020-05 B	1	93.00	93.00	D	8,400 GALLON FIXED ROOF CONDENSATE TANK ID# E-12, EXETER LEASE ***CANCELLED PER COMPANY REQUEST 6/20/94 MPE***
S-1135-206-1	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF CLARIFIER TANK ID# E-13, WITH VAPOR RECOVERY, EXETER LEASE
S-1135-207-1	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF SUMP TANK ID# E-14, WITH VAPOR CONTROL (EXETER LEASE)
S-1135-208-0	63,000 GALLONS	3020-05 D	1	185.00	185.00	D	63,000 GALLONS FIXED ROOF PETROLEUM STORAGE TANK ID# AG-18

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-209-0	21,000 GALLONS	3020-05 C	1	135.00	135.00	D	21,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK ID# AG-19
S-1135-210-0	8,820 GALLONS	3020-05 B	1	93.00	93.00	D	8,820 GALLON FIXED ROOF STORAGE TANK ID# GU-19
S-1135-211-0	8,820 GALLONS	3020-05 B	1	93.00	93.00	D	8,820 GALLON FIXED ROOF STORAGE TANK ID# GU-20
S-1135-212-8	210,000 GALLONS	3020-05 E	1	246.00	246.00	D	210,000 GALLON FIXED ROOF CLARIFIER TANK #9 WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-213, '281, '284, '285, '286, '287 - NEELY LEASE
S-1135-213-4	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF REJECT TANK #1 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-212 - NEELY LEASE
S-1135-214-3	67,200 GALLONS	3020-05 D	1	185.00	185.00	D	67,200 GALLON FIXED ROOF REJECT TANK #2 WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-212, '-213, '-219, '-281, '-282, '-284, '-285, '-286, AND '-287. NEELY LEASE TANK BATTERY**CANCELED PER COMPLIANCE REQUEST,DOES NOT EXIST,DBT,6 16/99**
S-1135-219-3	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF CRUDE OIL REJECT TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-212 - NEELY LEASE
S-1135-220-1	42,000 GALLONS	3020-05 C	1	135.00	135.00	D	42,000 GALLON FIXED ROOF PRODUCED WATER TANK #4 WITH VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1135-212, '-213, '-214, '-219, '-221, '-284, '-285, '-286, AND '-287. NEELY LEASE TANK BATTERY "" CANCELLED - NOW PERMIT S-1135-281""
S-1135-221-0	16,800 GALLONS	3020-05 B	1	93.00	93.00	D	16,800 GALLON FIXED ROOF POLISH TANK, WITH NO VAPOR CONTROL. NEELY TANK BATTERY ""CANCELLED - NOW PERMIT S-1135-282""
S-1135-222-0	6,300 GALLONS SUMP REPLACEMENT TANK	3020-05 B	1	93.00	93.00	D	6,300 GALLON (150 BBL) SUMP REPLACEMENT TANK. W & S LEASE.
S-1135-224-25	78,200 kW	3020-08A G	1	10,215.00	10,215.00	A	NOMINALLY RATED 78.2 MW COGENERATION UNIT A WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)
S-1135-225-23	78,200 kW	3020-08A G	1	10,215.00	10,215.00	A	NOMINALLY RATED 78.2 MW COGENERATION UNIT B WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS, SELECTIVE CATALYTIC REDUCTION (SCR), AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)
S-1135-226-24	78,200 kW	3020-08A G	1	10,215.00	10,215.00	A	NOMINALLY RATED 78.2 MW COGENERATION UNIT C WITH GE MODEL G7111E FRAME 7E GAS TURBINE ENGINE WITH DRY LOW NOX COMBUSTORS AND SELECTIVE CATALYTIC REDUCTION (SCR) AND UNFIRED HEAT RECOVERY STEAM GENERATOR (HRSG)
S-1135-227-0	252,000 GAL.	3020-05 G	1	382.00	382.00	D	252,000 GALLON FLOATING ROOF TANK #T300-A, INCLUDING: LIQUID MOUNTED FOAM FILLED PRIMARY SEAL AND RIM-MOUNTED SECONDARY SEAL (CANCELED BY PERMITTEE CONVERTED TO FEEDWATER STORAGE TANKS-(NOT SUBJECTED TO 4623, CEC CEQA BACT REG'T.) TEG 8/3/98)

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-228-0	252,000 GAL.	3020-05 G	1	382.00	382.00	D	252,000 GALLON FLOATING ROOF TANK #T300-B, INCLUDING: LIQUID MOUNTED FOAM FILLED PRIMARY SEAL AND RIM-MOUNTED SECONDARY SEAL (CANCELED BY PERMITTEE-CONVERTED TO FEEDWATER TANKS (NOT SUBJECT TO 4623, CEC CEQA BACT REQ'T.) TEG 8/3/98)
S-1135-230-2	18,000 GALLONS	3020-05 B	1	93.00	93.00	A	1 MISC. STEAM DUMPING-ROCK BED MUFFLER OPERATION FOR MIDWAY SUNSET COGENERATION BLOWDOWN.
S-1135-231-4	165 hp IC Engine	3020-10 B	1	117.00	117.00	A	165 HP DIESEL-FIRED I.C. ENGINE POWERING A FIREWATER PUMP
S-1135-232-1	8.4 MM BTU/HR	3020-02 G	1	815.00	815.00	D	8.4 MMBTU/HR HEATER TREATER #2 CONSISTING OF TWO 4.2 MMBTU/HR BURNERS WITH SEPARATE STACKS (KENDON LEASE)
S-1135-233-0	8,400,000 BTU/HR	3020-02 G	1	815.00	815.00	D	4.2 MMBTU/HR HEATER TREATER
S-1135-235-1	2,520 BHP	3020-10 F	1	749.00	749.00	A	2,520 BHP DIESEL FIRED I.C. ENGINE FOR EMERGENCY POWER GENERATION, INCLUDING: ONE CATERPILLAR MODEL #3516STD 16 CYLINDER I.C. ENGINE OPERATING A 1500 KW ELECTRIC GENERATOR, VALVE CONNECTING CRANKCASE TO INTAKE MANIFOLD, & ELAPSED OPERATING TIME METER
S-1135-236-1			1	0.00	0.00	D	0 CONTROLLED CYCLIC WELLS (77 EXISTING CONTROLLED WELLS TRANSFERRED TO ATC S-1135-283-1).
S-1135-264-0	42,000 GALLONS	3020-05 C	1	135.00	135.00	D	42,000 GALLON FIXED ROOF SUMP REPLACEMENT TANK WITH PRESSURE/VACUUM RELIEF VALVE. MOCAL LEASE
S-1135-266-8	62.5 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR STRUTHERS STEAM GENERATOR, WITH A COEN QLN-ULN BURNER, O2 CONTROLLER, AND FLUE GAS RECIRCULATION (METSON 48)
S-1135-267-8	62,500 kBtu/hr burner	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR STRUTHERS GAS-FIRED STEAM GENERATOR (#49) WITH A COEN MODEL QLN-ULN BURNER WITH FLUE GAS RECIRCULATION (FGR) (KENDON LEASE)
S-1135-270-10	210,000 gallon	3020-05 E	1	246.00	246.00	A	210,000 GALLON FIXED ROOF OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)
S-1135-281-12	126,000 gallons	3020-05 E	1	246.00	246.00	A	3,000 BBL FIXED ROOF SUMP REPLACEMENT TANK WITH VAPOR CONTROL SYSTEM SHARED WITH S-1135-284, -285, -286, -287, -328, '-329, '-330, '-331, '-332, '-333, '-334, '-335, AND '-336
S-1135-282-0	84,000 GALLONS	3020-05 D	1	185.00	185.00	D	84,000 GALLON FIXED ROOF PRODUCED WATER TANK WITH VAPOR CONTROL SYSTEM SHARED WITH TANK S-1135-212, '-213, '-214, '-219, ' 281, '-284, '-285, '-286, AND '-287. NEELY LEASE TANK BATTERY.
S-1135-283-6	90 wells	3020-09 A	90	9.34	840.60	A	THERMALLY ENHANCED OIL RECOVERY OPERATION (TEOR) SERVING 90 STEAM ENHANCED WELLS WITH CLOSED CASING VENTS (ANDERSON LEASE)
S-1135-284-12	126,000 gal storage	3020-05 E	1	246.00	246.00	A	126,000 GALLON FIXED ROOF RUN TANK #5, WITH VAPOR CONTROL SYSTEM LISTED ON S-1135-281

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-285-14	126,000 gal storage	3020-05 E	1	246.00	246.00	A	126,000 GALLON FIXED ROOF LACT TANK #6 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281
S-1135-286-14	126,000 gal storage	3020-05 E	1	246.00	246.00	A	126,000 GALLON FIXED ROOF LACT TANK #7 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281
S-1135-287-14	126,000 gal storage	3020-05 E	1	246.00	246.00	A	126,000 GALLON FIXED ROOF LACT TANK #8 SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-281
S-1135-288-0	70 BHP	3020-10 A	1	80.00	80.00	D	ONE M & M 70 BHP RICH BURN, NATURAL GAS FIRED INTERNAL COMBUSTION ENGINE USED TO POWER AN OIL WELL RECIPROCATING PUMP UNIT.
S-1135-293-7	300 STEAM DRIVE WELLS	3020-09 A	300	9.34	2,802.00	A	THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION SERVING 300 STEAM DRIVE WELLS WITH CASING VENTS TIED TO VAPOR CONTROL SYSTEM INCLUDING, THREE VAPOR CONTROL SKIDS WITH SEPARATOR(S), HEAT EXCHANGER(S), FAN(S), AND COMPRESSOR(S), WITH NON-CONDENSIBLE VAPOR PIPING SHARED WITH TEOR OPERATION S-1135-124 (EXETER LEASE) CONTROLLED BY BALANCED CASING VENT COLLECTION SYSTEM OR RE-INJECTION INTO DOGGR APPROVED DISPOSAL WELL (GLOBE LEASE)
S-1135-294-8	126,000 gallon	3020-05 E	1	246.00	246.00	D	126,000 GALLON FIXED ROOF SUMP REPLACEMENT TANK VENTED TO VAPOR CONTROL SKID LISTED ON S-1135-129 (ANDERSON/GOODWIN LEASE)
S-1135-296-5	285,600 gallons	3020-05 E	1	246.00	246.00	D	285,600 GALLON FIXED ROOF REJECT TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-118 (MAXWELL LEASE)
S-1135-297-1	126,000 GALLON TANK	3020-05 E	1	246.00	246.00	D	126,000 GALLON, 30 FT DIAMETER, FIXED ROOF STOCK TANK WITH VAPOR CONTROL SYSTEM (KENDON LEASE)
S-1135-299-5	62,500 kBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR GAS-/LPG-FIRED STEAM GENERATOR #50 WITH A COEN MODEL QLN-ULN LOW-NOX BURNER, A FLUE GAS RECIRCULATION SYSTEM AND AN OXYGEN CONTROLLER (KENDON LEASE)
S-1135-301-11	281,400 gallon	3020-05 E	1	246.00	246.00	A	281,400 GALLON FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-149 (ANDERSON/GOODWIN LEASE)
S-1135-302-4	62,500 kBtu/hr burner	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR (#5) WITH A COEN MODEL QLN-ULN ULTRA LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) (BUENA FE LEASE)
S-1135-305-3	62.5 MMbtu/hr	3020-02 H	1	1,030.00	1,030.00	A	62.5 MMBTU/HR NAT GAS-FIRED STEAM GENERATOR # 52, WITH A COEN QLN-ULN LOW NOX BURNER, WITH FLUE GAS RECIRCULATION, (PRU LEASE)
S-1135-322-2	126,000 gallons	3020-05 E	1	246.00	246.00	A	126,000 GALLON FIXED ROOF WASH TANK T-101, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY
S-1135-323-3	3000 bbl	3020-05 E	1	246.00	246.00	A	3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-129 - ANDERSON GOODWIN LEASE

Detailed Facility Report

For Facility=1135

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1135-325-1	126,000 gallons	3020-05 E	1	246.00	246.00	A	3,000 BBL FIXED ROOF CRUDE OIL STORAGE TANK, HANDLING MAXWELL LEASE PRODUCTION, SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W & S LEASE)
S-1135-326-2	126,000 gallons	3020-05 E	1	246.00	246.00	A	126,000 GALLON FIXED ROOF WASH TANK T-102, WITH VAPOR RECOVERY (LISTED IN S-1135-70) - METSON LEASE TANK BATTERY
S-1135-327-1	38,000 gal	3020-05 C	1	135.00	135.00	A	905 BBL FWKO VESSEL (V-100) CONNECTED TO VAPOR RECOVERY SYSTEM LISTED ON S-1135-70
S-1135-328-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL FLOW SPLITTER PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-329-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL FWKO PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-330-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL "GAS BUSTER" PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-331-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL UNFIRED TREATER #1 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-332-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL UNFIRED TREATER #2 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-333-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL UNFIRED TREATER #4 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-334-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL UNFIRED TREATER #6 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-335-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL UNFIRED TREATER #7 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-336-0	50,400 gallons	3020-05 D	1	185.00	185.00	A	1,200 BBL UNFIRED TREATER #8 PRESSURE VESSEL VENTED TO THE VAPOR CONTROL SYSTEM LISTED ON S-1135-281 (NEELY)
S-1135-337-1	126,000 gallon tank	3020-05 E	1	246.00	246.00	A	3,000 BBL (126,000 GALLON) FIXED ROOF STOCK TANK ID# WS-04, HANDLING MAXWELL LEASE PRODUCTION, CONNECTED TO VAPOR CONTROL SYSTEM LISTED ON S-1135-173 (W&S LEASE)

Number of Facilities Reported: 1